

# Machine Intelligence & Deep Learning Workshop

Raymond Ptucha, Majid Rabbani, Mark Smith

The Kate Gleason **COLLEGE OF  
ENGINEERING**

## Graph CNN



Raymond Ptucha  
June 27-29, 2018  
Rochester Institute of Technology  
[www.rit.edu/kgcoe/cqas/machinelearning](http://www.rit.edu/kgcoe/cqas/machinelearning)



© 2018 Ray Ptucha, Rochester Institute of Technology

1

## Fair Use Agreement

This agreement covers the use of all slides in this document, please read carefully.

- You may freely use these slides for personal use, if:
  - My name (R. Ptucha) appears on each slide.
- You may freely use these slides externally, if:
  - You send me an email telling me the conference/venue/company name in advance, and which slides you wish to use.
  - You receive a positive confirmation email back from me.
  - My name (R. Ptucha) appears on each slide you use.

(c) Raymond Ptucha, [rwpeec@rit.edu](mailto:rwpeec@rit.edu)

© 2018 Ray Ptucha, Rochester Institute of Technology

2


# Agenda

- Wed, June 27
  - 9-10:30am Regression and Classification
  - 10:30-10:45pm Break
  - 10:45-12:15pm Boosting and SVM
  - 12:15-1:30pm Lunch
  - 1:30-3:30pm Neural Networks and Dimensionality Reduction
  - 3:30-5pm Hands-on Python and Machine Learning
- Thur, June 28
  - 9-10:30am Introduction to deep learning
  - 10:30-10:45pm Break
  - 10:45-12:15pm Convolutional Neural Networks
  - 12:15-1:30pm Lunch
  - 1:30-3:30pm Region and pixel-level convolutions
  - 3:30-5pm Hands-on CNNs
- Fri, June 29
  - 9-10:30am Recurrent neural networks
  - 10:30-10:45pm Break
  - 10:45-12:15pm Language and Vision
  - 12:15-1:30pm Lunch
  - 1:30-3:30pm **Graph convolutional neural networks**; Generative adversarial networks
  - 3:30-5pm Hands-on regional CNNs, RNNs


© 2018 Ray Ptucha, Rochester Institute of Technology

3


## Many Flavors of CNNs...



LeNet-5, LeCun 1989



AlexNet, Krizhevsky 2012



VGGNet, Simonyan 2014



GoogLeNet (Inception), Szegedy 2014



ResNet, He 2015




DenseNet, Huang 2017

© 2018 Ray Ptucha, Rochester Institute of Technology

4

# Image Convolution




[https://github.com/vdumoulin/conv\\_arithmetic](https://github.com/vdumoulin/conv_arithmetic)

© 2018 Ray Ptucha, Rochester Institute of Technology

5


## Max Pooling- Reducing the Size of an Image



© 2018 Ray Ptucha, Rochester Institute of Technology


6

# Convolution Neural Network (CNN) Building Block



7

## Putting it All Together




© 2018 Ray Ptucha, Rochester Institute of Technology

8

# CNN Architecture

(Not so) Toy Example



© 2018 Ray Ptucha, Rochester Institute of Technology

9


But, the vast majority of the world's problems can't be described by gridded structures such as images. Have you ever tried to do a CNN on a graph?



**Images**

**Graphs**




Convolution



Pooling




Classification




© 2018 Ray Ptucha, Rochester Institute of Technology

11


GraphCNN affords the wonderful CNN benefits to non-gridded problems such as trade, security, protein structures, weather, brain scans, etc.




Gridded



Non-Gridded



Homogeneous




Heterogeneous

(Each sample has different number vertices or edges.)


## Spatial Approaches

- Graph Kernels- comparison of local neighborhoods



P. Yanardag and S. Vishwanathan, "Deep graph kernels," in Proceedings of the 21th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining. ACM, 2015, pp. 1365–1374.

- Turn Vertices into Padded Vectors



Niepert, Mathias, Mohamed Ahmed, and Konstantin Kutzkov. "Learning Convolutional Neural Networks for Graphs." *arXiv preprint arXiv:1605.05273*(2016).

# Spectral Approaches


- Filter in a spectral domain by constructing an analogue to the DFT
  - Eigenvector decomposition of the graph Laplacian
  - Laplacian  $L = D - A$ ;
    - A is adjacency matrix,
    - D is diagonal matrix of row-wise sums of A
- Apply PCA, to get to spectral space
- Filter in PCA space (convolutions are multiplies)
- Pool in PCA space (trim out high frequencies and resample)

© 2018 Ray Ptucha, Rochester Institute of Technology

14

# Graph Convolutional Neural Network (Graph CNN)

- Replaces classic layers with graph capable alternatives.
  - Superset of CNNs.
  - CNN techniques can be transferred (e.g. SGD, BatchNorm, Dropout, Regularization).



© 2018 Ray Ptucha, Rochester Institute of Technology

15


# CNN - Convolution

2 x 2 filter with a stride of 2


$$\begin{bmatrix} 6 & 4 & 2 & 2 \\ 3 & 2 & 2 & 2 \\ 0 & 0 & 4 & 2 \\ 5 & 4 & 3 & 3 \end{bmatrix} * \begin{bmatrix} 1 & -1 \\ 1 & -1 \end{bmatrix} = \begin{bmatrix} 3 & 0 \\ 1 & 2 \end{bmatrix}$$

Vector implementation (CUDA)

Vectorized using im2col



Matrix Mult. + Reshape




© 2018 Ray Ptucha, Rochester Institute of Technology

16

# Graph-CNN - Convolution

Adjacency Matrix



Can have multiple connection types (A can be a tensor) and can have multiple features (V can be a tensor)

© 2018 Ray Ptucha, Rochester Institute of Technology


17



# Graph-CNN - Convolution

A				A				V
0	0	1	1	0	0	0	0	0.2
0	0	0	0	1	0	0	0	1.3
0	0	0	0	1	0	0	0	0.7
0	1	0	0	0	0	1	0	1.8

Replace each vertex with  $2 \times \text{itself} + 1 \times \text{incoming purple} - 1 \times \text{incoming orange}$




# Graph-CNN - Convolution

A				A				V
0	0	1	1	0	0	0	0	0.2
0	0	0	0	1	0	0	0	1.3
0	0	0	0	1	0	0	0	0.7
0	1	0	0	0	0	1	0	1.8

In Graph CNN, we will learn many such filters (like the  $[2 \ 1 \ -1]$ ) per adjacency matrix.

Replace each vertex with  $2 \times \text{itself} + 1 \times \text{incoming purple} - 1 \times \text{incoming orange}$




© 2018 Ray Ptucha, Rochester Institute of Technology

19

# Graph-CNN - Convolution

A				A				V
0	0	1	1	0	0	0	0	0.2
0	0	0	0	1	0	0	0	1.3
0	0	0	0	1	0	0	0	0.7
0	1	0	0	0	0	1	0	1.8



Update V's for incoming A's

V	AV	AV
0.2	2.5	0
1.3	0	0.2
0.7	0	0.2
1.8	1.3	0.7

$$N_{i,ac+b}^l = A_{i,a,j} V_{j,b}^l$$

Matrix Multiplication

V	AV	AV
0.2	2.5	0
1.3	0	0.2
0.7	0	0.2
1.8	1.3	0.7

$$V_{i,k}^l = f(N_{i,d}^{l-1} W_{d,k})$$

© 2018 Ray Ptucha, Rochester Institute of Technology

20

# Graph-CNN - Convolution

- We are learning the **weights** of the filters.
- We don't care how many vertices!
- Can learn several sets of weights, one for each filter.

Update V's for incoming A's

V	AV	AV
0.2	2.5	0
1.3	0	0.2
0.7	0	0.2
1.8	1.3	0.7

$$N_{i,ac+b}^l = A_{i,a,j} V_{j,b}^l$$

Matrix Multiplication

V	AV	AV
0.2	2.5	0
1.3	0	0.2
0.7	0	0.2
1.8	1.3	0.7

$$V_{i,k}^l = f(N_{i,d}^{l-1} W_{d,k})$$

© 2018 Ray Ptucha, Rochester Institute of Technology

21

## CNN – Fully Connected Layer

$$\begin{bmatrix} 6 & 2 \\ 5 & 4 \end{bmatrix} \circ \begin{bmatrix} 1 & -1 \\ -1 & 1 \end{bmatrix} = 3$$


- Matrix multiplication.
  - Parameters are learned.
- Requires fixed input shape, size, and order.
- Obtains representation vector.

© 2018 Ray Ptucha, Rochester Institute of Technology

22

## Graph-CNN – Graph Representation Vector

Turn arbitrary # vertices into a single vertex



V
0.2
1.3
0.7
1.8

M
2
1
-2
1

 $\circ V^T M = 2.1$

V
0.2
1.3
0.7
1.8

M* = softmax(M)
0.57
0.21
0.01
0.21

 $\circ V^T M^* = 0.77$


- Graphs can have varying vertices, but we often need fixed nodes for say a final classification task.
- Define a soft attention applied to vertices of graph- learn  $M$ , a linear combination of all vertices.
- This reduces all vertices to a single vertex.
- A softmax is applied to  $M$  before computing linear combination, this ensures the sum of the weights=1.

```
x = [2 1 -2 1]
M* = exp(x) ./ sum(exp(x))
[0.2 1.3 0.7 1.8] * M*
```


© 2018 Ray Ptucha, Rochester Institute of Technology

23


# CNN - Pooling



Vectorized using im2col




Max + Reshape



© 2018 Ray Ptucha, Rochester Institute of Technology


24

# Graph-CNN – Embed Pooling



- Instead of generating a single vertex, generate many vertices.
- The number of output vertices is controlled, and can simplify the model.

We now have three  $M^*$  row vectors




If FC layer has ten connections, learn ten  $M^*$  row vectors!

© 2018 Ray Ptucha, Rochester Institute of Technology

25

## Graph-CNN – Embed Pooling



- Many Graph Representation Vectors combined.
- Output Adjacency matrix calculated accordingly.
- Fixed number of output vertices.
- Independent of number of input vertices.
- Results in fully connected graph, including self connections.

© 2018 Ray Ptucha, Rochester Institute of Technology

26

## Results - Cora

- Document Classification.
  - One large graph (2,708 vertices with 1,433 features).
  - Each vertex has 1 class out of 7.
  - Vertices in the test set are removed during training.

Method	Split	Accuracy
Yang [36]	1000 test	75.7
Kipf [37]	1000 test	81.5
Monti [38]	1000 test	81.69
DCNN [15]	3-fold	86.77
Ours	1000 test	<b>86.56 ± 0.68</b>
Ours	3 fold	<b>87.55 ± 1.38</b>
Ours	10 fold	<b>89.18 ± 1.96</b>

F. Petroski Such\*, S. Sah\*, M. Dominguez, S. Pillai, Chao Zhang, Andrew Michael, N. Cahill, R. Ptucha "Robust Spatial Filtering with Graph Convolutional Neural Networks," special issue IEEE Journal of Selected Topics in Signal Processing, Volume 11, Issue 6, 2017.


© 2018 Ray Ptucha, Rochester Institute of Technology

27

## Results – NCI1 / D&D

- Chemical Compound Classification
  - Each sample is a different graph
- Varying number of vertices
  - Each sample has their own A, V

Data set	NCI1	D&D
Maximum graph size	111	5748
Average graph size	29.87	284.32
# Graphs	4110	1178
GK * [34]	62.28 ± 0.29	78.45 ± 0.26
WL * [35]	80.22 ± 0.51	77.95 ± 0.70
PSCN [1]	78.59 ± 1.89	77.12 ± 2.41
Deep GK [32]	80.31 ± 0.46	–
3×16F-3×32F-GFC32	83.69 ± 1.40	–
6×32F-GFC32	83.57 ± 1.99	–
2×64F-Pool32-FC256	84.08 ± 1.45	–
2×64F-Pool32-32F-Pool8-FC256	<b>84.45 ± 0.94</b>	81.45 ± 2.87
2×64F-Pool32-32F-Pool8-64F-FC256	83.48 ± 1.36	–
2×64F-Pool32-64F-Pool8-FC256	84.35 ± 1.00	<b>81.88 ± 3.39</b>
5-hop DCNN # [15]	62.61	–
2×64F-Pool32-32F-Pool8-FC256 #	<b>81.98 ± 0.76</b>	–




# - 3-fold experiments

F. Petroski Such\*, S. Sah\*, M. Dominguez, S. Pillai, Chao Zhang, Andrew Michael, N. Cahill, R. Ptucha "Robust Spatial Filtering with Graph Convolutional Neural Networks," special issue IEEE Journal of Selected Topics in Signal Processing, Volume 11, Issue 6, 2017.

© 2018 Ray Ptucha, Rochester Institute of Technology

29

## Graph-CNN – Local Max Pooling



- Graph embed pooling replaces each output vertex as a linear combination of all input vertices.
- What if the graph had millions of vertices?
- Enforce graph clusters where output vertices are linear combination of local neighborhood.
- Cluster generated any greedy or exhaustive method.
- Output Adjacency matrix calculated accordingly.
- Variable number of input and output vertices.

© 2018 Ray Ptucha, Rochester Institute of Technology

30

# Thank you!!

Ray Ptucha

[rwpeec@rit.edu](mailto:rwpeec@rit.edu)



<https://www.rit.edu/mil>