

# Practical Applications of AI and Machine learning in different areas within the Game Development Industry and multiple implementation approaches.

Albert Rando, RESEARCH METHODS IN COMPUTING AND IT - GMIT,  
G00330058

Professor - Dr. Martin Kenirons

**Abstract**—This paper draws a rough sketch of what the gaming industry represents in the current world and how AI and Machine Learning became almost core to it. It explains some areas in video games where AI is implemented and the different approaches used in order to maximize "human like" behaviour when required and how AI can be used to improve performance in pathfinding for the game agents.

**Index Terms**—AI, Machine Learning, Gaming, Game Design, Pathfinding, Agents, RTS, AI Behaviour.

## 1 INTRODUCTION

WE have come a long way since first video games were created back in the 1950's. The first of which was 'Tennis for Two', introduced on October 18, 1958, at Brookhaven National Laboratory, An electronic tennis game that would become the father of modern video games[1]. But what is essentially a video game? As defined by [2] video game [noun] "A game played by electronically manipulating images produced by a computer program on a monitor or other display". Born in laboratories the first video games were developed by scientists putting the computational frames on Universities to the test.

On the other hand Artificial Intelligence as a concept was born earlier culturally in the form of robots on films and comic books. Alan Turing a British Mathematician started to tread the path by suggesting that just like human process information to make decisions, machines could equally do it. However, it was not until the 1950's that computational capabilities were powerful enough, not only to perform operations but also store to commands, to do some actual practical research. AI as such was conceived as such in a famous conference presented at the Dartmouth Summer Research Project on Artificial Intelligence (DSRPAI) hosted by John McCarthy and Marvin Minsky in 1956[3].

As technology progressed very much in accordance to Moore's law, the increase in computational power allowed both fields, AI and Video Games to develop even further from the expected. As video games have grown both in scope and depth, AI has become an entwined part of it. Not only to create bots capable of defeating humans in games such as Chess or Go, but also to create better gaming experiences and more realistic behaviours in NPC's (Non-playable Characters) in video games, and more enjoyable challenges in an ever growing industry. According to a new-zoo article[4] about the gaming Industry revenue in 2017, it

is expected that 2.2 billion gamers worldwide will generate \$108.9 billion in this year's exercise, which represents a significant increase from previous years.

In this paper, we pretend to introduce some of the most common uses for AI that predominate in video games, and provide a definition as well as to explain some approaches to implement them. We will also provide an insight of how machine learning has improved both capabilities and performance of some of the proposed models and algorithms and how can they be tuned to increase outputs.

## 2 PATHFINDING

Pathfinding is a technique or a process carried by a software running in a computer from which the shortest path or route between two points is extrapolated. Pathfinding is, not only important in video games, but also in other areas such as delivery, transport services and intelligent storage among others. Pathfinding algorithms are usually, although not only, heavily based on the Dijkstra's algorithm[5] which implies what follows: Let the node starting be X. Let the distance of node Y be the distance from X to Y. Dijkstra's algorithm will assign some initial distance values and will try iteratively to improve them step by step.

However there are other complementary approaches using different techniques that seek to improve such algorithms.

### 2.1 Techniques for Pathfinding

Pathfinding is usually a two-step process: first, a graph generation algorithm followed by a Pathfinding algorithm to calculate the best path. Zeyad Adb Algfoor et al[0] published a brief but thorough compendium of the most common techniques developed during the last 10 years.

### 2.1.1 Grids

In Pathfinding grids are represented as graphs, a list of vertices or points connected by edges to represent the map, the navigation performance of which is based on its attributes. The most popular grid approaches are: regular grids and irregular grids.

Regular grids use triangles, squares and hexagons to describe tessellations of a given terrain. The most prominent of which are the following:

- 2D hexagonal Grid
- 2D Square Grid
- 2D Triangular Grid
- 3D Cubic Grid

Whereas irregular grids use different techniques to define terrain topology such as:

- Visibility Graphs
- Mesh Navigation
- Waypoints

Further information on the actual implementation of these pathfinding techniques can be found in Zeyad et al[9].

## 2.2 Using Potential Fields

In 1985, Ossama Khatib discussed a new concept in regards a real-time obstacle avoidance for manipulators and mobile Robots. He named it Artificial Potential Fields[6]. In 2008, Johan Hagelback et al.[10] used it to create a Multi-agent Potential Field-based Bot for Real-Time Strategy Games(RTS) in which objects in the map were assigned charges (like magnetic chargers positive or negative) and such charges were used as forces to attract the agents to specific destination or to repel such agents to avoid collisions or to delimit the terrain.

They proposed two-different scenarios using Open real-time strategy (ORTS) engine to deploy the bot. In the first scenario the task of the bot was to recollect as many resource as possible in a limited amount of time. To do so Johan Hagelback et al. had 20 agents (workers) using a finite state machine (FSM) to define their behaviour and assigned the charges to the agents, to the resource gathering point, the base were resources had to be delivered and "sheep" moving around the map to provide moving obstacles. Even though the results shown that the bot was prone to disconnect from the game in some occasions, it beat bots developed in previous years improving the average of resources gathered.

The second scenario, using ORTS, was a tank game where two players had a number of tanks and bases and the goal of the game was to destroy both enemy bases and tanks. After outlining the rules for the game agents, they assigned the charges accordingly and programmed the bot to avoid situating tanks in the middle of enemy clusters. The results of such scenario, tested against other bots, were of a 98% of victory rate over their opponents.

## 2.3 Aesthetics in Pathfinding

While most of the algorithms focuses lies on obtaining the best suitable path, such path does not always meet the expectations by using an unrealistic behaviour that differs greatly of what a humans would perform. In order to find more "human-like" behaviour in Pathfinding some authors such as Coleman, R.[7] introduce the idea of Aesthetics in it.

The experiment's approach was to use Mandelbrot's Fractal Dimension Analysis[8] to determine the aesthetics level of certain paths, an A\* Pathfinding algorithm was used to create the path and then tweaked to reward paths that were obstacle-prone to simulate a behaviour of "stealthiness". By doing so the levels of aesthetics were higher than in those were paths were determined as best suited by the algorithm.

## 2.4 Machine Learning

Subsection text here.

## 3 DEFINING BEHAVIOUR

Subsection text here.

## 4 PERFORMANCE

Subsection text here.

## 5 THE FUTURE OF AI IN GAMES

Subsection text here.

## 6 CONCLUSION

Subsection text here.

## REFERENCES

- [1] Brookhaven National Laboratory, "The First Video Game?", Brookhaven National Laboratory, 1958. [Online] Available: <https://www.bnl.gov/about/history/firstvideo.php>
- [2] Oxford Dictionaries, "Video Game", 2017. [Online] Available: [https://en.oxforddictionaries.com/definition/video\\_game](https://en.oxforddictionaries.com/definition/video_game)
- [3] John McCarthy, Marvin L. Minsky, Nathaniel Rochester, and Claude E. Shannon, "A Proposal for the Dartmouth Summer Research Project on Artificial Intelligence", August 31, 1955.
- [4] Emma McDonald, "The Global Games Market Will Reach \$108.9 Billion in 2017 With Mobile Taking 42", April 20, 2017. [Online] Available: <https://newzoo.com/insights/articles/the-global-games-market-will-reach-108-9-billion-in-2017-with-mobile-taking-42/>
- [5] Dijkstra, E. W. (1959). "A note on two problems in connexion with graphs". *Numerische Mathematik*. 1: 269271. doi:10.1007/BF01386390.
- [6] O. Khatib. "Real-time obstacle avoidance for manipulators and mobile robots". *The international Journal of Robotics Research*, Vol 5, no.1, pp. 90-98, 1986.
- [7] Ron Coleman, Fractal Analysis of Stealthy Pathfinding Aesthetics, *International Journal of Computer Games Technology*, vol. 2009, Article ID 670459, 7 pages, 2009.

- [8] B. Mandelbrot, *The Fractal Geometry of Nature*, W. H. Freeman, San Francisco, Calif, USA, 1982
- [9] Zeyad Abd Algfoor, Mohd Shahrizal Sunar, and Hoshang Kolivand, "A Comprehensive Study on Pathfinding Techniques for Robotics and Video Games" *International Journal of Computer Games Technology*, vol. 2015, Article ID 736138, 11 pages, 2015.
- [10] Johan Hagelbck and Stefan J. Johansson, *A Multiagent Potential Field-Based Bot for Real-Time Strategy Games*, *International Journal of Computer Games Technology*, vol. 2009, Article ID 910819, 10 pages, 2009.
- [11] F. Dignum, J. Westra, W. A. van Doesburg, and M. Harbers, "Games and Agents: Designing Intelligent Gameplay" *International Journal of Computer Games Technology*, vol. 2009, Article ID 837095, 18 pages, 2009.
- [12] Cedric Beaulac and Fabrice Larribe, "Narrow Artificial Intelligence with Machine Learning for Real-Time Estimation of a Mobile Agents Location Using Hidden Markov Models" *International Journal of Computer Games Technology*, vol. 2017, Article ID 4939261, 10 pages, 2017.
- [13] Firas Safadi, Raphael Fonteneau, and Damien Ernst, "Artificial Intelligence in Video Games: Towards a Unified Framework" *International Journal of Computer Games Technology*, vol. 2015, Article ID 271296, 30 pages, 2015.

**Albert Rando** Student in GMIT, currently attending fourth year in BSC in Software Development.