太重集团
TZCO

TZPZ20KEF
TZPZ20KEF-L

Platform Kerja Udara Dengan Lengan Lurus 20 Meter



Performa luar biasa

- Kemampuan melintasi medan yang tangguh dan mudah menangani berbagai kondisi kerja kompleks
- Desain poros mengambang meningkatkan kinerja off-road dan kemampuan beradaptasi pada berbagai medan kerja
- Sistem kontrol sensitif beban dengan respons yang stabil, akurat, dan cepat, sangat efisien dan hemat energi

Biaya operasional rendah

- Keandalan yang tinggi dan biaya perawatan rendah
- Dapat diangkut menggunakan truk derek, biaya transportasi yang rendah.
- Kompatibilitas komponen yang tinggi, kebutuhan akan suku cadang menjadi lebih sedikit


Keuntungan tinggi


- Investasi rendah, biaya operasional dan pemeliharaan rendah, serta pengembalian investasi yang tinggi

TZPZ20KEF/TZPZ20KEF-L Platform Kerja Udara Dengan Lengan Lurus 20 Meter

●Konfigurasi Standar

-Poros mengambang/ Sistem penggerak roda empat/ Rem empat roda/ Kemudi dua roda
-Pelepasan mekanis untuk rem berjalan
-Kontrol hidrolik proportional/ Kontrol tuas proportional
-Sudut kemiringan maksimum yang diperbolehkan 5°
-Rotasi struktur atas 360° kontinu
-Layar pintar 5 inci
-Sistem diagnosa kerusakan
-Sistem penimbangan platform
-Sistem perlindungan kemiringan
-sistem penghentian darurat
-sistem penurunan darurat
-Perangkat anti-jepit
-Platform kerja perataan hidrolik/ Rotasi platform kerja
-Pemeriksaan belakang/ konfirmasi berkendara
-Lampu peringatan keselamatan
-Klakson dan bel peringatan keselamatan
-Siaran suara
-Pemantauan jarak jauh gps





●Fitur Opsional

-Kabel daya AC ke platform
-Ban padat
-Lampu kerja platform
-Perangkat anti benturan
-Kontrol jarak jauh nirkabel

●Parameter Teknis Utama

Type	Item	Unit	TZPZ20KEF TZPZ20KEF-L
Dimensions	Overall length	m	10.32
	Overall width	m	2.44
	Overall height	m	2.75
	Max. platform height	m	19.73
	Max. working height	m	21.73
	Max. horizontal reach (restricted/unrestricted)	m	11.8/13
	Max. horizontal working range (restricted/unrestricted)	m	12.4/13.6
	Platform dimension (LxWxH)	m	2.44 x 0.91 x 1.1
	Wheelbase D	m	2.49
	Ground clearance	m	0.38
	Tire	-	315/55-20 EL79 (Solid)
Weight parameters	Total weight	kg	9795 (Lead-Acid) / 9410 (Lithium)
Performance parameters	Platform rated load (restricted/unrestricted)	kg	340/250
	Max. platform occupants (restricted/unrestricted)	worker	2
	Platform rotation angle	°	180
	Turntable rotation angle	°	360 continous
	Max. allowable tilt angle	°	5
	Turntable tail swing	m	2.12
	Travel speed (stowed)	km/h	0 - 4.8
	Travel speed (raised)	km/h	0 - 1.1
	Grade-ability (4WD)	%	40
	Turning radius (inner wheel/outer wheel)	m	2.4/4.86
	Max. allowable side force	N	400
	Max. allowable wind speed	m/s	12.5
Power parameters	Drive x Steer	-	4WD x 2WS
	Battery specification	V/Ah	48V 530Ah (Lead-Acid) / 48V 420Ah (Lithium)
	Charger (output voltage/output current)	V/A	48/100
	Hydraulic oil tank capacity	L	180