


```

# compare whether we could replicate the factor returns from the existing Benchmark
benchmark = Benchmark[['Date', 'BP']].copy(deep=True)
benchmark['Date'] = pd.to_datetime(benchmark['Date'].astype(str), format='%Y%m%d')
benchmark['Date'] = benchmark['Date'].apply(lambda x:x.strftime('%Y%m'))

idx_t_start = Date_Unique.index(int(benchmark['Date'].iloc[0]))
idx_t_end = Date_Unique.index(int(benchmark['Date'].iloc[-1]))

test_factor = BM_Factor_Sort[idx_t_start:idx_t_end+1]
test_Qspread = BM_Qspread[idx_t_start:idx_t_end+1]
test_long = BM_RET_Sort_top[idx_t_start:idx_t_end+1]
test_short = BM_RET_Sort_bottom[idx_t_start:idx_t_end+1]

sp500 = SP500[idx_t_start:idx_t_end+1]

list_nfirms = []
list_long = []
list_short = []

for idx_t in range(len(test_factor)):
    list_nfirms.append(len(test_factor[idx_t]))

for idx_t in range(len(test_long)):
    list_long.append(np.nanmean(test_long[idx_t]['trtlm']))
    list_short.append(np.nanmean(test_short[idx_t]['trtlm']))

ret_sp500 = np.exp(np.cumsum(np.log(1+sp500['ret_sp500']))) - 1
ret_Qspread = np.exp(np.cumsum(np.log(1+np.array(test_Qspread)/100))) - 1
ret_Long = np.exp(np.cumsum(np.log(1+np.array(list_long)/100))) - 1
ret_Short = np.exp(np.cumsum(np.log(1+np.array(list_short)/100))) - 1

plt.figure(figsize=(10,22))
plt.subplot(4,1,1) # multiple plots in one figure
xvalues = [dt.datetime.strptime(d,"%Y%m").date() for d
            in np.asarray(benchmark['Date']).astype(str)]
plt.plot(xvalues, list_nfirms, '-m', label="The number of firms used at each time")
#plt.legend(loc='upper left')
plt.xlabel('Date')
plt.ylabel('Number')
plt.grid(True)
plt.title('The number of firms used at each time')

plt.subplot(4,1,2)
plt.plot(xvalues, test_Qspread, '-m', label="Replication")
plt.plot(xvalues, benchmark['BP'].values, '-b', label="Benchmark")
plt.legend(loc='upper left')
plt.xlabel('Date')
plt.ylabel('%')
plt.grid(True)
plt.title('QSpread of replicatation and benchmark for the factor')

plt.subplot(4,1,3)
plt.plot(xvalues, list_long, '-m', label="Long")
plt.plot(xvalues, list_short, '-b', label="Short")
plt.legend(loc='lower right')
plt.xlabel('Date')
plt.ylabel('%')
plt.grid(True)
plt.title('Long and Short of the QSpread')

plt.subplot(4,1,4)
plt.plot(xvalues, ret_sp500, '-m', label="SP500")




```


```

plt.plot(xvalues, ret_Qspread, '-b', label="Factor QSpread")
plt.plot(xvalues, ret_Long, '-g', label="Factor Long-Leg")
plt.plot(xvalues, ret_Short, '-r', label="Factor Short-Leg")
plt.legend(loc='lower right')
plt.xlabel('Date')
plt.ylabel('%')
plt.grid(True)
plt.title('SP500 and Factor QSpread')

plt.show()

```





Q2:

Compare the replication to the benchmark

Compute the correlation coefficients for each replicated factor with its benchmark;

Pick the same period of the benchmark;

The factor to be tested: MV, BM, HL1M

The criteria is a correlation coefficient greater than 0.9 (if the correlation is negative, take the inverse)

```
In [7]: from scipy import stats
list_factors = ['MV', 'BM', 'HL1M', 'S&P500']
test_MV_Qspread = MV_Qspread[idx_t_start:idx_t_end+1]
test_BM_Qspread = BM_Qspread[idx_t_start:idx_t_end+1]
test_HL1M_Qspread = HL1M_Qspread[idx_t_start:idx_t_end+1]

list_corr = []
list_corr.append(stats.pearsonr(test_MV_Qspread, Benchmark['LogMktCap'])[0])
list_corr.append(stats.pearsonr(test_BM_Qspread, Benchmark['BP'])[0])
list_corr.append(stats.pearsonr(test_HL1M_Qspread, Benchmark['HL1M'])[0])
```

```
df_corr = pd.DataFrame(list(zip(list_factors, list_corr)), columns = ['Factor', 'Corr'])
df_corr
```

```
Out[7]:
```

	Factor	Corr
0	MV	0.992169
1	BM	0.973885
2	HL1M	0.971786

Q3:

```
In [8]: list_mean = []
list_std = []
list_sr = []
list_skew = []
list_kurt = []
list_max = []
list_min = []
list_acf1 = []
list_acf12 = []
list_acf24 = []

list_test_factors = [test_MV_Qspread, test_BM_Qspread,
                     test_HL1M_Qspread, sp500['ret_sp500']]

for idx in range(len(list_test_factors)):
    list_mean.append(np.nanmean(list_test_factors[idx]))
    list_std.append(np.nanstd(list_test_factors[idx]))
    list_sr.append(np.sqrt(12)*list_mean[idx]/list_std[idx])
    list_skew.append(stats.skew(list_test_factors[idx]))
    list_kurt.append(stats.kurtosis(list_test_factors[idx]))
    list_max.append(np.nanmax(list_test_factors[idx]))
    list_min.append(np.nanmin(list_test_factors[idx]))
    list_acf1.append(sm.tsa.acf(list_test_factors[idx], nlags=24, fft=False)[1])
    list_acf12.append(sm.tsa.acf(list_test_factors[idx], nlags=24, fft=False)[12])
    list_acf24.append(sm.tsa.acf(list_test_factors[idx], nlags=24, fft=False)[24])

df_table = pd.DataFrame(list(zip(list_mean, list_std, list_sr, list_skew, list_kurt,
                                list_max, list_min, list_acf1, list_acf12, list_acf24),
                             columns = ['Mean', 'STD', 'Sharpe Ratio', 'Skewness', 'Kurtosis',
                                         'Max', 'Min', 'ACF1', 'ACF12', 'ACF24']))

df_table.index = list_factors
df_table.T
```

```
Out[8]:
```

	MV	BM	HL1M	S&P500
Mean	-0.351353	0.380835	0.792846	0.007414
STD	3.989772	4.006618	3.607656	0.044229
Sharpe Ratio	-0.305060	0.329268	0.761297	0.580661
Skewness	-1.080343	0.309535	1.286733	-0.727039
Kurtosis	9.677470	4.671547	5.748761	2.097639
Max	19.610220	23.844838	20.645740	0.131767

Min -30.725582 -18.943367 -9.717614 -0.217630

ACF1 0.172911 0.164694 -0.129980 0.023915

ACF12 0.140895 0.014665 -0.010097 0.034097

ACF24 0.064719 -0.022511 0.070606 0.050344

```
In [9]: df_test_factor = pd.DataFrame(list(zip(test_MV_Qspread, test_BM_Qspread,
                                             test_HL1M_Qspread, sp500['ret_sp500'])), columns = list_factors)

pd.DataFrame(np.corrcoef(df_test_factor.T), columns = list_factors,
              index = list_factors)
```

```
Out[9]:
```

	MV	BM	HL1M	S&P500
MV	1.000000	-0.731410	-0.469961	-0.328232
BM	-0.731410	1.000000	0.410794	0.187299
HL1M	-0.469961	0.410794	1.000000	0.340829
S&P500	-0.328232	0.187299	0.340829	1.000000

Q4:

```
In [10]: list_mean = []
list_tstats = []
list_pvalue = []

for idx in range(len(list_test_factors)):
    list_mean.append(np.nanmean(list_test_factors[idx]))
    list_tstats.append(stats.ttest_1samp(list_test_factors[idx], 0)[0])
    list_pvalue.append(stats.ttest_1samp(list_test_factors[idx], 0)[1])

df_table_test = pd.DataFrame(list(zip(list_mean, list_tstats, list_pvalue)),
                              columns = ['Mean', 'T Stats', 'p-Value'])
df_table_test.index = list_factors
df_table_test
```

```
Out[10]:
```

	Mean	T Stats	p-Value
MV	-0.351353	-1.828242	0.068204
BM	0.380835	1.973318	0.049098
HL1M	0.792846	4.562493	0.000007
S&P500	0.007414	3.479930	0.000553

```
In [ ]:
```