

Java

Thread

Multitasking

- Multitasking allows several activities to occur concurrently on the computer
- Levels of multitasking:
 - **Process-based multitasking**
 - Allows programs (processes) to run concurrently
 - **Thread-base multitasking (multithreading)**
 - Allows parts of the same process (threads) to run concurrently

Multitasking

- Advantages of multithreading over process-based multitasking
 - Threads share the same address space
 - Context switching between threads is usually inexpensive
 - Communication between thread is usually inexpensive
- Java supports ***thread-based multitasking*** and provides high-level facilities for ***multithreaded programming***

Main Thread

- When a Java program starts up, one thread begins running immediately
- This is called the ***main thread*** of the program
- It is the thread from which the child threads will be spawned
- Often, it must be the last thread to finish execution

Main Thread

```
3 public class MainThread {
4     public static void main(String[] args) {
5         Thread t = Thread.currentThread();
6         System.out.println("Current thread: " + t);
7         // change the name of the thread
8         t.setName("My Thread");
9         System.out.println("After name change: " + t);
10        try
11        {
12            for(int n = 5; n > 0; n--)
13            {
14                System.out.println(n);
15                Thread.sleep(1000);
16            }
17        } catch (InterruptedException e)
18        {
19            System.out.println("Main thread interrupted");
20        }
21    }
22 }
```

How to create Thread

1. By implementing ***Runnable*** Interface
 2. By extending the ***Thread*** class itself
- *Implementing Runnable*
 - Need to implement the public void run() method
 - *Extending Thread*
 - Need to override the public void run() method
 - Which one is better ?

Implementing Runnable

```
3  class NewThread1 implements Runnable
4  {
5      Thread t;
6      NewThread1() {
7          t = new Thread(this, "Runnable Thread");
8          t.start();
9      }
10     // This is the entry point for the thread.
11     public void run() {
12         try {
13             for(int i = 5; i > 0; i--) {
14                 System.out.println("Child Thread: " + i);
15                 Thread.sleep(500);
16             }
17         } catch (InterruptedException e) {
18             System.out.println("Child interrupted.");
19         }
20         System.out.println("Exiting child thread.");
21     }
22 }
23
24 public class RunnableThread {
25     public static void main(String[] args) {
26         new NewThread1();
27     }
28 }
```


Extending Thread

```
3  class NewThread2 extends Thread
4  {
5      NewThread2() {
6          super("Extends Thread");
7          start();
8      }
9      // This is the entry point for the thread.
10     public void run() {
11         try {
12             for(int i = 5; i > 0; i--) {
13                 System.out.println("Child Thread: " + i);
14                 Thread.sleep(500);
15             }
16         } catch (InterruptedException e) {
17             System.out.println("Child interrupted.");
18         }
19         System.out.println("Exiting child thread.");
20     }
21 }
22
23 public class ExtendsThread {
24     public static void main(String[] args) {
25         new NewThread2();
26     }
27 }
```


Multiple Threads

- It is possible to create more than one thread inside the main
- In multiple threads, often you will want the main thread to finish last. This is accomplished by
 - using a large delay in the main thread
 - using the **join()** method
- Whether a thread has finished or not can be known using **isAlive()** method
- **Example:** *MultipleThreads.java, JoinAliveThreads.java*

Thread States



Thread Pool

- Thread Pools are useful when you need to limit the number of threads running in your application
 - Performance overhead starting a new thread
 - Each thread is also allocated some memory for its stack
- Instead of starting a new thread for every task to execute concurrently, the task can be passed to a thread pool
 - As soon as the pool has any idle threads the task is assigned to one of them and executed

Thread Pool

- Thread pools are often used in multi threaded servers
 - Each connection arriving at the server via the network is wrapped as a task and passed on to a thread pool
 - The threads in the thread pool will process the requests on the connections concurrently
- Java provides Thread Pool implementation with ***java.util.concurrent.ExecutorService***

ExecutorService

```
3 import java.util.concurrent.ExecutorService;
4 import java.util.concurrent.Executors;
5 import java.util.concurrent.TimeUnit;
6
7 public class ExecutorServiceTest {
8     public static void main(String[] args) throws Exception{
9         ExecutorService executorService = Executors.newFixedThreadPool(10);
10
11         for (int i = 0; i < 20; i++) {
12             executorService.execute(new Runnable() { // execute or submit
13                 public void run() {
14                     System.out.println("Running task");
15                     for (int j = 5; j > 0; j--) {
16                         System.out.println(j);
17                     }
18                 }
19             });
20         }
21         executorService.shutdown();
22         executorService.awaitTermination(1, TimeUnit.MINUTES);
23         System.out.println(executorService);
24     }
25 }
```

Synchronization

- When two or more threads need access to a **shared resource**, they need some way to ensure that the resource will be used by only one thread at a time
- The process by which this is achieved is called **synchronization**
- Key to synchronization is the concept of the **monitor**
- A monitor is an object that is used as a mutually exclusive lock
 - Only one thread can own a monitor at a given time

Synchronization

- When a thread acquires a lock, it is said to have entered the monitor
- All other threads attempting to enter the locked monitor will be suspended until the first thread exits the monitor
- These other threads are said to be waiting for the monitor

Synchronization

- Two way to achieve synchronization.
- Synchronized method

synchronized void call(String msg) { }

- Synchronized block

***public void run() {
 synchronized(target) { target.call(msg); }
}***

- ***Example:*** *SynchronizedBlock.java, SynchronizedMethod.java, SynchronizationLock.java*

Inter Thread Communication

- One way is to use polling
 - a loop that is used to check some condition repeatedly
 - Once the condition is true, appropriate action is taken
- Java includes an elegant inter thread communication mechanism via the **wait()**, **notify()** and **notifyAll()** methods
- These methods are implemented as **final methods** in **Object**, so all classes have them
- **All three methods can be called only from within a synchronized method**

Inter Thread Communication

- ***wait()***
 - tells the calling thread to give up the monitor and go to sleep until some other thread enters the same monitor and calls `notify()`
- ***notify()***
 - wakes up the first thread that called `wait()` on same object
- ***notifyAll()***
 - wakes up all the threads that called `wait()` on same object. The highest priority thread will run first
- ***Example: IncorrectPC.java, CorrectPC.java, PCBlockingQueue.java***

Suspend, Resume and Stop

- Suspend
 - *Thread t; t.suspend();*
- Resume
 - *Thread t; t.resume();*
- Stop
 - *Thread t; t.stop();*
 - Cannot be resumed later
- suspend and stop can sometimes cause serious system failures
- **Example:** *SuspendResume.java*