

Contents

1 Data structures	2	3.10 Fast Hadamard Transform	14
1.1 Segment tree	2	3.11 Karatsuba	14
1.2 Segment tree - Lazy propagation	2	3.12 Modular inverse	15
1.3 Segment tree - Persistence	2	3.13 Chinese remainder theorem (Euge)	15
1.4 Segment tree - 2D	3	3.14 Mobius	15
1.5 Sparse table (static RMQ)	3	3.15 Linear Recurrence	15
1.6 Wavelet tree	3	3.16 Gaussian Elimination	16
1.7 STL extended set	4	3.17 Simplex	16
1.8 Treap (as BST)	4	4 Geometry	16
1.9 Treap (implicit key)	4	4.1 Point	16
1.10 Convex hull trick (static)	5	4.2 Line	16
1.11 Convex hull trick (dynamic)	6	4.3 Circle	17
1.12 Max Queue	6	4.4 Polygon	18
1.13 Union Find	6	4.5 Plane	19
2 Graphs	6	4.6 Convex hull	19
2.1 Bellman-Ford	6	5 Strings	19
2.2 Floyd-Warshall	6	5.1 KMP	19
2.3 Strongly connected components (+ 2-SAT)	7	5.2 Z function	20
2.4 Articulation - Bridges - Biconnected	7	5.3 Manacher	20
2.5 Chu-Liu (minimum spanning arborescence)	8	5.4 Aho-Corasick	20
2.6 LCA - Binary Lifting	8	5.5 Suffix automaton	21
2.7 Heavy-Light decomposition	8	5.6 Suffix array	21
2.8 Centroid decomposition	9	5.7 LCP (Longest Common Prefix)	21
2.9 Eulerian path	9	5.8 Suffix Tree (Ukkonen's algorithm)	21
2.10 Dynamic connectivity	9	5.9 Hashing	22
2.11 Edmond's blossom (matching in general graphs)	10	6 Flow	22
3 Math	11	6.1 Matching (slower)	22
3.1 Identities	11	6.2 Matching (Hopcroft-Karp)	22
3.2 Theorems	11	6.3 Hungarian	23
3.3 Integer floor division	11	6.4 Dinic	23
3.4 Extended Euclid	11	6.5 Min cost max flow	24
3.5 Pollard's rho	11	7 Other	24
3.6 Simpson's rule	12	7.1 Mo's algorithm	24
3.7 Polynomials	12	7.2 Divide and conquer DP optimization	25
3.8 Bairstow	13	7.3 Dates	25
3.9 Fast Fourier Transform	14	7.4 C++ stuff	25
		7.5 Max number of divisors up to 10^n	25

1 Data structures

1.1 Segment tree

```

1 #define oper min
2 #define NEUT INF
3 struct STree { // segment tree for min over integers
4     vector<int> st;int n;
5     STree(int n): st(4*n+5,NEUT), n(n) {}
6     void init(int k, int s, int e, int *a){
7         if(s+1==e){st[k]=a[s];return;}
8         int m=(s+e)/2;
9         init(2*k,s,m,a);init(2*k+1,m,e,a);
10        st[k]=oper(st[2*k],st[2*k+1]);
11    }
12    void upd(int k, int s, int e, int p, int v){
13        if(s+1==e){st[k]=v;return;}
14        int m=(s+e)/2;
15        if(p<m)upd(2*k,s,m,p,v);
16        else upd(2*k+1,m,e,p,v);
17        st[k]=oper(st[2*k],st[2*k+1]);
18    }
19    int query(int k, int s, int e, int a, int b){
20        if(s>=b||e<=a)return NEUT;
21        if(s>=a&&e<=b)return st[k];
22        int m=(s+e)/2;
23        return oper(query(2*k,s,m,a,b),query(2*k+1,m,e,a,b));
24    }
25    void init(int *a){init(1,0,n,a);}
26    void upd(int p, int v){upd(1,0,n,p,v);}
27    int query(int a, int b){return query(1,0,n,a,b);}
28 }; // usage: STree rmq(n);rmq.init(x);rmq.upd(i,v);rmq.query(s,e);

```

1.2 Segment tree - Lazy propagation

```

1 struct STree { // example: range sum with range addition
2     vector<int> st,lazy;int n;
3     STree(int n): st(4*n+5,0), lazy(4*n+5,0), n(n) {}
4     void init(int k, int s, int e, int *a){
5         lazy[k]=0; // lazy neutral element
6         if(s+1==e){st[k]=a[s];return;}
7         int m=(s+e)/2;
8         init(2*k,s,m,a);init(2*k+1,m,e,a);
9         st[k]=st[2*k]+st[2*k+1]; // operation
10    }

```

```

11 void push(int k, int s, int e){
12     if(!lazy[k])return; // if neutral, nothing to do
13     st[k]+=(e-s)*lazy[k]; // update st according to lazy
14     if(s+1<e){ // propagate to children
15         lazy[2*k]+=lazy[k];
16         lazy[2*k+1]+=lazy[k];
17     }
18     lazy[k]=0; // clear node lazy
19 }
20 void upd(int k, int s, int e, int a, int b, int v){
21     push(k,s,e);
22     if(s>=b||e<=a)return;
23     if(s>=a&&e<=b){
24         lazy[k]+=v; // accumulate lazy
25         push(k,s,e);return;
26     }
27     int m=(s+e)/2;
28     upd(2*k,s,m,a,b,v);upd(2*k+1,m,e,a,b,v);
29     st[k]=st[2*k]+st[2*k+1]; // operation
30 }
31 int query(int k, int s, int e, int a, int b){
32     if(s>=b||e<=a)return 0; // operation neutral
33     push(k,s,e);
34     if(s>=a&&e<=b)return st[k];
35     int m=(s+e)/2;
36     return query(2*k,s,m,a,b)+query(2*k+1,m,e,a,b); // operation
37 }
38 void init(int *a){init(1,0,n,a);}
39 void upd(int a, int b, int v){upd(1,0,n,a,b,v);}
40 int query(int a, int b){return query(1,0,n,a,b);}
41 }; // usage: STree rmq(n);rmq.init(x);rmq.upd(s,e,v);rmq.query(s,e);

```

1.3 Segment tree - Persistence

```

1 #define oper min
2 #define NEUT INF
3 struct STree { // persistent segment tree for min over integers
4     vector<int> st,l,r;int n,rt,sz;
5     STree(int n): st(24*n,NEUT),l(24*n,0),r(24*n,0),n(n),rt(0),sz(1){}
6     // be careful with memory! 4*n+q*log(n) . 24*n should be enough
7     int init(int s, int e, int *a){ // not necessary in most cases
8         int k=sz++;
9         if(s+1==e){st[k]=a[s];return k;}
10        int m=(s+e)/2;

```

```

11     l[k]=init(s,m,a);r[k]=init(m,e,a);
12     st[k]=oper(st[l[k]],st[r[k]]);
13     return k;
14 }
15 int upd(int k, int s, int e, int p, int v){
16     int nk=sz++;l[nk]=l[k];r[nk]=r[k];
17     if(s+1==e){st[nk]=v;return nk;}
18     int m=(s+e)/2;
19     if(p<m)l[nk]=upd(l[k],s,m,p,v);
20     else r[nk]=upd(r[k],m,e,p,v);
21     st[nk]=oper(st[l[nk]],st[r[nk]]);
22     return nk;
23 }
24 int query(int k, int s, int e, int a, int b){
25     if(s>=b||e<=a)return NEUT;
26     if(s>=a&&e<=b)return st[k];
27     int m=(s+e)/2;
28     return oper(query(l[k],s,m,a,b),query(r[k],m,e,a,b));
29 }
30 int init(int *a){return init(0,n,a);}
31 int upd(int k, int p, int v){return rt=upd(k,0,n,p,v);}
32 int upd(int p, int v){return upd(rt,p,v);} // update on last root
33 int query(int k, int a, int b){return query(k,0,n,a,b);}
34 }; // usage: STree rmq(n);root=rmq.init(x);new_root=rmq.upd(root,i,v);rmq.
    query(root,s,e);

```

1.4 Segment tree - 2D

```

1 int n,m;
2 int a[MAXN][MAXN],st[2*MAXN][2*MAXN];
3 void build(){
4     forn(i,n)forn(j,m)st[i+n][j+m]=a[i][j];
5     forn(i,n)for(int j=m-1;j>=1;j--){
6         st[i+n][j]=op(st[i+n][j<<1],st[i+n][j<<1|1]);
7     }
8     for(int i=n-1;i>=0;i--)for(int j=2*m;j>=1;j--){
9         st[i+n][j]=op(st[i+n][j<<1],st[i+n][j<<1|1]);
10    }
11 void upd(int x, int y, int v){
12     st[x+n][y+m]=v;
13     for(int j=y+m;j>1;j>=1)st[x+n][j>>1]=op(st[x+n][j],st[x+n][j^1]);
14     for(int i=x+n;i>1;i>=1)for(int j=y+m;j>=1;j--){
15         st[i+n][j]=op(st[i+n][j],st[i^1][j]);
16    }
17 int query(int x0, int x1, int y0, int y1){

```

```

17 int r=NEUT;
18 for(int i0=x0+n,i1=x1+n;i0<i1;i0>=1,i1>=1){
19     int t[4],q=0;
20     if(i0&1)t[q++]=i0++;
21     if(i1&1)t[q++]--;i1--;
22     forn(k,q)for(int j0=y0+m,j1=y1+m;j0<j1;j0>=1,j1>=1){
23         if(j0&1)r=op(r,st[t[k]][j0++]);
24         if(j1&1)r=op(r,st[t[k]][--j1]);
25     }
26 }
27 return r;
28 }

```

1.5 Sparse table (static RMQ)

```

1 #define oper min
2 int st[K][1<<K];int n; // K such that 2^K>n
3 void st_init(int *a){
4     forn(i,n)st[0][i]=a[i];
5     forr(k,1,K)forn(i,n-(1<<k)+1)
6         st[k][i]=oper(st[k-1][i],st[k-1][i+(1<<(k-1))]);
7 }
8 int st_query(int s, int e){
9     int k=31-__builtin_clz(e-s);
10    return oper(st[k][s],st[k][e-(1<<k)]);
11 }

```

1.6 Wavelet tree

```

1 struct WT {
2     vector<int> wt[1<<20];int n;
3     void init(int k, int s, int e){
4         if(s+1==e)return;
5         wt[k].clear();wt[k].pb(0);
6         int m=(s+e)/2;
7         init(2*k,s,m);init(2*k+1,m,e);
8     }
9     void add(int k, int s, int e, int v){
10        if(s+1==e)return;
11        int m=(s+e)/2;
12        if(v<m)wt[k].pb(wt[k].back()),add(2*k,s,m,v);
13        else wt[k].pb(wt[k].back()+1),add(2*k+1,m,e,v);
14    }
15 int query0(int k, int s, int e, int a, int b, int i){

```

```

16     if(s+1==e)return s;
17     int m=(s+e)/2;
18     int q=(b-a)-(wt[k][b]-wt[k][a]);
19     if(i<q)return query0(2*k,s,m,a-wt[k][a],b-wt[k][b],i);
20     else return query0(2*k+1,m,e,wt[k][a],wt[k][b],i-q);
21 }
22 void upd(int k, int s, int e, int i){
23     if(s+1==e)return;
24     int m=(s+e)/2;
25     int v0=wt[k][i+1]-wt[k][i],v1=wt[k][i+2]-wt[k][i+1];
26     if(!v0&&!v1)upd(2*k,s,m,i-wt[k][i]);
27     else if(v0&&v1)upd(2*k+1,m,e,wt[k][i]);
28     else if(v0)wt[k][i+1]--;
29     else wt[k][i+1]++;
30 }
31 void init(int _n){n=_n;init(1,0,n);} // (values in range [0,n))
32 void add(int v){add(1,0,n,v);}
33 int query0(int a, int b, int i){ // ith element in range [a,b)
34     return query0(1,0,n,a,b,i); // (if it was sorted)
35 }
36 void upd(int i){ // swap positions i,i+1
37     upd(1,0,n,i);
38 }
39 };

```

1.7 STL extended set

```

1 #include<ext/pb_ds/assoc_container.hpp>
2 #include<ext/pb_ds/tree_policy.hpp>
3 using namespace __gnu_pbds;
4 typedef tree<int,null_type,less<int>,rb_tree_tag,
5     tree_order_statistics_node_update> ordered_set;
6 // find_by_order(i) -> iterator to ith element
7 // order_of_key(k) -> position (int) of lower_bound of k

```

1.8 Treap (as BST)

```

1 typedef struct item *pitem;
2 struct item {
3     int key,pr,cnt;
4     pitem l,r;
5     item(int key):key(key),pr(rand()),cnt(1),l(0),r(0) {}
6 };
7 int cnt(pitem t){return t?t->cnt:0;}

```

```

8 void upd_cnt(pitem t){if(t)t->cnt=cnt(t->l)+cnt(t->r)+1;}
9 void split(pitem t, int key, pitem& l, pitem& r){ // l: < key, r: >= key
10     if(!t)l=r=0;
11     else if(key<t->key)split(t->l,key,l,t->l),r=t;
12     else split(t->r,key,t->r,r),l=t;
13     upd_cnt(t);
14 }
15 void insert(pitem& t, pitem it){
16     if(!t)t=it;
17     else if(it->pr>t->pr)split(t,it->key,it->l,it->r),t=it;
18     else insert(it->key<t->key?t->l:t->r,it);
19     upd_cnt(t);
20 }
21 void merge(pitem& t, pitem l, pitem r){
22     if(!l||!r)t=l?l:r;
23     else if(l->pr>r->pr)merge(l->r,l->r,r),t=l;
24     else merge(r->l,l,r->l),t=r;
25     upd_cnt(t);
26 }
27 void erase(pitem& t, int key){
28     if(t->key==key)merge(t,t->l,t->r);
29     else erase(key<t->key?t->l:t->r,key);
30     upd_cnt(t);
31 }
32 pitem kth(pitem t, int k){
33     if(!t)return 0;
34     if(k==cnt(t->l))return t;
35     return k<cnt(t->l)?kth(t->l,k):kth(t->r,k-cnt(t->l)-1);
36 }
37 pair<int,int> lb(pitem t, int key){ // position and value of lower_bound
38     if(!t)return mp(0,1<<30); // (special value)
39     if(key>t->key){
40         auto w=lb(t->r,key);w.fst+=cnt(t->l)+1;return w;
41     }
42     auto w=lb(t->l,key);
43     if(w.fst==cnt(t->l))w.snd=t->key;
44     return w;
45 }

```

1.9 Treap (implicit key)

```

1 // example that supports range reverse and addition updates, and range sum
  query
2 // (commented parts are specific to this problem)

```

```

3 typedef struct item *pitem;
4 struct item {
5     int cnt,pr,val;
6     // int sum; // (paramters for range query)
7     // bool rev;int add; // (parameters for lazy prop)
8     pitem l,r;
9     item(int val): pr(rand()),cnt(1),val(val),l(0),r(0){*,sum(val),rev(0),add
        (0)* / {}
10 };
11 void push(pitem it){
12     if(it){
13         /*if(it->rev){
14             swap(it->l,it->r);
15             if(it->l)it->l->rev^=true;
16             if(it->r)it->r->rev^=true;
17             it->rev=false;
18         }
19         it->val+=it->add;it->sum+=it->cnt*it->add;
20         if(it->l)it->l->add+=it->add;
21         if(it->r)it->r->add+=it->add;
22         it->add=0;*/
23     }
24 }
25 int cnt(pitem t){return t?t->cnt:0;}
26 // int sum(pitem t){return t?push(t),t->sum:0;}
27 void upd_cnt(pitem t){
28     if(t){
29         t->cnt=cnt(t->l)+cnt(t->r)+1;
30         // t->sum=t->val+sum(t->l)+sum(t->r);
31     }
32 }
33 void merge(pitem& t, pitem l, pitem r){
34     push(l);push(r);
35     if(!l||!r)t=l?l:r;
36     else if(l->pr>r->pr)merge(l->r,l->r,r),t=l;
37     else merge(r->l,l,r->l),t=r;
38     upd_cnt(t);
39 }
40 void split(pitem t, pitem& l, pitem& r, int sz){ // sz:desired size of l
41     if(!t){l=r=0;return;}
42     push(t);
43     if(sz<=cnt(t->l))split(t->l,l,t->l,sz),r=t;
44     else split(t->r,t->r,r,sz-1-cnt(t->l)),l=t;

```

```

45     upd_cnt(t);
46 }
47 void output(pitem t){ // useful for debugging
48     if(!t)return;
49     push(t);
50     output(t->l);printf("%d",t->val);output(t->r);
51 }
52 // use merge and split for range updates and queries

```

1.10 Convex hull trick (static)

```

1 typedef ll tc;
2 struct Line{tc m,h;};
3 struct CHT { // for minimum (for maximum just change the sign of lines)
4     vector<Line> c;
5     int pos=0;
6     tc in(Line a, Line b){
7         tc x=b.h-a.h,y=a.m-b.m;
8         return x/y+(x%y?!((x>0)^(y>0)):0); // ==ceil(x/y)
9     }
10 void add(tc m, tc h){ // m's should be non increasing
11     Line l=(Line){m,h};
12     if(c.size()&& m==c.back().m){
13         l.h=min(h,c.back().h);c.pop_back();if(pos)pos--;
14     }
15     while(c.size()>1&&in(c.back(),l)<=in(c[c.size()-2],c.back())){
16         c.pop_back();if(pos)pos--;
17     }
18     c.pb(l);
19 }
20 inline bool fbin(tc x, int m){return in(c[m],c[m+1])>x;}
21 tc eval(tc x){
22     // O(log n) query:
23     int s=0,e=c.size();
24     while(e-s>1){int m=(s+e)/2;
25         if(fbin(x,m-1))e=m;
26         else s=m;
27     }
28     return c[s].m*x+c[s].h;
29     // O(1) query (for ordered x's):
30     while(pos>0&&fbin(x,pos-1))pos--;
31     while(pos<c.size()-1&&!fbin(x,pos))pos++;
32     return c[pos].m*x+c[pos].h;
33 }

```

34 };

1.11 Convex hull trick (dynamic)

```

1 typedef ll tc;
2 const tc is_query=-(1LL<<62); // special value for query
3 struct Line {
4     tc m,b;
5     mutable multiset<Line>::iterator it,end;
6     const Line* succ(multiset<Line>::iterator it) const {
7         return (++it==end? NULL : &*it);}
8     bool operator<(const Line& rhs) const {
9         if(rhs.b!=is_query)return m<rhs.m;
10        const Line *s=succ(it);
11        if(!s)return 0;
12        return b-s->b<(s->m-m)*rhs.m;
13    }
14 };
15 struct HullDynamic : public multiset<Line> { // for maximum
16     bool bad(iterator y){
17         iterator z=next(y);
18         if(y==begin()){
19             if(z==end())return false;
20             return y->m==z->m&&y->b<=z->b;
21         }
22         iterator x=prev(y);
23         if(z==end())return y->m==x->m&&y->b<=x->b;
24         return (x->b-y->b)*(z->m-y->m)>=(y->b-z->b)*(y->m-x->m);
25     }
26     iterator next(iterator y){return ++y;}
27     iterator prev(iterator y){return --y;}
28     void add(tc m, tc b){
29         iterator y=insert((Line){m,b});
30         y->it=y;y->end=end();
31         if(bad(y)){erase(y);return;}
32         while(next(y)!=end()&&bad(next(y)))erase(next(y));
33         while(y!=begin()&&bad(prev(y)))erase(prev(y));
34     }
35     tc eval(tc x){
36         Line l=*lower_bound((Line){x,is_query});
37         return l.m*x+l.b;
38     }
39 };

```

1.12 Max Queue

```

1 struct MaxQueue { // for min, change < with >.
2     deque<int> d; queue<int> q;
3     void push(int v){while(sz(d)&&d.back()<v)d.pop_back();d.pb(v);q.push(v);}
4     void pop(){if(sz(d)&&d.front()==q.front())d.pop_front();q.pop();}
5     int getMax(){return sz(d)?d.front():NEUT;}
6 };

```

1.13 Union Find

```

1 int uf[MAXN];
2 void uf_init(){memset(uf,-1,sizeof(uf));}
3 int uf_find(int x){return uf[x]<0?x:uf[x]=uf_find(uf[x]);}
4 bool uf_join(int x, int y){
5     x=uf_find(x);y=uf_find(y);
6     if(x==y)return false;
7     if(uf[x]>uf[y])swap(x,y);
8     uf[x]+=uf[y];uf[y]=x;
9     return true;
10 }

```

2 Graphs

2.1 Bellman-Ford

```

1 int n;
2 vector<pair<int,int> > g[MAXN]; // u->[(v,cost)]
3 ll dist[MAXN];
4 void bford(int src){ // O(nm)
5     fill(dist,dist+n,INF);dist[src]=0;
6     forn(_,n-1)forn(x,n)if(dist[x]!=INF)for(auto t:g[x]){
7         dist[t.fst]=min(dist[t.fst],dist[x]+t.snd);
8     }
9     forn(x,n)if(dist[x]!=INF)for(auto t:g[x]){
10        if(dist[t.fst]>dist[x]+t.snd){
11            // neg cycle: all nodes reachable from t.fst have -INF distance
12            // to reconstruct neg cycle: save "prev" of each node, go up from t.
13            // fst until repeating a node. this node and all nodes between the
14            // two occurrences form a neg cycle
15        }
16    }
17 }

```

2.2 Floyd-Warshall

```

1 // g[i][j]: weight of edge (i, j) or INF if there's no edge
2 // g[i][i]=0
3 ll g[MAXN][MAXN];int n;
4 void floyd(){ // O(n^3) . Replaces g with min distances
5     forn(k,n)forn(i,n)if(g[i][k]<INF)forn(j,n)if(g[k][j]<INF)
6         g[i][j]=min(g[i][j],g[i][k]+g[k][j]);
7 }
8 bool inNegCycle(int v){return g[v][v]<0;}
9 bool hasNegCycle(int a, int b){ // true iff there's neg cycle in between
10     forn(i,n)if(g[a][i]<INF&&g[i][b]<INF&&g[i][i]<0)return true;
11     return false;
12 }

```

2.3 Strongly connected components (+ 2-SAT)

```

1 // MAXN: max number of nodes or 2 * max number of variables (2SAT)
2 bool truth[MAXN]; // truth[cmp[i]]=value of variable i (2SAT)
3 int nvar;int neg(int x){return MAXN-1-x;} // (2SAT)
4 vector<int> g[MAXN];
5 int n,lw[MAXN],idx[MAXN],qidx,cmp[MAXN],qcmp;
6 stack<int> st;
7 void tjn(int u){
8     lw[u]=idx[u]++;qidx;
9     st.push(u);cmp[u]=-2;
10    for(int v:g[u]){
11        if(!idx[v]||cmp[v]==-2){
12            if(!idx[v]) tjn(v);
13            lw[u]=min(lw[u],lw[v]);
14        }
15    }
16    if(lw[u]==idx[u]){
17        int x;
18        do{x=st.top();st.pop();cmp[x]=qcmp;}while(x!=u);
19        truth[qcmp]=(cmp[neg(u)]<0); // (2SAT)
20        qcmp++;
21    }
22 }
23 void scc(){
24     memset(idx,0,sizeof(idx));qidx=0;
25     memset(cmp,-1,sizeof(cmp));qcmp=0;
26     forn(i,n)if(!idx[i])tjn(i);
27 }
28 // Only for 2SAT:
29 void addor(int a, int b){g[neg(a)].pb(b);g[neg(b)].pb(a);}

```

```

30 bool satisf(int _nvar){
31     nvar=_nvar;n=MAXN;scc();
32     forn(i,nvar)if(cmp[i]==cmp[neg(i)])return false;
33     return true;
34 }

```

2.4 Articulation - Bridges - Biconnected

```

1 vector<int> g[MAXN];int n;
2 struct edge {int u,v,comp;bool bridge;};
3 vector<edge> e;
4 void add_edge(int u, int v){
5     g[u].pb(e.size());g[v].pb(e.size());
6     e.pb((edge){u,v,-1,false});
7 }
8 int D[MAXN],B[MAXN],T;
9 int nbc; // number of biconnected components
10 int art[MAXN]; // articulation point iff !=0
11 stack<int> st; // only for biconnected
12 void dfs(int u,int pe){
13     B[u]=D[u]=T++;
14     for(int ne:g[u])if(ne!=pe){
15         int v=e[ne].u^e[ne].v^u;
16         if(D[v]<0){
17             st.push(ne);dfs(v,ne);
18             if(B[v]>D[u])e[ne].bridge = true; // bridge
19             if(B[v]>=D[u]){
20                 art[u]++; // articulation
21                 int last; // start biconnected
22                 do {
23                     last=st.top();st.pop();
24                     e[last].comp=nbc;
25                 } while(last!=ne);
26                 nbc++; // end biconnected
27             }
28             B[u]=min(B[u],B[v]);
29         }
30         else if(D[v]<D[u])st.push(ne),B[u]=min(B[u],D[v]);
31     }
32 }
33 void doit(){
34     memset(D,-1,sizeof(D));memset(art,0,sizeof(art));
35     nbc=T=0;
36     forn(i,n)if(D[i]<0)dfs(i,-1),art[i]--;

```


37 | }

2.5 Chu-Liu (minimum spanning arborescence)

```

1 typedef ll tw; const tw INF=1LL<<60;
2 struct edge {int src,dst;tw w;};
3 struct ChuLiu {
4     int n,r;tw cost;bool found;
5     vector<int> no,pr,mark;
6     vector<vector<int>> > comp,nx;
7     vector<tw> mcost;
8     vector<vector<edge>> > h;
9     ChuLiu(int n):n(n),h(n){}
10    void add_edge(int x, int y, tw w){h[y].pb((edge){x,y,w});}
11    void visit(int v, int s){
12        if(mark[v]){
13            vector<int> temp=no;found=true;
14            do {
15                cost+=mcost[v];v=pr[v];
16                if(v!=s)while(comp[v].size()>0){
17                    no[comp[v].back()]=s;
18                    comp[s].pb(comp[v].back());
19                    comp[v].pop_back();
20                }
21            }while(v!=s);
22            for(int j:comp[s])if(j!=r)for(edge& e:h[j])
23                if(no[e.src]!=s)e.w-=mcost[temp[j]];
24        }
25        mark[v]=true;
26        for(int i:nx[v])if(no[i]!=no[v]&&pr[no[i]]==v)
27            if(!mark[no[i]]||i==s)
28                visit(i,s);
29    }
30    tw doit(int _r){ // r: root (0(nm))
31        r=_r;
32        no.resize(n);comp.clear();comp.resize(n);
33        forn(x,n)comp[x].pb(no[x]=x);
34        for(cost=0;;){
35            pr.clear();pr.resize(n,-1);
36            mcost=vector<tw>(n,INF);
37            forn(j,n)if(j!=r)for(edge e:h[j])
38                if(no[e.src]!=no[j]&&e.w<mcost[no[j]])
39                mcost[no[j]]=e.w,pr[no[j]]=no[e.src];
40            nx.clear();nx.resize(n);

```

```

41        forn(x,n)if(pr[x]>=0)nx[pr[x]].pb(x);
42        bool stop=true;
43        mark.clear();mark.resize(n);
44        forn(x,n)if(x!=r&&!mark[x]&&!comp[x].empty()){
45            found=false;visit(x,x);
46            if(found)stop=false;
47        }
48        if(stop){
49            forn(x,n)if(pr[x]>=0)cost+=mcost[x];
50            return cost;
51        }
52    }
53 }
54 };

```

2.6 LCA - Binary Lifting

```

1 vector<int> g[1<<K];int n; // K such that 2^K>=n
2 int F[K][1<<K],D[1<<K];
3 void lca_dfs(int x){
4     for(int y:g[x]){if(y==F[0][x])continue;
5         F[0][y]=x;D[y]=D[x]+1;lca_dfs(y);
6     }
7 }
8 void lca_init(){
9     D[0]=0;F[0][0]=-1;
10    lca_dfs(0);
11    forr(k,1,K)forn(x,n)
12        if(F[k-1][x]<0)F[k][x]=-1;
13        else F[k][x]=F[k-1][F[k-1][x]];
14 }
15 int lca(int x, int y){
16     if(D[x]<D[y])swap(x,y);
17     for(int k=K-1;k>=0;--k)if(D[x]-(1<<k)>=D[y])x=F[k][x];
18     if(x==y)return x;
19     for(int k=K-1;k>=0;--k)if(F[k][x]!=F[k][y])x=F[k][x],y=F[k][y];
20     return F[0][x];
21 }

```

2.7 Heavy-Light decomposition

```

1 vector<int> g[MAXN];
2 int wg[MAXN],dad[MAXN],dep[MAXN]; // weight,father,depth
3 void dfs1(int x){

```



```

4   wg[x]=1;
5   for(int y:g[x])if(y!=dad[x]){
6       dad[y]=x;dep[y]=dep[x]+1;dfs1(y);
7       wg[x]+=wg[y];
8   }
9   }
10  int curpos,pos[MAXN],head[MAXN];
11  void hld(int x, int c){
12      if(c<0)c=x;
13      pos[x]=curpos++;head[x]=c;
14      int mx=-1;
15      for(int y:g[x])if(y!=dad[x]&&(mx<0||wg[mx]<wg[y]))mx=y;
16      if(mx>=0)hld(mx,c);
17      for(int y:g[x])if(y!=mx&&y!=dad[x])hld(y,-1);
18  }
19  void hld_init(){dad[0]=-1;dep[0]=0;dfs1(0);curpos=0;hld(0,-1);}
20  int query(int x, int y, STree& rmq){
21      int r=NEUT;
22      while(head[x]!=head[y]){
23          if(dep[head[x]]>dep[head[y]])swap(x,y);
24          r=oper(r,rmq.query(pos[head[y]],pos[y]+1));
25          y=dad[head[y]];
26      }
27      if(dep[x]>dep[y])swap(x,y); // now x is lca
28      r=oper(r,rmq.query(pos[x],pos[y]+1));
29      return r;
30  }
31  // for updating: rmq.upd(pos[x],v);

```

2.8 Centroid decomposition

```

1  vector<int> g[MAXN];int n;
2  bool tk[MAXN];
3  int fat[MAXN]; // father in centroid decomposition
4  int szt[MAXN]; // size of subtree
5  int calcsz(int x, int f){
6      szt[x]=1;
7      for(auto y:g[x])if(y!=f&&!tk[y])szt[x]+=calcsz(y,x);
8      return szt[x];
9  }
10 void cdfs(int x=0, int f=-1, int sz=-1){ // 0(nlogn)
11     if(sz<0)sz=calcsz(x,-1);
12     for(auto y:g[x])if(!tk[y]&&szt[y]*2>=sz){
13         szt[x]=0;cdfs(y,f,sz);return;

```

```

14     }
15     tk[x]=true;fat[x]=f;
16     for(auto y:g[x])if(!tk[y])cdfs(y,x);
17 }
18 void centroid(){memset(tk,false,sizeof(tk));cdfs();}

```

2.9 Eulerian path

```

1  // Directed version (uncomment commented code for undirected)
2  struct edge {
3      int y;
4      // list<edge>::iterator rev;
5      edge(int y):y(y){}
6  };
7  list<edge> g[MAXN];
8  void add_edge(int a, int b){
9      g[a].push_front(edge(b));//auto ia=g[a].begin();
10     // g[b].push_front(edge(a));auto ib=g[b].begin();
11     // ia->rev=ib;ib->rev=ia;
12 }
13 vector<int> p;
14 void go(int x){
15     while(g[x].size()){
16         int y=g[x].front().y;
17         //g[y].erase(g[x].front().rev);
18         g[x].pop_front();
19         go(y);
20     }
21     p.push_back(x);
22 }
23 vector<int> get_path(int x){ // get a path that begins in x
24     // check that a path exists from x before calling to get_path!
25     p.clear();go(x);reverse(p.begin(),p.end());
26     return p;
27 }

```

2.10 Dynamic connectivity

```

1  struct UnionFind {
2      int n,comp;
3      vector<int> uf,si,c;
4      UnionFind(int n=0):n(n),comp(n),uf(n),si(n,1){
5          forn(i,n)uf[i]=i;}
6      int find(int x){return x==uf[x]?x:find(uf[x]);}

```

```

7  bool join(int x, int y){
8      if((x=find(x))==find(y))return false;
9      if(si[x]<si[y])swap(x,y);
10     si[x]+=si[y];uf[y]=x;comp--;c.pb(y);
11     return true;
12 }
13 int snap(){return c.size();}
14 void rollback(int snap){
15     while(c.size()>snap){
16         int x=c.back();c.pop_back();
17         si[uf[x]]-=si[x];uf[x]=x;comp++;
18     }
19 }
20 };
21 enum {ADD,DEL,QUERY};
22 struct Query {int type,x,y;};
23 struct DynCon {
24     vector<Query> q;
25     UnionFind dsu;
26     vector<int> mt;
27     map<pair<int,int>,int> last;
28     DynCon(int n):dsu(n){}
29     void add(int x, int y){
30         if(x>y)swap(x,y);
31         q.pb((Query){ADD,x,y});mt.pb(-1);last[mp(x,y)]=q.size()-1;
32     }
33     void remove(int x, int y){ // the edge to remove must exist
34         if(x>y)swap(x,y);
35         q.pb((Query){DEL,x,y});
36         int pr=last[mp(x,y)];mt[pr]=q.size()-1;mt.pb(pr);
37     }
38     void query(){q.pb((Query){QUERY,-1,-1});mt.pb(-1);}
39     void process(){ // answers all queries in order
40         if(!q.size())return;
41         for(i,q.size())if(q[i].type==ADD&&mt[i]<0)mt[i]=q.size();
42         go(0,q.size());
43     }
44     void go(int s, int e){
45         if(s+1==e){
46             if(q[s].type==QUERY // answer query using DSU
47                 printf("%d\n",dsu.comp);
48             return;
49         }

```

```

50     int k=dsu.snap(),m=(s+e)/2;
51     for(int i=e-1;i>=m;--i)if(mt[i]>=0&&mt[i]<s)dsu.join(q[i].x,q[i].y);
52     go(s,m);dsu.rollback(k);
53     for(int i=m-1;i>=s;--i)if(mt[i]>=e)dsu.join(q[i].x,q[i].y);
54     go(m,e);dsu.rollback(k);
55 }
56 };

```

2.11 Edmond's blossom (matching in general graphs)

```

1  vector<int> g[MAXN];
2  int n,m,mt[MAXN],qh,qt,q[MAXN],ft[MAXN],bs[MAXN];
3  bool inq[MAXN],inb[MAXN],inp[MAXN];
4  int lca(int root, int x, int y){
5      memset(inp,0,sizeof(inp));
6      while(1){
7          inp[x=bs[x]]=true;
8          if(x==root)break;
9          x=ft[mt[x]];
10     }
11     while(1){
12         if(inp[y=bs[y]])return y;
13         else y=ft[mt[y]];
14     }
15 }
16 void mark(int z, int x){
17     while(bs[x]!=z){
18         int y=mt[x];
19         inb[bs[x]]=inb[bs[y]]=true;
20         x=ft[y];
21         if(bs[x]!=z)ft[x]=y;
22     }
23 }
24 void contr(int s, int x, int y){
25     int z=lca(s,x,y);
26     memset(inb,0,sizeof(inb));
27     mark(z,x);mark(z,y);
28     if(bs[x]!=z)ft[x]=y;
29     if(bs[y]!=z)ft[y]=x;
30     forn(x,n)if(inb[bs[x]]){
31         bs[x]=z;
32         if(!inq[x])inq[q[++qt]=x]=true;
33     }
34 }

```

```

35 int findp(int s){
36     memset(inq,0,sizeof(inq));
37     memset(ft,-1,sizeof(ft));
38     forn(i,n)bs[i]=i;
39     inq[q[qh=qt=0]=s]=true;
40     while(qh<=qt){
41         int x=q[qh++];
42         for(int y:g[x])if(bs[x]!=bs[y]&&mt[x]!=y){
43             if(y==s|mt[y]>=0&&ft[mt[y]]>=0)contr(s,x,y);
44             else if(ft[y]<0){
45                 ft[y]=x;
46                 if(mt[y]<0)return y;
47                 else if(!inq[mt[y]])inq[q[++qt]=mt[y]]=true;
48             }
49         }
50     }
51     return -1;
52 }
53 int aug(int s, int t){
54     int x=t,y,z;
55     while(x>=0){
56         y=ft[x];
57         z=mt[y];
58         mt[y]=x;mt[x]=y;
59         x=z;
60     }
61     return t>=0;
62 }
63 int edmonds(){ // 0(n^2 m)
64     int r=0;
65     memset(mt,-1,sizeof(mt));
66     forn(x,n)if(mt[x]<0)r+=aug(x,findp(x));
67     return r;
68 }

```

3 Math

3.1 Identities

$$C_n' = \frac{2(2n-1)}{n+1} C_{n-1}$$

$$C_n = \frac{1}{n+1} \binom{2n}{n}$$

$$C_n \sim \frac{4^n}{n^{3/2} \sqrt{\pi}}$$

$$\sigma(n) = O(\log(\log(n))) \text{ (number of divisors of } n)$$

$$F_{2n+1} = F_n^2 + F_{n+1}^2$$

$$F_{2n} = F_{n+1}^2 - F_{n-1}^2$$

$$\sum_{i=1}^n F_i = F_{n+2} - 1$$

$$F_{n+i}F_{n+j} - F_nF_{n+i+j} = (-1)^n F_i F_j$$

$$\text{(Möbius Inv. Formula) Let } g(n) = \sum_{d|n} f(d), \text{ then } f(n) = \sum d \mid ng(d) \mu\left(\frac{n}{d}\right).$$

3.2 Theorems

- 1 (Tutte) A graph, $G = (V, E)$, has a perfect matching **if and only if** for every subset U of V , the subgraph induced by $V - U$ has at most $|U|$ connected components with an odd number of vertices.
- 2 Petersens Theorem. Every cubic, bridgeless graph contains a perfect matching.
- 3 (Dilworth) In any finite partially ordered set, the maximum number of elements in any antichain equals the minimum number of chains in any partition of the set into chains
- 4 Pick: $A = I + B/2 - 1$ (area of polygon, points inside, points on border)

3.3 Integer floor division

```

1 void floordiv(ll x, ll y, ll& q, ll& r) { // (for negative x)
2     q=x/y;r=x%y;
3     if((r!=0)&&((r<0)!=(y<0)))q--,r+=y;
4 }

```

3.4 Extended Euclid

```

1 ll euclid(ll a, ll b, ll& x, ll& y){ // a*(x+k*(b/d))+b*(y-k*(a/d))=d
2     if(!b){x=1;y=0;return a;} // (for any k)
3     ll d=euclid(b,a%b,x,y);
4     ll t=y;y=x-(a/b)*y;x=t;
5     return d;
6 }

```

3.5 Pollard's rho

```

1 ll gcd(ll a, ll b){return a?gcd(b%a,a):b;}
2 ull mulmod(ull a, ull b, ull m){ // 0 <= a, b < m
3     long double x; ull c; ll r;
4     x = a; c = x * b / m;
5     r = (ll)(a * b - c * m) % (ll)m;
6     return r < 0 ? r + m : r;
7 }
8 ll expmod(ll b, ll e, ll m){
9     if(!e)return 1;
10    ll q=expmod(b,e/2,m);q=mulmod(q,q,m);
11    return e&1?mulmod(b,q,m):q;

```

```

12 }
13 bool is_prime_prob(ll n, int a){
14     if(n==a)return true;
15     ll s=0,d=n-1;
16     while(d%2==0)s++,d/=2;
17     ll x=expmod(a,d,n);
18     if((x==1)|| (x+1==n))return true;
19     forn(_,s-1){
20         x=mulmod(x,x,n);
21         if(x==1)return false;
22         if(x+1==n)return true;
23     }
24     return false;
25 }
26 bool rabin(ll n){ // true iff n is prime
27     if(n==1)return false;
28     int ar[]={2,3,5,7,11,13,17,19,23};
29     forn(i,9)if(!is_prime_prob(n,ar[i]))return false;
30     return true;
31 }
32 ll rho(ll n){
33     if(!(n&1))return 2;
34     ll x=2,y=2,d=1;
35     ll c=rand()%n+1;
36     while(d==1){
37         x=(mulmod(x,x,n)+c)%n;
38         y=(mulmod(y,y,n)+c)%n;
39         y=(mulmod(y,y,n)+c)%n;
40         if(x>=y)d=gcd(x-y,n);
41         else d=gcd(y-x,n);
42     }
43     return d==n?rho(n):d;
44 }
45 void fact(ll n, map<ll,int>& f){ //0 (lg n)^3
46     if(n==1)return;
47     if(rabin(n)){f[n]++;return;}
48     ll q=rho(n);fact(q,f);fact(n/q,f);
49 }

```

3.6 Simpson's rule

```

1 double integrate(double f(double), double a, double b, int n=10000){
2     double r=0,h=(b-a)/n,fa=f(a),fb;
3     forn(i,n){

```

```

4         fb=f(a+h*(i+1));
5         r+=fa+4*f(a+h*(i+0.5))+fb;fa=fb;
6     }
7     return r*h/6.;
8 }

```

3.7 Polynomials

```

1 typedef int tp; // type of polynomial
2 template<class T=tp>
3 struct poly { // poly<> : 1 variable, poly<poly<>>: 2 variables, etc.
4     vector<T> c;
5     T& operator[](int k){return c[k];}
6     poly(vector<T>& c):c(c){}
7     poly(initializer_list<T> c):c(c){}
8     poly(int k):c(k){}
9     poly(){}
10    poly operator+(poly<T> o){
11        int m=c.size(),n=o.c.size();
12        poly res(max(m,n));
13        forn(i,m)res[i]=res[i]+c[i];
14        forn(i,n)res[i]=res[i]+o.c[i];
15        return res;
16    }
17    poly operator*(tp k){
18        poly res(c.size());
19        forn(i,c.size())res[i]=c[i]*k;
20        return res;
21    }
22    poly operator*(poly o){
23        int m=c.size(),n=o.c.size();
24        poly res(m+n-1);
25        forn(i,m)forn(j,n)res[i+j]=res[i+j]+c[i]*o.c[j];
26        return res;
27    }
28    poly operator-(poly<T> o){return *this+(o*-1);}
29    T operator()(tp v){
30        T sum(0);
31        for(int i=c.size()-1;i>=0;--i)sum=sum*v+c[i];
32        return sum;
33    }
34 };
35 // example: p(x,y)=2*x^2+3*x*y-y+4
36 // poly<poly<>> p={{4,-1},{0,3},{2}}

```

```

37 // printf("%d\n",p(2)(3)) // 27 (p(2,3))
38 set<tp> roots(poly<> p){ // only for integer polynomials
39     set<tp> r;
40     while(!p.c.empty()&&!p.c.back())p.c.pop_back();
41     if(!p(0))r.insert(0);
42     if(p.c.empty())return r;
43     tp a0=0,an=abs(p[p.c.size()-1]);
44     for(int k=0;!a0;a0=abs(p[k++]));
45     vector<tp> ps,qs;
46     forr(i,1,sqrt(a0)+1)if(a0%i==0)ps.pb(i),ps.pb(a0/i);
47     forr(i,1,sqrt(an)+1)if(an%i==0)qs.pb(i),qs.pb(an/i);
48     for(auto pt:ps)for(auto qt:qs)if(pt%qt==0){
49         tp x=pt/qt;
50         if(!p(x))r.insert(x);
51         if(!p(-x))r.insert(-x);
52     }
53     return r;
54 }
55 pair<poly<>,tp> ruffini(poly<> p, tp r){ // returns pair (result,rem)
56     int n=p.c.size()-1;
57     vector<tp> b(n);
58     b[n-1]=p[n];
59     for(int k=n-2;k>=0;--k)b[k]=p[k+1]+r*b[k+1];
60     return mp(poly<>(b),p[0]+r*b[0]);
61 }
62 // only for double polynomials
63 pair<poly<>,poly<> > polydiv(poly<> p, poly<> q){ // returns pair (result,
64     rem)
65     int n=p.c.size()-q.c.size()+1;
66     vector<tp> b(n);
67     for(int k=n-1;k>=0;--k){
68         b[k]=p.c.back()/q.c.back();
69         forn(i,q.c.size())p[i+k]-=b[k]*q[i];
70         p.c.pop_back();
71     }
72     while(!p.c.empty()&&abs(p.c.back())<EPS)p.c.pop_back();
73     return mp(poly<>(b),p);
74 }
75 // only for double polynomials
76 poly<> interpolate(vector<tp> x, vector<tp> y){ //TODO TEST
77     poly<> q={1},S={0};
78     for(tp a:x)q=poly<>({-a,1})*q;
79     forn(i,x.size()){

```

```

79     poly<> Li=ruffini(q,x[i]).fst;
80     Li=Li*(1.0/Li(x[i])); // change for int polynomials
81     S=S+Li*y[i];
82 }
83 return S;
84 }

```

3.8 Bairstow

```

1 double pget(poly<>& p, int k){return k<p.c.size()?p[k]:0;}
2 poly<> bairstow(poly<> p){ // returns polynomial of degree 2 that
3     int n=p.c.size()-1; // divides p
4     assert(n>=3&&abs(p.c.back())>EPS);
5     double u=p[n-1]/p[n],v=p[n-2]/p[n];
6     forn(_,ITER){
7         auto w=polydiv(p,{v,u,1});
8         poly<> q=w.fst,r0=w.snd;
9         poly<> r1=polydiv(q,{v,u,1}).snd;
10        double c=pget(r0,1),d=pget(r0,0),g=pget(r1,1),h=pget(r1,0);
11        double det=1/(v*g*g+h*(h-u*g)),uu=u;
12        u=-det*(-h*c+g*d);v=-det*(-g*v*c+(g*uu-h)*d);
13    }
14    return {v,u,1};
15 }
16 void addr(vector<double>& r, poly<>& p){
17     assert(p.c.size()<=3);
18     if(p.c.size()<=1)return;
19     if(p.c.size()==2)r.pb(-p[0]/p[1]);
20     if(p.c.size()==3){
21         double a=p[2],b=p[1],c=p[0];
22         double d=b*b-4*a*c;
23         if(d<-0.1)return; // huge epsilon because of bad precision
24         d=d>0?sqrt(d):0;r.pb((-b-d)/2/a);r.pb((-b+d)/2/a);
25     }
26 }
27 vector<double> roots(poly<> p){
28     while(!p.c.empty()&&abs(p.c.back())<EPS)p.c.pop_back();
29     forn(i,p.c.size())p[i]/=p.c.back();
30     vector<double> r;int n;
31     while((n=p.c.size()-1)>=3){
32         poly<> q=bairstow(p);addr(r,q);
33         p=polydiv(p,q).fst;
34         while(p.c.size()>n-1)p.c.pop_back();
35     }

```

```

36 }
37 addr(r,p);
38 return r;
39 }

```

3.9 Fast Fourier Transform

```

1 struct CD { // or typedef complex<double> CD; (but 4x slower)
2     double r,i;
3     CD(double r=0, double i=0):r(r),i(i){}
4     void operator/=(const int c){r/=c, i/=c;}
5 };
6 CD operator*(const CD& a, const CD& b){
7     return CD(a.r*b.r-a.i*b.i,a.r*b.i+a.i*b.r);}
8 CD operator+(const CD& a, const CD& b){return CD(a.r+b.r,a.i+b.i);}
9 CD operator-(const CD& a, const CD& b){return CD(a.r-b.r,a.i-b.i);}
10 const double pi=acos(-1.0);
11 CD cp1[MAXN+9],cp2[MAXN+9],w[MAXN+9]; // MAXN must be power of 2 !!
12 int R[MAXN+9];
13 void dft(CD* a, int n, bool inv){
14     for(int i,n)if(R[i]<i)swap(a[R[i]],a[i]);
15     for(int m=2;m<=n;m*=2){
16         double z=2*pi/m*(inv?-1:1);
17         CD wi=CD(cos(z),sin(z));
18         for(int j=0;j<n;j+=m){
19             w[0]=1;
20             for(int k=j,k2=j+m/2,t=1;k2<j+m;k++,k2++,t++){
21                 CD u=a[k];CD v=a[k2]*w[t-1];a[k]=u+v;a[k2]=u-v;
22                 w[t]=t%2?wi*w[t-1]:w[t/2]*w[t/2];
23             }
24         }
25     }
26     if(inv)for(int i,n)a[i]/=n;
27 }
28 vector<int> multiply(vector<int>& p1, vector<int>& p2){
29     int n=p1.size()+p2.size()+1;
30     int m=1,cnt=0;
31     while(m<=n)m+=m,cnt++;
32     for(int i,m){R[i]=0;for(int j,cnt)R[i]=(R[i]<<1)|((i>>j)&1);}
33     for(int i,m)cp1[i]=0,cp2[i]=0;
34     for(int i,p1.size())cp1[i]=p1[i];
35     for(int i,p2.size())cp2[i]=p2[i];
36     dft(cp1,m,false);dft(cp2,m,false);
37     for(int i,m)cp1[i]=cp1[i]*cp2[i];

```

```

38 dft(cp1,m,true);
39 vector<int> res;
40 n-=2;
41 for(int i,n)res.pb((1ll)floor(cp1[i].r+0.5));
42 return res;
43 }

```

3.10 Fast Hadamard Transform

```

1 ll c1[MAXN+9],c2[MAXN+9]; // MAXN must be power of 2 !!
2 void fht(ll* p, int n, bool inv){
3     for(int l=1;2*l<=n;l*=2){
4         for(int i=0;i<n;i+=2*l){
5             for(int j,l){
6                 ll u=p[i+j],v=p[i+l+j];
7                 // XOR
8                 if(!inv)p[i+j]=u+v,p[i+l+j]=u-v;
9                 else p[i+j]=(u+v)/2,p[i+l+j]=(u-v)/2;
10                // AND
11                //if(!inv)p[i+j]=v,p[i+l+j]=u+v;
12                //else p[i+j]=-u+v,p[i+l+j]=u;
13                // OR
14                //if(!inv)p[i+j]=u+v,p[i+l+j]=u;
15                //else p[i+j]=v,p[i+l+j]=u-v;
16            }
17        }
18    }
19 }
20 // like polynomial multiplication, but XORing exponents
21 // instead of adding them (also ANDing, ORing)
22 vector<ll> multiply(vector<ll>& p1, vector<ll>& p2){
23     int n=1<<(32-__builtin_clz(max(sz(p1),sz(p2))-1));
24     for(int i,n)c1[i]=0,c2[i]=0;
25     for(int i,sz(p1))c1[i]=p1[i];
26     for(int i,sz(p2))c2[i]=p2[i];
27     fht(c1,n,false);fht(c2,n,false);
28     for(int i,n)c1[i]*=c2[i];
29     fht(c1,n,true);
30     return vector<ll>(c1,c1+n);
31 }

```

3.11 Karatsuba

```

1 typedef ll tp;

```

```

2  #define add(n,s,d,k) forn(i,n)(d)[i]+=(s)[i]*k
3  tp* ini(int n){tp *r=new tp[n];fill(r,r+n,0);return r;}
4  void karatsura(int n, tp* p, tp* q, tp* r){
5      if(n<=0)return;
6      if(n<35)forn(i,n)forn(j,n)r[i+j]+=p[i]*q[j];
7      else {
8          int nac=n/2,nbd=n-n/2;
9          tp *a=p,*b=p+nac,*c=q,*d=q+nac;
10         tp *ab=ini(nbd+1),*cd=ini(nbd+1),*ac=ini(nac*2),*bd=ini(nbd*2);
11         add(nac,a,ab,1);add(nbd,b,ab,1);
12         add(nac,c,cd,1);add(nbd,d,cd,1);
13         karatsura(nac,a,c,ac);karatsura(nbd,b,d,bd);
14         add(nac*2,ac,r+nac,-1);
15         add(nbd*2,bd,r+nac,-1);
16         add(nac*2,ac,r,1);
17         add(nbd*2,bd,r+nac*2,1);
18         karatsura(nbd+1,ab,cd,r+nac);
19         free(ab);free(cd);free(ac);free(bd);
20     }
21 }
22 vector<tp> multiply(vector<tp> p0, vector<tp> p1){
23     int n=max(p0.size(),p1.size());
24     tp *p=ini(n),*q=ini(n),*r=ini(2*n);
25     forn(i,p0.size())p[i]=p0[i];
26     forn(i,p1.size())q[i]=p1[i];
27     karatsura(n,p,q,r);
28     vector<tp> rr(r,r+p0.size()+p1.size()-1);
29     free(p);free(q);free(r);
30     return rr;
31 }

```

3.12 Modular inverse

```

1  inv[1]=1; //O(MAXN), i*inv[i] = 1 mod p, MAXN <= p
2  forr(i, 2, MAXN) inv[i]=p-((11)(p/i)*inv[p%i])%p;

```

3.13 Chinese remainder theorem (Euge)

```

1  #define mod(a, m) (((a)%m + m)%m)
2  struct Meq { // requires euclid, inv, mulmod (from pollard rho)
3      ll a, b, m; // a*x = b (mod m)
4      Meq(ll a = 0, ll b = 0, ll m = 0): a(a), b(b), m(m){}
5      bool norm(){ // returns false if equation is not consistent
6          a = mod(a, m); b = mod(b, m);

```

```

7          ll g = __gcd(a, m); if(b%g) return false;
8          a/=g; b/=g; m/=g; b = b*inv(a, m)%m; a = 1;
9          return true;
10     }
11 };
12 Meq Euge(Meq S, Meq T){ // Requires S, T to be normalized first
13     ll x, y, g = euclid(S.m, -T.m, x, y);
14     if(g < 0) x *= -1, y *= -1, g *= -1;
15     if((S.b - T.b)%g) return Meq(); // returns m = 0 if not consistent
16     ll M = S.m * (T.m/g), r = (T.b - S.b)/g;
17     x = mulmod(x, r, M);
18     ll A = mod(mulmod(S.m, x, M) + S.b, M);
19     return Meq(1, A, M);
20 }

```

3.14 Mobius

```

1  short mu[MAXN] = {0,1};
2  void mobius(){
3      forr(i,1,MAXN)if(mu[i])for(int j=i+i;j<MAXN;j+=i)mu[j]-=mu[i];
4  }

```

3.15 Linear Recurrence

```

1  struct LRec{
2      int n; vector<int> In, T; vector<vector<int>>> B;
3      vector<int> add(vector<int> &a, vector<int> &b){
4          vector<int> ans(2*n+1, 0);
5          forn(i, n+1)forn(j, n+1)
6              ans[i+j] = (ans[i+j] + (11)a[i]*b[j]%MOD + MOD)%MOD;
7          for(int i = 2*n; i > n; i--)forn(j, n)
8              ans[i-1-j] = (ans[i-1-j] + (11)ans[i]*T[j]%MOD + MOD)%MOD;
9          ans.resize(n+1); return ans; }
10     LRec(vector<int> V, vector<int> T): In(V), T(T){
11         n = sz(V);
12         vector<int> a(n+1, 0);
13         a[1] = 1; B.pb(a);
14         forr(i, 1, LOG) B.pb(add(B[i-1], B[i-1])); }
15     int calc(ll k){
16         vector<int> a(n+1, 0); a[0] = 1;
17         forn(i, LOG)if(k>>i&1)a = add(a, B[i]);
18         int ret = 0;
19         forn(i, n)ret = (ret + (11)a[i+1]*In[i]%MOD + MOD)%MOD;
20         return ret; }
21 };

```


3.16 Gaussian Elimination

```

1 double reduce(vector<vector<double> >& x){ // returns determinant
2     int n=x.size(),m=x[0].size();
3     int i=0,j=0;double r=1.;
4     while(i<n&&j<m){
5         int l=i;
6         forr(k,i+1,n)if(abs(x[k][j])>abs(x[l][j]))l=k;
7         if(abs(x[l][j])<EPS){j++;r=0.;continue;}
8         if(l!=i){r=-r;swap(x[i],x[l]);}
9         r*=x[i][j];
10        for(int k=m-1;k>j;k--)x[i][k]/=x[i][j];
11        forn(k,n){
12            if(k==i)continue;
13            for(int l=m-1;l>=j;l--)x[k][l]-=x[k][j]*x[i][l];
14        }
15        i++;j++;
16    }
17    return r;
18 }

```

3.17 Simplex

```

1 vector<int> X,Y;
2 vector<vector<double> > A;
3 vector<double> b,c;
4 double z;
5 int n,m;
6 void pivot(int x,int y){
7     swap(X[y],Y[x]);
8     b[x]/=A[x][y];
9     forn(i,m)if(i!=y)A[x][i]/=A[x][y];
10    A[x][y]=1/A[x][y];
11    forn(i,n)if(i!=x&&abs(A[i][y])>EPS){
12        b[i]-=A[i][y]*b[x];
13        forn(j,m)if(j!=y)A[i][j]-=A[i][y]*A[x][j];
14        A[i][y]=-A[i][y]*A[x][y];
15    }
16    z+=c[y]*b[x];
17    forn(i,m)if(i!=y)c[i]-=c[y]*A[x][i];
18    c[y]=-c[y]*A[x][y];
19 }
20 pair<double,vector<double> > simplex( // maximize c^T x s.t. Ax<=b, x>=0
21     vector<vector<double> > _A, vector<double> _b, vector<double> _c){

```

```

22 // returns pair (maximum value, solution vector)
23 A=_A;b=_b;c=_c;
24 n=b.size();m=c.size();z=0.;
25 X=vector<int>(m);Y=vector<int>(n);
26 forn(i,m)X[i]=i;
27 forn(i,n)Y[i]=i+m;
28 while(1){
29     int x=-1,y=-1;
30     double mn=-EPS;
31     forn(i,n)if(b[i]<mn)mn=b[i],x=i;
32     if(x<0)break;
33     forn(i,m)if(A[x][i]<-EPS){y=i;break;}
34     assert(y>=0); // no solution to Ax<=b
35     pivot(x,y);
36 }
37 while(1){
38     double mx=EPS;
39     int x=-1,y=-1;
40     forn(i,m)if(c[i]>mx)mx=c[i],y=i;
41     if(y<0)break;
42     double mn=1e200;
43     forn(i,n)if(A[i][y]>EPS&&b[i]/A[i][y]<mn)mn=b[i]/A[i][y],x=i;
44     assert(x>=0); // c^T x is unbounded
45     pivot(x,y);
46 }
47 vector<double> r(m);
48 forn(i,n)if(Y[i]<m)r[Y[i]]=b[i];
49 return mp(z,r);
50 }

```

4 Geometry

4.1 Point

```

1 bool left(pt p, pt q){ // is it to the left of directed line pq?
2     return (q-p)%(*this-p)>EPS;}
3 pt rot(pt r){return pt(*this*r,*this*r);}
4 pt rot(double a){return pt(sin(a),cos(a));}
5 pt ccw90(1,0); pt cw90(-1,0);

```

4.2 Line

```

1 int sgn2(double x){return x<0?-1:1;}
2 struct ln {
3     pt p,pq;

```

```

4   ln(pt p, pt q):p(p),pq(q-p){}
5   ln(){ }
6   bool has(pt r){return dist(r)<EPS;}
7   bool seghas(pt r){return has(r)&&(r-p)*(r-(p+pq))-EPS<0;}
8   // bool operator /(ln l){return (pq.unit()^l.pq.unit()).norm()<EPS;} // 3D
9   bool operator/(ln l){return abs(pq.unit()^l.pq.unit())<EPS;} // 2D
10  bool operator==(ln l){return *this/l&&has(l.p);}
11  pt operator^(ln l){ // intersection
12      if(*this/l)return pt(DINF,DINF);
13      pt r=l.p+l.pq*((p-l.p)%pq/(l.pq%pq));
14      // if(!has(r)){return pt(NAN,NAN,NAN);} // check only for 3D
15      return r;
16  }
17  double angle(ln l){return pq.angle(l.pq);}
18  int side(pt r){return has(r)?0:sgn2(pq%(r-p));} // 2D
19  pt proj(pt r){return p+pq*((r-p)*pq/pq.norm2());}
20  pt ref(pt r){return proj(r)*2-r;}
21  double dist(pt r){return (r-proj(r)).norm();}
22  // double dist(ln l){ // only 3D
23  //     if(*this/l)return dist(l.p);
24  //     return abs((l.p-p)*(pq^l.pq))/(pq^l.pq).norm();
25  // }
26  ln rot(auto a){return ln(p,p+pq.rot(a));} // 2D
27  };
28  ln bisector(ln l, ln m){ // angle bisector
29      pt p=l~m;
30      return ln(p,p+l.pq.unit()+m.pq.unit());
31  }
32  ln bisector(pt p, pt q){ // segment bisector (2D)
33      return ln((p+q)*.5,p).rot(ccw90);
34  }

```

4.3 Circle

```

1  struct circle {
2      pt o;double r;
3      circle(pt o, double r):o(o),r(r){}
4      circle(pt x, pt y, pt z){o=bisector(x,y)^bisector(x,z);r=(o-x).norm();}
5      vector<pt> operator^(circle c){ // ccw
6          vector<pt> s;
7          double d=(o-c.o).norm();
8          if(d>r+c.r+EPS||d+min(r,c.r)+EPS<max(r,c.r))return s;
9          double x=(d*d-c.r*c.r+r*r)/(2*d);
10         double y=sqrt(r*r-x*x);

```

```

11         pt v=(c.o-o)/d;
12         s.pb(o+v*x-v.rot(ccw90)*y);
13         if(y>EPS)s.pb(o+v*x+v.rot(ccw90)*y);
14         return s;
15     }
16     vector<pt> operator^(ln l){
17         vector<pt> s;
18         pt p=l.proj(o);
19         double d=(p-o).norm();
20         if(d-EPS>r)return s;
21         if(abs(d-r)<EPS){s.pb(p);return s;}
22         d=sqrt(r*r-d*d);
23         s.pb(p+l.pq.unit()*d);
24         s.pb(p-l.pq.unit()*d);
25         return s;
26     }
27     vector<pt> tang(pt p){
28         double d=sqrt((p-o).norm2()-r*r);
29         return *this^circle(p,d);
30     }
31     double intertriangle(pt a, pt b){ // area of intersection with oab
32         if(abs((o-a)%(o-b))<EPS)return 0.;
33         vector<pt> q={a},w=*this^ln(a,b);
34         if(w.size()==2)for(auto p:w)if((a-p)*(b-p)<-EPS)q.pb(p);
35         q.pb(b);
36         if(q.size()==4&&(q[0]-q[1])*(q[2]-q[1])>EPS)swap(q[1],q[2]);
37         double s=0;
38         forn(i,q.size()-1){
39             if(!has(q[i])||!has(q[i+1]))s+=r*r*(q[i]-o).angle(q[i+1]-o)/2;
40             else s+=abs((q[i]-o)%(q[i+1]-o)/2);
41         }
42         return s;
43     }
44 };
45 vector<double> intercircles(vector<circle> c){
46     vector<double> r(sz(c)+1); // r[k]: area covered by at least k circles
47     forn(i,sz(c)){ // 0(n^2 log n) (high constant)
48         int k=1;Cmp s(c[i].o);
49         vector<pair<pt,int>> p={
50             mp(c[i].o+pt(1,0)*c[i].r,0),
51             mp(c[i].o-pt(1,0)*c[i].r,0)};
52         forn(j,sz(c))if(j!=i){
53             bool b0=c[i].in(c[j]),b1=c[j].in(c[i]);

```

```

54     if(b0&&(!b1||i<j))k++;
55     else if(!b0&&!b1){
56         auto v=c[i]^c[j];
57         if(sz(v)==2){
58             p.pb(mp(v[0],1));p.pb(mp(v[1],-1));
59             if(s(v[1],v[0]))k++;
60         }
61     }
62 }
63 sort(p.begin(),p.end(),
64      [&](pair<pt,int> a, pair<pt,int> b){return s(a.fst,b.fst);});
65 forn(j,sz(p)){
66     pt p0=p[j?j-1:sz(p)-1].fst,p1=p[j].fst;
67     double a=(p0-c[i].o).angle(p1-c[i].o);
68     r[k]+=(p0.x-p1.x)*(p0.y+p1.y)/2+c[i].r*c[i].r*(a-sin(a))/2;
69     k+=p[j].snd;
70 }
71 }
72 return r;
73 }

```

4.4 Polygon

```

1 int sgn(double x){return x<-EPS?-1:x>EPS;}
2 struct pol {
3     int n;vector<pt> p;
4     pol(){}
5     pol(vector<pt> _p){p=_p;n=p.size();}
6     bool has(pt q){ // O(n)
7         forn(i,n)if(ln(p[i],p[(i+1)%n]).seghas(q))return true;
8         int cnt=0;
9         forn(i,n){
10             int j=(i+1)%n;
11             int k=sgn((q-p[j])%(p[i]-p[j]));
12             int u=sgn(p[i].y-q.y),v=sgn(p[j].y-q.y);
13             if(k>0&&u<0&&v>=0)cnt++;
14             if(k<0&&v<0&&u>=0)cnt--;
15         }
16         return cnt!=0;
17     }
18     void normalize(){ // (call before haslog, remove collinear first)
19         if(p[2].left(p[0],p[1]))reverse(p.begin(),p.end());
20         int pi=min_element(p.begin(),p.end())-p.begin();
21         vector<pt> s(n);

```

```

22     forn(i,n)s[i]=p[(pi+i)%n];
23     p.swap(s);
24 }
25 bool haslog(pt q){ // O(log(n)) only CONVEX. Call normalize first
26     if(q.left(p[0],p[1])||q.left(p.back(),p[0]))return false;
27     int a=1,b=p.size()-1; // returns true if point on boundary
28     while(b-a>1){ // (change sign of EPS in left
29         int c=(a+b)/2; // to return false in such case)
30         if(!q.left(p[0],p[c]))a=c;
31         else b=c;
32     }
33     return !q.left(p[a],p[a+1]);
34 }
35 pt farthest(pt v){ // O(log(n)) only CONVEX
36     if(n<10){
37         int k=0;
38         forr(i,1,n)if(v*(p[i]-p[k])>EPS)k=i;
39         return p[k];
40     }
41     if(n==sz(p))p.pb(p[0]);
42     pt a=p[1]-p[0];
43     int s=0,e=n,ua=v*a>EPS;
44     if(!ua&&v*(p[n-1]-p[0])<=EPS)return p[0];
45     while(1){
46         int m=(s+e)/2;pt c=p[m+1]-p[m];
47         int uc=v*c>EPS;
48         if(!uc&&v*(p[m-1]-p[m])<=EPS)return p[m];
49         if(ua&&(!uc||v*(p[s]-p[m])>EPS))e=m;
50         else if(ua||uc||v*(p[s]-p[m])>=-EPS)s=m,a=c,ua=uc;
51         else e=m;
52         assert(e>s+1);
53     }
54 }
55 pol cut(ln l){ // cut CONVEX polygon by line l
56     vector<pt> q; // returns part at left of l.pq
57     forn(i,n){
58         int d0=sgn(l.pq%(p[i]-l.p)),d1=sgn(l.pq%(p[(i+1)%n]-l.p));
59         if(d0>=0)q.pb(p[i]);
60         ln m(p[i],p[(i+1)%n]);
61         if(d0*d1<0&&!(1/m))q.pb(l~m);
62     }
63     return pol(q);
64 }

```

```

65 double intercircle(circle c){ // area of intersection with circle
66     double r=0.;
67     forn(i,n){
68         int j=(i+1)%n;double w=c.intertriangle(p[i],p[j]);
69         if((p[j]-c.o)%(p[i]-c.o)>0)r+=w;
70         else r-=w;
71     }
72     return abs(r);
73 }
74 double callipers(){ // square distance of most distant points
75     double r=0; // prereq: convex, ccw, NO COLLINEAR POINTS
76     for(int i=0,j=n-2?0:1;i<j;++i){
77         for(;;j=(j+1)%n){
78             r=max(r,(p[i]-p[j]).norm2());
79             if((p[(i+1)%n]-p[i])%(p[(j+1)%n]-p[j])<=EPS)break;
80         }
81     }
82     return r;
83 }
84 };
85 // Dynamic convex hull trick
86 vector<pol> w;
87 void add(pt q){ // add(q), O(log^2(n))
88     vector<pt> p={q};
89     while(!w.empty()&&sz(w.back().p)<2*sz(p)){
90         for(pt v:w.back().p)p.pb(v);
91         w.pop_back();
92     }
93     w.pb(pol(chull(p)));
94 }
95 ll query(pt v){ // max(q*v:q in w), O(log^2(n))
96     ll r=-INF;
97     for(auto& p:w)r=max(r,p.farthest(v)*v);
98     return r;
99 }

```

4.5 Plane

```

1 struct plane {
2     pt a,n; // n: normal unit vector
3     plane(pt a, pt b, pt c):a(a),n(((b-a)^(c-a)).unit()){}
4     plane(){}
5     bool has(pt p){return abs((p-a)*n)<EPS;}
6     double angle(plane w){return acos(n*w.n);}

```

```

7     double dist(pt p){return abs((p-a)*n);}
8     pt proj(pt p){inter(ln(p,p+n),p);return p;}
9     bool inter(ln l, pt& r){
10         double x=n*(l.p+l.pq-a),y=n*(l.p-a);
11         if(abs(x-y)<EPS)return false;
12         r=(l.p*x-(l.p+l.pq)*y)/(x-y);
13         return true;
14     }
15     bool inter(plane w, ln& r){
16         pt nn=n^w.n;
17         pt v=n^nn;
18         double d=w.n*v;
19         if(abs(d)<EPS)return false;
20         pt p=a+v*(w.n*(w.a-a)/d);
21         r=ln(p,p+nn);
22         return true;
23     }
24 };

```

4.6 Convex hull

```

1 // CCW order
2 // Includes collinear points (change sign of EPS in left to exclude)
3 vector<pt> chull(vector<pt> p){
4     vector<pt> r;
5     sort(p.begin(),p.end()); // first x, then y
6     forn(i,p.size()){ // lower hull
7         while(r.size()>=2&&r.back().left(r[r.size()-2],p[i]))r.pop_back();
8         r.pb(p[i]);
9     }
10    r.pop_back();
11    int k=r.size();
12    for(int i=p.size()-1;i>=0;--i){ // upper hull
13        while(r.size()>=k+2&&r.back().left(r[r.size()-2],p[i]))r.pop_back();
14        r.pb(p[i]);
15    }
16    r.pop_back();
17    return r;
18 }

```

5 Strings

5.1 KMP

```

1 vector<int> kmppre(string& t){ // r[i]: longest border of t[0,i)

```

```

2  vector<int> r(t.size()+1);r[0]=-1;
3  int j=-1;
4  forn(i,t.size()){
5      while(j>=0&&t[i]!=t[j])j=r[j];
6      r[i+1]=++j;
7  }
8  return r;
9  }
10 void kmp(string& s, string& t){ // find t in s
11     int j=0;vector<int> b=kmppre(t);
12     forn(i,s.size()){
13         while(j>=0&&s[i]!=t[j])j=b[j];
14         if(++j==sz(t))printf("Match at %d\n",i-j+1),j=b[j];
15     }
16 }

```

5.2 Z function

```

1  vector<int> z_function(string& s){
2      int a=0,b=0,n=sz(s);
3      vector<int> z(n,0); // z[i] = max k: s[0,k] == s[i,i+k]
4      forr(i,1,n){
5          if(i<=b)z[i]=min(b-i+1,z[i-a]);
6          while(i+z[i]<n&&s[z[i]]==s[i+z[i]])z[i]++;
7          if(i+z[i]-1>b)a=i,b=i+z[i]-1;
8      }
9      return z;
10 }

```

5.3 Manacher

```

1  int d1[MAXN]; //d1[i] = max odd palindrome centered on i
2  int d2[MAXN]; //d2[i] = max even palindrome centered on i
3  //s aabbaacaabbaa
4  //d1 1111117111111
5  //d2 0103010010301
6  void manacher(string& s){
7      int l=0,r=-1,n=s.size();
8      forn(i,n){
9          int k=i>r?1:min(d1[l+r-i],r-i);
10         while(i+k<n&&i-k>=0&&s[i+k]==s[i-k])k++;
11         d1[i]=k--;
12         if(i+k>r)l=i-k,r=i+k;
13     }

```

```

14     l=0;r=-1;
15     forn(i,n){
16         int k=i>r?0:min(d2[l+r-i+1],r-i+1);k++;
17         while(i+k<n&&i-k>=0&&s[i+k-1]==s[i-k-1])k++;
18         d2[i]=--k;
19         if(i+k-1>r)l=i-k,r=i+k-1;
20     }
21 }

```

5.4 Aho-Corasick

```

1  struct vertex {
2      map<char,int> next,go;
3      int p,link;
4      char pch;
5      vector<int> leaf;
6      vertex(int p=-1, char pch=-1):p(p),pch(pch),link(-1){}
7  };
8  vector<vertex> t;
9  void aho_init(){ //do not forget!!
10     t.clear();t.pb(vertex());
11 }
12 void add_string(string s, int id){
13     int v=0;
14     for(char c:s){
15         if(!t[v].next.count(c)){
16             t[v].next[c]=t.size();
17             t.pb(vertex(v,c));
18         }
19         v=t[v].next[c];
20     }
21     t[v].leaf.pb(id);
22 }
23 int go(int v, char c);
24 int get_link(int v){
25     if(t[v].link<0)
26         if(!v||!t[v].p)t[v].link=0;
27         else t[v].link=go(get_link(t[v].p),t[v].pch);
28     return t[v].link;
29 }
30 int go(int v, char c){
31     if(!t[v].go.count(c))
32         if(t[v].next.count(c))t[v].go[c]=t[v].next[c];
33         else t[v].go[c]=v==0?0:go(get_link(v),c);

```

```

34     return t[v].go[c];
35 }

```

5.5 Suffix automaton

```

1 struct state {int len,link;map<char,int> next;}; //clear next!!
2 state st[100005]; // should be >= 2*sz(s)
3 int sz,last;
4 void sa_init(){
5     last=st[0].len=0;sz=1;
6     st[0].link=-1;
7 }
8 void sa_extend(char c){
9     int k=sz++,p;
10    st[k].len=st[last].len+1;
11    for(p=last;p!=-1&&!st[p].next.count(c);p=st[p].link)st[p].next[c]=k;
12    if(p==-1)st[k].link=0;
13    else {
14        int q=st[p].next[c];
15        if(st[p].len+1==st[q].len)st[k].link=q;
16        else {
17            int w=sz++;
18            st[w].len=st[p].len+1;
19            st[w].next=st[q].next;st[w].link=st[q].link;
20            for(;p!=-1&&st[p].next[c]==q;p=st[p].link)st[p].next[c]=w;
21            st[q].link=st[k].link=w;
22        }
23    }
24    last=k;
25 }

```

5.6 Suffix array

```

1 #define RB(x) (x<n?r[x]:0)
2 void csort(vector<int>& sa, vector<int>& r, int k){
3     int n=sa.size();
4     vector<int> f(max(255,n),0),t(n);
5     forn(i,n)f[RB(i+k)]++;
6     int sum=0;
7     forn(i,max(255,n))f[i]=(sum+=f[i])-f[i];
8     forn(i,n)t[f[RB(sa[i]+k)]++]=sa[i];
9     sa=t;
10 }
11 vector<int> constructSA(string& s){ // O(n logn)

```

```

12     int n=s.size(),rank;
13     vector<int> sa(n),r(n),t(n);
14     forn(i,n)sa[i]=i,r[i]=s[i];
15     for(int k=1;k<n;k*=2){
16         csort(sa,r,k);csort(sa,r,0);
17         t[sa[0]]=rank=0;
18         forr(i,1,n){
19             if(r[sa[i]]!=r[sa[i-1]]||RB(sa[i]+k)!=RB(sa[i-1]+k))rank++;
20             t[sa[i]]=rank;
21         }
22         r=t;
23         if(r[sa[n-1]]==n-1)break;
24     }
25     return sa;
26 }

```

5.7 LCP (Longest Common Prefix)

```

1 vector<int> computeLCP(string& s, vector<int>& sa){
2     int n=s.size(),L=0;
3     vector<int> lcp(n),plcp(n),phi(n);
4     phi[sa[0]]=-1;
5     forr(i,1,n)phi[sa[i]]=sa[i-1];
6     forn(i,n){
7         if(phi[i]<0){plcp[i]=0;continue;}
8         while(s[i+L]==s[phi[i]+L])L++;
9         plcp[i]=L;
10        L=max(L-1,0);
11    }
12    forn(i,n)lcp[i]=plcp[sa[i]];
13    return lcp; // lcp[i]=LCP(sa[i-1],sa[i])
14 }

```

5.8 Suffix Tree (Ukkonen's algorithm)

```

1 struct SuffixTree {
2     char s[MAXN];
3     map<int,int> to[MAXN];
4     int len[MAXN]={INF},fpos[MAXN],link[MAXN];
5     int node,pos,sz=1,n=0;
6     int make_node(int p, int l){
7         fpos[sz]=p;len[sz]=l;return sz++;}
8     void go_edge(){
9         while(pos>len[to[node]][s[n-pos]]){

```

```

10     node=to[node][s[n-pos]];
11     pos-=len[node];
12 }
13 }
14 void add(int c){
15     s[n++]=c;pos++;
16     int last=0;
17     while(pos>0){
18         go_edge();
19         int edge=s[n-pos];
20         int& v=to[node][edge];
21         int t=s[fpos[v]+pos-1];
22         if(v==0){
23             v=make_node(n-pos,INF);
24             link[last]=node;last=0;
25         }
26         else if(t==c){link[last]=node;return;}
27         else {
28             int u=make_node(fpos[v],pos-1);
29             to[u][c]=make_node(n-1,INF);
30             to[u][t]=v;
31             fpos[v]+=pos-1;len[v]-=pos-1;
32             v=u;link[last]=u;last=u;
33         }
34         if(node==0)pos--;
35         else node=link[node];
36     }
37 }
38 };

```

5.9 Hashing

```

1 struct Hash {
2     int P=1777771,MOD[2],PI[2];
3     vector<int> h[2],pi[2];
4     Hash(const string& s){
5         MOD[0]=999727999;MOD[1]=1070777777;
6         PI[0]=325255434;PI[1]=10018302;
7         forn(k,2)h[k].resize(sz(s)+1),pi[k].resize(sz(s)+1);
8         forn(k,2){
9             h[k][0]=0;pi[k][0]=1;
10            ll p=1;
11            forr(i,1,sz(s)+1){
12                h[k][i]=(h[k][i-1]+p*s[i-1])%MOD[k];

```

```

13         pi[k][i]=(1LL*pi[k][i-1]*PI[k])%MOD[k];
14         p=(p*p)%MOD[k];
15     }
16 }
17 }
18 ll get(int s, int e){
19     ll r[2]; forn(k, 2){
20         r[k]=(h[k][e]-h[k][s]+MOD[k])%MOD[k];
21         r[k]=(1LL*r[k]*pi[k][s])%MOD[k];
22     }
23     return (r[0]<<32)|r[1];
24 }
25 };

```

6 Flow

6.1 Matching (slower)

```

1 vector<int> g[MAXN]; // [0,n)->[0,m)
2 int n,m;
3 int mat[MAXM];bool vis[MAXN];
4 int match(int x){
5     if(vis[x])return 0;
6     vis[x]=true;
7     for(int y:g[x])if(mat[y]<0||match(mat[y])){mat[y]=x;return 1;}
8     return 0;
9 }
10 vector<pair<int,int> > max_matching(){
11     vector<pair<int,int> > r;
12     memset(mat,-1,sizeof(mat));
13     forn(i,n)memset(vis,false,sizeof(vis)),match(i);
14     forn(i,m)if(mat[i]>=0)r.pb(mp(mat[i],i));
15     return r;
16 }

```

6.2 Matching (Hopcroft-Karp)

```

1 vector<int> g[MAXN]; // [0,n)->[0,m)
2 int n,m;
3 int mt[MAXN],mt2[MAXN],ds[MAXN];
4 bool bfs(){
5     queue<int> q;
6     memset(ds,-1,sizeof(ds));
7     forn(i,n)if(mt2[i]<0)ds[i]=0,q.push(i);
8     bool r=false;

```



```

9   while(!q.empty()){
10       int x=q.front();q.pop();
11       for(int y:g[x]){
12           if(mt[y]>=0&&ds[mt[y]]<0)ds[mt[y]]=ds[x]+1,q.push(mt[y]);
13           else if(mt[y]<0)r=true;
14       }
15   }
16   return r;
17 }
18 bool dfs(int x){
19     for(int y:g[x])if(mt[y]<0||ds[mt[y]]==ds[x]+1&&dfs(mt[y])){
20         mt[y]=x;mt2[x]=y;
21         return true;
22     }
23     ds[x]=1<<30;
24     return false;
25 }
26 int mm(){
27     int r=0;
28     memset(mt,-1,sizeof(mt));memset(mt2,-1,sizeof(mt2));
29     while(bfs()){
30         forn(i,n)if(mt2[i]<0)r+=dfs(i);
31     }
32     return r;
33 }

```

6.3 Hungarian

```

1  typedef double th;
2  const th INF=1e18; // to maximize: set INF to 1, use negative values
3  struct Hungarian {
4      int n,m; // important: n must be <=m
5      vector<vector<th>> > a;
6      vector<th> u,v;vector<int> p,way; // p: assignment
7      Hungarian(int n, int m):
8          n(n),m(m),a(n+1,vector<th>(m+1,INF-1)),u(n+1),v(m+1),p(m+1),way(m+1){}
9      void set(int x, int y, th v){a[x+1][y+1]=v;}
10     th assign(){
11         forr(i,1,n+1){
12             int j0=0;p[0]=i;
13             vector<th> minv(m+1,INF);
14             vector<char> used(m+1,false);
15             do {
16                 used[j0]=true;

```

```

17         int i0=p[j0],j1;th delta=INF;
18         forr(j,1,m+1)if(!used[j]){
19             th cur=a[i0][j]-u[i0]-v[j];
20             if(cur<minv[j])minv[j]=cur,way[j]=j0;
21             if(minv[j]<delta)delta=minv[j],j1=j;
22         }
23         forn(j,m+1)
24             if(used[j])u[p[j]]+=delta,v[j]-=delta;
25             else minv[j]-=delta;
26         j0=j1;
27     } while(p[j0]);
28     do {
29         int j1=way[j0];p[j0]=p[j1];j0=j1;
30     } while(j0);
31 }
32 return -v[0]; // cost
33 }
34 };

```

6.4 Dinic

```

1  // Min cut: nodes with dist>=0 vs nodes with dist<0
2  // MVC (bipartite): left nodes with dist<0 + right nodes with dist>0
3  int nodes,src,dst; // remember to init nodes
4  int dist[MAXN],q[MAXN],work[MAXN];
5  // ll M[MAXN]; (MIN CAP)
6  struct edge {int to,rev;ll f,cap;};
7  vector<edge> g[MAXN];
8  void add_edge(int s, int t, ll cap/*, ll lcap = 0 (MIN CAP)*/) {
9      // if(lcap) M[s] -= lcap, M[t] += lcap, cap -= lcap; (MIN CAP)
10     g[s].pb((edge){t,sz(g[t]),0,cap});
11     g[t].pb((edge){s,sz(g[s])-1,0,0});
12 }
13 bool dinic_bfs(){
14     fill(dist,dist+nodes,-1);dist[src]=0;
15     int qt=0;q[qt++]=src;
16     forn(qh,qt){
17         int u=q[qh];
18         forn(i,sz(g[u])){
19             edge &e=g[u][i];int v=g[u][i].to;
20             if(dist[v]<0&&e.f<e.cap)dist[v]=dist[u]+1,q[qt++]=v;
21         }
22     }
23     return dist[dst]>=0;

```

```

24 }
25 ll dinic_dfs(int u, ll f){
26     if(u==dst)return f;
27     for(int &i=work[u];i<sz(g[u]);i++){
28         edge &e=g[u][i];
29         if(e.cap<=e.f)continue;
30         int v=e.to;
31         if(dist[v]==dist[u]+1){
32             ll df=dinic_dfs(v,min(f,e.cap-e.f));
33             if(df>0){e.f+=df;g[v][e.rev].f-=df;return df;}
34         }
35     }
36     return 0;
37 }
38 ll max_flow(int _src, int _dst){ // O(m n^2)
39     src=_src;dst=_dst; // if unit weights, O(m min(sqrt(m), n^{2/3}))
40     ll result=0; // if bipartite matching, O(m sqrt(n))
41     while(dinic_bfs()){
42         fill(work, work+nodes, 0);
43         while(ll delta=dinic_dfs(src,INF))result+=delta;
44     }
45     return result;
46 }
47 //Checks if a strongly connected flow network has a feasible flow
48 //distribution
49 bool feasible(int n){ // n = number of nodes in the network
50     src = n, dst = n+1, nodes = n+2;
51     forn(i, n){
52         if(M[i] > 0)add_edge(src, i, M[i]);
53         if(M[i] < 0)add_edge(i, dst, -M[i]);
54     }
55     max_flow(src, dst);
56     for(edge e : g[src]) if(e.f < e.cap) return false;
57     return true;
58 }

```

6.5 Min cost max flow

```

1 typedef ll tf;const tf INFFLUJO=1e14;
2 typedef ll tc;const tc INFCOSTO=1e14;
3 struct edge {
4     int u,v;tf cap,flow;tc cost;
5     tf rem(){return cap-flow;}
6 };

```

```

7 int nodes; // remember to init nodes
8 vector<int> g[MAXN];
9 vector<edge> e;
10 void add_edge(int u, int v, tf cap, tc cost) {
11     g[u].pb(e.size());e.pb((edge){u,v,cap,0,cost});
12     g[v].pb(e.size());e.pb((edge){v,u,0,0,-cost});
13 }
14 tc dist[MAXN],mncost;
15 int pre[MAXN];
16 tf cap[MAXN],mxflow;
17 bool in_queue[MAXN];
18 void flow(int s, int t){
19     memset(in_queue,0,sizeof(in_queue));
20     mxflow=mncost=0;
21     while(1){
22         fill(dist,dist+nodes,INFCOSTO);dist[s]=0;
23         memset(pre,-1,sizeof(pre));pre[s]=0;
24         memset(cap,0,sizeof(cap));cap[s]=INFFLUJO;
25         queue<int> q;q.push(s);in_queue[s]=1;
26         while(q.size()){
27             int u=q.front();q.pop();in_queue[u]=0;
28             forn(_,g[u].size()){
29                 int i=g[u][_];
30                 edge &E=e[i];
31                 if(E.rem()&&dist[E.v]>dist[u]+E.cost+1e-9){
32                     dist[E.v]=dist[u]+E.cost;
33                     pre[E.v]=i;
34                     cap[E.v]=min(cap[u],E.rem());
35                     if(!in_queue[E.v])q.push(E.v),in_queue[E.v]=1;
36                 }
37             }
38         }
39         if(pre[t]<0)break;
40         mxflow+=cap[t];mncost+=cap[t]*dist[t];
41         for(int v=t;v!=s;v=e[pre[v]].u){
42             e[pre[v]].flow+=cap[t];e[pre[v]^1].flow-=cap[t];
43         }
44     }
45 }

```

7 Other

7.1 Mo's algorithm

```

1 int n,sq,nq; // array size, sqrt(array size), #queries
2 struct qu{int l,r,id;}; // O((n+nq)*sqrt(n)*update)
3 qu qs[MAXN];
4 ll ans[MAXN]; // ans[i] = answer to ith query
5 bool qcomp(const qu &a, const qu &b){
6     if(a.l/sq!=b.l/sq) return a.l<b.l;
7     return (a.l/sq)&1?a.r<b.r:a.r>b.r;
8 }
9 void mos(){
10     forn(i,nq)qs[i].id=i;
11     sq=sqrt(n)+.5;
12     sort(qs,qs+nq,qcomp);
13     int l=0,r=0;
14     init();
15     forn(i,nq){
16         qu q=qs[i];
17         while(l>q.l)add(--l);
18         while(r<q.r)add(r++);
19         while(l<q.l)remove(l++);
20         while(r>q.r)remove(--r);
21         ans[q.id]=get_ans();
22     }
23 }

```

7.2 Divide and conquer DP optimization

```

1 // O(knlogn). For 2D dps, when the position of optimal choice is non-
   decreasing as the second variable increases
2 int k,n,f[MAXN],f2[MAXN];
3 void doit(int s, int e, int s0, int e0, int i){
4     // [s,e): range of calculation, [s0,e0): range of optimal choice
5     if(s==e)return;
6     int m=(s+e)/2,r=INF,rp;
7     forr(j,s0,min(e0,m)){
8         int r0=f[j]+something(j,m-1); // calculate cost of taking [j,m-1]
9         if(r0<r)r=r0,rp=j; // position of optimal choice
10    }
11    f2[m]=r;
12    doit(s,m,s0,rp+1,i);doit(m+1,e,rp,e0,i);
13 }
14 int doall(){
15     init_base_cases();
16     forr(i,1,k+1)doit(1,n+1,0,n,i),memcpy(f,f2,sizeof(f));
17     return f[n];

```

```

18 }

```

7.3 Dates

```

1 int dateToInt(int y, int m, int d){ // 1-indexado (mes 2 = febrero)
2     return 1461*(y+4800+(m-14)/12)/4+367*(m-2-(m-14)/12*12)/12-
3         3*((y+4900+(m-14)/12)/100)/4+d-32075;
4 }
5 void intToDate(int jd, int& y, int& m, int& d){
6     int x,n,i,j;x=jd+68569;
7     n=4*x/146097;x-=(146097*n+3)/4;
8     i=(4000*(x+1))/1461001;x-=1461*i/4-31;
9     j=80*x/2447;d=x-2447*j/80;
10    x=j/11;m=j+2-12*x;y=100*(n-49)+i+x;
11 }

```

7.4 C++ stuff

```

1 const double DINF=numeric_limits<double>::infinity(); // double inf
2 // Custom comparator for set/map
3 struct comp {
4     bool operator()(const double& a, const double& b) const {
5         return a+EPS<b;
6     };
7 set<double,comp> w; // or map<double,int,comp>
8 // Iterate over non empty subsets of bitmask
9 for(int s=m;s;(s-1)&m) // Decreasing order
10 for (int s=0;s=s-m&m;) // Increasing order
11 // Returns the number of trailing 0-bits in x. x=0 is undefined.
12 int __builtin_ctz (unsigned int x)
13 // Returns the number of leading 0-bits in x. x=0 is undefined.
14 int __builtin_clz (unsigned int x)
15 // Use corresponding versions for long long appending ll at the end.
16 v=(x&(-x)) // Get the value of the least significant bit that is one.

```

7.5 Max number of divisors up to 10^n

```

1 (0,1) (1,4) (2,12) (3,32) (4,64) (5,128) (6,240) (7,448) (8,768) (9,1344)
   (10,2304) (11,4032) (12,6720) (13,10752) (14,17280) (15,26880)
   (16,41472) (17,64512) (18,103680)

```