

Summary of "Fault-Tolerant Electric Actuator for Heavy Unmanned Aerial Vehicles Using a Harmonic Drive"

Author and Affiliation

- **Mohamed A.A. Ismail**
Interdisciplinary Research Center for Aviation and Space Exploration, Aerospace Engineering Department, King Fahd University of Petroleum & Minerals (KFUPM), Dhahran, Saudi Arabia.

Abstract

- Heavy unmanned aerial vehicles (UAVs) require high safety and reliability.
- Electromechanical actuators (EMAs) must have fault-tolerant features according to certification requirements.
- This study introduces a fault-tolerant EMA architecture using a dual coaxial electric motor and a harmonic drive gear for flight control and health monitoring.
- The system can measure aerodynamic loads without extra sensors, enhancing fault detection during extreme conditions.

Key Takeaways

Introduction

- Heavy UAVs (>25 kg) face stringent airworthiness standards, particularly for flight control systems.
- Fault-tolerant EMAs are essential to reduce failure rates compared to non-tolerant UAVs.
- The study addresses the gap in existing fault detection methods by integrating load data and sensorless estimation.

Fault-Tolerant Architecture

- **Design Overview:**
 - Segregated architecture enhances resilience with independent control and monitoring units.
 - Dual-channel setup allows for full isolation and operational redundancy.
 - Operating modes: nominal, fail operational, and fail safe.
- **Sensorless Load Estimation:**
 - Utilizes the harmonic drive's structural damping for torque estimation, avoiding the need for additional sensors.
- **Health Monitoring System:**
 - Comprises three monitoring units to detect faults within and across lanes, improving diagnostic capability.

Experimental Testing

- **Setup:**
 - Conducted on a test rig with real-time control and fault injection capabilities.
- **Nominal Performance Testing:**
 - Evaluated actuator performance against tracking and bandwidth requirements, achieving less than 0.1° steady-state error and exceeding the required bandwidth.
- **Fault-Tolerant Performance Testing:**
 - Tested response to sensor faults, demonstrating rapid fault detection and lane shutdown, confirming the system's reliability.

Conclusion

- The experimental results validate the fault-tolerant EMA prototype's robustness and precision.
- Advanced monitoring algorithms and a redundant control architecture ensure compliance with aviation safety standards.
- The actuator meets and exceeds performance requirements for UAV applications, enhancing operational safety and reliability.

Acknowledgment

- Sponsored by project no. INAE2404 funded by KFUPM, with research conducted as part of the TEMA UAV project at the German Aerospace Center (DLR).

This summary captures the essential information regarding the development and testing of a fault-tolerant electric actuator for heavy UAVs, emphasizing its design, performance, and significance in enhancing safety and reliability in aerial systems.