

Fast Fourier Transformation (FFT) How-to implement a FFT in Real Time

Dr. Rainer Nitsche¹

¹Dept. Robotics System Design Group

Control Methods for Industrial Applications, August 2021



FFT Objectives

FESTO

Objectives of this class of nonlinear control?

- Robustness versus uncertainties / perturbations
- Finite time convergence towards the control objectives

FFT Objectives

FESIL

Objectives of this class of nonlinear control?

- Robustness versus uncertainties / perturbations
- Finite time convergence towards the control objectives

Features for this class of control?

- Discontinuous control law
- For standard sliding mode (first order): chattering effect, robustness
- For higher order sliding mode: accuracy, finite time convergence, robustness

FFT Objectives

FESIL

Objectives of this class of nonlinear control?

- Robustness versus uncertainties / perturbations
- Finite time convergence towards the control objectives

Features for this class of control?

- Discontinuous control law
- For standard sliding mode (first order): chattering effect, robustness
- For higher order sliding mode: accuracy, finite time convergence, robustness

Remark

Sliding mode as a phenomenon may appear in a dynamic system governed by ordinary differential equation with *discontinuous right hand side*



FESTO

This is a text in second frame. For the sake of showing an example.

Good youtube video from Ali Nasir: Link

FESTO

This is a text in second frame. For the sake of showing an example.

- Good youtube video from Ali Nasir: Link
- Text visible on slide 2

FESTO

This is a text in second frame. For the sake of showing an example.

- Good youtube video from Ali Nasir: Link
- Text visible on slide 2
- Text visible on slide 3

FESTO

This is a text in second frame. For the sake of showing an example.

- Good youtube video from Ali Nasir: Link
- Text visible on slide 2
- Text visible on slide 4

A motivating Example for SMC

FESTO

Example

Sliding mode of the system [utkin2020]:


$$\ddot{x} = \sin(3t) + u \tag{1}$$

with sliding surface

$$s = c\dot{x} + x \tag{2}$$

with control law

$$u = -M\operatorname{sgn}(s) \tag{3}$$



Simulation results for M = 3 and $c = 1 \text{ s}^{-1}$

If the system is in sliding mode, *i. e.* s=0, the dynamics is $s=\dot{x}+x=0$ and therefore indepentend of system parameters or disturbance \leadsto robust!

Sample frame title

FESTO

In this slide, some important text will be highlighted because it's important. Please, don't abuse it.

Remark

Sample text

Important theorem

Sample text in red box


Examples

Sample text in green box. The title of the block is "Examples".



TikZ Test





References

FESTO