

# Summary of "On the Advancements of the Forward-Forward Algorithm"

**Authors:** Mauricio Ortiz Torres, Markus Lange, Arne P. Raulf

**Affiliation:** German Aerospace Center (DLR), Institut for AI-Safety and Security, Germany

## Abstract

The Forward-Forward (FF) algorithm, introduced by Geoffrey Hinton in 2022, has been enhanced to tackle complex machine learning tasks, notably improving performance on datasets like CIFAR10. Key improvements include:

- **Techniques Used:** Convolutional channel grouping, learning rate schedules, and independent block structures during training.
- **Performance Improvement:** Achieved a 20% reduction in test error rates.
- **Lightweight Models:** Developed lighter models with test error rates ranging from  $(21 \pm 6)\%$  and trainable parameters between 164,706 and 754,386.

## Introduction

- The FF algorithm is designed for low-power hardware applications, focusing on classification tasks with reduced memory consumption.
- It utilizes two forward passes during training rather than traditional backpropagation, resulting in lower memory requirements.

## The Forward-Forward (FF) Algorithm

### A. Original Approach

- Operates with two input spaces (positive and negative samples) created from the dataset.
- Uses a "goodness" loss function to adjust weights based on the goodness of layer outputs for both positive and negative samples.

### B. Variations to the Algorithm

1. **Input Data Creation:**
  - Improved techniques for generating positive and negative samples to enhance correlation.
2. **Loss Functions:**
  - New loss functions focus on better control of distances between data samples and their classes.
3. **Training Routines:**
  - Explores parallel training architectures to enhance efficiency.
4. **Faster Inference:**
  - Techniques to reduce the number of activity vectors used for predictions to improve inference speed.

### C. Unsupervised Learning Applications

- The principles of the FF algorithm have been adapted for unsupervised learning, leading to the development of Unsupervised learning Forward-Forward models (UFF).

## Results & Analysis

- Improved FF algorithm shows significant performance enhancements on MNIST and CIFAR10 datasets.
- Comparison of original and improved algorithms indicates a reduction in test error percentages and faster inference times.
- The improved algorithm maintains independent layer training, allowing for better hyperparameter tuning and convergence.

## Lightweight Models

- Developed several lighter FF models aimed at low-capacity hardware applications, achieving significant parameter reductions while maintaining low test error rates.
- The FF tiny model shows a 96% reduction in parameters compared to the FF deep model, with a test error of 24.1%.

## Conclusion

- The FF algorithm continues to evolve, demonstrating its potential for low-power hardware applications and improved performance on complex tasks.
- Future work will focus on verification and validation of these models.

## Key Takeaways

- **Performance:** Improved FF algorithm reduces test errors significantly.
- **Flexibility:** Maintains flexibility with lightweight models suitable for low-capacity hardware.
- **Future Research:** Will explore the verification and validation of FF models.

## Action Items

- Investigate further applications and improvements of the FF algorithm.
- Explore the implications of lightweight models in practical implementations.