

Capacitor-Driven Cascade Motor

By Milos M Ilic 2024

МИЛОШ
ИЛИЋ
0139627
00 Sign

Signed by:
МИЛОШ ИЛИЋ
013962700 Sign
Date: 2026-02-10
13:32:14 CET

The Capacitor Impulse Mechanism (The "Kick")

To satisfy your core requirement—that energy from one motor powers the next—we introduce Inter-Stage High-Voltage Capacitors. The Concept: Instead of connecting the motors directly (which causes drag), we place a capacitor bank between Motor A and Motor B. The Cycle: Harvesting: As Motor A spins, it generates Back-EMF (excess voltage). Instead of wasting this, it charges the capacitor. The "Hit": Once the capacitor is full and Motor B is in the correct position (the "socket"), the capacitor discharges its energy instantly into Motor B. Acceleration: This rapid discharge creates a massive magnetic spike (an electromagnetic "hit") that forces Motor B to accelerate faster than Motor A. This creates a "Bucket Brigade" of energy.

2. Electronic Torque Converter

The "Battery" (Blue - Fastest): This is the input motor. It spins freely at very high RPM (Spins Per Second) because it is not directly connected to the wheels. It builds up kinetic energy and charges the first capacitor bank. The Intermediate Stages: These motors act as transmission gears. They receive the "capacitor kicks" from the blue motor. They spin slightly slower but with more magnetic force (Torque). The Output (Dark Green - Slowest): This motor is connected to the load (wheels). It moves with immense power. It cannot get "stuck" because it is being "hit" by the accumulated energy of all previous motors. Key Improvement: This gradient solves the "locking" issue. The first motor never locks because it doesn't touch the ground 100%. It just pumps energy down the line.

Variable Load Transfer & Independent Power Injection:

The "Free Motor" Principle: To ensure the system never stalls, the first motor (Blue) operates on a Variable Load Gradient. It is never fully coupled to the next stage. instead, it retains 50% of its power to maintain maximum RPM (High Kinetic Potential), transferring only the remaining 50% as "friction" or drive force to the next motor. This guarantees the input source remains at peak efficiency and never locks up under load.

The Power Cascade (50% to 100%): This load transfer increases progressively down the line. While the first motor transfers 50%, the subsequent stages increase engagement: 60%, then 80%, up to the final motor.

Input Stage: Retains speed, transfers partial torque.

Output Stage: The final motor receives 100% of the accumulated power, converting the high-speed potential of the previous stages into raw torque for the wheels.

Dual-Source Propulsion (The "Turbo" Effect): Crucially, energy is not merely passed passively down the line. Every motor has its own independent energy source. Each stage receives:

- Mechanical Spin: The kinetic transfer from the previous motor.
- Active Power: Its own direct battery connection.
- The Turbo: The Capacitor Impulse (described in Sec 1). This means the capacitors act as a "Turbo Charger" on top of the motor's independent power, compounding the force rather than just splitting it. We can add more motors, and start with smaller percentage of friction given - 20 % or 5% and those may not remain fixed, but to be set to change based on the situation.

Cascaded Impulse-Augmented Multi-Motor Torque Cascade System (CIAMTCS)

1. System Overview and Core Innovation

The CIAMTCS is an all-electric propulsion architecture that delivers high torque multiplication and complete stall resistance without gearboxes, torque converters, clutches, or rigid mechanical connections between stages.

A series of electric motors is arranged along a shared rotational shaft line. Energy transfers downstream in a bucket-brigade sequence using timed, high-voltage capacitor impulse discharges. Each motor after the input stage receives three independent energy inputs at the same time:

- A precisely controlled fraction of mechanical drive from the upstream motor, adjusted via variable coupling (starting very low).
- Direct high-power electrical supply from its own dedicated battery bank or DC source.
- A powerful electromagnetic impulse from the rapid discharge of the upstream capacitor bank.

The impulse multiplies the effect of the independent power and partial mechanical input, creating strong, progressive torque amplification from very high input speed to very high output torque at low speed.

2. Physical Architecture

The system is built as one continuous cylindrical rotor assembly divided into graduated motor sections:

- Input section (blue) — high-RPM section designed for maximum rotational speed with almost no mechanical load.
- Intermediate sections (orange → yellow → green) — torque-building stages that combine upstream drive, full independent power, and capacitor impulses. Speed decreases while torque increases through these sections.
- Output section (dark green) — final drive stage connected directly to the load (vehicle wheels, industrial shaft, propeller, or other application).

Inter-stage components include:

- High-voltage capacitor banks placed between each motor pair for energy storage and impulse generation.
- Fast electronic switches for accurate, high-current discharge timing.
- Rotor position sensors to trigger discharges at the precise alignment point for best torque application.
- Variable couplers (electromagnetic, magnetic-particle, or flux-controlled) that dynamically set the mechanical transfer percentage.

3. Operating Cycle

1. Input Energy Collection

The input motor runs at high speed with minimal load. It generates back-EMF that charges the first capacitor bank quickly and efficiently.

2. Impulse Discharge

When the capacitor is fully charged and the downstream rotor is correctly aligned, the switch activates. A high-current pulse discharges through the next motor's windings, producing a strong magnetic force that accelerates the stage significantly more than steady power would.

3. Progressive Energy Buildup

Each stage collects back-EMF to charge the next capacitor, then delivers a timed impulse. All stages receive continuous independent power. The impulses add to and multiply the baseline torque, resulting in cumulative torque increase down the chain as rotational speed reduces.

4. Variable Load Gradient and Stall Prevention

Mechanical transfer begins low at the input (typically 5–15%) to keep the input motor at high RPM without drag. The transfer percentage rises steadily through the stages (20% → 50% → 75% → nearly 100% at output).

If load increases sharply, the system automatically lowers upstream mechanical transfer (down to near-zero when necessary) and depends more on independent power and impulses. This keeps the input motor running at full speed, avoids any stage locking, and ensures the system stays responsive under all conditions.

4. Main Advantages

- Electronic Torque Multiplication — Converts high input kinetic energy into high output torque using only impulses and multi-input compounding, without mechanical gearing.
- Complete Stall Resistance — Variable coupling and per-stage independent power make it impossible for the system to lock or stall, even under very high or sudden loads.
- Energy Compounding — Impulses recycle collected energy while enhancing independent inputs, producing more total torque than the separate contributions alone.
- Scalable Design — Add more intermediate stages to increase torque ratio or refine the speed-to-torque transition. Adaptive control (via microcontroller with sensor inputs for RPM, torque, current, and temperature) continuously optimizes the transfer percentages.
- High Efficiency Potential — Very low input drag combined with reuse of generated energy as forward-driving impulses reduces overall losses compared to traditional or rigidly coupled systems.

5. Simplified Mathematical Representation

n stages (1 = input, n = output)

Mechanical transfer fraction at stage k: f_k

(f_1 low, e.g. 0.05–0.15; increases progressively to $f_n \approx 1.0$)

Torque at stage k:

$$\tau_k = f_k \cdot \tau_{\{k-1\}} + \tau_{\text{indep},k} + \Delta\tau_{\text{impulse},k-1}$$

Where:

- $\tau_{\text{indep},k} \approx k_t \cdot I_{\text{indep},k}$ (k_t = torque constant, $I_{\text{indep},k}$ = current from dedicated supply)

- $\Delta\tau_{\text{impulse},k-1}$ scales with capacitor stored energy ($\frac{1}{2} C V^2$), discharge characteristics, winding properties, and magnetic interaction

Speed decreases across stages: $\omega_1 \gg \omega_2 > \dots > \omega_n$

The impulse term provides the main step-up in torque at each transition.

Adaptive control adjusts f_k in real time to maintain optimal speed at the input and maximum torque delivery at the output.

