

# Text Technologies for Data Science INFR11145

## **Text Classification** (2)

Instructor: Walid Magdy

07-Nov-2017

#### **Lecture Objectives**


- <u>Implement</u> your first text classifier easy steps
- This is practical lecture
   No equations this time ©

THE UNIVERSITY of EDINBURGH

### My first text classifier: Ingredients

- Text elements to be classified
  - Document, paragraph, sentence
- Set of predefined classes (classification task)
  - At least two (binary)
  - · Topical, spam, relevance, sentiment, ...
- Training set
  - · Enough samples of text elements for each class
- Test set
  - Some samples of each class that not used in training
- Features set
  - A set of features extracted from the text to train the classifier
- Classifier
  - The ML module that learns a classification model






#### My first text classifier: Steps

- Prepare training data required: piece of text + label to class
- 2. Extract features
  - 1. Pre-process text: lowercase, tokenise, remove useless strings
  - 2. Create a list of all unique terms in the training data. Give each term a unique ID
  - Convert the text into features, by replacing each term with its corresponding feature ID.
     Add value to the feature (simplest value "1" if exists)
  - 4. For SVM<sub>light</sub>, zero value features could be neglected. Features need to be listed in order
- 3. Prepare test file
  - Convert test file text into features using the same mapping from the training data. For terms that are not in the features list, it could be neglected, or assigned to an ID the represents OOV.
- 4. Run the learning process on the training data features files to create a model
- 5. Run the classification on the features file of the test data and save predictions into a file
- 6. Evaluate performance using accuracy and Macro-F1





#### **Possible Improvements**

- Feature Extraction
  - · Apply stemming & stopping
  - Duplicate hashtags words (#car → #car car)
  - Expand tweet text that has link with the page title of that link
  - Add new set of features to the terms appearing in the profile description of the author of the tweet
    - E.g. tweets terms features: ID range: 1 → 12000 profile terms features: ID range: 12001 → 20000
    - If a term appeared in the tweet and in the profile description, these are two different features with two different IDs
  - Try non-textual features
    - Tweet length, presence of hashtags, links, emojis ...

Walid Magdy, TTDS 201<u>7/2018</u>



#### **Possible Improvements**

- Feature weighting
  - Using tfidf, BM25 as the feature value instead of binary
- · Learning method
  - Test other ML learning methods other than SVM
    - · Random forest
    - Decision trees
    - · Naive Bayesian
  - Test DNNs with word embeddings
- Add more training data
  - · Think about a way to create more training data

THE UNIVERSITY of EDINBURGH

#### Resources

- Magdy W., H. Sajjad, T. El-Ganainy and F. Sebastiani. (2015)
   Bridging Social Media via Distant Supervision.
   Springer SNAM 2015 <u>link</u>, <u>arXiv</u>
- Additional reading:
   Nguyen, D. P., Gravel, R., Trieschnigg, R. B., & Meder, T.
   How old do you think I am? A study of language and age in Twitter.

   ICWSM 2013

