

ApiGenie — User Guide

Get started fast: deploy, configure sources, test with curl, push logs, create detection rules.

1. Deploy

```
git clone <repo-url> && cd apigenie
./scripts/bootstrap.sh           # generates TLS certs, configures domain
docker compose up -d --build     # starts all containers
```

Verify:

```
curl -sk https://localhost/health
# {"status":"ok","service":"apigenie"}
```

Open the Admin UI: `https://<your-domain>/admin` Default credentials: `admin` / `apigenie`



API Genie ADMIN CONSOLE

Sign in

Restricted access · authorised operators only

Username



Password

Continue

Crafted with ❤️ by the [RoarinPenguin](#)


2. Source Details — View Configuration

Navigate to **Source Details** in the left menu. Click any source chip to see:

- **Auth type** and credentials

Crafted with ❤️ by the [RoarinPenguin](#)

- **Endpoints** (method, path, description)
- **Ready-to-use curl command**



3. Test Pull Sources with curl

SentinelOne

```
# Threats (MITRE-mapped, full agent info)
curl -sk -H "Authorization: ApiToken apigenie-valid-token-001" \
  "https://localhost/web/api/v2.1/threats?limit=5"

# Activities (agent lifecycle, scans, STAR rules)
curl -sk -H "Authorization: ApiToken apigenie-valid-token-001" \
  "https://localhost/web/api/v2.1/activities?limit=5"

# Agent inventory
curl -sk -H "Authorization: ApiToken apigenie-valid-token-001" \
  "https://localhost/web/api/v2.1/agents?limit=5"
```

Okta

```
curl -sk -H "Authorization: SSWS apigenie-valid-token-001" \
  "https://localhost/api/v1/logs?limit=5"
```

Cloudflare

```
curl -sk -H "Authorization: Bearer apigenie-valid-token-001" \
  "https://localhost/client/v4/zones/zone_abc123/logs/received?count=5"
```

Cato Networks (GraphQL)

```
curl -sk -X POST "https://localhost/api/v1/graphql2" \
  -H "x-api-key: any-key" -H "Content-Type: application/json" \
  -d '{"query":"{ eventsFeed(accountIDs:[12345]) { marker fetchedCount accounts { records { event_type time } } } }"}'
```

Zscaler ZPA

```
curl -sk -H "Authorization: Bearer apigenie-valid-token-001" \
  "https://localhost/mgmtconfig/v2/admin/customers/12345/userActivity?
  pagesize=5"
```

Microsoft Entra ID

```
curl -sk -H "Authorization: Bearer apigenie-valid-token-001" \
  "https://localhost/v1.0/auditLogs/directoryAudits"
```

Wiz (GraphQL)

```
curl -sk -H "Authorization: Bearer apigenie-valid-token-001" \
  -X POST -H "Content-Type: application/json" \
  -d '{"query":"{ issues { nodes { id severity } } }"}' \
  "https://localhost/graphql"
```

Darktrace

```
curl -sk "https://localhost/modelbreaches?limit=5"
```

Snyk

```
curl -sk -H "Authorization: token apigenie-valid-token-001" \
  "https://localhost/v1/org/test-org/audit"
```

Proofpoint TAP

```
curl -sk -u "apigenie-principal-001:apigenie-secret-001" \  
  "https://localhost/v2/siem/all"
```

Tenable (async export)

```
# Start export  
curl -sk -H "X-ApiKeys: accessKey=apigenie-access-001;secretKey=apigenie-secret-001" \  
  -X POST "https://localhost/vulns/export" \  
  -H "Content-Type: application/json" -d '{"filters":{}}'  
  
# Check status (use uuid from response)  
curl -sk -H "X-ApiKeys: accessKey=apigenie-access-001;secretKey=apigenie-secret-001" \  
  "https://localhost/vulns/export/<uuid>/status"  
  
# Download chunk  
curl -sk -H "X-ApiKeys: accessKey=apigenie-access-001;secretKey=apigenie-secret-001" \  
  "https://localhost/vulns/export/<uuid>/chunks/0"
```


4. Quick Reference — Auth per Source

Source	Auth header	Token value
Okta	Authorization: SSWS <token>	apigenie-valid-token-001
Netskope	Netskope-API-Token: <token>	apigenie-valid-token-001
Entra ID / Defender	Authorization: Bearer <token>	apigenie-valid-token-001
Cisco Duo	HMAC-SHA1 (mock accepts any)	any
Tenable	X-ApiKeys: accessKey=...;secretKey=...	apigenie-access-001 / apigenie-secret-001
Proofpoint	HTTP Basic	apigenie-principal-001 / apigenie-secret-001
Wiz	Authorization: Bearer <token>	apigenie-valid-token-001
Snyk	Authorization: token <token>	apigenie-valid-token-001
Darktrace	HMAC (mock accepts any)	any
M365	OAuth2 → JWT	any client_id/secret
Cato	x-api-key: <key>	any
Cloudflare	Authorization: Bearer <token>	apigenie-valid-token-001
Zscaler ZPA	Authorization: Bearer <token>	apigenie-valid-token-001
SentinelOne	Authorization: ApiToken <token>	apigenie-valid-token-001

5. Log Push — Send Logs to External Destinations

Step 1: Open Log Push tab

Navigate to **Log Push** in the left menu.




Step 2: Create a push profile

Click **+ New profile** and fill in:

Field	Description	Example
Name	Profile identifier	paloalto-to-s1-siem
Source	Log source type	Palo Alto PAN-OS
Format	JSON, Syslog, or CEF	JSON
Transport	HEC, Syslog, or HTTP POST	HEC
HEC Flavour	Splunk / S1 AI SIEM / Observo	S1 AI SIEM
Host	Destination hostname	ingest.usea1.sentinelone.net
Port	Destination port	443
Path	HEC endpoint path	/services/collector/raw
Token	Auth token	<your-api-token>
Account ID	S1 account ID (S1 SIEM only)	2149421019176225082
Duration	How long to push (seconds)	300
Rate (EPS)	Events per second	10
TLS	Enable HTTPS	✓

Step 3: Start pushing

Click **Start** on the profile card. Logs stream in real-time.



Available sources for push

All 16 push sources are listed in the Source dropdown. Each generates realistic, weighted events matching the real vendor log format.

6. Log Profiles — Entity Blending

What are profiles?

Profiles define **entity pools** — realistic users, machines, C2 servers, malware samples, and mail senders. When assigned to a source, profile entities are blended into generated logs.

Step 1: Create a profile

Go to **Log Profiles & Detection Rules** → expand ▶ **Log Profiles** → click **+ New profile**.

Define entity pools:

Pool	Example entries
Users	jsmith (username), CORP\jsmith (domain), jsmith@contoso.com (email)
Machines	DESKTOP-HQ01 (workstation), 192.168.1.100 (IP), Windows 11 (OS)
C2 servers	evil.com (FQDN), 198.51.100.1 (IP), 4444 (port)
Malware	payload.exe (filename), mimikatz (family), cmd.exe /c whoami (cmdline)
Mail senders	phisher@evil.com (from), Urgent Invoice (subject)

Step 2: Bind to sources

Expand ► **Source** ↔ **Profile bindings**. For each source:


- Select the profile
- Set **signal-to-noise ratio** (how often profile entities appear vs random)
- Set **log volume** (1–100% of max output per API call)

The screenshot shows the 'Log Profiles & Detection Rules' section of the ApiGenie Admin interface. The sidebar on the left contains navigation links: MONITOR (Observability, Requests), TROUBLESHOOTING (Intrusions, Investigations, Container Logs), CONFIGURATION & REFERENCE (Listeners, Log Profiles & Detection Rules, Log Push, Source Details, System Settings), and a Sign out button. The main content area is titled 'Log Profiles & Detection Rules' and includes a '+ New profile' button. Below this is a section for 'SOURCE ↔ PROFILE BINDINGS' with a descriptive text: 'Assign profiles to sources, tune signal-to-noise ratio, and control log volume per source (1–100% of max output per API call)'. The interface displays a grid of 15 source bindings, each with a dropdown menu for profile selection, a slider for signal-to-noise ratio, and a slider for log volume. The sources listed are Okta, Microsoft 365, GCP Cloud Logging (Pub/Sub emulator), Wiz, Darktrace, Zscaler Private Access (ZPA), Netskope, Microsoft Defender, Tenable, Snyk, Cato Networks SASE, SentinelOne, Microsoft Entra ID, Cisco Duo, Proofpoint TAP, Azure Platform (Event Hubs), Cloudflare, and The Roarin Listener (endpoint). Each binding has a 'Save' button, and some have an 'Unbind' button.

7. Request Inspector

The **Requests** tab shows all incoming API requests in real-time:

- Method, path, query parameters
- Source auto-detection
- Response status code
- Timing



8. Observability

The **Observability** tab provides:

- **Sankey diagram** — request flow by source
- **Geographic map** — client IP distribution
- **Usage chart** — requests over time
- **System metrics** — CPU and container stats

