

CSE 549: Hidden Markov Models (in prep for ab initio gene finding)

A Basic Probability Refresher

Ω — The sample space (set of all possible outcomes)

e.g. all possible values for a roll of a die $\{1,2,3,4,5,6\}$, need not be finite

E — An event; a subset of the sample space


e.g. all even rolls of a die $\{2,4,6\}$

X — Random variable; measurable function from $\Omega \rightarrow E$

e.g. X = value on the upward face of the die

$\Pr(E)$ — Probability of the event E

e.g. $\Pr(X \text{ is even}) = \Pr(X \in \{2,4,6\}) = |\{2,4,6\}| / |\{1,2,3,4,5,6\}| = 0.5$




In a discrete, finite, sample space, **if all outcomes are equally likely**, one can think of this as $|E| / |\Omega|$

Probabilities

Joint Probability


$$\Pr(A,B) = \Pr(A \cap B) = \Pr(A|B) \Pr(B)$$



Probabilities

Probability of Union of Two Events


$$\Pr(A \cup B) = \Pr(A) + \Pr(B) - \Pr(A, B)$$



Probabilities

Conditional Probability

$$\Pr(A|B) = \Pr(A, B) / \Pr(B)$$



Independence

Independent Events

$$X \perp Y \iff \Pr(X, Y) = \Pr(X) \Pr(Y)$$

Conditionally Independent Events

$$X \perp Y \mid Z \iff \Pr(X, Y \mid Z) = \Pr(X \mid Z) \Pr(Y \mid Z)$$

Checking a Casino



Fair coin:
 $\text{Pr}(\text{Heads}) = 0.5$



Biased coin:
 $\text{Pr}(\text{Heads}) = 0.75$



Suppose either a fair or biased coin was used to generate a sequence of heads & tails. But we don't know which type of coin was actual used.

Heads/Tails: ↑ ↑ ↓ ↓ ↓ ↓ ↑ ↑ ↑ ↑ ↓ ↑ ↓ ↑ ↓ ↑

How could we guess which coin was more likely?

Compute the Probability of the Observed Sequence

Fair coin: $\Pr(\text{Heads}) = 0.5$
Biased coin: $\Pr(\text{Heads}) = 0.75$

$x =$ 

$$\Pr(x \mid \text{Fair}) = 0.5 \times 0.5 \times 0.5 \times 0.5 \times 0.5 \times 0.5 \times 0.5 = 0.5^7 = 0.0078125$$

$$\Pr(x \mid \text{Biased}) = 0.75 \times 0.75 \times 0.25 \times 0.25 \times 0.25 \times 0.25 \times 0.75 = 0.001647949$$

The *log-odds* score:

$$\log_2 \frac{\Pr(x \mid \text{Fair})}{\Pr(x \mid \text{Biased})} = \log_2 \frac{0.0078}{0.0016} = 2.245$$

> 0 . Hence “Fair” is a better guess.


(1st order) Markov Chain

What if the coin tosses weren't independent?

e.g. coin tended to have “runs” of the same value.

Discrete, random process where the ***next state depends only on the current state.***

Markov Chain describing a “hot” coin



Total transition probability at each state is unity

(1st order) Markov Chain

What if the coin tosses weren't independent?

e.g. coin tended to have “runs” of the same value.


Discrete, random process where the ***next state depends only on the current state***.

Factorization Always True

$$\Pr(x_1, x_2, \dots, x_n) = \Pr(x_n \mid x_1, x_2, \dots, x_{n-1}) \Pr(x_{n-1} \mid x_1, x_2, \dots, x_{n-2}) \dots \\ \Pr(x_2 \mid x_1) \Pr(x_1)$$


Factorization True if process is Markovian

$$\Pr(x_1, x_2, \dots, x_n) = \Pr(x_n \mid x_{n-1}) \Pr(x_{n-1} \mid x_{n-2}) \dots \Pr(x_2 \mid x_1) \Pr(x_1)$$



(1st order) Markov Chain

Markov Chain describing a “hot” coin



Can define the joint probability for a sequence of observations:

x = H T T T T T H H H H T T T H H H H H

$$\Pr(\mathbf{x}) = \Pr(x_1, x_2, \dots, x_n) = \Pr(x_1) \prod_{t=2}^n \Pr(x_t \mid x_{t-1})$$

e.g. above, if we were equally likely to start at H or T

$$\begin{aligned} \Pr(\mathbf{x}) &= 0.5 \times 0.2 \times 0.8 \times 0.8 \times 0.8 \times 0.8 \times 0.2 \times 0.8 \times 0.8 \times 0.8 \times 0.2 \times 0.8 \times 0.8 \times 0.2 \times 0.8 \times 0.8 \times 0.8 \times 0.8 \\ &\approx .000043980465111040 \end{aligned}$$

Markov Chain Detour

Mark V Shaney

Developed by Bruce Ellis & Rob Pike in the 1980s

>From mvs Fri Nov 16 17:11 EST 1984 remote from alice

It looks like Reagan is going to say? Ummm... Oh yes, I was looking for. I'm so glad I remembered it. Yeah, what I have wondered if I had committed a crime. Don't eat with your assessment of Reagan and Mondale. Up your nose with a guy from a firm that specifically researches the teen-age market. As a friend of mine would say, "It really doesn't matter"... It looks like Reagan is holding back the arms of the American eating public have changed dramatically, and it got pretty boring after about 300 games.

People, having a much larger number of varieties, and are very different from what one can find in Chinatowns across the country (things like pork buns, steamed dumplings, etc.) They can be cheap, being sold for around 30 to 75 cents apiece (depending on size), are generally not greasy, can be adequately explained by stupidity. Singles have felt insecure since we came down from the Conservative world at large. But Chuqui is the way it happened and the prices are VERY reasonable.

Can anyone think of myself as a third sex. Yes, I am expected to have. People often get used to me knowing these things and then a cover is placed over all of them. Along the side of the \$\$ are spent by (or at least for) the girls. You can't settle the issue. It seems I've forgotten what it is, but I don't. I know about violence against women, and I really doubt they will ever join together into a large number of jokes. It showed Adam, just after being created. He has a modem and an autodial routine. He calls my number 1440 times a day. So I will conclude by saying that I can well understand that she might soon have the time, it makes sense, again, to get the gist of my argument, I was in that (though it's a Republican administration).


__-__-__-Mark

- "I spent an interesting evening recently with a grain of salt."
- "I hope that there are sour apples in every bushel."

One appealing property of Markov Chains is that they are **generative** models

Walk the model and take transitions proportional to their probabilities — you get a stochastic output that is consistent with your model!


Back to the casino: What if the casino can switch coins?



Looks like a Markov chain, but different. The “state” (i.e. “fair” or “biased”) is not observed. **However**, we do observe output that depends, probabilistically, on the states (e.g. heads or tails). This is a **Hidden Markov Model** (HMM).

Typically, we're interested in questions involving these hidden states

Fair coin: $\Pr(\text{Heads}) = 0.5$
Biased coin: $\Pr(\text{Heads}) = 0.75$
Probability of switching coins = 0.1




How can we compute the probability of the entire sequence?

How could we guess which coin was more likely **at each position**?

How can we compute the probability of the entire sequence?


Fair coin: $\Pr(\text{Heads}) = 0.5$
Biased coin: $\Pr(\text{Heads}) = 0.75$
Probability of switching coins = 0.1



If we knew the set of hidden states, computing this would be easy!


What if the casino switches coins?

How can we compute the probability of the entire sequence?



What if the casino switches coins?


How can we compute the probability of the entire sequence?



What if the casino switches coins?

*


How can we compute the probability of the entire sequence?



What if the casino switches coins?

*

How can we compute the probability of the entire sequence?



But, remember, we don't observe π in practice

What if the casino switches coins?

How can we compute the probability of the entire sequence?

We'll return to how to tackle this later.

First, how is this related to Biology?

But, remember, we don't observe π in practice

What does this have to do with biology?

Before:


How likely is it that this sequence was generated by a fair coin?

Which parts were generated by a biased coin?

Now:

How likely is it that this is a gene?

Which parts are the start, middle and end?




Eukaryotic Genes & Exon Splicing

Prokaryotic (bacterial) genes look like this:



Eukaryotic genes usually look like this:



This spliced RNA is what is translated into a protein.

Eukaryotic Genes & Exon Splicing

Given this




Recover this



Under what sequence of “states” (exon, intron, start codon etc.) is the observed sequence of nucleotides maximized?


Hidden Markov Model (Think of this picture)



$p = \{p_1, p_2, \dots, p_n\}$ is a sequence of *states* (AKA a *path*). Each p_i takes a value from set Q . We **do not** observe p .

$x = \{x_1, x_2, \dots, x_n\}$ is a sequence of *emissions*. Each x_i takes a value from set Σ . We **do** observe x .

Hidden Markov Model



Like for Markov chains, edges capture conditional independence:

x_2 is **conditionally independent** of everything else given p_2

p_4 is **conditionally independent** of everything else given p_3

Probability of being in a particular state at step i is known once we know what state we were in at step $i-1$. Probability of seeing a particular emission at step i is known once we know what state we were in at step i .

Formal Definition of a HMM

Σ = alphabet of symbols.

Q = set of states.

A = an $|Q| \times |Q|$ matrix where entry (k,l) is the probability of moving from state k to state l .

E = a $|Q| \times |\Sigma|$ matrix, where entry (k,b) is the probability of emitting b when in state k .

$A =$

7							
6							
5							
4							
3							
2							
1							
	1	2	3	4	5	6	7



Probability of going from state 5 to state 7

$E =$

7				
6				
5				
4				
3				
2				
1				
	A	C	G	T

Probability of emitting T when in state 4.

Constraints on A and E



Sum of the # in each row must be 1.

The Decoding Problem

Given x and π , we can compute:

- $\Pr(x \mid \pi)$: product of $\Pr(x_i \mid \pi_i)$
- $\Pr(\pi)$: product of $\Pr(\pi_i \rightarrow \pi_{i+1})$
- $\Pr(x, \pi)$: product of all the $\Pr(x_i \mid \pi_i)$ and $\Pr(\pi_i \rightarrow \pi_{i+1})$


$$\Pr(x, \pi) = \Pr(\pi_0 \rightarrow \pi_1) \prod_{i=1}^n \Pr(x_i \mid \pi_i) \Pr(\pi_i \rightarrow \pi_{i+1})$$

But they are “hidden” Markov models because π is unknown.


Decoding Problem: Given a sequence $x_1, x_2, x_3, \dots, x_n$ generated by an HMM (Σ, Q, A, E) , find a path π that maximizes $\Pr(x, \pi)$.

The Viterbi Algorithm to Find Best Path


$A[a, k] :=$ the probability of the **best** path for $x_1 \dots x_k$ that ends at state a .



$A[a, k] =$ the probability of the best path for $x_1 \dots x_{k-1}$ that goes to some state b times probability of a transition from b to a , and then the probability to output x_k from state a .



Viterbi DP Recurrence



$$A[a, k] = \max_{b \in Q} \{ \underbrace{A[b, k-1]}_{\text{Best path for } x_1 \dots x_k \text{ ending in state } b} \times \underbrace{\text{Pr}(b \rightarrow a)}_{\text{Probability of transitioning from state } b \text{ to state } a} \times \underbrace{\text{Pr}(x_k \mid \pi_k = a)}_{\text{Probability of outputting } x_k \text{ given that the } k^{\text{th}} \text{ state is } a} \}$$

Over all possible previous states.

Best path for $x_1 \dots x_k$ ending in state b

Probability of transitioning from state b to state a

Probability of outputting x_k given that the k^{th} state is a .

Base case:


$$A[a, 1] = \underbrace{\text{Pr}(\pi_1 = a)}_{\text{Probability that the first state is } a} \times \underbrace{\text{Pr}(x_1 \mid \pi_1 = a)}_{\text{Probability of emitting } x_1 \text{ given the first state is } a}$$

Probability that the first state is a


Probability of emitting x_1 given the first state is a .

Generally, our model can include an “initial”/starting distribution


Which Cells Do We Depend On?




Order to Fill in the Matrix:



Where's the answer?




Trellis Graph



The trellis graph “unfolds” the states of the HMM over (discrete) time.

Trellis Graph



Finding the maximum probability path through the trellis graph can be accomplished efficiently with the Viterbi algorithm — think back to lecture 3

DAG View of Dynamic Programming

The formulation of a DP as traversal of a DAG is a very powerful framework for thinking about and implementing different DPs.

1. topological sort
2. visit each vertex in the topological ordering and do updates

The pseudo-code of the Viterbi algorithm is presented in Algorithm 1.

Algorithm 1 Viterbi Algorithm.


```
1: procedure VITERBI( $G, w, s$ )
2:   topologically sort the vertices of  $G$ 
3:   INITIALIZE( $G, s$ )
4:   for each vertex  $v$  in topological order do
5:     for each edge  $e = (u, v)$  in  $BS(v)$  do
6:        $d(v) \oplus = d(u) \otimes w(e)$ 
```

Semiring	Set	\oplus	\otimes	$\bar{0}$	$\bar{1}$	intuition/application
Boolean	$\{0, 1\}$	\vee	\wedge	0	1	logical deduction, recognition
Viterbi	$[0, 1]$	max	\times	0	1	prob. of the best derivation
Inside	$\mathbb{R}^+ \cup \{+\infty\}$	+	\times	0	1	prob. of a string
Real	$\mathbb{R} \cup \{+\infty\}$	min	+	$+\infty$	0	shortest-distance
Tropical	$\mathbb{R}^+ \cup \{+\infty\}$	min	+	$+\infty$	0	with non-negative weights
Counting	\mathbb{N}	+	\times	0	1	number of paths



Table 1: Examples of semirings

Trellis Graph



When we want to compute the prob.
of the best path ending here, we already
have the prob. of the best path at all
predecessors, as well as the conditional
prob. of each incoming edge





Graph View of Viterbi





Graph View of Viterbi





Graph View of Viterbi





Graph View of Viterbi





Graph View of Viterbi





Graph View of Viterbi





Graph View of Viterbi





Graph View of Viterbi





Graph View of Viterbi





Graph View of Viterbi





Graph View of Viterbi





Graph View of Viterbi





Graph View of Viterbi





Graph View of Viterbi





Graph View of Viterbi





Graph View of Viterbi





Graph View of Viterbi





Graph View of Viterbi





Graph View of Viterbi





Graph View of Viterbi





Graph View of Viterbi





Graph View of Viterbi





Graph View of Viterbi





Graph View of Viterbi





Graph View of Viterbi





Graph View of Viterbi





Graph View of Viterbi



Graph View of Viterbi





Graph View of Viterbi





In this case, transitions to the end state (emitting no symbol), won't matter

Graph View of Viterbi





We can “trace back” our path to determine the hidden states taken on when traversing the optimal path.

Graph View of Viterbi



In this case, the path was simple — implying a biased coin the entire time.

Graph View of Viterbi



Note that in practice, esp. with long sequences, the absolute prob. of the best path may be **very** small.

Running Time

- # of subproblems = $O(n|Q|)$, where n is the length of the sequence.
- Time to solve a subproblem = $O(|Q|)$
- Total running time: $O(n|Q|^2)$

Using Logs

Typically, we take the log of the probabilities to avoid multiplying a lot of terms:

$$\begin{aligned}\log(A[a, k]) &= \max_{b \in Q} \{\log(A[b, k-1] \times \Pr(b \rightarrow a) \times \Pr(x_k \mid \pi_k = a))\} \\ &= \max_{b \in Q} \{\log(A[b, k-1]) + \log(\Pr(b \rightarrow a)) + \log(\Pr(x_k \mid \pi_k = a))\}\end{aligned}$$

Remember: $\log(ab) = \log(a) + \log(b)$

Why do we want to avoid multiplying lots of terms?

Multiplying leads to very small numbers:

$$0.1 \times 0.1 \times 0.1 \times 0.1 \times 0.1 = 0.00001$$

This can lead to underflow.

Taking logs and adding keeps numbers bigger.

Estimating HMM Parameters

$$\begin{aligned}
 (\mathbf{x}^{(1)}, \boldsymbol{\pi}^{(1)}) &= \left. \begin{array}{cccccc} x_1^{(1)} & x_2^{(1)} & x_3^{(1)} & x_4^{(1)} & x_5^{(1)} & \dots & x_n^{(1)} \\ \pi_1^{(1)} & \pi_2^{(1)} & \pi_3^{(1)} & \pi_4^{(1)} & \pi_5^{(1)} & \dots & \pi_n^{(1)} \end{array} \right\} \\
 (\mathbf{x}^{(2)}, \boldsymbol{\pi}^{(2)}) &= \left. \begin{array}{cccccc} x_1^{(2)} & x_2^{(2)} & x_3^{(2)} & x_4^{(2)} & x_5^{(2)} & \dots & x_n^{(2)} \\ \pi_1^{(2)} & \pi_2^{(2)} & \pi_3^{(2)} & \pi_4^{(2)} & \pi_5^{(2)} & \dots & \pi_n^{(2)} \end{array} \right\}
 \end{aligned}$$

Training examples where outputs and paths are known.

of times transition
 $a \rightarrow b$ is observed.

$$\Pr(a \rightarrow b) = \frac{A_{ab}}{\sum_{q \in Q} A_{aq}}$$

of times x was
 observed to be
 output from state a .

$$\Pr(x \mid a) = \frac{E_{xa}}{\sum_{x' \in \Sigma} E_{x'a}}$$

Pseudocounts

of times transition
 $a \rightarrow b$ is observed.

$$\Pr(a \rightarrow b) = \frac{A_{ab}}{\sum_{q \in Q} A_{aq}}$$

of times x was
observed to be
output from state a .

$$\Pr(x \mid a) = \frac{E_{xa}}{\sum_{x \in \Sigma} E_{xa}}$$

What if a transition or emission is never observed in the training data?
 \Rightarrow 0 probability

Meaning that if we observe an example with that transition or emission in the real world, we will give it 0 probability.

But it's unlikely that our training set will be large enough to observe every possible transition.

Hence: we take $A_{ab} = (\text{\#times } a \rightarrow b \text{ was observed}) + 1$ \leftarrow “pseudocount”
Similarly for E_{xa} .

Viterbi Training

- **Problem:** typically, in the real world we only have examples of the output x , and we don't know the paths π .

Viterbi Training Algorithm:

1. Choose a random set of parameters.
2. Repeat:
 1. Find the best paths.
 2. Use those paths to estimate new parameters.

This is a local search algorithm.

It's also an example of a “Gibbs sampling” style algorithm.

The Baum-Welch algorithm is similar, but doesn't commit to a single best path for each example. (basically EM for HMM training)

Some probabilities in which we are interested

What is the probability of observing a string x under the assumed HMM?

$$\Pr(x) = \sum_{\pi} \Pr(x, \pi)$$

What is the probability of observing x using a path where the i^{th} state is a ?

$$\Pr(x, \pi_i = a) = \sum_{\pi: \pi_i = a} \Pr(x, \pi)$$

What is the probability that the i^{th} state is a ?

$$\Pr(\pi_i = a | x) = \frac{\Pr(x, \pi_i = a)}{\Pr(x)}$$

How do we compute this:

$$\Pr(x, \pi_k = a) = \Pr(x_1, \dots, x_i, \pi_i = a) \Pr(x_{i+1}, \dots, x_n \mid \pi_i = a)$$

Recall the recurrence to compute **best** path for $x_1 \dots x_k$ that ends at state a :

$$A[a, k] = \max_{b \in Q} \{ A[b, k-1] \times \text{Pr}(b \rightarrow a) \times \text{Pr}(x_k \mid \pi_k = a) \}$$

We can compute the probability of emitting x_1, \dots, x_k using **any** path that ends in a :

$$F[a, k] = \sum_{b \in Q} F[b, k-1] \times \text{Pr}(b \rightarrow a) \times \text{Pr}(x_k \mid \pi_k = a)$$

The Forward Algorithm

We can compute the probability of emitting x_1, \dots, x_k using **any** path that ends in a :

$$F[a, k] = \sum_{b \in Q} F[b, k - 1] \times \text{Pr}(b \rightarrow a) \times \text{Pr}(x_k \mid \pi_k = a)$$

The forward algorithm also allows us to solve the “Evaluation Problem”.

Evaluation Problem:


Given an HMM $\lambda = (\Sigma, Q, A, E)$ and an observation \mathbf{x}

Find $\text{Pr}(\mathbf{x} \mid \lambda)$ — the prob. of the observations under the model

The Forward Algorithm

Computes the total probability
of all the paths of length k
ending in state a .

Still need to compute the
probability of paths leaving a
and going to the end.



The Backward Algorithm


The same idea as the forward algorithm, we just start from the *end* of the input string and work towards the beginning:

$B[a,k]$ = “the probability of generating string x_{k+1}, \dots, x_n starting from state b ”

$$B[a, k] = \sum_{b \in Q} \underbrace{B[b, k+1]}_{\substack{\text{Prob for} \\ x_{k+1} \dots x_n \\ \text{starting in} \\ \text{state } b}} \times \underbrace{\Pr(a \rightarrow b)}_{\substack{\text{Probability} \\ \text{going from} \\ \text{state } a \text{ to } b}} \times \underbrace{\Pr(x_{k+1} \mid \pi_{k+1} = b)}_{\substack{\text{Probability of emitting} \\ x_{k+1} \text{ given that the next} \\ \text{state is } b.}}$$


The Forward-Backward Algorithm

$$\Pr(\pi_i = a \mid x) = \frac{\Pr(x, \pi_i = k)}{\Pr(x)} = \frac{F[a, i] \cdot B[a, i]}{\Pr(x)}$$



The Forward-Backward Algorithm

$$\Pr(\pi_i = a \mid x) = \frac{\Pr(x, \pi_i = k)}{\Pr(x)} = \frac{F[a, i] \cdot B[a, i]}{\Pr(x)}$$



This works because $F[a,i]$ is independent of $B[a,i]$, given that we are in state **a** at time **i** (the Markovian assumption).

Recap

- Hidden Markov Model (HMM) model the generation of sequences of symbols.
- They are governed by a symbol alphabet (Σ), a set of states (Q), a set of transition probabilities A , and a set of emission probabilities for each state (E).
- Given a string and an HMM, we can compute:
 - The most probable path the HMM took to generate the sequence (Viterbi).
 - The probability that the HMM was in a particular state at a given step (forward-backward algorithm).
- Algorithms are based on dynamic programming.
- *Finding* good parameters is a much harder problem.
The Baum-Welch algorithm is an oft-used heuristic algorithm.