



The QMdbSim2 Project

An Improved Microchip Device Simulator Framework For QSpice

Document History

2026.07.01 – Initial documentation. Caveat emptor.

Notes

All projects mentioned in this document along with source code and examples are available on my [QSpice GitHub repository](#).

I assume that you have experience using the Microchip MPLabX tools to create micro-controller device code (*.elf/*.hex files).

Parts of this project use Java. Pre-compiled JAR files are provided so you don't need to know anything about Java unless you wish to modify the simulator interface code. However, you will need to install a 32-bit Java 8+ JRE to run simulations (see below).

Project Overview

The QMdbSim2 Project is a framework for using Microchip micro-controller devices in QSpice simulations. You drop a micro-controller symbol to your schematic, select a specific device, provide the name of your compiled device code (*.elf/*.hex), and, when you run the QSpice simulation, your device code drives the device symbol pins in the schematic circuit.

Under the covers, the project uses Microchip's software simulator SDK (MDBCore) so it supports the same PIC and AVR devices to the same degree that Microchip's software debugger supports the devices. Examples for PIC16F1521x and ATtiny85 devices are provided but you can easily create other devices using the QSymGen3 tool from the QParser2 project.

The project is easy to use but, underneath the covers, it's rather complex. This document includes:

- A high-level architecture overview.
- Terminology used in this project.
- Definitions of “user types” (i.e., Basic User, Device Developer, and API Developer), what they do, tools required, and pointers to other documents relevant to those activities.
- Information about QMdbSim2 limitations.
- Frequently Asked Questions.

Architecture & Terminology

At a high level, a QMdbSim2-based project works like this:

- A top-level QSpice schematic containing the circuitry connected to a QMdbSim2 *Device Symbol*. The symbol is “device-specific,” i.e., created for a particular Microchip device of family of devices. For example, the project sample PIC16F1521x.qsym supports PIC16F15213 & PIC16F15214 devices.
- This Device Symbol contains a “clock pin” used to advance the device simulation in single-instruction steps under QSpice control.
- The Symbol Properties pane contains a drop-down list for selecting the specific device and edit boxes to specify paths to a configuration file (QMdbCfg.ini) and to the user’s device-specific program. This *Device Program* is the user-supplied/compiled *.elf/*.hex program to load into the simulation.
- The Device Symbol is a hierarchical schematic block which loads a device-specific schematic (*Device Schematic*). For example, PIC16F1521x.qsym loads PIC16F21x.qsch. The Device Schematic *is not intended* for user modification. (There is a tool to generate this schematic: QSymGen3.)
- The Device Schematic contains a hierarchical DLL block which loads the *Device DLL*, e.g., PIC16F1521x.dll. This DLL does all of the magic to pass pin/port states between QSpice and the Java-based Microchip software simulator.
- This *Device DLL* loads a configuration file, QMdbCfg.ini, to obtain the paths to:
 - The MPLabX IDE installation location.
 - A 32-bit Java runtime environment (JRE or JDK).
 - An instance of the QMdbSim2 project’s QMdbCS.jar file.
- The Device DLL launches Java and loads the QMdbCS.jar file. (Note: The JAR is device-agnostic and used by all QMdbSim2 devices.)
- For the remainder of the QSpice simulation, the DLL passes pin/port states between QSpice and the Microchip software simulator on each trigger of the Device Symbol clock pin.

OK, I said “high level.” And that was pretty high-level. I also said that it’s easy to use. And it is, at least after the initial configuration.

User Types

I’ll classify users into three groups: *Basic Users*, *Device Developers*, and *API Developers*.

Basic Users

Basic users use *existing* device-specific elements (symbols, schematics, DLLs) and common QMdbSim2 project files to create top-level schematics. They write and compile Device Programs (*.elf/*.hex) to use in QSpice simulations. They must install certain tools and edit a configuration file to point to those tools. (This is one-time installation and doesn't change for different Microchip devices.)

Need a specific device but nobody has created one? It's easy – become a Device Developer.

Device Developers

Device Developers *create new* device-specific elements (symbols, schematics, DLLs) for Basic Users. The QSymGen3 command-line tool (part of the QParser2 project) makes it easy to create these bits from a Microchip datasheet. (Seriously, simply define the device characteristics and pins in a text file. Run QSymGen3.exe to generate the device-specific symbols, schematics, and DLL code. Compile the DLL code. Distribute.)

API Developers

API Developers modify/compile the device-agnostic DLL-to-Java interface code. The DLL and QMdbCS.jar communicate using JNI for efficiency/speed.

Reasons to become an API Developer include improving simulation speed and adding device-specific features that QMdbSim2's simple set/step/fetch pin interface doesn't support.

Tool Requirements

The QMdbSim2 project requires some initial one-time setup and configuration. Here's a summary of requirements.

Tool	Basic User	Device Developer	API Developer
MPLabX v6.30 (for simulator API and Device Program development)	✓	✓	✓
32-bit Java v8 JRE or newer	✓	✓	✓
MSVS 2026 (for C++20 DLL compiles)		✓	✓
QSymGen3 command-line tool to create new device-specific files		✓	
Microchip device datasheet(s)		✓	
QMdbSim2 project files (for DLL compiles)		✓	
32-bit Java JDK, v8 or newer (to compile Device DLLs)		✓	✓
32- or 64-bit Java JDK, v8 or newer (to compile QMdbCS.jar)			✓
Microchip SDK			✓
Ant (recommended for QMdbCS.jar builds)			✓

Specific instructions are in the Basic User, Device Developer, and API Developer PDFs:

QMdbSim2_Basic_User.pdf	Initial installation and configuration. Basic usage.
QMdbSim2_Device_Dev.pdf	Device files overview. Creating new device-specific files using QSymGen3 project tools.
QMdbSim2_API_Dev.pdf	Back-end software simulator API. Overview and resources.

Known QMdbSim2 Limitations

Microchip Simulator Peripheral Support By Device

For a given microcontroller device, some peripherals may not be supported by the simulator. If the simulator doesn't support a given peripheral for a given device, then QMdbSim2 doesn't support it.

To determine what peripherals are supported for a given device by the currently installed version of the software simulator, look for the following files in the ...\\docs\\FeatureSupport folder (e.g., C:\\Program Files\\Microchip\\MPLabX\\v6.30\\docs\\FeatureSupport):

- SimPeripheralSupport.html – Complete list in HTML format.
- SimPeripheralSupport.csv – Complete list in comma-separated values format.
- SimPeripheralSupportInfo.html – Explanations of peripheral abbreviations.

That said, I am uncertain that this is correct for software simulation. For example, the dsPIC33FJ128MC802 entry in MPLabX v6.30 says that pull-up circuitry is supported. I don't see how that could work in software where only an external pin voltage is known to the simulator.

Bottom line: Do a small test before building a big QSpice circuit around peripheral features.

Electrical Fidelity

QMdbSim2 devices are digital simulators and not “electrically correct.” In QSpice DLLs, DLL input pins consume no current; output pins are voltage sources with some fixed output resistance.

See FAQs for suggestions for more accurate electrical modeling.

Frequently Asked Questions (FAQs)

Where can I get support for the QMdbSim2 project?

The best place to contact me is on the Qorvo QSpice forum (@RDunn).

Can I compile sources with the DMC compiler shipped with QSpice?

The Digital Mars C/C++ compiler (DMC) is ancient and support ended with C++98. The absence of a modern IDE and lack of support for current C++ standards makes it unsuitable for projects of this complexity. So, no.

This project seems pretty complicated. Isn't there an easier way?

The original QMdbSim project was simpler – it used the Microchip MDB.bat command-line debugger included in the MPLabX installation. No additional Java tools required. That project remains available on the GitHub repository.

That said, QMdbSim2 simulations run much, much faster via Java Native Interface (JNI) calls. Developing new device-specific symbols, schematics, and DLLs is automated with QSymGen3. Configuration is now contained in the QMdbCfg.ini file.

Bottom line: After the initial setup, QMdbSim2 is better in almost every way.

Why are simulations so slow?

QSpice simulations can run slowly for many reasons. I'll assume that you've ruled out the normal stuff (convergence issues and whatnot). That leaves us with the QMdbSim2-specific speed question.

The project uses Microchip software simulator for the back-end. This is Java code (aka "slow") and it emulates hardware (aka "slow"). That said, my tests suggest that the first 10-20+ seconds of a simulation are burned spinning up Java and initializing the simulator. A second simulation run generally starts up and executes much faster (presumably due to JIT and/or operating system caching).

Note: Oddly, my tests suggest that a Java 8 JRE runs faster than newer versions. I'm still investigating whether there are switches/options that resolve this strangeness. In the interim, I suggest using Java 8 for simulations.

Where can I find the QMdbSim2 files for the XXX Microchip device?

See the Devices folder in this project. If you don't find them there, please consider becoming a Device Developer and sharing.

I created new device-specific files. Is there an official repository where I can share them?

Yes, community contributions will be included in the QMdbSim2 Devices folder. Please send your devices (sources required) and I'll post them with credit to you.

Can I put two instances of a device symbol in the same schematic? Can I run a simulation with multiple steps?

Excellent questions. I've not yet tested either case. They are on my post-first-release list to investigate. In the meantime, there's no harm in testing it yourself. (If you do, please let me know what you find.)

The performance timer times don't match QSpice simulation time. Why?

The embedded timers have, I think, roughly micro-second resolution. They are not highly accurate and subject to rounding. They are intended solely as rough estimates of how much time is spent initializing the Java simulation vs time spent actually executing simulation Java code.

MPLabX includes a Java JRE. Why can't I use that? What Java versions can I use?

The Device DLL is a 32-bit process. It cannot launch a 64-bit Java instance. The MPLabX JRE is a 64-bit JRE so you must install a 32-bit Java JRE. Annoying but unavoidable.

My XXX device has pull-up resistors that can be enabled in device software. When my Device Program enables/disables them, nothing changes. Why?

Whether or not a device pin supports internal pull-ups and which pins support them is highly device-specific. The project does not currently support this functionality.

[Workaround] As far as I know, pins with “internal weak pull-up resistors” are usually open-collector/open-drain pins. You can add external transistors/resistors in the top-level schematic to electrically simulate a weak pull-up configuration. However, that's static – if you truly need to dynamically switch the pull-ups on/off in the Device Program, well again, not yet supported.

Why does the electrical behavior of my XXX device not match the datasheet? For example, the current at the supply pin appears to be 0A and the current on output pins seems unlimited.

QSpice DLL blocks are very basic, ideal models. Input pins do not consume current. Output pins are *voltage sources* with a default internal resistance of 1K.

The project sets the internal resistance of output pins to 1 Ω in the project Device Schematic using the ROUT instance parameter. Bi-directional pins add an additional 1 Ω resistor in the default GPIO implementation (GPIO_IMPL.qsch). You can, of course, change these.

Why am I getting time-step too small errors?

The only case that I've encountered so far where this was actually related to using the QMdbSim2 project was where I tied a Device Symbol output pin or bi-directional pin to a top-level schematic voltage source. QSpice doesn't like it when two voltage sources with different voltage values are connected.

If you find other sources of this error, please let me know.

Why are messages in the QSpice Output window corrupted?

This is a long-term problem with QSpice DLLs. I'll not burden you with the underlying details but I've not found a reliable solution. At the moment, I'm letting Microchip's Java simulator write messages to the Output Window. Once we get past the initial release shakedown, I'll consider trapping or logging the messages to reduce the noise.

Can I use QMdbSim2 with a hardware debugger?

Microchip sells a number of hardware debuggers: PICKit, ICE, etc. QMdbSim2 uses the Microchip SDK to load the software simulator/debugger. A hardware debugger could be loaded using the same SDK interfaces. I might explore hardware debuggers in the future. But, at the moment, no.

Resources

My GitHub QSpice Repository

<https://github.com/robdunn4/QSpice>

In addition to this project, you'll find information about C-Block component concepts ("C-Block Basics"), various C-Block component examples, tips on using VSCode and Microsoft Visual Studio (MSVS) IDEs for C-Block development and debugging, and links to other useful QSpice-related sites/repositories.

Microchip

[MPLabX IDE](#) (free)

[PIC16F15213/14/23/24/43/44 Low Pin Count Micro-Controllers](#) (datasheet)

[Microchip Debugger \(MDB\) User's Guide](#) (one)

[Microchip Debugger \(MDB\) User's Guide](#) (another one)

Microsoft

[Visual Studio Downloads](#) (2026 Community Edition is free)

Java JRE/JDK

All users (Basic User, Device Developer, API Developer) must have a 32-bit Java v8 or later runtime (JRE) or JDK (which includes the JRE). I recommend the Eclipse Temurin JDK. This is a bit hard to find on the Adoptium site – you must start by selecting Java v17 or earlier (v17 is the last 32-bit version). Then you must select Windows 32-bit. Then you must click through a "show unsupported versions" option (not a pop-up so it's easy to miss).

[Eclipse Adoptium Downloads](#)

[Eclipse Adoptium Temurin Releases](#)

[Eclipse Adoptium Temurin v17 32-bit JDK](#) (MSI installer)

Note: To my surprise, *Java 8 JRE seems to run much faster than the Java 17*. That is, instruction stepping is on the order of 2.5x faster on the older version. I spent a full day trying different options to get v17 to run as fast as v8 without success. ***I recommend Java 8 for now.***

Conclusion

I hope that you find this project to be useful or – at least – interesting. Please let me know if you find problems or suggestions for improving the code or this documentation.

You can find me on the QSpice Forums as @RDunn.

--robert