

Hochschule RheinMain - University of Applied Sciences

University of Applied Sciences
Department of
Design, Computer Science, Media
Prof. Dr. D. Richter

Transilvania University Brasov
Faculty of
Mathematics and Informatics
Dr. I. Plajer

ISIP 2019
International School on Image Processing
July 15th - 26th, 2019



detlef.richter@HS-RM.de

Prof. Dr. D. Richter Department [Design>Computer Science>Media] 10

Hochschule RheinMain - University of Applied Sciences

Notice to Copyright

All information in this paper and part thereof
is only for private use
in connection with the lecture
of Prof. Dr. D. Richter
Wiesbaden University of Applied Sciences
Hochschule RheinMain

Reproduction or publication and part thereof
is not allowed
without written permission of the author.

Prof. Dr. D. Richter Department [Design>Computer Science>Media] 10

Hochschule RheinMain - University of Applied Sciences

3. Global Operations in Spatial Domain, Filters

- 3.1 Low-pass filter
 - 3.1.1 Mean filter
 - 3.1.2 Rang order filter / Median filter
 - 3.1.3 Gauss filter
 - 3.1.4 Binomial filter
 - 3.1.5 Unsharp masking
- 3.2 High-pass filter
 - 3.2.1 Prewitt filter
 - 3.2.2 Sobel filter
 - 3.2.3 Roberts filter
 - 3.2.4 Laplace filter
 - 3.2.5 Laplacian of Gaussian filter
 - 3.2.6 optional: Canny filter
- 3.3 optional: Harris filter / Corner filter

Prof. Dr. D. Richter Department [Design>Computer Science>Media] 10

Hochschule RheinMain - University of Applied Sciences

3. Global Operations in Spatial Domain, Filters

Following notation is used :


- Pixel position : $p(x, y)$
- Grey level at position $p(x, y)$: $g(x, y)$
- Modified grey level by an operation : $g'(x, y)$
- Derivative of grey level at position p : $g_x(x, y), g_y(x, y)$
- Source pixel / Target pixel g_{old} / g_{new}

Prof. Dr. D. Richter Department [Design>Computer Science>Media] 10

Hochschule RheinMain - University of Applied Sciences

3. Global Operations in Spatial Domain, Filters

- 4-Neighborhood : (adjacent pixels by edges)
- 8-Neighborhood : (adjacent pixels by edges and corners)
- Round Neighborhood: (3-5-5-3)



All operations are mask operations
(most commonly used: 8-Neighborhood)


Note : In contrast to the mathematical coordinate system, the positive y-axis directs downwards. This fact originates from the time dependency of the pixel source in video.

Prof. Dr. D. Richter Department [Design>Computer Science>Media] 10

Hochschule RheinMain - University of Applied Sciences

3.1 Global Operations in Spatial Domain, Low-pass Filters


- $n \times n$ filter
- $n = 2k+1, k=1,2,\dots$
- $p(x, y) = p(x-u, y-v)$
- u and $v \in \{-(n-1)/2, \dots, 0, \dots, (n-1)/2\}$
- In the following :
 $n = 3$ unless stated otherwise



Prof. Dr. D. Richter Department [Design>Computer Science>Media] 10



3.1.1 Global Operations in Spatial Domain, Low-pass Filters



• Mean Filter

$$g'(x, y) = \frac{1}{n^2} \sum_{u=-\frac{n-1}{2}}^{\frac{n-1}{2}} \sum_{v=-\frac{n-1}{2}}^{\frac{n-1}{2}} g(x-u, y-v)$$

$$g'(x, y) = \frac{1}{n^2} \sum_{u=-\frac{n-1}{2}}^{\frac{n-1}{2}} \sum_{v=-\frac{n-1}{2}}^{\frac{n-1}{2}} g(x-u, y-v) * h(u, v)$$

$$H = h(u, v) = \begin{pmatrix} 1 & 1 & 1 \\ 1 & 1 & 1 \\ 1 & 1 & 1 \end{pmatrix}$$

Prof. Dr. D. Richter

Department [Design>Computer Science>Media] 10



3.1.1 Global Operations in Spatial Domain, Low-pass Filters


- Problem : margin area (upper and lower line / left and right column)
 - Use unchanged data, in most cases optimal procedure
- Result of operation :
 - No effect on areas with constant grey values
 - No effect on average grey value of image
 - Significant on image noise (desired)
 - Smoothing of edges (undesired)

Prof. Dr. D. Richter

Department [Design>Computer Science>Media] 10



3.1.1 Global Operations in Spatial Domain, Low-pass Filters



• Example :

Filter mask 3 x 1 on ideal edge

Weights of mask elements are 1

Generation of new grey values

Prof. Dr. D. Richter

Department [Design>Computer Science>Media] 10



3.1.1 Global Operations in Spatial Domain, Low-pass Filters

- Empirical modification of mask weights (edge sensitive mask) :


$$H = \begin{pmatrix} 0,9 & 0,9 & 0,9 \\ 0,9 & 1,8 & 0,9 \\ 0,9 & 0,9 & 0,9 \end{pmatrix}$$
- Average value of mask elements : $h_{\text{average}}(u, v) = 1$
- Normalizing requires : $\sum h(u, v) = n^2$
 - Average grey level remains constant
 - Algorithm requires floating point values
 - Correct rounding and data conversion for output data necessary
 - $g'(x, y) \in \{0, \dots, 255\}$

Prof. Dr. D. Richter

Department [Design>Computer Science>Media] 10



3.1.2 Global Operations in Spatial Domain, Low-pass Filters



• Rank order filter

- Mean filter : $g' \notin \{G^*\}$
- Rank ordering filter : $g' \in \{G^*\}$
- G^* : Set of initial grey values
- $F(g(r))$ increasing (or decreasing) sequence of grey values
- $r = \{1, \dots, n^2\}$; $n > 1$ and odd
- Def. : $\text{med}\{F(g(r))\} = g((n^2+1)/2)$
→ Median filter
- "median value of sorted sequence" instead of Mean value

Prof. Dr. D. Richter

Department [Design>Computer Science>Media] 10



3.1.3 Global Operations in Spatial Domain, Low-pass Filters

- Gauss filter
- Edge smoothing filter

• One dimensional Gauss function

$$h(u) = \frac{1}{\sigma\sqrt{2\pi}} * e^{-\frac{u^2}{2\sigma^2}}$$

Maximum at $h(u=0)$ = $\frac{1}{\sigma\sqrt{2\pi}}$

Minimum at $h(u \rightarrow \pm\infty)$ = 0

Point of inflection at $h(u=\pm\sigma)$ = $\frac{1}{\sigma\sqrt{2\pi}} * \frac{1}{\sqrt{e}}$

• Two dimensional Gauss function

$$h(u, v) = \frac{1}{\sigma^2 * 2\pi} * e^{-\frac{u^2 + v^2}{2\sigma^2}}$$

Prof. Dr. D. Richter

Department [Design>Computer Science>Media] 10

Hochschule RheinMain - University of Applied Sciences

3.1.3 One-dimensional and two-dimensional Gauss function

Maximum of $f(0) = 1/\sigma\sqrt{2\pi} \approx 0.2$ for $\sigma = 2$

Points of inflection $x = \pm \sigma$

Maximum of $f(0,0) = 1/(\sigma^2 \cdot 2\pi) \approx 0.04$ for $\sigma = 2$

Prof. Dr. D. Richter Department [Design>Computer Science>Media] **10**

Hochschule RheinMain - University of Applied Sciences

3.1.3 Global Operations in Spatial Domain, Low-pass Filters

Let be $\sigma = 1$ and pre-factor = 4, one gets for $n = 3$ or $n = 5$:

$H = 1/16 \cdot$

0	0	1	0	0
0	1	2	1	0
1	2	4	2	1
0	1	2	1	0
0	0	1	0	0

Integer values

$H = 1/20 \cdot$

0	0	0.5	0	0
0	1.5	2.4	1.5	0
0.5	2.4	4	2.4	0.5
0	1.5	2.4	1.5	0
0	0	0.5	0	0

Float values

σ defines the range of the filter
The pre-factor is arbitrary and is compensated by the normalizing factor

Prof. Dr. D. Richter Department [Design>Computer Science>Media] **10**

Hochschule RheinMain - University of Applied Sciences

3.1.4 Global Operations in Spatial Domain, Low-pass Filters

- n-Binomial filter, n even
- Normalized binomial coefficients
[e.g. $n = 4 : (a+b)^4 \rightarrow 1/16 \cdot \{ 1 \ 4 \ 6 \ 4 \ 1 \}$]
- Multiplication column vector * row vector \rightarrow Binomial mask elements

$$H = h(u, v) = \frac{1}{256} \cdot \begin{pmatrix} 1 & 4 & 6 & 4 & 1 \\ 4 & 16 & 24 & 16 & 4 \\ 6 & 24 & 36 & 24 & 6 \\ 4 & 16 & 24 & 16 & 4 \\ 1 & 4 & 6 & 4 & 1 \end{pmatrix}$$

Prof. Dr. D. Richter Department [Design>Computer Science>Media] **10**

Hochschule RheinMain - University of Applied Sciences

Question about Low-pass Filters

What are the image processing differences between the algorithms of

- Mean filter
- Median filter
- Gauss filter
- Binomial filter

?

Prof. Dr. D. Richter Department [Design>Computer Science>Media] **10**

Hochschule RheinMain - University of Applied Sciences

3.1.5 Global Operations in Spatial Domain, Unsharp Masking

Original image: $f(x,y)$
 Low-pass filtered image: $f_L(x,y)$
 Unsharp mask: $g_{mask}(x,y) = f(x,y) - f_L(x,y) \approx 0$
 Enhanced image: $f_{enhanced}(x,y) = f(x,y) + k \cdot g_{mask}(x,y)$

If $k = 1$: unsharp masking
 If $k \geq 1$: highboost filtering

UnsharpMasking.xmcd

Prof. Dr. D. Richter Department [Design>Computer Science>Media] **10**


Hochschule RheinMain - University of Applied Sciences

High-pass Filters

Prof. Dr. D. Richter Department [Design>Computer Science>Media] **10**

Hochschule RheinMain - University of Applied Sciences

3.2 Global Operations in Spatial Domain, High-pass Filters



Edges : Significant change of grey values

Suppose to have a continuous step-function $g(x)$

How can we find changes of $g(x)$?

Prof. Dr. D. Richter Department [Design>Computer Science>Media] 10

Hochschule RheinMain - University of Applied Sciences

3.2 Global Operations in Spatial Domain, High-pass Filters


$$\frac{d}{dx} g(x) = \lim_{\Delta x \rightarrow 0} \frac{g(x + \Delta x) - g(x)}{\Delta x} = g_x(x)$$

In the discrete domain limit $\Delta x \rightarrow 0$ not realizable.
Which limit is realizable ?

$\Delta x \rightarrow ?$

We get

$g_x(x) = g(x+1) - g(x)$ forward differences
 $g_x(x) = g(x) - g(x-1)$ backward differences



Problem : There exists no position between x and $x+1$ respectively between $x-1$ and x .

Prof. Dr. D. Richter Department [Design>Computer Science>Media] 10

Hochschule RheinMain - University of Applied Sciences

3.2 Global Operations in Spatial Domain, High-pass Filters

Let be $g(x,y)$ the central pixel of mask H

$$H = \begin{vmatrix} g(x-1, y-1) & g(x, y-1) & g(x+1, y-1) \\ g(x-1, y) & g(x, y) & g(x+1, y) \\ g(x-1, y+1) & g(x, y+1) & g(x+1, y+1) \end{vmatrix}$$

Prof. Dr. D. Richter Department [Design>Computer Science>Media] 10

Hochschule RheinMain - University of Applied Sciences

3.2 Global Operations in Spatial Domain, High-pass Filters

The differential in x direction defines the edge in y direction

$$H_y = \begin{vmatrix} 0 & 0 & 0 \\ 0 & -1 & +1 \\ 0 & 0 & 0 \end{vmatrix} \quad \text{or} \quad \begin{vmatrix} 0 & 0 & 0 \\ -1 & +1 & 0 \\ 0 & 0 & 0 \end{vmatrix}$$

forward differences backward differences

Prof. Dr. D. Richter Department [Design>Computer Science>Media] 10

Hochschule RheinMain - University of Applied Sciences

3.2 Global Operations in Spatial Domain, High-pass Filters

Accordingly we get for edge in x direction :

$$H_x = \begin{vmatrix} 0 & 0 & 0 \\ 0 & -1 & 0 \\ 0 & +1 & 0 \end{vmatrix} \quad \text{or} \quad \begin{vmatrix} 0 & -1 & 0 \\ 0 & +1 & 0 \\ 0 & 0 & 0 \end{vmatrix}$$

Prof. Dr. D. Richter Department [Design>Computer Science>Media] 10

Hochschule RheinMain - University of Applied Sciences

3.2 Global Operations in Spatial Domain, High-pass Filters

These masks are noise sensitive.

Edges are supposed to have certain lengths.

With distinct probability they continue into adjacent rows or columns.

Use $\Delta x \rightarrow 2$ instead of $\Delta x \rightarrow 1$ to find a pixel position for the result

We get an empirical extension of the filter mask.

Prof. Dr. D. Richter Department [Design>Computer Science>Media] 10



3.2.1 Global Operations in Spatial Domain, High-pass Filters

We define as **Prewitt-Operator** :

$$g_x = H_y = \begin{bmatrix} -1 & 0 & +1 \\ -1 & 0 & +1 \\ -1 & 0 & +1 \end{bmatrix} \text{ und } g_y = H_x = \begin{bmatrix} -1 & -1 & -1 \\ 0 & 0 & 0 \\ +1 & +1 & +1 \end{bmatrix}$$

Note:

- H_y finds edges in y-direction, derivative in x direction,
 - H_x finds edges in x-direction, derivative in y direction,
- All lines / columns are treated with the same weights



3.2.2 Global Operations in Spatial Domain, High-pass Filters

We define as **Sobel-Operator** :

$$H_y = \begin{bmatrix} -1 & 0 & +1 \\ -2 & 0 & +2 \\ -1 & 0 & +1 \end{bmatrix} \text{ und } H_x = \begin{bmatrix} -1 & -2 & -1 \\ 0 & 0 & 0 \\ +1 & +2 & +1 \end{bmatrix}$$

The source line / column are weighted double



3.2.2 Global Operations in Spatial Domain, High-pass Filters

The grey value function is a two dimensional function.

We define the **Nabla-Operator** :

$$\nabla = \begin{pmatrix} \frac{\partial}{\partial x} \\ \frac{\partial}{\partial y} \end{pmatrix}$$

The Nabla-Operator is a vector operator, $g(x, y)$ is a scalar function.

We define :

$$\nabla g(x, y) = \text{grad } g(x, y) = \begin{pmatrix} g_x(x, y) \\ g_y(x, y) \end{pmatrix}$$

$\text{grad } g(x, y)$ is a vector.



3.2.2 Global Operations in Spatial Domain, High-pass Filters

$$\text{Magnitude of grad } g(x, y) : |\text{grad } g(x, y)| = \sqrt{g_x^2 + g_y^2}$$

Here we lose the information of the direction.


$$\text{Direction of grad } g(x, y) : \tan \alpha = \frac{g_y}{g_x}$$



3.2.2 Global Operations in Spatial Domain, High-pass Filters

$\text{grad } g(x, y)$ shows into direction of largest change of luminance.

Representation in mathematical coordinate system :



Mind the use of a mathematical coordinate system



3.2.2 Global Operations in Spatial Domain, High-pass Filters

Visualization as binary image (target image) :

$$g'(x, y) = \begin{cases} 0, & \text{if } |\text{grad } g(x, y)| \leq T \\ 255, & \text{otherwise} \end{cases}$$

Visualization in grey level image (source image) :

$$g'(x, y) = \begin{cases} g(x, y), & \text{if } |\text{grad } g(x, y)| \leq T \\ \text{const.}, & \text{otherwise} \end{cases}$$

Visualization of vector direction (target image) :

$$g'(x, y) = \begin{cases} 0, & \text{if } |\text{grad } g(x, y)| \leq T \\ \text{angle coded as grey value}, & \text{otherwise} \end{cases}$$

3.2.2 Global Operations in Spatial Domain, High-pass Filters



Example of direction-independent Sobel filtering as binary image.
Threshold = 150

HochpassFilter-Sobel.xmcd

Prof. Dr. D. Richter

Department [Design>Computer Science>Media]

10

3.2.2 Global Operations in Spatial Domain, High-pass Filters



Example of direction-independent Sobel filtering as grey value image


Prof. Dr. D. Richter

Department [Design>Computer Science>Media]

10

3.2.2 Global Operations in Spatial Domain, High-pass Filters

Example of direction-dependent Sobel filtering



atan2()-function

atan()-function

HochpassFilter-Sobel-RA

Prof. Dr. D. Richter

Department [Design>Computer Science>Media]

10

3.2.3 Global Operations in Spatial Domain, High-pass Filters



Sobelfilter

Roberts.tif



Robertsfilter

Roberts.tif

- Roberts filter
- The basis of gradient components are the diagonals

$$g_x = g(x+1, y-1) - g(x-1, y+1)$$

$$g_y = g(x+1, y+1) - g(x-1, y-1)$$

$$|\text{grad } g(x, y)| = \sqrt{g_x^2 + g_y^2}$$

Difference to Sobel filter ?

Prof. Dr. D. Richter

Department [Design>Computer Science>Media]

10

3.2.3 Global Operations in Spatial Domain, High-pass Filters

$$H_- = \begin{bmatrix} -2 & -1 & 0 \\ -1 & 0 & +1 \\ 0 & +1 & +2 \end{bmatrix}$$

$$H_+ = \begin{bmatrix} 0 & +1 & +2 \\ -1 & 0 & +1 \\ -2 & -1 & 0 \end{bmatrix}$$

Roberts.tif



Robertsfilter

Filter masks, when using main and adjacent diagonals :

$$g_x = 2*[g(x+1, y-1) - g(x-1, y+1)] + g(x, y-1) - g(x-1, y) + g(x+1, y) - g(x, y+1)$$

$$g_y = 2*[g(x+1, y+1) - g(x-1, y-1)] + g(x, y+1) - g(x-1, y) + g(x+1, y) - g(x, y-1)$$

$$|\text{grad } g(x, y)| = \sqrt{g_x^2 + g_y^2}$$

Prof. Dr. D. Richter

Department [Design>Computer Science>Media]

10

3.2 Global Operations in Spatial Domain, High-pass Filters

The filters need interactions by thresholding, therefore we use :

Global adaptive threshold

- Calculate entire gradient image : $g'(x, y) = \text{grad } g(x, y)$
- Find maximum of all gradients : $\text{grad}_{\text{max, glob}} = \max\{ \text{grad } g(x, y) \}$
- Define adaptive threshold : $T_{\text{adaptiv, glob}} = \text{Factor}_{\text{glob}} * \text{grad}_{\text{max, glob}}$
- Empirical : approx. $0.2 \leq \text{Factor}_{\text{glob}} \leq$ approx. 0.7

Prof. Dr. D. Richter

Department [Design>Computer Science>Media]

10

3.2 Global Operations in Spatial Domain, High-pass Filters


Alternative option : Local adaptive threshold

- Calculate entire gradient image : $g'(x,y) = \text{grad } g(x,y)$
- Find within $n \times n$ - mask
maximum of gradients : $\text{grad}_{\max, \text{local}} = \max\{ \text{grad } g(x,y) \}_{n \times n}$
minimum of gradients : $\text{grad}_{\min, \text{local}} = \min\{ \text{grad } g(x,y) \}_{n \times n}$
- Define adaptive local threshold
 $T_{\text{adaptiv, local}} = \text{Factor}_{\text{local}} * \text{grad}_{\max, \text{local}} + (1 - \text{Factor}_{\text{local}}) * \text{grad}_{\min, \text{local}}$
- Empirical : approx. $0,5 \leq \text{Factor}_{\text{local}} \leq \text{approx. } 0,7$
- Empirical : approx. $11 \leq n \leq 25$
according to image content and structure

3.2 Global Operations in Spatial Domain, High-pass Filters

Example for $\text{grad}_{\max, \text{local}} = 200$ and $\text{grad}_{\min, \text{local}} = 100$

$$T_{\text{adaptiv, local}} = \text{Factor}_{\text{local}} * \text{grad}_{\max, \text{local}} + (1 - \text{Factor}_{\text{local}}) * \text{grad}_{\min, \text{local}}$$




3.2 Global Operations in Spatial Domain, High-pass Filters

- This procedure may produce very small threshold values in cases when

$$\text{grad}_{\max, \text{local}} \approx \text{grad}_{\min, \text{local}}$$

- Define a minimal threshold, which may not be surpassed.

3.2.4 Global Operations in Spatial Domain, High-pass Filters



Laplace-Filter

The edge is defined by Zero-crossing of 2nd derivative of grey level function.

- Calculate 2nd derivative by applying Nabla operator onto 1st derivative of grey level function.
- Vector operator applied on vector function results in scalar value.

3.2.4 Global Operations in Spatial Domain, High-pass Filters

$$\Delta g(x, y) = \nabla \left(\nabla g(x, y) \right) = \nabla \left(\frac{\partial}{\partial x} g(x, y), \frac{\partial}{\partial y} g(x, y) \right) =$$

$$\left(\frac{\partial}{\partial x}, \frac{\partial}{\partial y} \right) \left(\frac{\partial}{\partial x} g(x, y), \frac{\partial}{\partial y} g(x, y) \right) = \frac{\partial^2 g(x, y)}{\partial x^2} + \frac{\partial^2 g(x, y)}{\partial y^2} =$$

$$\frac{\partial}{\partial x} (g(x+1, y) - g(x, y)) + \frac{\partial}{\partial y} (g(x, y+1) - g(x, y)) =$$

$$g(x+1, y) - g(x, y) - g(x, y) + g(x-1, y) + g(x, y+1) - g(x, y) - g(x, y) + g(x, y-1)$$

Note : backward und forward differences are applied alternately !

3.2.4 Global Operations in Spatial Domain, High-pass Filters

$$H_{\text{math}} = \text{const} * \begin{bmatrix} 0 & -1 & 0 \\ -1 & +4 & -1 \\ 0 & -1 & 0 \end{bmatrix} \text{ oder } H_{\text{emp1}} = \text{const} * \begin{bmatrix} -1 & -1 & -1 \\ -1 & +8 & -1 \\ -1 & -1 & -1 \end{bmatrix} \text{ oder } H_{\text{emp2}} = \text{const} * \begin{bmatrix} -1 & -2 & -1 \\ -2 & +12 & -2 \\ -1 & -2 & -1 \end{bmatrix}$$

- H_{math} is deduced from Math, H_{emp1} und H_{emp2} are empirical deduced masks.
- Note : $\sum h(u,v) = 0$, i.e. image areas with constant grey level result in $g' = 0$.
- The masks produce symmetrical positive and negative grey values, negative grey values cannot be visualized.
- For visualization use according Look-up-Tables
- Find Zero-crossings (or crossing at 127.5 if scaled)

Hochschule RheinMain - University of Applied Sciences

3.2.4 Global Operations in Spatial Domain, High-pass Filters

Zero crossing detection :

if $((A_i \geq \text{Zero point} + T \text{ AND } B_i \leq \text{Zero point} - T) \text{ OR-ed for } i = 1, 2, 3, 4) = 1$
 OR
 $(A_i \leq \text{Zero point} - T \text{ AND } B_i \geq \text{Zero point} + T)) \text{ OR-ed for } i = 1, 2, 3, 4) = 1$
 then $g' = 255$
 else $g' = 0$

A1	A2	A3
B4	g'	A4
B3	B2	B1

ZeroCrossing.tif

Zero point = 0 or 127.5 if scaled;
 Threshold T : $\{0 \leq T < \approx 10\}$

Prof. Dr. D. Richter Department [Design>Computer Science>Media] 10

Hochschule RheinMain - University of Applied Sciences

3.2.4 Global Operations in Spatial Domain, Enhancement by Laplace

greylevel $g(x)$

1st derivative $g_x(x)$

2nd derivative $g_{xx}(x)$

$g_{new}(x) = g(x) - g_x(x) - g_{xx}(x)$

Prof. Dr. D. Richter Department [Design>Computer Science>Media] 10

Hochschule RheinMain - University of Applied Sciences

3.2.4 Global Operations in Spatial Domain, Enhancement by Laplace

Original Image

Enhanced Image by Laplace

Prof. Dr. D. Richter Department [Design>Computer Science>Media] 10

Hochschule RheinMain - University of Applied Sciences

3.2.5 Global Operations in Spatial Domain, High-pass Filters

- Laplace filter is extremely sensitive for noise.
- Apply low-pass filter before application of Laplace filter
- Ideal low-pass filter : Gauss filter
- Result : Laplacian of Gaussian (LoG)

Prof. Dr. D. Richter Department [Design>Computer Science>Media] 10

Hochschule RheinMain - University of Applied Sciences

3.2.5 Global Operations in Spatial Domain, LoG Filter

- Gauss-Filter : $G(u, v, \sigma)$ (two-dimensional)

$$g'(x, y) = \Delta \{ G(u, v, \sigma) * g(x, y) \} = \{ \Delta G(u, v, \sigma) \} * g(x, y)$$

(stated without mathematical proof)

$$\Delta G(u, v, \sigma) = h(u, v) = \frac{1}{2\pi\sigma^2} e^{-\frac{u^2 + v^2}{2\sigma^2}} \left(\frac{u^2 + v^2}{\sigma^2} - 2 \right) e^{-\frac{u^2 + v^2}{2\sigma^2}}$$

(Mexican hat shaped function)

$$g'(x, y) = h(u, v) * g(x, y)$$

Prof. Dr. D. Richter Department [Design>Computer Science>Media] 10

Hochschule RheinMain - University of Applied Sciences

3.2.5 Global Operations in Spatial Domain, LoG Filter

$M_{ij} = h(u, v), u = 0 \dots 12, v = 0 \dots 12$
 using prefactor -2 to get center element $M_{6,6} = 4$

$$M_{i,j} := -2 \left[\frac{[(i-6)^2 + (j-6)^2]}{\sigma^2} - 2 \right] e^{-\frac{[(i-6)^2 + (j-6)^2]}{2\sigma^2}}$$

Prof. Dr. D. Richter Department [Design>Computer Science>Media] 10



3.2.5 Global Operations in Spatial Domain, LoG Filter

	0	1	2	3	4	5	6	7
0	-0	-0	-0	-0	-0	-0.01	-0.01	-0.01
1	-0	-0	-0	-0.01	-0.03	-0.06	-0.07	-0.06
2	-0	-0	-0.02	-0.07	-0.16	-0.25	-0.29	-0.25
3	-0	-0.01	-0.07	-0.22	-0.42	-0.53	-0.54	-0.53
4	-0	-0.03	-0.16	-0.42	-0.53	-0.15	0.18	-0.15
5	-0.01	-0.06	-0.25	-0.53	-0.15	1.42	2.49	1.42
6	-0.01	-0.07	-0.29	-0.54	0.18	2.49	4	2.49
7	-0.01	-0.06	-0.25	-0.53	-0.15	1.42	2.49	...

- 2D-example with $\sigma=1,5$
- Range : 6 elements resp. 13 x 13 mask
- Cut-out of mask shown, missing elements are symmetrical to $h(6,6)$
- Element values rounded to 2 decimals
- Mask may be cut-off, if absolute values of $h(u,v) / h(6,6)$ are less then 0.1 \Rightarrow 9 x 9 mask



3.2.5 Global Operations in Spatial Domain, LoG Filter

For $r \rightarrow \infty$ we obtain $h(u,v) \rightarrow 0$

Cut-off for filter range assumed as $h(u,v) / h(0,0) > -0.1$

Range of filter : $h(u,v) / h(0,0) =$

- $\sigma = 1$: $h(u,v) / h(0,0) > -0.1$ for $u = 2,5$; 7 x 7 mask
- $\sigma = 1,5$: $h(u,v) / h(0,0) > -0.1$ for $u = 3,8$; 9 x 9 mask
- $\sigma = 2$: $h(u,v) / h(0,0) > -0.1$ for $u = 5,0$; 11 x 11 mask
- $\sigma = 3$: $h(u,v) / h(0,0) > -0.1$ for $u = 7,5$; 17 x 17 mask
- $\sigma = 4$: $h(u,v) / h(0,0) > -0.1$ for $u = 10,0$; 21 x 21 mask



3.2.5 Global Operations in Spatial Domain, LoG Filter

Let $\sigma = 2$ and get for $h(u,v)/h(0,0)$ the following linear mask :

-0,039|-0,093|-0,135|-0,041| 0,303| 0,772| 1,0 | 0,772| 0,303|-0,041|-0,135|-0,093|-0,039

Sum of mask elements / 11 elements = 0.237

Subtract 0.237 from all mask elements to achieve Σ of elements = 0 :

-0,330|-0,372|-0,278| 0,066| 0,535| 0,763| 0,535| 0,066|-0,278|-0,372|-0,330

Apply mask elements on grey level step from $g = 100$ to $g = 200$:

0 -33 -70 -98 -91 -38 +38 +91 +98 +70 +33 0

Zero-crossing defines position of edge

LoG01 engl.tif



3.2.5 Global Operations in Spatial Domain, LoG Filter

- Scaling to $G \in \{0, \dots, 255\}$

- $g'(g) = m * g + n$


with boundary condition $g(g_{\min} = -98) = 0$ und $g(g_{\max} = +98) = 255$

$$g'(g) = \frac{255}{g_{\max} - g_{\min}} * (g - g_{\min})$$

- In general in images g_{\max} and g_{\min} are not symmetrical to zero



3.2.5 Global Operations in Spatial Domain, LoG Filter



- $\Rightarrow g'(g=-98) = 0$ $g'(g=0) = 127,5$ $g'(g=+98) = 255$
- Zero-crossing is shifted in this case to 127,5 !



3.2.5 Global Operations in Spatial Domain, LoG Filter

- Define appropriate Mask size
- Calculate the sum of all mask elements, which is $\neq 0$
- Divide sum by number of all mask elements $n \times n$
- Subtract result from all mask elements
- Check sum of all mask elements to be 0
- Apply mask on image
- Calculate crossings of average grey value of laplace filtered image.



3.2.5 Global Operations in Spatial Domain, LoG Filter, Results



Image:
Synthetic image ParabolaTestImage04
without noise

Average grey value of Laplace filtered image 134.8

Target Image threshold $T = 15$



3.2.6 High Pass Filters, Canny Filter


Canny filter is a multi-step operator and generates one-pixel-wide edges

- Gauss Filter ($\sigma = 1$ or $\sigma = 1.4$)
- Direction dependent and independent Sobel Filter
- Thinning of edges
- Closing of gaps



3.2.6 High Pass Filters, Canny Filter

(www.pages.drexel.edu/~weg22/can_tut.html)



Canny filter is a multi-step operator and generates one-pixel-wide edges

5 x 5 Gauss filter

0.5	1.1	1.4	1.1	0.5
1.1	2.4	3.1	2.4	1.1
1.4	3.1	4.0	3.1	1.4
1.1	2.4	3.1	2.4	1.1
0.5	1.1	1.4	1.1	0.5

3 x 3 Gauss filter


1	2	1
2	4	2
1	2	1

- Apply low-pass filter on source image (QB) for noise reduction, e.g. 5*5-Gauss filter with $\sigma = 1$ or $\sigma = 1.4$, (Action: QB \rightarrow ZW1)



3.2.6 High Pass Filters, Canny Filter


(www.pages.drexel.edu/~weg22/can_tut.html)



- Apply Sobel *highpass* filter on ZW1 for edge extraction.
- Store direction independent magnitude (Action: ZW1 \rightarrow ZW2)
- Scale ZW2 to values 0, ... 255
- Store 4-direction dependent value in ZW3 (e.g. 0, 45, 90, 135 or 0, 1, 2, 3) for the discrete direction (Action: ZW1 \rightarrow ZW3).




3.2.6 High Pass Filters, Canny Filter




Thinning of edges :

- Scan ZW2 :
- Set actual magnitude value (white element) in ZW2 to 0, if it is **not** the maximum within the direction of the respective mask defined in ZW3 (e.g. white and yellow elements, white and green elements etc).
- Action : (ZW2 \rightarrow ZW2)



3.2.6 Global Operations in Spatial Domain, Canny Filter



Closing of gaps (Connectivity)

- Define two thresholds $0 < T_1 < T_2 < 255$
- Scan ZW2 :
 - if $g > T_2$: set ZW2 = 0 and ZB = 255
 - if $g < T_1$: set ZW2 = 0
 - if $T_1 < g < T_2$: leave ZW2 = g unchanged
- Action : (ZW2 \rightarrow ZW2 and ZW2 \rightarrow ZB)

Hochschule RheinMain - University of Applied Sciences

3.2.6 Global Operations in Spatial Domain, Canny Filter

Completion of target image (ZB):

- Scan ZB : if in ZB the actual pixel = 255 AND within the mask in ZW2 any value $g \neq 0$, i.e. $T_1 < g < T_2$, \rightarrow set the corresponding pixel in ZB to $g = 255$.

Action: (ZB \rightarrow ZB)

0	0	0
0	0	0
0	0	0

0	0	0
255	255	255
0	0	0

0	0	0
255	255	255
0	255	0

change 0 to 255

Canny.tif

Prof. Dr. D. Richter

Department [Design>Computer Science>Media] **10**

Hochschule RheinMain - University of Applied Sciences

3.2.6 Global Operations in Spatial Domain, Canny Filter

Prof. Dr. D. Richter

Department [Design>Computer Science>Media] **10**

Hochschule RheinMain - University of Applied Sciences

3.3 High Pass Filters, Harris Filter / Corner Filter

- Corners: significant structures in an image
- Applications:
 - Tracking of structures in image sequences
 - Search for corresponding points in stereo vision
 - Reference points for automatic measurements
 - Calibration of cameras
- Widely independent of illumination
- Requirements:
 - Differing between significant and non significant points
 - Independence of noise
 - Real time performance for video-tracking

Prof. Dr. D. Richter

Department [Design>Computer Science>Media] **10**

Hochschule RheinMain - University of Applied Sciences

3.3 High Pass Filters, Harris Filter / Corner Filter (1)

- Edges: significant magnitude of gradients in only one direction
- Corners: significant magnitude of gradients in more than one direction
- Calculate the gradients
by using Prewitt or Sobel: $I_x(x,y) = \frac{\partial}{\partial x} I(x,y)$ $I_y(x,y) = \frac{\partial}{\partial y} I(x,y)$
- Calculate matrices: $A(x,y) = I_x^2$ $B(x,y) = I_x I_y$ $C(x,y) = I_y^2$
- Construct matrix $M(x,y)$: $M = \begin{pmatrix} I_x^2 & I_x I_y \\ I_x I_y & I_y^2 \end{pmatrix} = \begin{pmatrix} A & B \\ B & C \end{pmatrix}$
- Filter the matrices A, B and C by using e.g. 5 x 5 low pass filter:
etc $A \rightarrow \bar{A}$

Prof. Dr. D. Richter

Department [Design>Computer Science>Media] **10**

Hochschule RheinMain - University of Applied Sciences

3.3 High Pass Filters, Harris Filter / Corner Filter (3)

Set $\bar{M} = \begin{pmatrix} \bar{A} & \bar{C} \\ \bar{C} & \bar{B} \end{pmatrix}$

Define a „corner response function“ $Q(x,y)$:

$$Q(x,y) = \det \bar{M} - \text{thr1} (\text{trace } \bar{M})^2$$

$$= \text{thr2} \{ (\bar{A} \bar{B} - \bar{C}^2) - \text{thr1} (\bar{A} + \bar{B})^2 \} \rightarrow \text{large}$$

Default value for $\text{thr1} \Rightarrow 0.04 \dots 0.06$, max. value 0.25

Check $Q(x,y) > \text{thr2}$ with $\text{thr2} \approx 10^4 \dots 10^8$

Prof. Dr. D. Richter

Department [Design>Computer Science>Media] **10**

Hochschule RheinMain - University of Applied Sciences

3.3 High Pass Filters, Harris Filter (Mathematical Background)


- Let be $\bar{M} = \begin{pmatrix} \bar{A} & \bar{C} \\ \bar{C} & \bar{B} \end{pmatrix}$
- The matrices M resp. \bar{M} are symmetrical and can be diagonalized:
 $\bar{M} = \begin{pmatrix} \lambda_1 & 0 \\ 0 & \lambda_2 \end{pmatrix}$ in which $\lambda_1 > 0$ and $\lambda_2 = 0$
 λ_i are called eigenvalues of \bar{M}
 $\lambda_{1,2} = \frac{\text{trace } \bar{M}}{2} \pm \sqrt{\left(\frac{\text{trace } \bar{M}}{2}\right)^2 - \det(\bar{M})}$
 $= \frac{1}{2} (\bar{A} + \bar{B} \pm \sqrt{\bar{A}^2 - 2\bar{A}\bar{B} + \bar{B}^2 + 4\bar{C}^2})$
- The eigenvalues define the strength of the edge.
- The eigenvectors v_1 and v_2 define the direction of the corresponding edge.
- Calculation of eigenvectors: <http://www.youtube.com/watch?v=I0ggTPAe1GU>

Prof. Dr. D. Richter

Department [Design>Computer Science>Media] **10**

Hochschule RheinMain - University of Applied Sciences

3.3 High Pass Filters, Harris Filter (Mathematical Background)




Synthetic Image
if $y < -2/3 x + 80 \rightarrow g = 80$
 $g = 120$ else
 $g(48,48) = 120$
 $lx(x,y) = 44,44..$
 $ly(x,y) = 71,11..$
 $lx^2 = 1975,31..$
 $ly^2 = 5056,79..$
 $lxl y = 3160,13..$
 $\lambda_1 = 7031,77..$
 $\lambda_2 = 0,3279..$
 $v_1 = \text{eigenvector}(\lambda_1) = \{0,6249.., 1\}$
 $v_2 = \text{eigenvector}(\lambda_2) = \{-1,600.., 1\}$


Prof. Dr. D. Richter Department [Design>Computer Science>Media] 10

Hochschule RheinMain - University of Applied Sciences

3.3 High Pass Filters, Harris Filter (Mathematical Background)



Synthetic Image
if $y < -2/3 x + 80 \rightarrow g = 80$
If $y > +3/2 x - 22 \rightarrow g = 80$
 $g = 120$ else
 $g(48,48) = 120$



filtered image by 3x3 Mean filter
 $g(49,48) = 106$
 $\bar{A} = 3919 \quad \bar{B} = 879.. \quad \bar{C} = 36..$
 $\lambda_1 = 4203,9.. \quad v_1 = (84,45.., 1)$
 $\lambda_2 = 752,0.. \quad v_2 = (-0,011.., 1)$

Prof. Dr. D. Richter Department [Design>Computer Science>Media] 10

Hochschule RheinMain - University of Applied Sciences

3.3 High Pass Filters, Harris Filter (Mathematical Background)

- Both eigenvalues λ_1 and λ_2 should be significant in corner positions or

$$\lambda_1 - \lambda_2 = 2 * \sqrt{\left(\frac{\text{trace } \bar{M}}{2}\right)^2 - \det \bar{M}}$$

should be small. Note: $(0,5 * \text{trace } \bar{M})^2 > \det \bar{M}$

Define a „corner response function“ $Q(x,y)$:

$$Q(x,y) = \det \bar{M} - \text{thr} (\text{trace } \bar{M})^2$$

$$= (\bar{A} \bar{B} - \bar{C}^2) - \text{thr} (\bar{A} + \bar{B})^2 \rightarrow \text{large}$$


Default value for thr 0.04 ... 0.06, max. value 0.25

Check $Q(x,y) > \text{thr2}$ with $\text{thr2} \approx 10^4 \dots 10^6$

Prof. Dr. D. Richter Department [Design>Computer Science>Media] 10

Hochschule RheinMain - University of Applied Sciences

3.3 High Pass Filters, Harris Filter / Corner Filter





Result with $\text{thr2} = 2 * 10^6$

Prof. Dr. D. Richter Department [Design>Computer Science>Media] 10

Hochschule RheinMain - University of Applied Sciences

3.3 High Pass Filters, Harris Filter / Corner Filter

Source image Harris filtered image,
for better visibility the grey intensity is set to 80%

Prof. Dr. D. Richter Department [Design>Computer Science>Media] 10


Hochschule RheinMain - University of Applied Sciences

Modellbildung:

- Lineare Bewegung ohne Rotation
- Rotation bei konstantem Schwerpunkt
- Lineare Bewegung des Schwerpunktes mit Rotation
- Nichtlineare Bewegung des Schwerpunktes mit Rotation
- Zoom-in / zoom-out Bewegung

Prof. Dr. D. Richter Department [Design>Computer Science>Media] 10

3.3 High Pass Filters, Harris Filter / Corner Filter



Originalbild und Harris-gefiltertes Bild zur Bewegungsanalyse

Review of Chapter 3

- Low pass filters (Mean / Median / Gauss / Binomial)
- High pass filters (Prewitt / Sobel / Roberts / Laplace / LoG
optional: Canny filter)
- Filtering as mask operation (no pixel operation)
- Filtering with masks of fixed and variable size
- Gradient of grey levels defined as vector
- Threshold operations (fixed / adaptive)
- Direction dependent and direction independent filtering
- Local and global filters
- Corner filter