

Hochschule RheinMain - University of Applied Sciences

University of Applied Sciences
Department of
Design, Computer Science, Media
Prof. Dr. D. Richter

Transilvania University Brasov
Faculty of
Mathematics and Informatics
Dr. I. Plajer

ISIP 2019
International School on Image Processing
July 15th - 26th, 2019




detlef.richter@HS-RM.de

Prof. Dr. D. Richter Department [Design>Computer Science>Media] 10

Hochschule RheinMain - University of Applied Sciences

University of Applied Sciences
Department of
Design, Computer Science, Media
Prof. Dr. D. Richter

Lectures on Image Processing

Chapter 8A

Selected Algorithms and Applications

Einige Bildbeispiele gem. UrhG §52a nicht enthalten

Prof. Dr. D. Richter Department [Design>Computer Science>Media] 10

Hochschule RheinMain - University of Applied Sciences

Notice to Copyright

All information in this paper and part thereof
is only for private use
in connection with the lecture
of Prof. Dr. D. Richter
from Hochschule RheinMain - University of Applied Sciences

Reproduction or publication and part thereof
is not allowed
without written permission of the author.

Prof. Dr. D. Richter Department [Design>Computer Science>Media] 10

Hochschule RheinMain - University of Applied Sciences


8.1 Selected Algorithms and Applications

8.1 Otsu – Binarization (s. Chapt.2)	8.8 Template Matching
8.2 Pyramid Algorithm	8.9 Seed-Algorithm
8.3 Wavelet Algorithm	8.10 Grey level slope at edges
8.4 Angular Orientation	8.11 Autocorrelation function
8.5 Error Propagation	8.12 Real time Properties
8.6 Tracing of Isophotes	8.13 Canny-Filter (s. Chapt. 3)
8.7 Connect Component Labeling	8.14 Distance Maps

Prof. Dr. D. Richter Department [Design>Computer Science>Media] 10

Hochschule RheinMain - University of Applied Sciences

8.2 Selected Algorithms and Applications, Pyramid Algorithm



- Define 512² array
- Use 256² source image Q1, differential image in Q4, Q2 und Q3 unused
- Calculate mean value for 4 pixel
- Store mean value in q1 of Q1
- Store differences in homologue positions in Q4
- Iteration with q1 and q4 in Q1
- Procedure terminates when mean value of source image is in pixel (0,0).
- Reconstruct source image after transmission until desired resolution.

Pyramidalgo-engl.doc



Prof. Dr. D. Richter Department [Design>Computer Science>Media] 10

Hochschule RheinMain - University of Applied Sciences

8.2 Selected Algorithms and Applications, Pyramid Algorithm

Source Image 512 x 512, Array 1024 x 1024

1. Step: Image 512 x 512 → 256 x 256
Differences: dark (pos.) / white (neg.)

Prof. Dr. D. Richter Department [Design>Computer Science>Media] 10



8.3 Selected Algorithms, example for Pyramid Algorithm

Resolution from 1^2 to 256^2


Rasterung.jpg

Prof. Dr. D. Richter

Department [Design>Computer Science>Media]



8.3 Selected Algorithms and Applications, Wavelet Algorithm



- Define two 512^2 arrays, write 512^2 source image into left array.
- Calculate mean value of 2 adjacent pixels in a line, store mean value in left half (LO) of 2nd array and store the difference value in right half (HI) of 2nd array.
- Repeat procedure column wise from right array and store results in upper and lower half of left array.

Prof. Dr. D. Richter

Department [Design>Computer Science>Media]



8.3 Selected Algorithms and Applications, Wavelet Algorithm

Source Image 512×512 1. Step: Image $512 \times 512 \rightarrow 256 \times 256$
Differences pos. and neg. with offset 128

Prof. Dr. D. Richter

Department [Design>Computer Science>Media]



8.3 Selected Algorithms and Applications, Wavelet Algorithm

2. Step: Image $512 \times 256 \rightarrow 256 \times 256$
Differences pos. and neg. with offset 128

Prof. Dr. D. Richter

Department [Design>Computer Science>Media]



8.3 Selected Algorithms and Applications, Wavelet Algorithm




- Result:
- 4 quadrants LOLO, LOHI, HILO, HIII in left array.
- LOLO contains a frequency reduced image.

Prof. Dr. D. Richter

Department [Design>Computer Science>Media]



8.3 Selected Algorithms and Applications, Wavelet Algorithm




- Iteration of the procedure out of LOLO-image in Q1 of left array.
- Procedure terminates when mean value of source image is in pixel (0,0).
- Reconstruct source image after transmission until desired resolution.

Prof. Dr. D. Richter

Department [Design>Computer Science>Media]



8.4 Selected Algorithms and Applications, Angular Orientation



Teach-in Phase :

- Calculate center of binary object S in defined position (red).
- Determine lengths of radial vectors in steps of $\Delta\alpha$.
- Store function $r_1 = f_1(\alpha)$ in an appropriate array.

Working Phase :


- Calculate S (black).
- Determine lengths of radial vectors in steps of $\Delta\alpha$, get $r_2 = f_2(\alpha + \Delta\Phi)$.
- Shift function f_2 against f_1 until difference of f_1 and f_2 is minimum to define $\Delta\Phi$.

Independency of object position

Prof. Dr. D. Richter

Department [Design>Computer Science>Media] 10


8.4 Application of Angular Orientation for Robotics



Prof. Dr. D. Richter

Department [Design>Computer Science>Media] 10

8.5 Selected Algorithms and Applications, Error Propagation




Rotationsmatrix.dsif

- Calculate circle by applying a rotational matrix R in arbitrary steps of $\Delta\alpha$.
- Plot a circle line by repeated application of the matrix on last point.
- Use different data types (integers without rounding (truncation), integers with correct rounding, float or double)
- Choose correct center of image for the circle, e.g. $M = (383.5, 287.5)$
- choose correct radius to plot the line, e.g. $R = xxx.5$

Prof. Dr. D. Richter

Department [Design>Computer Science>Media] 10

8.5 Selected Algorithms and Applications, Error Propagation



Computation with angular steps of $\Delta\alpha = (360/320)^\circ$ and 320 steps


upper left : Float data
upper right : rounded Integer data
lower left : Integer data

Result dependent on resolution of $\Delta\alpha$

Prof. Dr. D. Richter

Department [Design>Computer Science>Media] 10

8.7 Selected Algorithms and Applications, Connect Component Labelling



CCL.dsif

Separation of disjoint objects in binary images. (Lit : Rosenfeld A., Kak A.C., Digital Picture Processing, Vol. 2, Academic Press, New York, 1982)


1st step : scanning binary image from upper left to lower right by given mask for white pixel. For white pixel do:

- None of the pixels P_1 to P_4 is labelled : then : $P(x,y) \leftarrow$ new label $L_i = \min\{\text{set of not assigned labels } L_i\}$ (Start condition)
- At least one of the pixels P_1 to P_4 is labelled with label L_m : then $P(x,y) \leftarrow L_p = \min\{L_m\}$. In case of two different labels L_m and L_n are occurring : Note it within a list of equivalencies.

Prof. Dr. D. Richter

Department [Design>Computer Science>Media] 10

8.7 Selected Algorithms and Applications, Connect Component Labelling



CCL.dsif


2nd step : replace equivalent labels in the list of equivalencies by their smallest equivalent.

Visualize all individual objects by bounding boxes or by different grey levels.

Prof. Dr. D. Richter

Department [Design>Computer Science>Media] 10

8.8 Selected Algorithms and Applications, Template Matching



- Searching of defined patterns by templates
- Simple algorithm even for complex patterns
- Scanning of image using a template $T = t(i,j)$ of size $b \times h$
- b and h odd,


$$-\frac{b-1}{2} \leq i \leq \frac{b-1}{2}$$

$$-\frac{h-1}{2} \leq j \leq \frac{h-1}{2}$$

Prof. Dr. D. Richter

Department [Design>Computer Science>Media] 10

8.8 Selected Algorithms and Applications, Template Matching




- Calculation of similarity measure d between image and template :
$$d(x,y) = \sum \sum (g(x+i,y+j) - t(i,j))^2$$
- If $d(x,y) \Rightarrow$ minimum and $d(x,y) \leq T$, then template pattern matches image
- Thresholding is necessary, because there exists always a minimum

Prof. Dr. D. Richter

Department [Design>Computer Science>Media] 10

8.9 Selected Algorithms and Applications, Seed-Algorithm




- Search for connected structures or tissues, defined by special properties.
- Thresholding mostly not applicable (e.g. medical images).
- 2 voxel belong to the same object, if there exists a chain of connected voxels with same properties (homogeneity criterion).
- Normally check two adjacent voxels.
- Problems :
concave structures (2D, 3D);
partial effects (area, volume) : pixel or voxel belongs to different objects.

Prof. Dr. D. Richter

Department [Design>Computer Science>Media] 10

8.9 Selected Algorithms and Applications, Seed-Algorithm

4-neighborhood in case of 2-dim image




Add pixel to requested structure according homogeneity criterion

Prof. Dr. D. Richter

Department [Design>Computer Science>Media] 10

8.10 Selected Algorithms and Applications, Grey level slope at edges




- Suppose to have a bimodal histogram (Chapter 2) in full image or in region of interest. Determine mean upper g_u and lower g_l grey level.
- Define a linear grey level transition function between 10 % and 90 %
- Calculate a subpixel precise position of grey values : $g(x) < g_{\text{calculated}} < g(x+1)$
- Determine the slope of linear grey level transition function (sharpness)
- Define the edge at 50 % range.

Prof. Dr. D. Richter

Department [Design>Computer Science>Media] 10

8.10 Selected Algorithms and Applications, Grey level slope at edges




- On-line measurement of grey level slope assists optimal focusing for automatic camera calibration either with manually operated or computer operated objectives.

Prof. Dr. D. Richter

Department [Design>Computer Science>Media] 10

8.11 Selected Algorithms and Applications, Autocorrelation funct.




- Suppose to have the given cut out of an image line :
- $g(n)$, $n=1, \dots, N$, (black curve)
- Calculate $R(0) = \sum_{n=1}^N g(n) * g(n)$
- Shift $g(n)$ for k pixel (red curve)
- $R(k) = \sum_{n=1}^N g(n) * g(n+k)$
- Normalize $R(k)$: $r(k) = \frac{R(k)}{R(0)}$
- In case of an existing periodicity with period k $r(k)$ shows a local maximum in the approximate size of 1.


Prof. Dr. D. Richter

Department [Design>Computer Science>Media] 10

8.11 Selected Algorithms and Applications, Autocorrelation funct.



Original Image (576 x 786)



$r(k) = R(k)/R(0)$ for $k = 0 \dots 99$
 $\max\{r(k = 73)\} = 0.998\dots$


Prof. Dr. D. Richter

Department [Design>Computer Science>Media] 10

8.11 Selected Algorithms and Applications, Autocorrelation funct.



Original Image (512 x 512)




$r(k) = R(k)/R(0)$ for $k = 0 \dots 99$
 $\max\{r(k = 29)\} = 0.998\dots$
 $\max\{r(k = 57)\} = 0.993\dots$
 $\max\{r(k = 86)\} = 0.986\dots$

Prof. Dr. D. Richter

Department [Design>Computer Science>Media] 10

8.14 Mobile Roboter, Distanzkarten, Distance Maps




To find a path for an autonomous moving robot from starting point to destination it is necessary to find the most distant points from any obstacles in an environment. These points are calculated by distance maps. To calculate distance maps different masks are used, e.g.

- City-Block-mask,
- Chess-Board-mask,
- Euclidean mask.

Prof. Dr. D. Richter

Department [Design>Computer Science>Media] 10

8.14 Mobile Roboter, Distanzkarten, Distance Maps



$$d_c = |i-h| + |j-k|$$

$$d_{cb} = \max\{|i-h|, |j-k|\}$$

$$d_e = \sqrt{(i-h)^2 + (j-k)^2}$$

$$\text{Distance01.dsf}$$

Distance d between any two points: $P_1 = (i, j)$ and $P_2 = (h, k)$

Prof. Dr. D. Richter

Department [Design>Computer Science>Media] 10

8.14 Mobile Roboter, Distanzkarten, Distance Maps

Define:

White objects or obstacles ($g=255$) \rightarrow preset distance map with 0 (distance from object = 0)

Black background means no object ($g=0$) \rightarrow preset distance map with 1 (distance not yet calculated)

Prof. Dr. D. Richter

Department [Design>Computer Science>Media] 10

8.14 Mobile Roboter, Distanzkarten, Algorithmus

Example: Euclidean Distance

Forward calculation (blue mask elements) from top left to bottom right:

$d(x,y) = \min \{ \text{mask elements} + \text{value at pixel position} \}$ if $d(x,y) = 1$

e.g.

$d(x,y) = \min \{ \sqrt{2} + d(x-1,y-1), 1 + d(x,y-1), \sqrt{2} + d(x+1,y-1), 1 + d(x-1,y) \}$

Backward calculation (red mask elements) from bottom right to top left:

$d(x,y) = \min \{ \text{mask elements} + \text{pixel position} \}$ if $d(x,y) \neq 0$

e.g.


$d(x,y) = \min \{ d(x,y), 1 + d(x+1,y), \sqrt{2} + d(x+1,y+1), 1 + d(x,y+1), \sqrt{2} + d(x-1,y+1) \}$

City Block- und Chess Board Distance are calculated accordingly.

Prof. Dr. D. Richter

Department [Design>Computer Science>Media] 10


8.14 Mobile Robots, Distance Maps, City-Block-Distance



Prof. Dr. D. Richter

Department [Design>Computer Science>Media] 10

8.14 Mobile Robots, Distance Maps, Chess-Board-Distance




Prof. Dr. D. Richter

Department [Design>Computer Science>Media] 10

8.14 Mobile Robots, Distance Maps, Euclidean-Distance


Mathcad/Bilder/Umgebungsmodell01



Prof. Dr. D. Richter

Department [Design>Computer Science>Media] 10

8.14 Mobile Robots, Distance Maps, Path-Finding




Prof. Dr. D. Richter

Department [Design>Computer Science>Media] 10

8.14 Mobile Robots, Distance Maps, Path-Finding

- Decent from start with maximum gradient down to valley.
- Along valley to nearest position to destination (ambiguous).
- Ascent with maximum gradient to destination.



Prof. Dr. D. Richter

Department [Design>Computer Science>Media] 10

Hochschule RheinMain - University of Applied Sciences

8.16 Object Tracking

Insert Special Chapter
Kalman Filter

Prof. Dr. D. Richter Department [Design>Computer Science>Media] 10

Hochschule RheinMain - University of Applied Sciences

Review of Chapter 8

- Automatic binarization according to Otsu
- Pyramid and the wavelet algorithm for adaptive image size
- Calculation of the angular position of objects in binary images
- Error propagation due to wrong data formats
- Tracing of isophotes in grey level images

Prof. Dr. D. Richter Department [Design>Computer Science>Media] 10

Hochschule RheinMain - University of Applied Sciences

Review of Chapter 8 (continued)

- Labeling of disjoint objects in binary images by Connect Component Labeling
- Template Matching for search of complex patterns in images
- Segmentation by seed algorithm in medical images
- Automatic focus adjustment by analysis of grey level slopes at edges
- Search for periodic structures by autocorrelation function

Prof. Dr. D. Richter Department [Design>Computer Science>Media] 10

Hochschule RheinMain - University of Applied Sciences

Review of Chapter 8 (continued)

- Performance optimizing by real time measurement of algorithms
- Producing one-pixel wide edges in grey level images by Canny filter
- Distance maps for robot path planning

Prof. Dr. D. Richter Department [Design>Computer Science>Media] 10