

Hochschule RheinMain - University of Applied Sciences

University of Applied Sciences  
Department of  
Design, Computer Science, Media  
Prof. Dr. D. Richter

Transilvania University Brasov  
Faculty of  
Mathematics and Informatics  
Dr. I. Plajer

*ISIP 2019  
International School on Image Processing  
July 15<sup>th</sup> - 26<sup>th</sup>, 2019*



[detlef.richter@HS-RM.de](mailto:detlef.richter@HS-RM.de)

Prof. Dr. D. Richter Department [Design>Computer Science>Media] 10

Hochschule RheinMain - University of Applied Sciences

University of Applied Sciences  
Department of  
Design, Computer Science, Media  
Study Courses AI und MI  
Prof. Dr. D. Richter  
[detlef.richter@HS-RM.de](mailto:detlef.richter@HS-RM.de)

Lectures on Image Processing

## Chapter 8B Face Detection

Einige Bildbeispiele gem. UrhG §52a nicht enthalten

Prof. Dr. D. Richter Department [Design>Computer Science>Media] 10

Hochschule RheinMain - University of Applied Sciences

### Notice to Copyright

All information in this paper and part thereof  
is only for private use  
in connection with the lecture  
of Prof. Dr. D. Richter  
from Hochschule RheinMain - University of Applied Sciences

Reproduction or publication and part thereof  
is not allowed  
without written permission of the author.

Prof. Dr. D. Richter Department [Design>Computer Science>Media] 10

Hochschule RheinMain - University of Applied Sciences

### 8B. Face Detection

- Face detection: Is there any face in the image?
- Face recognition: Is a face identical to a specific person?
- Face identification: Which does this face belong to out of a given number of faces?

Prof. Dr. D. Richter Department [Design>Computer Science>Media] 10

Hochschule RheinMain - University of Applied Sciences

### 8B. Face Detection

Different Methods:

- Rapid object detection using a boosted cascade of simple features, Viola, Paul and Jones, Michael, 2001
- Eigenfaces for face recognition (not treated in this chapter)

Prof. Dr. D. Richter Department [Design>Computer Science>Media] 10

Hochschule RheinMain - University of Applied Sciences

### 8B. Face Detection

Because of the large variety of faces many „weak“ conditions have to be fulfilled to detect a face within an image.

Conditions may be developed from shades of grey within a face.

Area of eyes is darker than the forehead,  
eyes are darker than the nose in between,  
... and many other conditions.


For fast calculation of grey level areas integral images are used.

All face images are taken from free accessible images of the internet and may be used only for exercises of this chapter.

Prof. Dr. D. Richter Department [Design>Computer Science>Media] 10


Hochschule RheinMain - University of Applied Sciences

### 8B. Face Detection, Integral Image



Integral Image 01

$i(x,y)$ : grey value at position  $P(x,y)$




Integral Image 02

$I(x,y)$ : sum of all grey values  $P(0,0) \rightarrow P(x,y)$

Prof. Dr. D. Richter      Department [Design>Computer Science>Media] **10**

Hochschule RheinMain - University of Applied Sciences

### 8B. Face Detection, Integral Image



How will the integral image look like?

Take a sheet of paper and make a sketch of the integral image.



Original Image

Normalized Integral Image

Prof. Dr. D. Richter      Department [Design>Computer Science>Media] **10**

Hochschule RheinMain - University of Applied Sciences

### 8B. Face Detection, Integral Image


Original Image      Normalized Integral Image

Prof. Dr. D. Richter      Department [Design>Computer Science>Media] **10**

Hochschule RheinMain - University of Applied Sciences

### 8B. Face Detection, Calculation


How to calculate the integral image



Integral Image 03

$I(x,y) = I(x-1,y) + S(x,y-1) + i(x,y)$

How to calculate the mean grey value of any square



Integral Image 04

$F = D - C - B + A$

Calculation time is independent of area size


Prof. Dr. D. Richter      Department [Design>Computer Science>Media] **10**

Hochschule RheinMain - University of Applied Sciences


### 8B. Face Detection, Some Feature Types

Scan image with following masks


mask 1




mask 2



mask 3



mask 4





Integral Image Masks.dsf

If conditions are met, face might be detected

Prof. Dr. D. Richter      Department [Design>Computer Science>Media] **10**

Hochschule RheinMain - University of Applied Sciences

### 8B. Face Detection, Analysis of Synthetic Image

Mark of detected face

Analysis using four masks

Prof. Dr. D. Richter      Department [Design>Computer Science>Media] **10**

## 8B. Face Detection, Analysis of Natural Image



Analysis by mask 1 and mask 2




Analysis by mask 3 and mask 4

Prof. Dr. D. Richter

Department [Design>Computer Science>Media] 10

## 8B. Face Detection, Analysis




Coincidence of masks 1 to 4

Prof. Dr. D. Richter

Department [Design>Computer Science>Media] 10

## 8B. Face Detection, Results (only four features used)




All faces from internet

Prof. Dr. D. Richter

Department [Design>Computer Science>Media] 10


Source: A. Sommer, HS-RM, WS 2016/17



Prof. Dr. D. Richter

Department [Design>Computer Science>Media] 10

Source: A. Sommer, HS-RM, WS 2016/17



Schritt 1

Schritt 2

Schritt 3

Prof. Dr. D. Richter

Department [Design>Computer Science>Media] 10

## Review of Chapter 8B

- Meaning of face detection / recognition / identification
- What is the meaning of integral image
- How to calculate the integral image
- How to calculate the mean grey value of any square
- Useful masks for face detection
- How many „weak“ conditions may detect a face

Prof. Dr. D. Richter

Department [Design>Computer Science>Media] 10