

# Contents

<b>1 Basic</b>	<b>1</b>	<b>5.8 Palindrome Tree</b>	<b>11</b>
1.1 Default Code	1	<b>5.9 Duval</b>	<b>11</b>
1.2 Compare Fuction	1	<b>6 Math</b>	<b>11</b>
1.3 Pbds	1	6.1 Modulo	11
1.4 Double	1	6.2 Combination	12
1.5 Int128	1	6.3 Sieve	12
1.6 Rng	1	6.4 CRT	12
<b>2 Graph</b>	<b>2</b>	6.5 Matrix	12
2.1 DFS And BFS	2	6.6 Integer Partition	12
2.2 Prim	2	6.7 Mobius Theorem	12
2.3 Bellman-Ford	2	6.8 Mobius Inverse	13
2.4 Floyd-Warshall	2	6.9 Catalan Theorem	13
2.5 Euler	2	6.10 Burnside's Lemma	13
2.6 DSU	2	<b>7 Search and Greedy</b>	<b>13</b>
2.7 SCC	3	7.1 Binary Search	13
2.8 VBCC	3	7.2 Ternary Search	13
2.9 EBCC	3	<b>8 Tree</b>	<b>13</b>
2.10 2-SAT	4	8.1 LCA	13
2.11 Funtional Graph	4	8.2 Centroid Decomposition	14
<b>3 Data Structure</b>	<b>4</b>	8.3 Tree Flattening	14
3.1 BIT	4	8.4 Heavy Light Decomposition	14
3.2 RangeBit	5	8.5 Link Cut Tree	15
3.3 Segment Tree	5	8.6 Virtual Tree	15
3.4 Lazy Segment Tree	6	8.7 Dominator Tree	16
3.5 Persistent Segment Tree	6	<b>9 DP</b>	<b>16</b>
3.6 Treap	7	9.1 LCS	16
3.7 RMQ	7	9.2 LIS	16
3.8 Mo	7	9.3 Edit Distance	16
<b>4 Flow Matching</b>	<b>8</b>	9.4 Bitmask	17
4.1 Dinic	8	9.5 Projects	17
4.2 Min Cut	8	9.6 Removal Game	17
4.3 MCMF	8	9.7 Monotonic Queue	17
4.4 Hungarian	9	9.8 SOS	17
4.5 Theorem	9	9.9 CHT	17
<b>5 String</b>	<b>9</b>	9.10 DNC	18
5.1 Hash	9	9.11 LiChao Segment Tree	18
5.2 KMP	9	9.12 Codeforces Example	18
5.3 Z Function	10	<b>10 Geometry</b>	<b>18</b>
5.4 Manacher	10	10.1 Basic	18
5.5 Trie	10	10.2 Convex Hull	20
5.6 SA	10	10.3 Minimum Euclidean Distance	20
5.7 SAM	10	10.4 Lattice Points	20
		10.5 Minimum Cover Circle	20

## 1 Basic

### 1.1 Default Code [d41d8c]

```
#include <bits/stdc++.h>

using namespace std;
using ll = long long;

void solve() {

}

int main() {
    ios_base::sync_with_stdio(false);
    cin.tie(nullptr);
    int t = 1;
    cin >> t;
    while (t--) {
        solve();
    }
    return 0;
}
```

### 1.2 Compare Fuction [d41d8c]

```
// 1. sort, 二分搜刻在函式內 lambda 就好
// 2. priority queue 小到大是 >, set 是 <
// 3. set 不能 =, multiset 必須 =
// 4. 確保每個成員都要比到
// 5. pbds_multiset 不要用 lower_bound
// 6. 如果要用 find, 插入 inf 後使用 upper_bound
// 7. multiset 可以跟 set 一樣使用, 但請注意第 3、4 點

auto cmp = [](int i, int j) { return i > j; };
priority_queue<int, vector<int>, decltype(cmp)> pq(cmp);

vector<int> a {1, 2, 5, 4, 3}; // 小心不要改到 a
auto cmp = [&a](int i, int j) { return a[i] > a[j]; };
priority_queue<int, vector<int>, decltype(cmp)> pq(cmp);
```

### 1.3 Pbds [d41d8c]

```
#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>
using namespace __gnu_pbds;
template<class T>
```

```
using pbds_set = tree<T, null_type,
    less<T>, rb_tree_tag, tree_order_statistics_node_update>;
template<class T>
using pbds_multiset = tree<T, null_type, less_equal
    <T>, rb_tree_tag, tree_order_statistics_node_update>;
```

### 1.4 Double [f7a49d]

```
struct D {
    double x;
    constexpr static double eps = 1E-12;
    D() : x{0.0} {}
    D(double v) : x{v} {}
    double val() const { return x; }
    explicit operator double() const { return x; }
    D operator-(const D &rhs) const {
        return D(-x);
    }
    D &operator+=(const D &rhs) & {
        x += rhs.x; return *this;
    }
    D &operator-=(const D &rhs) & {
        x -= rhs.x; return *this;
    }
    D &operator*=(const D &rhs) & {
        x *= rhs.x; return *this;
    }
    D &operator/=(const D &rhs) & {
        assert(fabs(rhs.x) > eps);
        x /= rhs.x; return *this;
    }
    friend D operator+(D lhs, const D &rhs) {
        return lhs + rhs;
    }
    friend D operator-(D lhs, const D &rhs) {
        return lhs - rhs;
    }
    friend D operator*(D lhs, const D &rhs) {
        return lhs * rhs;
    }
    friend D operator/(D lhs, const D &rhs) {
        return lhs / rhs;
    }
    friend bool operator<(const D &lhs, const D &rhs) {
        return lhs.x - rhs.x < -eps;
    }
    friend bool operator>(const D &lhs, const D &rhs) {
        return lhs.x - rhs.x > eps;
    }
    friend bool operator==(const D &lhs, const D &rhs) {
        return fabs(lhs.x - rhs.x) < eps;
    }
    friend bool operator<=(const D &lhs, const D &rhs) {
        return lhs < rhs || lhs == rhs;
    }
    friend bool operator>=(const D &lhs, const D &rhs) {
        return lhs > rhs || lhs == rhs;
    }
    friend bool operator!=(const D &lhs, const D &rhs) {
        return !(lhs == rhs);
    }
    friend istream &operator>>(istream &is, D &a) {
        double v; is >> v; a = D(v); return is;
    }
    friend ostream &operator<<(ostream &os, const D &a) {
        return os << fixed << setprecision(10) << a.val()
            + (a.val() > 0 ? eps : a.val() < 0 ? -eps : 0);
    } // eps should < precision
};
```

### 1.5 Int128 [9454fa]

```
using i128 = __int128_t; // 1.7E38
inline i128 read() {
    i128 sgn = 1, x = 0;
    char c = getchar();
    while (c < '0' || c > '9') {
        if (c == '-') sgn = -1;
        c = getchar();
    }
    while (c >= '0' && c <= '9') {
        x = x * 10 + c - '0';
        c = getchar();
    }
    return x * sgn;
}
inline void write(i128 x) {
    if (x < 0) {
        putchar('-');
        x = -x;
    }
    if (x > 9) write(x / 10);
    putchar(x % 10 + '0');
}
```

### 1.6 Rng [401544]

```
mt19937_64 rng
    (chrono::steady_clock::now().time_since_epoch().count());
ll x = rng(); shuffle(a.begin(), a.end(), rng);
```

## 2 Graph

### 2.1 DFS And BFS [e2d856]

```
int main() {
    int n;
    vector<vector<int>> adj(n);
    // dfs_graph
    vector<bool> vis(n);
    auto dfs = [&](auto self, int u) -> void {
        if (vis[u]) return;
        vis[u] = true;
        for (auto v: adj[u]) {
            self(self, v);
        }
    };
    dfs(dfs, 0);
    // bfs
    vector<int> depth(n, 1e9);
    queue<int> q;
    auto bfs = [&](auto self, int s) -> void {
        vis[s] = true, depth[s] = 0;
        q.push(s);
        while (!q.empty()) {
            int u = q.front(); q.pop();
            for (auto v: adj[u]) {
                if (vis[v]) continue;
                vis[v] = true;
                depth[v] = depth[u] + 1;
                q.push(v);
            }
        }
    };
    bfs(bfs, 0);
}
```

### 2.2 Prim [3a3805]

```
auto prim =
    [&](int n, vector<vector<pair<int, int>>> &adj) -> bool {
        int node_sz = 0;
        priority_queue<pair<int, int>,
            vector<pair<int, int>>, greater<pair<int, int>>> pq;
        pq.emplace(0, 0); // w, vertex
        vector<bool> vis(n);
        while (!pq.empty()) {
            auto [u, w] = pq.top(); pq.pop();
            if (vis[u]) continue;
            vis[u] = true;
            node_sz++;
            for (auto v: adj[u]) {
                if (!vis[v.first]) {
                    pq.emplace(v.second, v.first);
                }
            }
        }
        if (node_sz == n) return true;
        return false;
    };
```

### 2.3 Bellman-Ford [430ded]

```
// 用 Bellman Ford 找負環
int main() {
    int n, m; cin >> n >> m;
    vector<array<int, 3>> e;
    for (int i = 0; i < m; i++) {
        int u, v, w; cin >> u >> v >> w;
        u--, v--; e.push_back({u, v, w});
    }
    vector<ll> dis(n, inf), par(n);
    int t = -1; dis[0] = 0;
    for (int i = 1; i <= n; i++) {
        for (auto [u, v, w]: e) {
            if (dis[v] > dis[u] + w) {
                dis[v] = dis[u] + w;
                par[v] = u;
                if (i == n) t = v;
            }
        }
    }
    if (t == -1) { cout << "NO\n"; return; }
    for (int i = 1; i < n; i++) t = par[t];
    vector<int> ans {t};
    int i = t;
    do {
        i = par[i];
        ans.push_back(i);
    } while (i != t);
    reverse(ans.begin(), ans.end());
    cout << "YES\n";
    for (auto x: ans) cout << x + 1 << " ";
}
```

### 2.4 Floyd-Warshall [3f61a4]

```
constexpr ll inf = 1e18;
void FloydWarshall(int n, int m) {
    int n, m; cin >> n >> m;
    vector<vector<int>> dis(n, vector<int>(n, inf));
    for (int i = 0; i < m; i++) {
        int u, v, w; cin >> u >> v >> w;
```

```
        dis[u][v] = min(dis[u][v], w);
        dis[v][u] = min(dis[v][u], w);
    }
    for (int i = 0; i < n; i++) dis[i][i] = 0;
    for (int k = 0; k < n; k++) {
        for (int i = 0; i < n; i++) {
            for (int j = 0; j < n; j++) {
                dis[i][j] = min(dis[i][j], dis[i][k] + dis[k][j]);
            }
        }
    }
}

const int N = 500; // Floyd 封包
void Floyd(int n, vector<bitset<N>> &dp) {
    for (int k = 0; k < n; k++) {
        for (int i = 0; i < n; i++) {
            if (dp[i][k]) {
                dp[i] |= dp[k];
            }
        }
    }
}
```

### 2.5 Euler [4177d]

```
// 1. 無向圖是歐拉圖：
// 非零度頂點是連通的
// 頂點的度數都是偶數

// 2. 無向圖是半歐拉圖(有路沒有環)：
// 非零度頂點是連通的
// 恰有 2 個奇度頂點

// 3. 有向圖是歐拉圖：
// 非零度頂點是強連通的
// 每個頂點的入度和出度相等

// 4. 有向圖是半歐拉圖(有路沒有環)：
// 非零度頂點是弱連通的
// 至多一個頂點的出度與入度之差為 1
// 至多一個頂點的入度與出度之差為 1
// 其他頂點的入度和出度相等
vector<int> ans;
auto dfs = [&](auto &&self, int u) -> void {
    while (g[u].size()) {
        int v = *g[u].begin();
        g[u].erase(v);
        self(self, v);
    }
    ans.push_back(u);
};
dfs(dfs, 0);
reverse(ans.begin(), ans.end());
```

### 2.6 DSU [749620]

```
struct DSU {
    int n;
    vector<int> boss, siz;
    DSU() {}
    DSU(int n_) { init(n_); }
    void init(int n_) {
        n = n_; boss.resize(n);
        iota(boss.begin(), boss.end(), 0);
        siz.assign(n, 1);
    }
    int find(int x) {
        if (boss[x] == x) return x;
        return boss[x] = find(boss[x]);
    }
    bool same(int x, int y) {
        return find(x) == find(y);
    }
    bool merge(int x, int y) {
        x = find(x); y = find(y);
        if (x == y) return false;
        if (siz[x] < siz[y]) swap(x, y);
        siz[x] += siz[y];
        boss[y] = x;
        n--;
        return true;
    }
    int size(int x) {
        return siz[find(x)];
    }
};

struct DSU {
    int n;
    vector<int> boss, siz, stk;
    DSU() {}
    DSU(int n_) { init(n_); }
    void init(int n_) {
        n = n_;
        boss.resize(n);
        iota(boss.begin(), boss.end(), 0);
        siz.assign(n, 1);
        stk.clear();
    }
    int find(int x) {
```

```

    return x == boss[x] ? x : find(boss[x]);
}
bool same(int x, int y) {
    return find(x) == find(y);
}
bool merge(int x, int y) {
    x = find(x); y = find(y);
    if (x == y) return false;
    if (siz[x] < siz[y]) swap(x, y);
    siz[x] += siz[y];
    boss[y] = x;
    n--;
    stk.push_back(y);
    return true;
}
void undo(int x) {
    while (stk.size() > x) {
        int y = stk.back();
        stk.pop_back();
        n++;
        siz[boss[y]] -= siz[y];
        boss[y] = y;
    }
}
int size(int x) {
    return siz[find(x)];
}
};

```

## 2.7 SCC [5d3e16]

```

struct SCC {
    int n, cur, cnt;
    vector<vector<int>>> adj;
    vector<int> stk, dfn, low, bel;
    SCC(int n_ = 0) { init(n_); }
    void init(int n_) {
        n = n_;
        adj.assign(n, {});
        dfn.assign(n, -1);
        low.resize(n);
        bel.assign(n, -1);
        stk.clear();
        cur = cnt = 0;
    }
    void addEdge(int u, int v) {
        adj[u].push_back(v);
    }
    void dfs(int x) {
        dfn[x] = low[x] = cur++;
        stk.push_back(x);
        for (auto y : adj[x]) {
            if (dfn[y] == -1) {
                dfs(y);
                low[x] = min(low[x], low[y]);
            } else if (bel[y] == -1) {
                low[x] = min(low[x], dfn[y]);
            }
        }
        if (dfn[x] == low[x]) {
            int y;
            do {
                y = stk.back();
                bel[y] = cnt;
                stk.pop_back();
            } while (y != x);
            cnt++;
        }
    }
    vector<int> work() {
        for (int i = 0; i < n; i++) {
            if (dfn[i] == -1) dfs(i);
        }
        return bel;
    }
};

struct Graph { // 可能有重邊
    int n;
    vector<pair<int, int>> edges;
    vector<int> siz;
    vector<int> cnte;
};

Graph compress() {
    Graph g;
    g.n = cnt;
    g.siz.resize(cnt);
    g.cnte.resize(cnt);
    for (int i = 0; i < n; i++) {
        g.siz[bel[i]]++;
        for (auto j : adj[i]) {
            if (bel[i] != bel[j]) {
                g.edges.emplace_back(bel[i], bel[j]);
            } else {
                g.cnte[bel[i]]++;
            }
        }
    }
    return g;
}
};

```

## 2.8 VBCC [170604]

```

struct VBCC {
    int n, cur;
    vector<vector<int>>> adj;
    vector<int> dfn, low, parent;
    vector<bool> is_cut;
    VBCC(int n_ = 0) { init(n_); }
    void init(int n_) {
        n = n_;
        adj.assign(n, {});
        dfn.assign(n, -1);
        low.resize(n);
        parent.assign(n, -1);
        is_cut.assign(n, false);
        cur = 0;
    }
    void addEdge(int u, int v) {
        adj[u].push_back(v);
        adj[v].push_back(u);
    }
    void dfs(int x) {
        int children = 0;
        dfn[x] = low[x] = cur++;
        for (int v : adj[x]) {
            if (dfn[v] == -1) {
                children++;
                parent[v] = x;
                dfs(v);
                low[x] = min(low[x], low[v]);

                if (parent[x] != -1 && low[v] >= dfn[x]) {
                    is_cut[x] = true;
                }
            } else if (v != parent[x]) {
                low[x] = min(low[x], dfn[v]);
            }
        }
        if (parent[x] == -1 && children > 1) {
            is_cut[x] = true;
        }
    }
    void work() {
        for (int i = 0; i < n; i++) {
            if (dfn[i] == -1) {
                dfs(i);
            }
        }
    }
};

```

## 2.9 EBCC [59d8ca]

```

struct EBCC { // CF/contest/1986/pF
    int n, cur, cnt;
    vector<vector<int>>> adj;
    vector<int> stk, dfn, low, bel;
    vector<pair<int, int>> bridges; // 關鍵邊
    EBCC(int n_ = 0) { init(n_); }
    void init(int n_) {
        n = n_;
        adj.assign(n, {});
        dfn.assign(n, -1);
        low.resize(n);
        bel.assign(n, -1);
        stk.clear();
        bridges.clear();
        cur = cnt = 0;
    }
    void addEdge(int u, int v) {
        adj[u].push_back(v);
        adj[v].push_back(u);
    }
    void dfs(int x, int p) {
        dfn[x] = low[x] = cur++;
        stk.push_back(x);
        for (auto y : adj[x]) {
            if (y == p) continue;
            if (dfn[y] == -1) {
                dfs(y, x);
                low[x] = min(low[x], low[y]);
                if (low[y] > dfn[x]) {
                    bridges.emplace_back(x, y);
                }
            } else if (bel[y] == -1) {
                low[x] = min(low[x], dfn[y]);
            }
        }
        if (dfn[x] == low[x]) {
            int y;
            do {
                y = stk.back();
                bel[y] = cnt;
                stk.pop_back();
            } while (y != x);
            cnt++;
        }
    }
    vector<int> work() { // not connected
        for (int i = 0; i < n; i++) {
            if (dfn[i] == -1) {
                dfs(i, -1);
            }
        }
    }
};

```

```

    return bel;
}
struct Graph { // 不會有重邊
    int n;
    vector<pair<int, int>> edges;
    vector<int> siz; // BCC 內節點數
    vector<int> cnte; // BCC 內邊數
};
Graph compress() {
    Graph g;
    g.n = cnt;
    g.siz.resize(cnt);
    g.cnte.resize(cnt);
    for (int i = 0; i < n; i++) {
        g.siz[bel[i]]++;
        for (auto j : adj[i]) {
            if (bel[i] < bel[j]) {
                g.edges.emplace_back(bel[i], bel[j]);
            } else if (i < j) {
                g.cnte[bel[i]]++;
            }
        }
    }
    return g;
}
};

```

## 2.10 2-SAT [3f3604]

```

// CS5E Giant Pizza
struct TwoSat {
    int n; vector<vector<int>> e;
    vector<bool> ans;
    TwoSat(int n) : n(n), e(2 * n), ans(n) {}
    void addClause(int u, bool f, int v, bool g) {
        e[2 * u + !f].push_back(2 * v + g);
        e[2 * v + !g].push_back(2 * u + f);
    }
    void ifThen(int u, bool f, int v, bool g) {
        // 必取 A: not A -> A
        e[2 * u + !f].push_back(2 * v + g);
    }
    bool satisfiable() {
        vector<int>
            > id(2 * n, -1), dfn(2 * n, -1), low(2 * n, -1);
        vector<int> stk;
        int now = 0, cnt = 0;
        function<void(int)> tarjan = [&](int u) {
            stk.push_back(u);
            dfn[u] = low[u] = now++;
            for (auto v : e[u]) {
                if (dfn[v] == -1) {
                    tarjan(v);
                    low[u] = min(low[u], low[v]);
                } else if (id[v] == -1) { // in stk
                    low[u] = min(low[u], dfn[v]);
                }
            }
            if (dfn[u] == low[u]) {
                int v;
                do {
                    v = stk.back();
                    stk.pop_back();
                    id[v] = cnt;
                } while (v != u);
                ++cnt;
            }
        };
        for (int i = 0; i < 2 * n; ++i) if (dfn[i] == -1) tarjan(i);
        for (int i = 0; i < n; ++i) {
            if (id[2 * i] == id[2 * i + 1]) return false;
            ans[i] = id[2 * i] > id[2 * i + 1];
        }
        return true;
    }
    vector<bool> answer() { return ans; }
};
int main() {
    int m, n; cin >> m >> n;
    TwoSat ts(n);
    for (int i = 0; i < m; ++i) {
        int u, v; char x, y;
        cin >> x >> u >> y >> v;
        ts.addClause(u - 1, x == '+', v - 1, y == '+');
    }
    if (ts.satisfiable()) {
        for (int i = 0; i < n; ++i) {
            cout << (ts.answer()[i] ? '+' : '-') << " ";
        }
    }
    else cout << "IMPOSSIBLE\n";
}

```

## 2.11 Funtional Graph [e8fd64]

```

constexpr int N = 2E5 + 5;
int cht[N][31]; // 倍增表, 放外面不然 TLE
struct FuntionalGraph {
    int n, cnt;
    vector<int> g, bel, id, len, in, top;

```

```

    FuntionalGraph() : n(0) {}
    FuntionalGraph(vector<int> g_) { init(g_); }
    void init(vector<int> g_) {
        n = g_.size(); cnt = 0;
        g = g_; bel.assign(n, -1);
        id.resize(n); len.clear();
        in.assign(n, 0); top.assign(n, -1);
        build();
    }
    void build() {
        for (int i = 0; i < n; i++) {
            cht[i][0] = g[i];
            in[g[i]]++;
        }
        for (int i = 1; i <= 30; i++)
            for (int u = 0; u < n; u++)
                cht[u][i] = cht[cht[u][i - 1]][i - 1];
        for (int i = 0; i < n; i++)
            if (in[i] == 0) label(i);
        for (int i = 0; i < n; i++)
            if (top[i] == -1) label(i);
    }
    void label(int u) {
        vector<int> p; int cur = u;
        while (top[cur] == -1) {
            top[cur] = u;
            p.push_back(cur);
            cur = g[cur];
        }
        auto s = find(p.begin(), p.end(), cur);
        vector<int> cyc(s, p.end());
        p.erase(s, p.end()); p.push_back(cur);
        for (int i = 0; i < (int)cyc.size(); i++) {
            bel[cyc[i]] = cnt;
            id[cyc[i]] = i;
        }
        if (!cyc.empty())
            ++cnt, len.push_back(cyc.size());
        for (int i = p.size() - 1; i > 0; i--)
            id[p[i - 1]] = id[p[i]] - 1;
    }
    int jump(int u, int k) {
        for (int b = 0; k > 0; b++) {
            if (k & 1) u = cht[u][b];
            k >>= 1;
        }
        return u;
    }
};

```

## 3 Data Structure

### 3.1 BIT [d41d8c]

```

template<typename T>
struct Fenwick { // 全部以 0 based 使用
    int n; vector<T> a;
    Fenwick(int n_) { init(n_); }
    void init(int n_) {
        n = n_;
        a.assign(n, T{});
    }
    void add(int x, const T &v) {
        for (int i = x + 1; i <= n; i += i & -i) {
            a[i - 1] = a[i - 1] + v;
        }
    }
    T sum(int x) { // 左閉右開查詢
        T ans{};
        for (int i = x; i > 0; i -= i & -i) {
            ans = ans + a[i - 1];
        }
        return ans;
    }
    T rangeSum(int l, int r) { // 左閉右開查詢
        return sum(r) - sum(l);
    }
    int select(const T &k, int start = 0) {
        // 找到最小的 x, 使得 sum(x + 1) - sum(start) > k
        int x = 0; T cur = -sum(start);
        for (int i = 1 << __lg(n); i; i /= 2) {
            if (x + i <= n && cur + a[x + i - 1] <= k) {
                x += i;
                cur = cur + a[x - 1];
            }
        }
        return x;
    }
};
template<class T>
struct TwoDFenwick { // 全部以 0 based 使用
    int nx, ny; // row, col 個數
    vector<vector<T>> a;
    TwoDFenwick(int nx_ = 0, int ny_ = 0) {
        init(nx_, ny_);
    }
    void init(int nx_, int ny_) {
        nx = nx_; ny = ny_;
        a.assign(nx, vector<T>(ny, T{}));
    }
    void add(int x, int y, const T &v) {

```

```

    for (int i = x + 1; i <= nx; i += i & -i) {
        for (int j = y + 1; j <= ny; j += j & -j) {
            a[i - 1][j - 1] = a[i - 1][j - 1] + v;
        }
    }
}
T sum(int x, int y) { // 左閉右開查詢
    T ans{};
    for (int i = x; i > 0; i -= i & -i) {
        for (int j = y; j > 0; j -= j & -j) {
            ans = ans + a[i - 1][j - 1];
        }
    }
    return ans;
}
T rangeSum
(int lx, int ly, int rx, int ry) { // 左閉右開查詢
    return sum(
        rx, ry) - sum(lx, ry) - sum(rx, ly) + sum(lx, ly);
};

```

## 3.2 RangeBit [d41d8c]

```

template<class T>
struct rangeFenwick { // 全部以 0 based 使用
    int n;
    vector<T> d, di;
    rangeFenwick(int n_ = 0) { init(n_); }
    void init(int n_) {
        n = n_;
        d.assign(n, T{});
        di.assign(n, T{});
    }
    void add(int x, const T &v) {
        T vi = v * (x + 1);
        for (int i = x + 1; i <= n; i += i & -i) {
            d[i - 1] = d[i - 1] + v;
            di[i - 1] = di[i - 1] + vi;
        }
    }
    void rangeAdd(int l, int r, const T &v) {
        add(l, v); add(r, -v);
    }
    T sum(int x) { // 左閉右開查詢
        T ans{};
        for (int i = x; i > 0; i -= i & -i) {
            ans = ans + T(x + 1) * d[i - 1];
            ans = ans - di[i - 1];
        }
        return ans;
    }
    T rangeSum(int l, int r) { // 左閉右開查詢
        return sum(r) - sum(l);
    }
    int select(const T &k, int start = 0) {
        // 找到最小的 x, 使得 sum(x + 1) - sum(start) > k
        int x = 0; T cur = -sum(start);
        for (int i = 1 << __lg(n); i; i /= 2) {
            if (x + i <= n) {
                T val = T(
                    x + i + 1) * d[x + i - 1] - di[x + i - 1];
                if (cur + val <= k) {
                    x += i;
                    cur = cur + val;
                }
            }
        }
        return x;
    }
};

template<class T>
struct rangeTwoDFenwick { // 全部以 0 based 使用
    int nx, ny; // row, col 個數
    vector<vector<T>> d, di, dj;
    rangeTwoDFenwick(int nx_ = 0, int ny_ = 0) {
        init(nx_, ny_);
    }
    void init(int nx_, int ny_) {
        nx = nx_; ny = ny_;
        d.assign(nx, vector<T>(ny, T{}));
        di.assign(nx, vector<T>(ny, T{}));
        dj.assign(nx, vector<T>(ny, T{}));
        dij.assign(nx, vector<T>(ny, T{}));
    }
    void add(int x, int y, const T &v) {
        T vi = v * (x + 1);
        T vj = v * (y + 1);
        T vij = v * (x + 1) * (y + 1);
        for (int i = x + 1; i <= nx; i += i & -i) {
            for (int j = y + 1; j <= ny; j += j & -j) {
                d[i - 1][j - 1] = d[i - 1][j - 1] + v;
                di[i - 1][j - 1] = di[i - 1][j - 1] + vi;
                dj[i - 1][j - 1] = dj[i - 1][j - 1] + vj;
                dij[i - 1][j - 1] = dij[i - 1][j - 1] + vij;
            }
        }
    }
    void rangeAdd(int lx, int ly, int rx, int ry, const T &v) {
        add(rx, ry, v);
        add(lx, ry, -v);
    }
};

```

```

    add(rx, ly, -v);
    add(lx, ly, v);
}
T sum(int x, int y) { // 左閉右開查詢
    T ans{};
    for (int i = x; i > 0; i -= i & -i) {
        for (int j = y; j > 0; j -= j & -j) {
            ans = ans
                + T(x * y + x + y + 1) * d[i - 1][j - 1];
            ans = ans - T(y + 1) * di[i - 1][j - 1];
            ans = ans - T(x + 1) * dj[i - 1][j - 1];
            ans = ans + dij[i - 1][j - 1];
        }
    }
    return ans;
}
T rangeSum
(int lx, int ly, int rx, int ry) { // 左閉右開查詢
    return sum(
        rx, ry) - sum(lx, ry) - sum(rx, ly) + sum(lx, ly);
};

```

## 3.3 Segment Tree [d41d8c]

```

template<class Info>
struct Seg { // 左閉右開寫法
    int n; vector<Info> info;
    Seg(): n(0) {}
    Seg(int n_, Info v_ = Info()) { init(n_, v_); }
    template<class T>
    Seg(vector<T> init_) { init(init_); }
    void init(int n_, Info v_ = Info()) {
        init(vector(n_, v_));
    }
    template<class T>
    void init(vector<T> init_) {
        n = init_.size();
        info.assign(4 << __lg(n), Info());
        function<void(
            int, int, int)> build = [&](int p, int l, int r) {
            if (r - l == 1) {
                info[p] = init_[l];
                return;
            }
            int m = (l + r) / 2;
            build(p * 2, l, m);
            build(p * 2 + 1, m, r);
            pull(p);
        };
        build(1, 0, n);
    }
    void pull(int p) {
        info[p] = info[p * 2] + info[p * 2 + 1];
    }
    void modify(int p, int l, int r, int x, const Info &v) {
        if (r - l == 1) {
            info[p] = v; return;
        }
        int m = (l + r) / 2;
        if (x < m) modify(2 * p, l, m, x, v);
        else modify(2 * p + 1, m, r, x, v);
        pull(p);
    }
    void modify(int p, const Info &i) {
        modify(1, 0, n, p, i);
    }
    Info query(int p, int l, int r, int ql, int qr) {
        if (qr <= l || ql >= r) return Info();
        if (ql <= l && r <= qr) return info[p];
        int m = (l + r) / 2;
        return query(p * 2, l, m, ql, qr) + query(p * 2 + 1, m, r, ql, qr);
    }
    Info query(int ql, int qr) {
        return query(1, 0, n, ql, qr);
    }
};

template<class F> // 尋找區間內，第一個符合條件的
int findFirst
(int p, int l, int r, int x, int y, F &&pred) {
    if (l >= y || r <= x)
        return -1;
    if (l >= x && r <= y && !pred(info[p]))
        return -1;
    if (r - l == 1)
        return l;
    int m = (l + r) / 2;
    int res = findFirst(2 * p, l, m, x, y, pred);
    if (res == -1)
        res = findFirst(2 * p + 1, m, r, x, y, pred);
    return res;
}

template<class F> // 若要找 last, 先右子樹遞迴即可
int findFirst(int l, int r, F &&pred) {
    return findFirst(1, 0, n, l, r, pred);
};

struct Info {
    int n = 0;
    int sum = 0;
};

```

```
};
Info operator+(const Info &a, const Info &b) {
    return { a.n + b.n, a.sum + b.sum };
}
```

### 3.4 Lazy Segment Tree [d41d8c]

```
template<class Info, class Tag>
struct LazySeg { // 左閉右開寫法
    int n;
    vector<Info> info;
    vector<Tag> tag;
    LazySeg() : n(0) {}
    LazySeg(int n_, Info v_ = Info()) {
        init(n_, v_);
    }
    template<class T>
    LazySeg(vector<T> init_) {
        init(init_);
    }
    void init(int n_, Info v_ = Info()) {
        init(vector(n_, v_));
    }
    template<class T>
    void init(vector<T> init_) {
        n = init_.size();
        info.assign(4 << __lg(n), Info());
        tag.assign(4 << __lg(n), Tag());
        function<void(
            int, int, int)> build = [&](int p, int l, int r) {
            if (r - l == 1) {
                info[p] = init_[l];
                return;
            }
            int m = (l + r) / 2;
            build(p * 2, l, m);
            build(p * 2 + 1, m, r);
            pull(p);
        };
        build(1, 0, n);
    }
    void pull
        (int p) { info[p] = info[p * 2] + info[p * 2 + 1]; }
    void apply(int p, int l, int r, const Tag &v) {
        info[p].apply(l, r, v);
        tag[p].apply(v);
    }
    void push(int p, int l, int r) {
        int m = (l + r) / 2;
        if (r - l >= 1) {
            apply(p * 2, l, m, tag[p]);
            apply(p * 2 + 1, m, r, tag[p]);
        }
        tag[p] = Tag();
    }
    void modify(int p, int l, int r, int x, const Info &v) {
        if (r - l == 1) {
            info[p] = v;
            return;
        }
        int m = (l + r) / 2;
        push(p, l, r);
        if (x < m) {
            modify(2 * p, l, m, x, v);
        } else {
            modify(2 * p + 1, m, r, x, v);
        }
        pull(p);
    }
    void modify(int p, const Info &i) {
        modify(1, 0, n, p, i);
    }
    Info query(int p, int l, int r, int ql, int qr) {
        if (qr <= l || ql >= r) return Info();
        if (ql <= l && r <= qr) return info[p];
        int m = (l + r) / 2;
        push(p, l, r);
        return query(p * 2, l, m, ql, qr) + query(p * 2 + 1, m, r, ql, qr);
    }
    Info query
        (int ql, int qr) { return query(1, 0, n, ql, qr); }
    void range_apply
        (int p, int l, int r, int ql, int qr, const Tag &v) {
        if (qr <= l || ql >= r) return;
        if (ql <= l && r <= qr) {
            apply(p, l, r, v);
            return;
        }
        int m = (l + r) / 2;
        push(p, l, r);
        range_apply(p * 2, l, m, ql, qr, v);
        range_apply(p * 2 + 1, m, r, ql, qr, v);
        pull(p);
    }
    void range_apply(int l, int r, const Tag &v) {
        range_apply(1, 0, n, l, r, v);
    }
    template<class F> // 尋找區間內，第一個符合條件的
    int findFirst
        (int p, int l, int r, int x, int y, F &&pred) {
        if (l >= y || r <= x) {
```

```
            return -1;
        }
        if (l >= x && r <= y && !pred(info[p])) {
            return -1;
        }
        if (r - l == 1) {
            return l;
        }
        int m = (l + r) / 2;
        push(p);
        int res = findFirst(2 * p, l, m, x, y, pred);
        if (res == -1) {
            res = findFirst(2 * p + 1, m, r, x, y, pred);
        }
        return res;
    }
    template<class F> // 若要找 last，先右子樹遞迴即可
    int findFirst(int l, int r, F &&pred) {
        return findFirst(1, 0, n, l, r, pred);
    }
};
struct Tag { // 有些 Tag 不用 push 例如 sweepLine
    int set_val; int add;
    void apply(const Tag &v) {
        if (v.set_val) {
            set_val = v.set_val;
            add = v.add;
        }
        else {
            add += v.add;
        }
    }
};
struct Info {
    int sum;
    void apply(int l, int r, const Tag &v) {
        if (v.set_val) {
            sum = (r - l) * v.set_val;
        }
        sum += (r - l) * v.add;
    }
    // Info& operator=(const Info &rhs) {
    //     // 部分 assignment 使用
    //     return *this;
    // }
};
Info operator+(const Info &a, const Info &b) {
    return { a.sum + b.sum };
}
```

### 3.5 Persistent Segment Tree [d41d8c]

```
template<class Info>
struct PST {
    struct Node {
        Info info = Info();
        int lc = 0, rc = 0;
    };
    vector<Node> nd;
    int n = 0; vector<int> rt;
    PST() : n(0) {}
    PST(int n_, Info v_ = Info()) { init(n_, v_); }
    template<class T>
    PST(vector<T> init_) { init(init_); }
    void init(int n_, Info v_ = Info()) {
        init(vector<Info>(n_, v_));
    }
    template<class T>
    void init(vector<T> init_) {
        n = init_.size();
        nd.clear(); rt.clear();
        nd.emplace_back(); // 讓 root 指向 1-based
        rt.push_back(build(0, n, init_));
    }
    int build(int l, int r, vector<Info> &init_) {
        int id = nd.size();
        nd.emplace_back();
        if (r - l == 1) {
            nd[id].info = init_[l];
            return id;
        }
        int m = (l + r) >> 1;
        nd[id].lc = build(l, m, init_);
        nd[id].rc = build(m, r, init_);
        pull(nd[id]);
        return id;
    }
    void pull(Node &t) {
        t.info = nd[t.lc].info + nd[t.rc].info;
    }
    int copy(int t) { // copy 一個 node
        nd.push_back(nd[t]);
        return nd.size() - 1;
    }
    int generate() { // 創立新的 node
        nd.emplace_back();
        return nd.size() - 1;
    }
    int modify(int t, int l, int r, int x, const Info &v) {
        t = t ? copy(t) : generate();
        if (r - l == 1) {
```



```

        nd[t].info = v;
        return t;
    }
    int m = (l + r) >> 1;
    if (x < m) {
        nd[t].lc = modify(nd[t].lc, l, m, x, v);
    } else {
        nd[t].rc = modify(nd[t].rc, m, r, x, v);
    }
    pull(nd[t]);
    return t;
}
void modify(int ver, int pos, const Info &val) {
    if (int(r.size()) <= ver) rt.resize(ver + 1);
    rt[ver] = modify(rt[ver], 0, n, pos, val);
}
Info query(int t, int l, int r, int ql, int qr) {
    if (l >= qr || r <= ql) return Info();
    if (ql <= l && r <= qr) return nd[t].info;
    int m = (l + r) >> 1;
    return query(nd[t].lc, l, m, ql, qr) + query(nd[t].rc, m, r, ql, qr);
}
Info query(int ver, int ql, int qr) {
    return query(rt[ver], 0, n, ql, qr);
}
void createVersion(int ori_ver) {
    rt.push_back(copy(rt[ori_ver]));
}
void reserve(int n, int q) {
    nd.reserve(n + q * (2 * __lg(n) + 1));
    rt.reserve(q + 1);
}
void resize(int n) {
    rt.resize(n);
}
};
struct Info {
    int sum = 0;
};
Info operator+(const Info &a, const Info &b) {
    return { a.sum + b.sum };
}

```

### 3.6 Treap [d41d8c]

```

struct Treap {
    Treap *lc, *rc;
    int pri, siz; bool rev_valid;
    int val; int min;
    Treap(int val_) {
        min = val = val_;
        pri = rand();
        lc = rc = nullptr;
        siz = 1; rev_valid = 0;
    }
    void pull() { // update siz or other information
        siz = 1;
        min = val;
        for (auto c : {lc, rc}) {
            if (!c) continue;
            siz += c->siz;
            min = std::min(min, c->min);
        }
    }
    void push() {
        if (rev_valid) {
            swap(lc, rc);
            if (lc) lc->rev_valid ^= 1;
            if (rc) rc->rev_valid ^= 1;
        }
        rev_valid = false;
    }
    int find(int k) { // 找到 min 是 k 的位置 (1-based)
        push();
        int ls = (lc ? lc->siz : 0) + 1;
        if (val == k) return ls;
        if (lc && lc->min == k) return lc->find(k);
        else return rc->find(k) + ls;
    }
};
int size(Treap *t) {
    return t ? t->siz : 0;
}
Treap *merge(Treap *a, Treap *b) {
    if (!a || !b) return a ? a : b;
    a->push(); b->push();
    if (a->pri > b->pri) {
        a->rc = merge(a->rc, b);
        a->pull();
        return a;
    } else {
        b->lc = merge(a, b->lc);
        b->pull();
        return b;
    }
}
pair<Treap*, Treap*> split(Treap *t, int k) {
    // 分割前 k 個在 first，剩下的在 second
    if (t == nullptr) return {nullptr, nullptr};
    t->push();

```

```

    if (size(t->lc) < k) {
        auto [a, b] = split(t->rc, k - size(t->lc) - 1);
        t->rc = a;
        t->pull();
        return {t, b};
    } else {
        auto [a, b] = split(t->lc, k);
        t->lc = b;
        t->pull();
        return {a, t};
    }
}
void Print(Treap *t) {
    if (!t) return;
    t->push();
    Print(t->lc);
    cout << t->val;
    Print(t->rc);
}

```

### 3.7 RMQ [d41d8c]

```

template<class T, class Cmp = greater<T>>
struct RMQ {
    const Cmp cmp = Cmp();
    static constexpr unsigned B = 64;
    using u64 = unsigned long long;
    int n;
    vector<vector<T>> a;
    vector<T> pre, suf, ini;
    vector<u64> stk;
    RMQ() {}
    RMQ(const vector<T> &v) { init(v); }
    void init(const vector<T> &v) {
        n = v.size();
        pre = suf = ini = v;
        stk.resize(n);
        if (!n) {
            return;
        }
        const int M = (n - 1) / B + 1;
        const int lg = __lg(M);
        a.assign(lg + 1, vector<T>(M));
        for (int i = 0; i < M; i++) {
            a[0][i] = v[i * B];
            for (int j = 1; j < B && i * B + j < n; j++) {
                a[0][i] = min(a[0][i], v[i * B + j], cmp);
            }
        }
        for (int i = 1; i < n; i++) {
            if (i % B) {
                pre[i] = min(pre[i], pre[i - 1], cmp);
            }
        }
        for (int i = n - 2; i >= 0; i--) {
            if (i % B != B - 1) {
                suf[i] = min(suf[i], suf[i + 1], cmp);
            }
        }
        for (int j = 0; j < lg; j++) {
            for (int i = 0; i + (2 << j) <= M; i++) {
                a[j + 1][i] = min(a[j][i], a[j][i + (1 << j)], cmp);
            }
        }
        for (int i = 0; i < M; i++) {
            const int l = i * B;
            const int r = min(1U * n, l + B);
            u64 s = 0;
            for (int j = l; j < r; j++) {
                while (s && cmp(v[j], v[__lg(s) + l])) {
                    s ^= 1ULL << __lg(s);
                }
                s |= 1ULL << (j - l);
                stk[j] = s;
            }
        }
    }
    T operator()(int l, int r) {
        if (l / B != (r - 1) / B) {
            T ans = min(suf[l], pre[r - 1], cmp);
            l = l / B + 1;
            r = r / B;
            if (l < r) {
                int k = __lg(r - l);
                ans = min(
                    ({ans, a[k][l], a[k][r - (1 << k)]}, cmp);
            }
            return ans;
        } else {
            int x = B * (l / B);
            return ini[
                __builtin_ctzll(stk[r - 1] >> (l - x)) + l];
        }
    }
};

```

### 3.8 Mo [d41d8c]

```

struct query {
    int l, r, id;

```

```

} typedef query;
void MO(int n, vector<query> &queries) {
    int block = sqrt(n);
    function<bool(query, query)> cmp = [&](query a, query b) {
        int block_a = a.l / block;
        int block_b = b.l / block;
        if (block_a != block_b) return block_a < block_b;
        return a.r < b.r;
    };
    sort(queries.begin(), queries.end(), cmp);
}
void compress(vector<int> &nums) {
    vector<int> sorted = nums;
    sort(sorted.begin(), sorted.end());
    sorted.erase(
        unique(sorted.begin(), sorted.end()), sorted.end());
    for (int i = 0; i < nums.size(); i++) {
        nums[i] = lower_bound(sorted.begin(), sorted.end(), nums[i]) - sorted.begin() + 1;
    }
}

```

## 4 Flow Matching

### 4.1 Dinic [d41d8c]

```

template<class T>
struct Dinic {
    struct Edge {
        int to;
        T flow, cap; // 流量跟容量
    };
    int n, m, s, t;
    const T INF_FLOW = 1 << 30;
    vector<vector<int>> adj; // 此點對應的 edges 編號
    vector<Edge> edges; // 幫每個 edge 編號
    vector<int> dis, ptr;
    Dinic(int n_) { init(n_); }
    void init(int n_) {
        n = n_; m = 0;
        dis.resize(n); ptr.resize(n);
        adj.assign(n, vector<int>{});
        edges.clear();
    }
    void add_edge(int u, int v, T cap) {
        // 偶數 id 是正向邊
        edges.push_back({v, 0, cap});
        edges.push_back({u, 0, 0});
        adj[u].push_back(m++);
        adj[v].push_back(m++);
    }
    bool bfs() {
        fill(dis.begin(), dis.end(), -1);
        dis[s] = 0; queue<int> q;
        q.push(s);
        while (!q.empty() && dis[t] == -1) {
            int u = q.front(); q.pop();
            for (int id : adj[u]) {
                Edge &e = edges[id];
                if (e.flow == e.cap) continue;
                if (dis[e.to] == -1) {
                    dis[e.to] = dis[u] + 1;
                    q.push(e.to);
                }
            }
        }
        return dis[t] != -1;
    }
    T dfs(int u, T flow) {
        if (flow == 0) return 0;
        if (u == t) return flow;
        for (int &cur = ptr[u]; cur < (int)adj[u].size(); cur++) {
            Edge &e = edges[adj[u][cur]];
            if (dis[u] + 1 != dis[e.to]) continue;
            if (e.cap == e.flow) continue;
            T mn = dfs(e.to, min(flow, e.cap - e.flow));
            if (mn > 0) {
                e.flow += mn;
                edges[adj[u][cur] ^ 1].flow -= mn;
                return mn;
            }
        }
        return 0; // 到不了終點就會 return 0
    }
    T work(int s_, int t_) {
        s = s_; t = t_; T flow = 0;
        while (bfs()) {
            fill(ptr.begin(), ptr.end(), 0);
            while (true) {
                T res = dfs(s, INF_FLOW);
                if (res == 0) break;
                flow += res;
            }
        }
        return flow;
    }
    void reset() {
        for (int i = 0; i < m; i++) edges[i].flow = 0;
    }
};

```

### 4.2 Min Cut [d41d8c]

```

// CSES Police Chase
int main() {
    int n, m; cin >> n >> m;
    Dinic<int> g(n);
    for (int i = 0; i < m; i++) {
        int u, v, cap = 1;
        cin >> u >> v;
        u--; v--;
        g.add_edge(u, v, cap);
        g.add_edge(v, u, cap);
    }
    int res = g.work(0, n - 1);
    cout << res << "\n";
    if (res == 0) return;

    vector<int> vis(n);
    auto find = [&](auto self, int u) -> void {
        if (!vis[u]) {
            vis[u] = 1;
            for (int id : g.adj[u]) {
                auto e = g.edges[id];
                if (e.cap - e.flow > 0) {
                    self(self, e.to);
                }
            }
        }
    };
    find(find, 0);
    for (int i = 0; i < n; i++) {
        if (!vis[i]) continue;
        for (int id : g.adj[i]) {
            if (id & 1) continue;
            auto e = g.edges[id];
            if (!vis[e.to]) {
                cout << i + 1 << " " << e.to + 1 << "\n";
            }
        }
    }
}

```

### 4.3 MCMF [d41d8c]

```

template<class Tf, class Tc>
struct MCMF {
    struct Edge {
        int to;
        Tf flow, cap; // 流量跟容量
        Tc cost;
    };
    // 可以只用 spfa 或 dijkstra, 把跟 pot 有關的拿掉就好
    int n, m, s, t;
    const Tf INF_FLOW = 1 << 30;
    const Tc INF_COST = 1 << 30;
    vector<vector<int>> adj;
    vector<Edge> edges; // 幫每個 edge 編號
    vector<Tc> dis, pot; // johnson algorithm, using spfa
    vector<int> rt; // 路徑恢復, 對應 id
    vector<bool> inq;
    MCMF(int n_) { init(n_); }
    void init(int n_) {
        n = n_; m = 0;
        edges.clear();
        adj.assign(n, vector<int>{});
    }
    void add_edge(int u, int v, Tf cap, Tc cost) {
        edges.push_back({v, 0, cap, cost});
        edges.push_back({u, 0, 0, -cost});
        adj[u].push_back(m++);
        adj[v].push_back(m++);
    }
    bool spfa() {
        dis.assign(n, INF_COST);
        rt.assign(n, -1); inq.assign(n, false);
        queue<int> q;
        q.push(s); dis[s] = 0; inq[s] = true;
        while (!q.empty()) {
            int u = q.front(); q.pop();
            inq[u] = false;
            for (int id : adj[u]) {
                auto [v, flow, cap, cost] = edges[id];
                Tc ndis = dis[u] + cost + pot[u] - pot[v];
                if (flow < cap && dis[v] > ndis) {
                    dis[v] = ndis; rt[v] = id;
                    if (!inq[v]) {
                        q.push(v); inq[v] = true;
                    }
                }
            }
        }
        return dis[t] != INF_COST;
    }
    bool dijkstra() {
        dis.assign(n, INF_COST); rt.assign(n, -1);
        priority_queue<pair<Tc, int>, vector<pair<Tc, int>, greater<pair<Tc, int>>> pq;
        dis[s] = 0; pq.emplace(dis[s], s);
        while (!pq.empty()) {
            auto [d, u] = pq.top(); pq.pop();
            if (dis[u] < d) continue;
        }
    }
};

```



```

    for (int id : adj[u]) {
        auto [v, flow, cap, cost] = edges[id];
        Tc ndis = dis[u] + cost + pot[u] - pot[v];
        if (flow < cap && dis[v] > ndis) {
            dis[v] = ndis; rt[v] = id;
            pq.emplace(ndis, v);
        }
    }
}
return dis[t] != INF_COST;
}
// 限定 flow, 最小化 cost
pair<Tf, Tc> work_flow(int s_, int t_, Tf need) {
    s = s_, t = t_; pot.assign(n, 0);
    Tf flow{}; Tc cost{}; bool fr = true;
    while ((fr ? spfa() : dijkstra())) {
        for (int i = 0; i < n; i++) {
            dis[i] += pot[i] - pot[s];
        }
        Tf f = INF_FLOW;
        for (int i = t; i != s; i = edges[rt[i] ^ 1].to) {
            f = min(f, edges[rt[i]].cap - edges[rt[i]].flow);
        }
        f = min<Tf>(f, need);
        for (int i = t; i != s; i = edges[rt[i] ^ 1].to) {
            edges[rt[i]].flow += f;
            edges[rt[i] ^ 1].flow -= f;
        }
        flow += f; need -= f;
        cost += f * dis[t]; fr = false;
        swap(dis, pot);
        if (need == 0) break;
    }
    return make_pair(flow, cost);
}
// 限定 cost, 最大化 flow
pair<Tf, Tc> work_budget(int s_, int t_, Tc budget) {
    s = s_, t = t_; pot.assign(n, 0);
    Tf flow{}; Tc cost{}; bool fr = true;
    while ((fr ? spfa() : dijkstra())) {
        for (int i = 0; i < n; i++) {
            dis[i] += pot[i] - pot[s];
        }
        Tf f = INF_FLOW;
        for (int i = t; i != s; i = edges[rt[i] ^ 1].to) {
            f = min(f, edges[rt[i]].cap - edges[rt[i]].flow);
        }
        f = min<Tf>(f, budget / dis[t]);
        for (int i = t; i != s; i = edges[rt[i] ^ 1].to) {
            edges[rt[i]].flow += f;
            edges[rt[i] ^ 1].flow -= f;
        }
        flow += f; budget -= f * dis[t];
        cost += f * dis[t]; fr = false;
        swap(dis, pot);
        if (budget == 0 || f == 0) break;
    }
    return make_pair(flow, cost);
}
void reset() {
    for (int i = 0; i < m; i++) edges[i].flow = 0;
}
};

```

## 4.4 Hungarian [d41d8c]

```

struct Hungarian { // 0-based
    int n, m;
    vector<vector<int>> adj;
    vector<int> used, vis;
    vector<pair<int, int>> match;
    Hungarian(int n_ = 0, int m_ = 0) {
        init(n_, m_);
    }
    void init(int n_, int m_) {
        n = n_; m = m_;
        adj.assign(n + m, vector<int>());
        used.assign(n + m, -1);
        vis.assign(n + m, 0);
    }
    void addEdge(int u, int v) {
        adj[u].push_back(n + v);
        adj[n + v].push_back(u);
    }
    bool dfs(int u) {
        int sz = adj[u].size();
        for (int i = 0; i < sz; i++) {
            int v = adj[u][i];
            if (vis[v] == 0) {
                vis[v] = 1;
                if (used[v] == -1 || dfs(used[v])) {
                    used[v] = u;
                    return true;
                }
            }
        }
        return false;
    }
    vector<pair<int, int>> work() {

```

```

        match.clear(); used.assign(n + m, -1);
        vis.assign(n + m, 0);
        for (int i = 0; i < n; i++) {
            fill(vis.begin(), vis.end(), 0); dfs(i);
        }
        for (int i = n; i < n + m; i++) {
            if (used[i] != -1) {
                match.push_back(make_pair(used[i], i - n));
            }
        }
        return match;
    }
};

```

## 4.5 Theorem [d41d8c]

// 有向無環圖：

// 最小不相交路徑覆蓋：

// 最小路徑數 = 頂點數 - 最大匹配數

// 最小相交路徑覆蓋：

// 先用

Floyd 求傳遞封包，有連邊就建邊，然後再套最小不相交路徑覆蓋

// 二分圖：

// 最小點

覆蓋：選出一些點，讓所有邊至少有一個端點在點集中的最少數量

// 最小點覆蓋 = 最大匹配數

// 還原解，flow 的作法是從源點開始 dfs，只走 cap - flow > 0

的邊，最後挑選左邊還沒被跑過的點和右邊被跑過的點當作覆蓋的點

// 最少邊覆蓋：選出一些邊，讓所有點都覆蓋到的最少數量

// 最少邊覆蓋 = 點數 - 最大匹配數

// 最大獨立集：選出一些點，使這些點兩兩沒有邊連接的最大數量

// 最大獨立集 = 點數 - 最大匹配數

## 5 String

### 5.1 Hash [852711]

```

constexpr int B = 59;
vector<Z> Hash(string &s) {
    vector<Z> ans {0};
    for (auto c : s) {
        ans.push_back(ans.back() * B + (c - 'a' + 1));
    }
    return ans;
}
void solve() {
    string s, sub;
    cin >> s >> sub;
    auto a = Hash(s);
    auto q = Hash(sub);
    auto find = q.back();
    int ans = 0;
    int l = 1, r = sub.size(), len = sub.size();
    while (r <= s.size()) {
        if (a[r] - a[l - 1] * power(Z(B), len) == find) {
            ans++;
        }
        l++, r++;
    }
    cout << ans << "\n";
}

```

### 5.2 KMP [cddf9]

```

struct KMP {
    string sub;
    vector<int> failure;
    KMP(string sub_) {
        sub = sub_;
        failure.resize(sub.size(), -1);
        buildFailFunction();
    }
    void buildFailFunction() {
        for (int i = 1; i < (int)sub.size(); i++) {
            int now = failure[i - 1];
            while (now != -1
                && sub[now + 1] != sub[i]) now = failure[now];
            if (sub[now + 1] == sub[i]) failure[i] = now + 1;
        }
    }
    vector<int> match(string &s) {
        vector<int> match;
        for (int i = 0, now = -1; i < (int)s.size(); i++) {
            // now is the compare succeeded length -1
            while (s[i] !=
                sub[now + 1] && now != -1) now = failure[now];
            // failure stores if comparison fail, move to where
            if (s[i] == sub[now + 1]) now++;
            if (now + 1 == (int)sub.size()) {
                match.push_back(i - now);
                now = failure[now];
            }
        }
    }
}

```

```

    }
    return match;
};

```

### 5.3 Z Function [764b31]

```

// z[i] 表示 s 和 s[i, n - 1] (以 s[i] 開頭的后綴)
// 的最長公共前綴 (LCP) 的長度
vector<int> Z(string s) {
    int n = s.size();
    vector<int> z(n); z[0] = n;
    for (int i = 1, j = 1; i < n; i++) {
        z[i] = max(0, min(j + z[j] - i, z[i - j]));
        while (i + z[i] < n && s[z[i]] == s[i + z[i]])
            z[i]++;
        if (i + z[i] > j + z[j]) j = i;
    }
    return z; // 最後一格不算
}

```

### 5.4 Manacher [9c9ca6]

```

// 找到對於每個位置的迴文半徑
vector<int> manacher(string s) {
    string t = "#";
    for (auto c : s) {
        t += c;
        t += '#';
    }
    int n = t.size();
    vector<int> r(n);
    for (int i = 0, j = 0; i < n; i++) {
        // i 是中心, j 是最長回文字串中心
        if (2 * j - i >= 0 && j + r[j] > i) {
            r[i] = min(r[2 * j - i], j + r[j] - i);
        }
        while (i - r[i] >= 0 && i + r[i] < n && t[i - r[i]] == t[i + r[i]]) {
            r[i]++;
        }
        if (i + r[i] > j + r[j]) {
            j = i;
        }
    }
    return r;
    // # a # b # a #
    // 1 2 1 4 1 2 1
    // # a # b # b # a #
    // 1 2 1 2 5 2 1 2 1
    // 值 -1 代表原回文字串長度
    // (id - val + 1) / 2 可得原字串回文開頭
}

```

### 5.5 Trie [31e4ff]

```

constexpr int N = 1E7;
int tot = 0;
int trie[N][26], cnt[N];
void reset() {
    tot = 0, fill_n(trie[0], 26, 0);
}
int newNode() {
    int x = ++tot;
    cnt[x] = 0, fill_n(trie[x], 26, 0);
    return x;
}
void add(string &s) {
    int p = 0;
    for (auto c : s) {
        int &q = trie[p][c - 'a'];
        if (!q) q = newNode();
        p = q;
    }
    cnt[p]++;
}
int find(string &s) {
    int p = 0;
    for (auto c : s) {
        int q = trie[p][c - 'a'];
        if (!q) return 0;
        p = q;
    }
    return cnt[p];
}

```

### 5.6 SA [b58946]

```

struct SuffixArray {
    int n; string s;
    vector<int> sa, rk, lc;
    // n: 字串長度
    // sa: 後綴數組, sa[i] 表示第 i 小的後綴的起始位置
    // rk: 排名數組, rk[i] 表示從位置 i 開始的後綴的排名
    // lc: LCP
    // 數組, lc[i] 表示 sa[i] 和 sa[i + 1] 的最長公共前綴長度
    SuffixArray(const string &s_) {
        s = s_; n = s.length();
        sa.resize(n);
        lc.resize(n - 1);
    }
}

```

```

rk.resize(n);
iota(sa.begin(), sa.end(), 0);
sort(sa.begin(), sa,
    end(), [&](int a, int b) { return s[a] < s[b]; });
rk[sa[0]] = 0;
for (int i = 1; i < n; i++)
    rk[sa[i]] = rk[sa[i - 1]] + (s[sa[i]] != s[sa[i - 1]]);

int k = 1;
vector<int> tmp, cnt(n);
tmp.reserve(n);
while (rk[sa[n - 1]] < n - 1) {
    tmp.clear();
    for (int i = 0; i < k; i++)
        tmp.push_back(n - k + i);
    for (auto i : sa)
        if (i >= k)
            tmp.push_back(i - k);
    fill(cnt.begin(), cnt.end(), 0);
    for (int i = 0; i < n; i++)
        ++cnt[rk[i]];
    for (int i = 1; i < n; i++)
        cnt[i] += cnt[i - 1];
    for (int i = n - 1; i >= 0; i--)
        sa[--cnt[rk[tmp[i]]]] = tmp[i];
    swap(rk, tmp);
    rk[sa[0]] = 0;
    for (int i = 1; i < n; i++)
        rk[sa[i]] = rk[sa[i - 1]] + (tmp[sa[i - 1]] < tmp[sa[i]] || sa[i - 1] + k == n || tmp[sa[i - 1] + k] < tmp[sa[i] + k]);
    k *= 2;
}
for (int i = 0, j = 0; i < n; i++) {
    if (rk[i] == 0) {
        j = 0;
    } else {
        for (j -= j > 0; i + j < n && sa[rk[i] - 1] + j < n && s[i + j] == s[sa[rk[i] - 1] + j]; j++);
        lc[rk[i] - 1] = j;
    }
}
}
};

```

### 5.7 SAM [b7d7b1]

```

struct SAM {
    // 1 -> initial state
    static constexpr int ALPHABET_SIZE = 26;
    struct Node {
        int len;
        int link;
        array<int, ALPHABET_SIZE> next;
        Node() : len{0}, link{-1}, next{} {}
    };
    vector<Node> t;
    SAM() {
        init();
    }
    void init() {
        t.assign(2, Node());
        t[0].next.fill(1);
        t[0].len = -1;
    }
    int newNode() {
        t.emplace_back();
        return t.size() - 1;
    }
    int extend(int p, int c) {
        if (t[p].next[c]) {
            int q = t[p].next[c];
            if (t[q].len == t[p].len + 1) {
                return q;
            }
            int r = newNode();
            t[r].len = t[p].len + 1;
            t[r].link = t[q].link;
            t[r].next = t[q].next;
            t[q].link = r;
            while (t[p].next[c] == q) {
                t[p].next[c] = r;
                p = t[p].link;
            }
            return r;
        }
        int cur = newNode();
        t[cur].len = t[p].len + 1;
        while (!t[p].next[c]) {
            t[p].next[c] = cur;
            p = t[p].link;
        }
        t[cur].link = extend(p, c);
        return cur;
    }
}
void solve() {
    string s; cin >> s;
    int n = s.length();
    vector<int> last(n + 1); // s[i - 1] 的後綴終點位置
    last[0] = 1;
}

```

```

SAM sam;
for (int i = 0; i < n; i++) {
    last[i + 1] = sam.extend(last[i], s[i] - 'a');
}
int sz = sam.t.size();
vector<int> cnt(sz);
for (int i = 1; i <= n; i++) {
    cnt[last[i]]++; // 去重 = 1
}
vector<vector<int>> order(sz);
for (int i = 1; i <= sz; i++) {
    order[sam.t[i].len].push_back(i);
}
for (int i = sz - 1; i > 0; i--) {
    for (int u : order[i]) {
        if (sam.t[u].link != -1) {
            cnt[sam.t[u].link] += cnt[u];
        }
    }
}
}
}

```

## 5.8 Palindrome Tree [f10e9d]

```

struct PAM {
    // 0 -> even root, 1 -> odd root
    static constexpr int ALPHABET_SIZE = 26;
    struct Node {
        int len;
        int fail;
        array<int, ALPHABET_SIZE> next;
        Node() : len{0}, fail{-1}, next{} {}
    };
    vector<int> s;
    vector<Node> t;
    PAM() {
        init();
    }
    void init() {
        t.assign(2, Node());
        s.clear();
        t[0].len = 0;
        t[1].len = -1;
        t[0].fail = 1;
    }
    int newNode() {
        t.emplace_back();
        return t.size() - 1;
    }
    int extend(int p, int c) {
        int n = s.size();
        s.push_back(c);
        while (s[n - t[p].len - 1] != c) {
            p = t[p].fail;
        }
        if (!t[p].next[c]) {
            int r = newNode();
            t[r].len = t[p].len + 2;
            int cur = t[p].fail;
            while (s[n - t[cur].len - 1] != c) {
                cur = t[cur].fail;
            }
            t[r].fail = t[cur].next[c];
            t[p].next[c] = r;
        }
        p = t[p].next[c];
        return p;
    }
};
void solve() {
    string s; cin >> s;
    int n = s.length();
    vector<int> last(n + 1);
    last[0] = 1;
    PAM pam;
    for (int i = 0; i < n; i++) {
        last[i + 1] = pam.extend(last[i], s[i] - 'a');
    }
    int sz = pam.t.size();
    vector<int> cnt(sz);
    for (int i = 1; i <= n; i++) {
        cnt[last[i]]++; // 去重 = 1
    }
    for (int i = sz - 1; i > 1; i--) {
        cnt[pam.t[i].fail] += cnt[i];
    }
}

```

## 5.9 Duval [f9dcca]

```

// duval_algorithm
// 將字串分解成若干個非嚴格遞減的非嚴格遞增字串
vector<string> duval(string s) {
    int i = 0, n = s.size();
    vector<string> res;
    while (i < n) {
        int k = i, j = i + 1;
        while (s[k] <= s[j] && j < n) {
            if (s[k] < s[j]) k = i;
            else k++;
        }
        j++;
    }
}

```

```

    }
    while (i <= k) {
        res.push_back(s.substr(i, j - k));
        i += j - k;
    }
}
return res;
}
// 最小旋轉字串
string min_round(string s) {
    s += s;
    int i = 0, n = s.size();
    int start = i;
    while (i < n / 2) {
        start = i;
        int k = i, j = i + 1;
        while (s[k] <= s[j] && j < n) {
            if (s[k] < s[j]) k = i;
            else k++;
        }
        j++;
        while (i <= k) {
            i += j - k;
        }
    }
    return s.substr(start, n / 2);
}

```

## 6 Math

### 6.1 Modulo [80b974]

```

template<class T>
constexpr T power(T a, ll b) {
    T res {1};
    for (; b; b /= 2, a *= a)
        if (b % 2) res *= a;
    return res;
}
constexpr ll mul(ll a, ll b, ll p) {
    ll res = a * b - ll(1.L * a * b / p) * p;
    res %= p;
    if (res < 0) res += p;
    return res;
}
template<ll P>
struct MInt {
    ll x;
    constexpr MInt() : x {0} {}
    constexpr MInt(ll x) : x {norm(x % getMod())} {}
    static ll Mod;
    constexpr static ll getMod() {
        if (P > 0) return P;
        else return Mod;
    }
    constexpr static void setMod(ll Mod_) {
        Mod = Mod_;
    }
    constexpr ll norm(ll x) const {
        if (x < 0) x += getMod();
        if (x >= getMod()) x -= getMod();
        return x;
    }
    constexpr MInt operator-(const MInt &rhs) const {
        MInt res;
        res.x = norm(getMod() - x);
        return res;
    }
    constexpr MInt inv() const {
        return power(*this, getMod() - 2);
    }
    constexpr MInt &operator*=(MInt rhs) & {
        if (getMod() < (1ULL << 31)) {
            x = x * rhs.x % int(getMod());
        } else {
            x = mul(x, rhs.x, getMod());
        }
        return *this;
    }
    constexpr MInt &operator+=(MInt rhs) & {
        x = norm(x + rhs.x);
        return *this;
    }
    constexpr MInt &operator-=(MInt rhs) & {
        x = norm(x - rhs.x);
        return *this;
    }
    constexpr MInt &operator/=(MInt rhs) & {
        return *this *= rhs.inv();
    }
    friend constexpr MInt operator*(MInt lhs, MInt rhs) {
        MInt res = lhs; return res *= rhs;
    }
    friend constexpr MInt operator+(MInt lhs, MInt rhs) {
        MInt res = lhs; return res += rhs;
    }
    friend constexpr MInt operator-(MInt lhs, MInt rhs) {
        MInt res = lhs; return res -= rhs;
    }
    friend constexpr MInt operator/(MInt lhs, MInt rhs) {
        MInt res = lhs; return res /= rhs;
    }
}

```

```

friend
constexpr istream &operator>>(istream &is, MInt &a) {
    ll v; is >> v; a = MInt(v); return is;
}
friend constexpr
ostream &operator<<(ostream &os, const MInt &a) {
    return os << a.x;
}
friend constexpr bool operator==(MInt lhs, MInt rhs) {
    return lhs.x == rhs.x;
}
friend constexpr bool operator!=(MInt lhs, MInt rhs) {
    return lhs.x != rhs.x;
}
friend constexpr bool operator<(MInt lhs, MInt rhs) {
    return lhs.x < rhs.x;
}
};
template<>
ll MInt<0>::Mod = 998244353;
constexpr ll P = 1E9 + 7;
using Z = MInt<P>;

```

## 6.2 Combination [6aa734]

```

struct Comb {
    ll n; vector<Z> _fac, _invfac, _inv;
    Comb() : n{0}, _fac{1}, _invfac{1}, _inv{0} {}
    Comb(ll n) : Comb() { init(n); }
    void init(ll m) {
        m = min(m, Z::getMod() - 1);
        if (m <= n) return;
        _fac.resize(m + 1);
        _invfac.resize(m + 1);
        _inv.resize(m + 1);
        for (int i = n + 1; i <= m; i++) {
            _fac[i] = _fac[i - 1] * i;
        }
        _invfac[m] = _fac[m].inv();
        for (int i = m; i > n; i--) {
            _invfac[i - 1] = _invfac[i] * i;
            _inv[i] = _invfac[i] * _fac[i - 1];
        }
        n = m;
    }
    Z fac(ll m) {
        if (m > n) init(2 * m);
        return _fac[m];
    }
    Z invfac(ll m) {
        if (m > n) init(2 * m);
        return _invfac[m];
    }
    Z inv(ll m) {
        if (m > n) init(2 * m);
        return _inv[m];
    }
    Z binom(ll n, ll m) {
        if (n < m || m < 0) return 0;
        return fac(n) * invfac(m) * invfac(n - m);
    }
    Z lucas(ll n, ll m) { // Mod 要在 1E5 左右
        if (m == 0) return 1;
        return binom(n % Z::getMod(), m % Z::getMod())
            * lucas(n / Z::getMod(), m / Z::getMod());
    }
} comb; // 注意宣告，若要換模數需重新宣告

```

## 6.3 Sieve [8a3c1c]

```

vector<int> prime, minp;
void sieve(int n) {
    minp.assign(n + 1, 1); // 1 代表是質數，非 1 不是
    minp[0] = minp[1] = -1;
    int m = int(sqrt(n)) + 1;
    for (int i = 2; i <= m; i++) {
        if (minp[i] == 1) {
            prime.push_back(i);
            for (int j = 2; i * j <= n; j++) {
                minp[i * j] = i;
            }
        }
    }
}
// a ^ (m-1) = 1 (Mod m)
// a ^ (m-2) = 1/a (Mod m)
// Exp2: cout << power(x, power(y, p, Mod - 1), Mod)
// Num = (x+1) * (y+1) * (z+1)...
// Sum = (a^0 + a^1 + ... + a^x) * (b^0 + ... + b^y)
// Mul = N * (x+1) * (y+1) * (z+1) / 2

```

## 6.4 CRT [d41d8c]

```

ll exgcd(ll a, ll b, ll &x, ll &y) {
    if (!b) {
        x = 1, y = 0;
        return a;
    }
    ll g = exgcd(b, a % b, y, x);
    y -= a / b * x;
    return g;
}

```

```

}
ll inv(ll x, ll m){
    ll a, b;
    exgcd(x, m, a, b);
    a %= m;
    if (a < 0) a += m;
    return a;
}
// remain, mod
ll CRT(vector<pair<ll, ll>> &a){
    ll prod = 1;
    for (auto x : a) {
        prod *= x.second;
    }
    ll res = 0;
    for (auto x : a) {
        auto t = prod / x.second;
        res += x.first * t % prod * inv(t, x.second) % prod;
        if (res >= prod) res -= prod;
    }
    return res;
}

```

## 6.5 Matrix [bec759]

```

template<class T>
struct Matrix {
    int n, m;
    vector<vector<T>> mat;
    constexpr Matrix(int n_, int m_) { init(n_, m_); }
    constexpr Matrix(vector<vector<T>> mat_) { init(mat_); }
    constexpr void init(int n_, int m_) {
        n = n_; m = m_;
        mat.assign(n, vector<T>(m));
    }
    constexpr void init(vector<vector<T>> mat_) {
        n = mat_.size();
        m = mat_[0].size();
        mat = mat_;
    }
    constexpr Matrix &operator*=(const Matrix &rhs) & {
        assert(mat[0].size() == rhs.mat.size());
        int n = mat.size(), k = mat[0].size(), m = rhs.mat[0].size();
        Matrix res(n, m);
        for (int i = 0; i < n; i++) {
            for (int j = 0; j < m; j++) {
                for (int l = 0; l < k; l++) {
                    res.mat[i][j] += mat[i][l] * rhs.mat[l][j];
                }
            }
        }
        mat = res.mat;
        return *this;
    }
    friend constexpr
    Matrix operator*(Matrix lhs, const Matrix &rhs) {
        return lhs * rhs;
    }
};
template<class T>
constexpr Matrix<T> unit(int n) {
    Matrix<T> res(n, n);
    for (int i = 0; i < n; i++) {
        res.mat[i][i] = 1;
    }
    return res;
}
template<class T>
constexpr Matrix<T> power(Matrix<T> a, ll b) {
    assert(a.n == a.m);
    Matrix<T> res = unit<T>(a.n);
    for (; b; b /= 2, a *= a) {
        if (b % 2) res *= a;
    }
    return res;
}

```

## 6.6 Integer Partition [595ed2]

```

// CSES_Sum_of_Divisors
const int mod = 1e9 + 7;
const int inv_2 = 500000004;
// n / 1 * 1 + n / 2 * 2 + n / 3 * 3 + ... + n / n * n
int main() {
    ll ans = 0;
    ll n; cin >> n;
    for (ll l = 1, r; l <= n; l = r + 1) {
        r = n / (n / l);
        ll val = n / l; // n / l 到 n / r 一樣的值
        ll sum = (((l + r) % mod) *
            ((r - l + 1) % mod)) % mod * inv_2; // l 加到 r
        val %= mod; sum %= mod;
        ans += val * sum;
        ans %= mod;
    }
    cout << ans << "\n";
}

```

## 6.7 Mobius Theorem

- 數論分塊可以快速計算一些含有除法向下取整的和式，就是像  $\sum_{i=1}^n f(i)g\left(\left\lfloor \frac{n}{i} \right\rfloor\right)$  的和式。當可以在  $O(1)$  內計算  $f(r) - f(l)$  或已經預處理出  $f$  的前綴和時，數論分塊就可以在  $O(\sqrt{n})$  的時間內計算上述和式的值。

• 迪利克雷捲積  $h(x) = \sum_{d|x} f(d)g(\frac{x}{d})$

• 積性函數

– 莫比烏斯函數

1. 定義

$$\sum_{d|n} \mu(d) = \begin{cases} 1 & \text{for } n=1 \\ 0 & \text{for } n \neq 1 \end{cases}$$

2.  $\mu$  是常數函數 1 的反元素

$\Rightarrow \mu * 1 = \epsilon$ ,  $\epsilon(n)$  只在  $n=1$  時為 1, 其餘情況皆為 0。

–  $\phi$  歐拉函數:  $x$  以下與  $x$  互質的數量

$$\begin{aligned} \phi * 1 &= \sum_{d|n} \phi\left(\frac{n}{d}\right) \text{ 質因數分解} \\ &= \sum_{i=1}^c \phi(p^i) \\ &= 1 + p^0(p-1) + p^1(p-1) + \dots + p^{c-1}(p-1) \\ &= p^c \\ &= id \end{aligned}$$

• 莫比烏斯反演公式

–  $f(n) = \sum_{d|n} g(d) \Leftrightarrow g(n) = \sum_{d|n} \mu(d)f(\frac{n}{d})$

–  $f(n) = \sum_{n|d} g(d) \Leftrightarrow g(n) = \sum_{n|d} \mu(\frac{d}{n})f(d)$


• 例子

$$\begin{aligned} &\sum_{i=1}^b \sum_{j=1}^d [gcd(i, j) = k] \\ &\Rightarrow \sum_{i=1}^{\lfloor \frac{b}{k} \rfloor} \sum_{j=1}^{\lfloor \frac{d}{k} \rfloor} [gcd(i, j) = 1] \\ &= \sum_{i=1}^{\lfloor \frac{b}{k} \rfloor} \sum_{j=1}^{\lfloor \frac{d}{k} \rfloor} \epsilon(gcd(i, j)) \\ &= \sum_{i=1}^{\lfloor \frac{b}{k} \rfloor} \sum_{j=1}^{\lfloor \frac{d}{k} \rfloor} \sum_{d|gcd(i, j)} \mu(d) \\ &= \sum_{d=1}^{\infty} \mu(d) \sum_{i=1}^{\lfloor \frac{b}{kd} \rfloor} [d|i] \sum_{j=1}^{\lfloor \frac{d}{kd} \rfloor} [d|j] \text{ } d \text{ 可整除 } i \text{ 時為 } 1 \\ &= \sum_{d=1}^{\min(\lfloor \frac{b}{k} \rfloor, \lfloor \frac{d}{k} \rfloor)} \mu(d) \lfloor \frac{x}{kd} \rfloor \lfloor \frac{y}{kd} \rfloor \end{aligned}$$

## 6.8 Mobius Inverse [d41d8c]

```
const int maxn = 2e5;
ll mobius_pref[maxn];
void init() {
    mobius_pref[1] = 1;
    vector<ll> wei
        (maxn); // wei = 0 代表是質數, -1 代表可被平方數整除
    for (ll i = 2; i < maxn; i++) {
        if (wei[i] == -1) {
            mobius_pref[i] = mobius_pref[i - 1];
            continue; // 包含平方
        }
        if (wei[i] == 0) {
            wei[i] = 1;
            for (ll j = 2; i * j < maxn; j++) {
                if (j % i == 0) wei[i * j] = -1;
                else if (wei[i * j] != -1) wei[i * j]++;
            }
        }
        mobius_pref[i]
            = mobius_pref[i - 1] + (wei[i] % 2 == 0 ? 1 : -1);
    }
}
void solve() {
    ll a, b, c, d, k; cin >> a >> b >> c >> d >> k;
    auto cal = [&](ll x, ll y) -> int {
        int res = 0;
        for (int l = 1, r; l <= min(x, y); l = r + 1) {
            r = min(x / (x / l), y / (y / l));
            res += (mobius_pref[r] - mobius_pref[l
                - 1]) * (x / l) * (y / l); // 代推出來的式子
        }
        return res;
    };
    cout << cal
        (b / k, d / k) - cal((a - 1) / k, d / k) - cal(b / k,
            (c - 1) / k) + cal((a - 1) / k, (c - 1) / k) << "\n";
}
```

## 6.9 Catalan Theorem



1.  $n$  個往上  $n$  個往下, 先枚舉所有情況  $\frac{(2n)!}{n!n!} = C_n^{2n}$
  2. 扣掉非法的, 有多少種可能讓最後的點落在  $(2n, -2)$
- 假設往上有  $x$  個, 往下有  $y$  個, 會有:

$$\begin{cases} x+y=2n \\ y-x=2 \end{cases} \Rightarrow \begin{cases} x=n-1 \\ y=n+1 \end{cases}$$

所以只要扣掉  $C_{n-1}^{2n}$  即可

## 6.10 Burnside's Lemma

$$|X/G| = \frac{1}{|G|} \sum_{g \in G} |X^g|$$

- $G$ : 各種翻轉操作所構成的置換群
- $X/G$ : 本質不同的方案的集合
- $X^g$ : 對於某一種操作  $g$ , 所有方案中, 經過  $g$  這種翻轉後保持不變的方案
- 集合取絕對值代表集合數

## 7 Search and Greedy

### 7.1 Binary Search [d41d8c]

```
int main() {
    // 二分找上界
    while (lo < hi) {
        int x = (lo + hi + 1) / 2;
        if (check(x)) lo = x;
        else hi = x - 1;
    }
    cout << lo; // 保證有解

    while (lo <= hi) {
        int x = (lo + hi) / 2;
        if (check(x)) lo = x + 1;
        else hi = x - 1;
    }
    cout << hi; // 範圍外代表無解

    // 二分找下界
    while (lo < hi) {
        int x = (lo + hi) / 2;
        if (check(m)) hi = x;
        else lo = x + 1;
    }
    cout << lo; // 保證有解

    while (lo <= hi) {
        int x = (lo + hi) / 2;
        if (check(m)) hi = x - 1;
        else lo = x + 1;
    }
    cout << lo; // 範圍外代表無解
}
```

### 7.2 Ternary Search [d41d8c]

```
int main() {
    int lo = 0, hi = 10;
    while (lo <= hi) {
        int xl = lo + (hi - lo) / 3;
        int xr = hi - (hi - lo) / 3;
        int ans1 = check(xl), ans2 = check(xr);
        if (ans1 < ans2) {
            lo = xl + 1;
        } else {
            hi = xr - 1;
        }
        // record ans and index
    }
}
```

## 8 Tree

### 8.1 LCA [f45014]

```
vector<vector<int>> par;
vector<int> dep;
void build(int n, vector<vector<int>> &tree, int u = 0) {
    par.assign(n, vector<int>(B + 1, -1));
    dep.assign(n, 0);
    auto dfs = [&](auto self, int x, int p) -> void {
        par[x][0] = p;
        for (int i = 1; i <= B; i++) {
            par[x][i] = par[par[x][i-1]][i-1];
        }
        for (int v : tree[x]) {
            if (v != p) {
                dep[v] = dep[x] + 1;
                self(self, v, x);
            }
        }
    };
    dfs(dfs, 0, -1);
}
```

```

    for (auto y : tree[x]) {
        if (y == p) continue;
        par[y][0] = x; // 2^0
        dep[y] = dep[x] + 1;
        self(self, y, x);
    }
};
par[u][0] = u; dfs(dfs, 0, -1);
for (int i = 1; i <= B; i++) {
    for (int j = 0; j < n; j++) {
        par[j][i] = par[par[j][i-1]][i-1];
    }
}
int lca(int a, int b) {
    if (dep[a] < dep[b]) swap(a, b);
    int pull = dep[a] - dep[b];
    for (int i = 0; i <= B; i++) {
        if (pull & (1 << i)) {
            a = par[a][i];
        }
    }
    if (a == b) return a;
    for (int i = B; i >= 0; i--) {
        if (par[a][i] != par[b][i]) {
            a = par[a][i]; b = par[b][i];
        }
    }
    return par[a][0];
}
int jump(int x, int k) {
    for (int i = B; i >= 0; i--) {
        if (k >> i & 1) {
            x = par[x][i];
        }
    }
    return x;
}

```

## 8.2 Centroid Decomposition [ec760b]

```

#include <bits/stdc++.h>
using namespace std;
struct CenDecom {
    int n;
    vector<vector<int>> adj;
    vector<bool> vis;
    vector<int> siz;
    CenDecom(int n_) { init(n_); }
    void init(int n_) {
        n = n_;
        adj.assign(n, {});
        vis.assign(n, false);
        siz.assign(n, 1);
    }
    void addEdge(int u, int v) {
        adj[u].push_back(v);
        adj[v].push_back(u);
    }
    void get_siz(int x, int p = -1) {
        siz[x] = 1;
        for (int y : adj[x]) {
            if (y == p || vis[y]) continue;
            get_siz(y, x);
            siz[x] += siz[y];
        }
    }
    int get_cen(int x, int sz, int p = -1) {
        for (int y : adj[x]) {
            if (y == p || vis[y]) continue;
            if (siz[y] * 2 > sz) {
                return get_cen(y, sz, x);
            }
        }
        return x;
    }
    void get_ans(int x, int p) {
        // do something
        for (int y : adj[x]) {
            if (y == p || vis[y]) continue;
            get_ans(y, x);
        }
    }
    void work(int x = 0) {
        get_siz(0, x);
        int cen = get_cen(x, siz[x]);
        vis[cen] = true;
        for (int y : adj[cen]) {
            if (vis[y]) continue;
            get_ans(y, cen);
        }
        for (int y : adj[cen]) {
            if (vis[y]) continue;
            work(y);
        }
    }
};

```

## 8.3 Tree Flattening [5293b7]

// 父節  
點加值 = 所有子節點區間加值，求單點，使用 bit，做前綴差分

```

// CSES 1138_Path Queries
int main() {
    int n, q; cin >> n >> q;
    vector<int> val(n + 1), dfnToVal(n);
    for (int i = 1; i <= n; i++) {
        cin >> val[i];
    }
    vector<vector<int>> tree(n + 1);
    for (int i = 1; i < n; i++) {
        int u, v; cin >> u >> v;
        tree[u].push_back(v);
        tree[v].push_back(u);
    }
    vector<pair<int, int>> mp(n + 1); // dfn 區間
    int cnt = 0;
    auto dfs = [&](auto self, int u, int par) -> void {
        dfnToVal[++cnt] = val[u];
        mp[u].first = cnt;
        for (auto v : tree[u]) {
            if (v == par) continue;
            self(self, v, u);
        }
        mp[u].second = cnt;
    };
    dfs(dfs, 1, 0);
    BIT bit(n);
    for (int i = 1; i <= n; i++) {
        bit.modify(mp[i].first, val[i]);
        if (mp[i].first < n) { // root 就不用扣了
            bit.modify(mp[i].second + 1, -val[i]);
        }
    }
    for (int i = 0; i < q; i++) {
        int op; cin >> op;
        if (op == 1) {
            int s, x; cin >> s >> x;
            int add = x - dfnToVal[mp[s].first];
            dfnToVal[mp[s].first] = x;
            bit.modify(mp[s].first, add);
            if (mp[s].first < n) { // root 就不用扣了
                bit.modify(mp[s].second + 1, -add);
            }
        }
        else {
            int node; cin >> node;
            cout << bit.query(mp[node].first) << "\n";
        }
    }
}

```

## 8.4 Heavy Light Decomposition [41d99e]

```

struct HLD {
    int n, cur;
    vector<int> siz, top, dep, parent, in, out, seq;
    vector<vector<int>> adj;
    HLD(int n_) { init(n_); }
    void init(int n_) {
        n = n_; cur = 0;
        siz.resize(n); top.resize(n); dep.resize(n);
        parent.resize(n); in.resize(n); out.resize(n);
        seq.resize(n); adj.assign(n, {});
    }
    void addEdge(int u, int v) {
        adj[u].push_back(v);
        adj[v].push_back(u);
    }
    void work(int rt = 0) {
        top[rt] = rt;
        dep[rt] = 0;
        parent[rt] = -1;
        dfs1(rt); dfs2(rt);
    }
    void dfs1(int u) {
        if (parent[u] != -1)
            adj[u].erase(find(
                adj[u].begin(), adj[u].end(), parent[u]));
        siz[u] = 1;
        for (auto &v : adj[u]) {
            parent[v] = u, dep[v] = dep[u] + 1;
            dfs1(v);
            siz[u] += siz[v];
            if (siz[v] > siz[adj[u][0]]) {
                swap(v, adj[u][0]);
            } // 讓 adj[u][0] 是重子節點
        }
    }
    void dfs2(int u) {
        in[u] = cur++;
        seq[in[u]] = u; // dfn 對應的編號
        for (auto v : adj[u]) {
            top[v] = v == adj[u][0] ? top[u] : v;
            dfs2(v);
        }
        out[u] = cur;
    }
    int lca(int u, int v) {
        while (top[u] != top[v]) {
            if (dep[top[u]] > dep[top[v]]) {
                u = parent[top[u]];
            } else {

```



```

        v = parent[top[v]];
    }
    return dep[u] < dep[v] ? u : v;
}
int dist(int u, int v) {
    return dep[u] + dep[v] - 2 * dep[lca(u, v)];
}
int jump(int u, int k) {
    if (dep[u] < k) return -1;
    int d = dep[u] - k;
    while (dep[top[u]] > d)
        u = parent[top[u]];
    return seq[in[u] - dep[u] + d];
}
bool isAncestor(int u, int v) {
    return in[u] <= in[v] && in[v] < out[u];
}
int rootedParent(int rt, int v) {
    swap(rt, v);
    if (rt == v) return rt;
    if (!isAncestor(rt, v)) return parent[rt];
    auto it = upper_bound(adj[rt].begin(), adj[rt].end(), v, [&](int x, int y) {
        return in[x] < in[y];
    }) - 1;
    return *it;
}
int rootedSize(int rt, int v) {
    if (rt == v) return n;
    if (!isAncestor(v, rt)) return siz[v];
    return n - siz[rootedParent(rt, v)];
}
int rootedLca(int rt, int a, int b) {
    return lca(rt, a) ^ lca(a, b) ^ lca(b, rt);
}
};

```

## 8.5 Link Cut Tree [d69ee0]

```

template<class Info, class Tag>
struct Node {
    Node *ch[2], *p;
    bool rev = false; int size = 1;
    Info info = Info(); Tag tag = Tag();
    Node() : ch(nullptr, nullptr), p(nullptr) {}
    bool isrt() {
        return !p || (p->ch[0] != this && p->ch[1] != this);
    }
    void make_rev() {
        swap(ch[0], ch[1]);
        rev ^= true;
    }
    void apply(const Tag &v) {
        info.apply(size, v);
        tag.apply(v);
    }
    void push() {
        if (rev) {
            if (ch[0]) ch[0]->make_rev();
            if (ch[1]) ch[1]->make_rev();
            rev = false;
        }
        if (ch[0]) ch[0]->apply(tag);
        if (ch[1]) ch[1]->apply(tag);
        tag = Tag();
    }
    void pull() {
        size = 1 + (ch[0]
            ? ch[0]->size : 0) + (ch[1] ? ch[1]->size : 0);
        info.pull(ch[0] ? ch
            [0]->info : Info(), ch[1] ? ch[1]->info : Info());
    }
    int pos() {
        return p->ch[1] == this;
    }
    void pushAll() {
        if (!isrt()) {
            p->pushAll();
        }
        push();
    }
    void rotate() {
        Node *q = p;
        int x = !pos();
        q->ch[!x] = ch[x];
        if (ch[x]) ch[x]->p = q;
        p = q->p;
        if (!q->isrt()) q->p->ch[q->pos()] = this;
        ch[x] = q;
        q->p = this;
        q->pull();
    }
    void splay() {
        pushAll();
        while (!isrt()) {
            if (!p->isrt()) {
                if (pos() == p->pos()) {
                    p->rotate();
                } else {
                    rotate();
                }
            }
        }
    }
};

```

```

    }
    rotate();
}
pull();
}
void access() { // access 後自動 splay
    for (Node
        *i = this, *q = nullptr; i; q = i, i = i->p) {
        i->splay();
        i->ch[1] = q;
        i->pull();
    }
    splay();
}
void makeRoot() {
    access();
    make_rev();
}
Node* findRoot() {
    access();
    Node *t = this;
    while (t->ch[0]) {
        t->push();
        t = t->ch[0];
    }
    t->access();
    return t;
}
};
template<class Info, class Tag>
bool connected(Node<Info, Tag> *x, Node<Info, Tag> *y) {
    return x->findRoot() == y->findRoot();
}
template<class Info, class Tag>
bool neighbor(Node<Info, Tag> *x, Node<Info, Tag> *y) {
    x->makeRoot();
    y->access();
    if (y->ch[0] != x || x->ch[1]) return false;
    return true;
}
template<class Info, class Tag>
void split(Node<Info, Tag> *rt, Node<Info, Tag> *y) {
    y->makeRoot();
    rt->access();
}
template<class Info, class Tag>
void link(Node<Info, Tag> *t, Node<Info, Tag> *p) {
    t->makeRoot();
    if (p->findRoot() != t) {
        t->p = p;
    }
}
template<class Info, class Tag>
bool cut(Node<Info, Tag> *x, Node<Info, Tag> *y) {
    x->makeRoot();
    y->access();
    if (y->ch[0] != x || x->ch[1]) return false;
    y->ch[0] = y->ch[0]->p = nullptr;
    x->pull();
    y->pull();
    return true;
}
template<class Info, class Tag>
void modify(Node<Info, Tag> *x, const Info &v) {
    x->access();
    x->info = v;
}
template<class Info, class Tag>
void path_apply
    (Node<Info, Tag> *x, Node<Info, Tag> *y, const Tag &v) {
    assert(connected(x, y));
    split(x, y);
    x->apply(v);
}
template<class Info, class Tag>
Info path_query(Node<Info, Tag> *x, Node<Info, Tag> *y) {
    assert(connected(x, y));
    split(x, y);
    return x->info;
}
}
constexpr int Mod = 51061;
struct Tag {
    ll add = 0; ll mul = 1;
    void apply(const Tag &v) {
        mul = mul * v.mul % Mod;
        add = (add * v.mul % Mod + v.add) % Mod;
    }
};
struct Info {
    ll val = 0; ll sum = 0;
    void apply(int size, const Tag &v) {
        val = (val * v.mul % Mod + v.add) % Mod;
        sum = (sum * v.mul % Mod + v.add * size % Mod) % Mod;
    }
    void pull(const Info &l, const Info &r) {
        sum = (l.sum + r.sum + val) % Mod;
    }
};
using lct = Node<Info, Tag>;

```

## 8.6 Virtual Tree [622e69]

```
// 當存在關鍵點且除了關鍵點的根關鍵點的 LCA 都沒用處
// 可以建立虛樹達成快速樹 DP
// 例如這題是有權樹，跟 vertex 1 隔開的最小成本
int top = -1; vector<int> stk(maxn);
void insert(int u, vector<vector<int>> &vt) {
    if (top == -1) return stk[++top] = u, void();
    int l = lca(stk[top], u);
    if (l == stk[top]) return stk[++top] = u, void();
    while (dfn[l] < dfn[stk[top - 1]])
        vt[stk[top - 1]].push_back(stk[top]), top--;
    if (stk[top - 1] != l) {
        vt[l].push_back(stk[top]);
        stk[top] = l;
    } else vt[l].push_back(stk[top--]);
    stk[++top] = u;
}
void reset(int u, vector<vector<int>> &vt) {
    for (int i : vt[u]) reset(i, vt);
    vt[u].clear();
}
void solve(int n, int q) {
    vector g(n + 1, vector<pair<int, int>>());
    vector vt(n + 1, vector<int>());
    vector<ll> dp(n + 1), iskey(n + 1);
    for (int i = 0; i < n - 1; i++) {
        int u, v, w; cin >> u >> v >> w;
        g[u].push_back({v, w});
        g[v].push_back({u, w});
    }
    build_lca(n, g);
    build(n, g);
    for (int i = 0; i < q; i++) {
        int m; top = -1; cin >> m;
        vector<int> key(m);
        for (int j = 0; j < m; j++) {
            cin >> key[j];
            iskey[key[j]] = 1;
        }
        key.push_back(1); // 看題目，需要才放
        sort(all(key), [&](int a, int b) {
            return dfn[a] < dfn[b];
        });
        for (int x : key) insert(x, vt);
        while (top > 0) vt[stk[top - 1]].push_back(stk[top]), --top;
        // DP
        auto dfs = [&](auto self, int u) -> void {
            for (auto v : vt[u]) {
                self(self, v);
                if (iskey[v]) {
                    dp[u] += min_dis[v];
                    // 砍掉 1 到 v 之間最短的路
                } else {
                    dp[u] += min(dp[v], min_dis[v]);
                }
                iskey[v] = dp[v] = 0;
            }
            vt[u].clear();
        };
        dfs(dfs, key[0]); // key[0] 一定是 root
        cout << dp[key[0]] << "\n";
        iskey[key[0]] = dp[key[0]] = 0;
    }
}
```

## 8.7 Dominator Tree [baa540]

```
struct Dominator_tree {
    int n, id;
    vector<vector<int>> adj, radj, bucket;
    vector<int> sdom, dom, vis, rev, pa, rt, mn, res;
    Dominator_tree(int n = 0) { init(n); }
    void init(int _n) {
        n = _n, id = 0;
        adj.assign(n, vector<int>());
        radj.assign(n, vector<int>());
        bucket.assign(n, vector<int>());
        sdom.resize(n); dom.assign(n, -1);
        vis.assign(n, -1); rev.resize(n);
        pa.resize(n); rt.resize(n);
        mn.resize(n); res.resize(n);
    }
    void add_edge(int u, int v) { adj[u].push_back(v); }
    int query(int v, int x) {
        if (rt[v] == v) return x ? -1 : v;
        int p = query(rt[v], 1);
        if (p == -1) return x ? rt[v] : mn[v];
        if (sdom[mn[v]] > sdom[mn[rt[v]]]) mn[v] = mn[rt[v]];
        rt[v] = p;
        return x ? p : mn[v];
    }
    void dfs(int v) {
        vis[v] = id, rev[id] = v;
        rt[id] = mn[id] = sdom[id] = id, id++;
        for (int u : adj[v]) {
            if (vis[u] == -1) dfs(u, pa[vis[u]] = vis[v];
            radj[vis[u]].push_back(vis[v]);
        }
    }
    void build(int s) {
```

```
dfs(s);
for (int i = id - 1; i >= 0; i--) {
    for (int u : radj[i])
        sdom[i] = min(sdom[i], sdom[query(u, 0)]);
    if (i) bucket[sdom[i]].push_back(i);
    for (int u : bucket[i]) {
        int p = query(u, 0);
        dom[u] = sdom[p] == i ? i : p;
    }
    if (i) rt[i] = pa[i];
}
res.assign(n, -1);
for (int i = 1; i < id; i++)
    if (dom[i] != sdom[i]) dom[i] = dom[dom[i]];
for (int i = 1; i < id; i++) res[rev[i]] = rev[dom[i]];
res[s] = s;
for (int i = 0; i < n; i++) dom[i] = res[i];
};
```

## 9 DP

### 9.1 LCS [5781cf]

```
int main() {
    int m, n; cin >> m >> n;
    string s1, s2; cin >> s1 >> s2;
    int L = 0;
    vector<vector<int>> dp(m + 1, vector<int>(n + 1, 0));
    for (int i = 1; i <= m; i++) {
        for (int j = 1; j <= n; j++) {
            if (s1[i - 1] == s2[j - 1])
                dp[i][j] = dp[i - 1][j - 1] + 1;
            else
                dp[i][j] = max(dp[i - 1][j], dp[i][j - 1]);
        }
    }
    int length = dp[m][n]; cout << length << "\n";
    string s(length, 'c'); // backtracking
    while (m >= 1 && n >= 1) {
        if (s1[m - 1] == s2[n - 1]) {
            s[length - 1] = s1[m - 1];
            m--, n--, length--;
        } else {
            if (dp[m - 1][n] > dp[m][n - 1]) m--;
            else n--;
        }
    }
    cout << s << "\n";
}
```

### 9.2 LIS [66d09f]

```
int main() {
    int n; cin >> n;
    vector<int> v(n);
    for (int i = 0; i < n; i++) cin >> v[i];
    int dp[n]; vector<int> stk;
    stk.push_back(v[0]);
    dp[0] = 1; int L = 1;
    for (int i = 1; i < n; i++) {
        if (v[i] > stk.back()) {
            stk.push_back(v[i]);
            dp[i] = ++L;
        } else {
            auto it
                = lower_bound(stk.begin(), stk.end(), v[i]);
            *it = v[i]; dp[i] = it - stk.begin() + 1;
        }
    }
    vector<int> ans; cout << L << "\n";
    for (int i = n - 1; i >= 0; i--) {
        if (dp[i] == L) {
            ans.push_back(v[i]); L--;
        }
    }
    reverse(ans.begin(), ans.end());
    for (auto i : ans) cout << i << " ";
}
```

### 9.3 Edit Distance [308023]

```
int main() {
    string s1, s2; cin >> s1 >> s2;
    int n1 = s1.size(), n2 = s2.size();
    // dp[i][j] 為 s1 的前 i 個字元，跟 s2 的前 j 個字元
    vector<int> dp(n2 + 1);
    iota(dp.begin(), dp.end(), 0);
    for (int i = 1; i <= n1; i++) {
        vector<int> cur(n2 + 1); cur[0] = i;
        for (int j = 1; j <= n2; j++) {
            if (s1[i - 1] == s2[j - 1]) {
                cur[j] = dp[j - 1];
            } else {
                // s1 新增等價於 s2 砍掉
                // dp[i][j] = min(s2 新增, 修改, s1 新增);
                cur[j]
                    = min({cur[j - 1], dp[j - 1], dp[j]} + 1;
            }
        }
    }
}
```

```

        swap(dp, cur);
    }
    cout << dp[n2] << "\n";
}

```

## 9.4 Bitmask [a626f9]

```

void hamiltonianPath() {
    int n, m; cin >> n >> m;
    vector adj(n, vector<int>());
    for (int i = 0; i < m; i++) {
        int u, v; cin >> u >> v;
        adj[--v].push_back(--u);
    }

    // 以...為終點，走過...
    vector dp(n, vector<int>(findBit(n)));
    dp[0][1] = 1;
    for (int mask = 1; mask < findBit(n); mask++) {
        if ((mask & 1) == 0) continue;
        for (int i = 0; i < n; i++) {
            if ((mask & findBit(i)) == 0) continue;
            if (i == n - 1 && mask != findBit(n) - 1) continue;
            int pre_mask = mask ^ findBit(i);
            for (int j : adj[i]) {
                if ((pre_mask & findBit(j)) == 0) continue;
                dp[i][mask] = (dp[i][pre_mask] + dp[j][pre_mask]) % Mod;
            }
        }
    }
    cout << dp[n - 1][findBit(n) - 1] << "\n";
}

void elevatorRides() {
    int n, x; cin >> n >> x; vector<int> a(n);
    for (int i = 0; i < n; i++) cin >> a[i];
    vector<array<int, 2>> dp(findBit(n));
    dp[0][0] = 1; // 次數、已使用人數
    for (int mask = 1; mask < findBit(n); mask++) {
        dp[mask][0] = dp[mask][1] = 2e9;
        for (int i = 0; i < n; i++) {
            if ((mask & findBit(i)) == 0) continue;
            int pre_mask = mask ^ findBit(i);
            if (dp[pre_mask][1] + a[i] <= x) {
                if (dp[pre_mask][0] < dp[mask][0] || dp[pre_mask][0] == dp[mask][0] && dp[pre_mask][1] + a[i] < dp[mask][1]) {
                    dp[mask][0] = dp[pre_mask][0];
                    dp[mask][1] = dp[pre_mask][1] + a[i];
                }
            } else if (dp[pre_mask][0] + 1 < dp[mask][0] || dp[pre_mask][0] + 1 == dp[mask][0] && a[i] < dp[mask][1]) {
                dp[mask][0] = dp[pre_mask][0] + 1;
                dp[mask][1] = a[i];
            }
        }
    }
    cout << dp[findBit(n) - 1][0] << "\n";
}

```

## 9.5 Projects [0942aa]

```

int main() { // 排序有權重問題，輸出價值最多且時間最少
    struct E {
        int from, to, w, id;
        bool operator<(const E &rhs) {
            return to == rhs.to ? w > rhs.w : to < rhs.to;
        }
    };

    int n; cin >> n; vector<E> a(n + 1);
    for (int i = 1; i <= n; i++) {
        int u, v, w; cin >> u >> v >> w;
        a[i] = {u, v, w, i};
    }

    vector<array<ll, 2>> dp(n + 1); // w, time
    vector<array<int, 2>> rec(n + 1); // 有沒選，上個是誰
    sort(a.begin(), a.end());
    for (int i = 1; i <= n; i++) {
        auto it = --lower_bound(all(a), E{0, a[i].from});
        [(E x, E y){ return x.to < y.to; }];
        int id = it - a.begin(); dp[i] = dp[i - 1];
        ll nw = dp[id][0] + a[i].w;
        ll nt = dp[id][1] + a[i].to - a[i].from;
        if (dp[i][0] < nw || dp[i][0] == nw && dp[i][1] > nt) {
            dp[i] = {nw, nt}; rec[i] = {1, id};
        }
    }

    vector<int> ans;
    for (int i = n; i != 0; i--) {
        if (rec[i][0]) {
            ans.push_back(a[i].id);
            i = rec[i][1];
        } else i--;
    }
}

```

## 9.6 Removal Game [7bb56b]

// 兩個人比賽，每個人輪流取一個數字且只能是頭尾  
 // 問兩人都選得好，第一出手的人可取得的最大分數

```

int main() {
    int n; cin >> n;

```

```

    vector<ll> a(n);
    for (int i = 0; i < n; i++) cin >> a[i];
    vector dp(n, vector<ll>(n)); // i 到 j 區間的最大 diff
    for (int i = n - 1; i >= 0; i--) {
        dp[i][i] = a[i];
        for (int j = i + 1; j < n; j++)
            dp[i][j] = max(a[i] - dp[i + 1][j], a[j] - dp[i][j - 1]);
    }
    // x + y = sum; // x - y = dp[0][n - 1]
    cout << (accumulate
        (a.begin(), a.end(), 0LL) + dp[0][n - 1]) / 2 << "\n";
}

```

## 9.7 Monotonic Queue [f4976d]

```

// 應用: dp(i) = h(i) + max(A(j)), for l(i) ≤ j ≤ r(i)
// A(j) 可能包含 dp(j), h(i) 可 O(1)
void Bounded_Knapsack() {
    int n, k; // 0(nk)
    vector<int> w(n), v(n), num(n); deque<int> q;
    // 於是我們將同餘的數分在同一組
    // 每次取出連續 num[i] 格中最大值
    // g_x = max_{k=0}^{num[i]} (g'_{x-k} + v_i * k)
    // G_x = g'_{x} - v_i * x
    // x 代 x-k => v_i * (x-k)
    // g_x = max_{k=0}^{num[i]} (G_{x-k} + v_i * x)
    vector<vector<ll>> dp(2, vector<ll>(k + 1));
    for (int i = 0; i < n; i++) {
        for (int r = 0; r < w[i]; r++) { // 餘數
            q.clear(); // q 記錄在 x = i 時的 dp 有單調性
            for (int x = 0; x * w[i] + r <= k; x++) {
                while (!q.empty() && q.front() < x - num[i])
                    q.pop_front(); // 維護遞減
                ll nxt = dp[0][x * w[i] + r] - x * v[i];
                while (!q.empty() && dp[0][q.back()
                    () * w[i] + r] - q.back() * v[i] < nxt)
                    q.pop_back();
                q.push_back(x);
                dp[1][x * w[i] + r] = dp[0][q.front()
                    () * w[i] + r] - q.front() * v[i] + x * v[i];
            }
            swap(dp[0], dp[1]);
        }
    }
    cout << dp[0][k] << "\n";
}

```

## 9.8 SOS [93cb19]

// 使用情況：跟 bit 與(被)包含有關，且 x 在 1e6 左右  
 // 題目：一數組，問有多少所有數 & 起來為 0 的集合數  
 // dp[x] 代表包含 x 的 y 個數 (比 x 大且 bit 1 全包含 x 的有幾個)  
 // 答案應該包含在 dp[0] 內，但是有重複元素，所以考慮容斥  
 // => ans = ∑\_{i=0}^n (-1)^{pop\_count(i)} \* 2^{dp[i]-1}  
 // => 全部為 0 的個數 - 至少一個為 1 的個數 + 至少兩個為 1 的個數

```

void solve() {
    int n; cin >> n; Z ans = 0;
    vector<int> a(n);
    for (int i = 0; i < n; i++)
        cin >> a[i];
    int m = __lg(*max_element(a.begin(), a.end())) + 1;
    // 定義 dp[mask] 為 mask 被包含於 a[i] 的 a[i] 個數
    vector<Z> dp(1 << m);
    for (int i = 0; i < n; i++)
        dp[a[i]] += 1;
    for (int i = 0; i < m; i++)
        for (int mask = 0; mask < 1 << m; mask++)
            if (mask >> i & 1) {
                int pre = mask ^ (1 << i);
                dp[pre] += dp[mask];
            }
    for (int mask = 0; mask < 1 << m; mask++) {
        int sgn = __builtin_popcount(mask) & 1 ? -1 : 1;
        ans += sgn * (power(Z(2), dp[mask].val()) - 1);
    }
    cout << ans << "\n";
}

```

## 9.9 CHT [5f5c25]

// 應用: dp(i) = h(i) + min/max(A(j)X(i) + B(j)), for j ≤ r(i)  
 // A(j), B(j) 可能包含 dp(j)，分別就是 m 跟 b

```

struct Line {
    ll m, b;
    Line(ll m = 0, ll b = 0) : m(m), b(b) {}
    ll eval(ll x) {
        return m * x + b;
    }
};

struct CHT { // 用在查詢單調斜率也單調
    int n, lptr, rptr; vector<Line> hull;
    CHT(int n_ = 0, Line init_ = Line()) {
        init(n_, init_);
    }
    void init(int n_ = 0, Line init_ = Line()) {
        n = n_; hull.resize(n);
    }
}

```

```

void reset(Line init_ = Line()) {
    lptr = rptr = 0; hull[0] = init_;
}
bool pop_front(Line &l1, Line &l2, ll x) {
    // 斜率遞減、查詢遞增，因此只要左直線的 y >= 右直線的 y
    // 代表查詢的當下，右線段的高度已經低於左線段了
    return l1.eval(x) >= l2.eval(x);
}
bool pop_back(Line &l1, Line &l2, Line &l3) {
    // 本題斜率遞減、上凸包
    // 因此只要 l2 跟
    // l3 的 x 交點 <= l1 跟 l3 的 x 交點，l2 就用不到了
    return (l3.b - l2.b)
        * (l1.m - l3.m) <= (l3.b - l1.b) * (l2.m - l3.m);
}
void insert(Line L) {
    while (rptr - lptr
        > 0 && pop_back(hull[rptr - 1], hull[rptr], L))
        rptr--;
    hull[++rptr] = L;
}
ll query(ll x) {
    while (rptr - lptr
        > 0 && pop_front(hull[lptr], hull[lptr + 1], x))
        lptr++;
    return hull[lptr].eval(x);
}
};

```

## 9.10 DNC [61c639]

```

// 應用：切 k 段問題，且滿足四邊形不等式
// w(a,c) + w(b,d) <= w(a,d) + w(b,c)
// dp[k][j] = min(dp[k-1][i] + cost[i][j])
// cost: (i, j)
constexpr int N = 3e3 + 5;
constexpr ll inf = 4e18;
ll dp[N][N]; // 1-based
ll get_cost(int l, int r) {}
void DNC(int k, int l, int r, int optl, int optr) {
    if (l > r) return;
    int m = (l + r) >> 1, opt = -1;
    dp[k][m] = inf;
    for (int i = max(k, optl); i <= min(m, optr); i++) {
        // 注意 i 的範圍、get_cost 與 dp 的邊界
        ll cur = dp[k-1][i] + get_cost(i, m);
        if (cur < dp[k][m]) {
            dp[k][m] = cur, opt = i;
        }
    }
    DNC(k, l, m-1, optl, opt);
    DNC(k, m+1, r, opt, optr);
}
int main() {
    // first build cost...
    for (int i = 1; i <= n; i++) {
        // init dp[i][i]
    }
    for (int i = 2; i <= k; i++) {
        DNC(i, 1, n, 1, n);
    }
    cout << dp[k][n] << "\n";
}

```

## 9.11 LiChao Segment Tree [f23ef4]

```

// 應用：dp(i) = h(i) + min/max(A(j)X(i) + B(j)), for j ≤ r(i)
// y = c + m * x + b
constexpr ll inf = 4e18;
struct Line {
    ll m, b;
    Line(ll m = 0, ll b = inf) : m(m), b(b) {}
    ll eval(ll x) const { return m * x + b; }
};
struct LiChaoSeg { // 取 max 再變換就好
    int n;
    vector<Line> info;
    LiChaoSeg(int n_ = 0) { init(n_); }
    void init(int n_) {
        n = n_;
        info.assign(4 << __lg(n), Line());
    }
    void update(Line line, int node, int l, int r) {
        int m = (l + r) / 2;
        bool left = line.eval(l) < info[node].eval(l);
        bool mid = line.eval(m) < info[node].eval(m);
        if (mid) swap(info[node], line); // 如果新線段比較好
        if (r - l == 1) return;
        else if (left != mid) update(line, 2 * node, l, m);
        // 代表左半有交點
        else update(line, 2 * node + 1, m, r);
        // 代表如果有交點一定在右半
    }
    void add_line(Line line) { update(line, 1, 0, n); }
    ll query(int x, int node, int l, int r) {
        if (r - l == 1) return info[node].eval(x);
        int m = (l + r) / 2;
        if (x < m) return
            min(info[node].eval(x), query(x, 2 * node, l, m));
    }
};

```

```

    else return min(
        info[node].eval(x), query(x, 2 * node + 1, m, r));
}
ll query(int x) { return query(x, 1, 0, n); }
};

```

## 9.12 Codeforces Example [7d37ea]

```

// CF 1932 pF
// 給你很多區間，你可以選一些點，重疊到的線段得到 1 分
// 請問在線段不重複的情況下，最多獲得幾分
int main() {
    int n, m;
    cin >> n >> m;
    // 記錄每點有幾個線段
    // 再一個紀錄，包含這個點的左界
    vector<int> l_side(n + 1, inf), cnt(n + 5, 0);
    for (int i = 0; i < m; i++) {
        int l, r; cin >> l >> r;
        l_side[r] = min(l_side[r], l);
        cnt[l]++;
        cnt[r + 1]--;
    }
    for (int i = 2; i <= n; i++) {
        cnt[i] += cnt[i - 1];
    }
    for (int i = n; i >= 2; i--) {
        l_side[i - 1] = min(l_side[i - 1], l_side[i]);
    }
    vector<int> dp(n + 1);
    dp[0] = 0;
    for (int i = 1; i <= n; i++) {
        dp[i] = cnt[i];
        if (l_side[i] != inf) {
            dp[i] += dp[l_side[i] - 1];
        }
        dp[i] = max(dp[i], dp[i - 1]);
    }
    cout << dp[n] << "\n";
}

// CF 1935 pC
// 給你每個事件的 a, b，挑事件會把 a 全部加起來
// 再加上 max(bi) - min(bi)
int main() {
    int n, k, ans = 0; cin >> n >> k;
    vector<pii> v(n + 1);
    for (int i = 1; i <= n; i++) {
        int a, b; cin >> a >> b;
        v[i] = {a, b};
        if (a <= k) ans = 1;
    }
    sort(v.begin() + 1, v.end(), [](pii &a, pii &b) {
        return a.second < b.second;
    }); // 用 bi 來排，考慮第 i 個時可以先扣
    vector<vector<int>> dp(n + 1, vector<int>(n + 1, inf));
    // 考慮 v[i] 時，選 j 個的 sum(ai) - min(bi)
    for (int i = 1; i <= n; i++) { // 滾動 dp
        for (int j = n; j >= 2; j--) {
            dp[i][j] = min(
                (dp[i-1][j], dp[i-1][j-1] + v[i].first);
            // min(不選，選)
            if (dp[i-1][j-1] + v[i].first + v[i].second <= k) {
                // 假如可以選，更新 ans 時再加回去 bi
                ans = max(ans, j);
            }
        }
        dp[i][1] = min(dp[i-1][1], v[i].first - v[i].second);
    }
    cout << ans << endl;
}

```

# 10 Geometry

## 10.1 Basic [d41d8c]

```

template<class T>
struct Point {
    T x, y;
    Point(const T &x_ = 0, const T &y_ = 0) : x(x_), y(y_) {}
    template<class U>
    operator Point<U>() {
        return Point<U>(U(x), U(y));
    }
    Point &operator+=(const Point &p) & {
        x += p.x; y += p.y; return *this;
    }
    Point &operator-=(const Point &p) & {
        x -= p.x; y -= p.y; return *this;
    }
    Point &operator*=(const T &v) & {
        x *= v; y *= v; return *this;
    }
    Point &operator/=(const T &v) & {
        x /= v; y /= v; return *this;
    }
    Point operator-(const {
        return Point(-x, -y);
    }
};

```

```

    }
    friend Point operator+(Point a, const Point &b) {
        return a + b;
    }
    friend Point operator-(Point a, const Point &b) {
        return a - b;
    }
    friend Point operator*(Point a, const T &b) {
        return a * b;
    }
    friend Point operator/(Point a, const T &b) {
        return a / b;
    }
    friend Point operator*(const T &a, Point b) {
        return b * a;
    }
    friend bool operator==(const Point &a, const Point &b) {
        return a.x == b.x && a.y == b.y;
    }
    friend istream &operator>>(istream &is, Point &p) {
        return is >> p.x >> p.y;
    }
    friend ostream &operator<<(ostream &os, const Point &p) {
        return os << "(" << p.x << ", " << p.y << ")";
    }
};

template<class T>
struct Line {
    Point<T> a;
    Point<T> b;
    Line(const Point<T> &a_ = Point<T>(),
          const Point<T> &b_ = Point<T>()) : a(a_), b(b_) {}
};

template<class T>
T dot(const Point<T> &a, const Point<T> &b) {
    return a.x * b.x + a.y * b.y;
}

template<class T>
T cross(const Point<T> &a, const Point<T> &b) {
    return a.x * b.y - a.y * b.x;
}

template<class T>
T square(const Point<T> &p) {
    return dot(p, p);
}

template<class T>
double length(const Point<T> &p) {
    return sqrt(double(square(p)));
}

template<class T>
double length(const Line<T> &l) {
    return length(l.a - l.b);
}

template<class T>
Point<T> normalize(const Point<T> &p) {
    return p / length(p);
}

template<class T>
bool parallel(const Line<T> &l1, const Line<T> &l2) {
    return cross(l1.b - l1.a, l2.b - l2.a) == 0;
}

template<class T>
double distance(const Point<T> &a, const Point<T> &b) {
    return length(a - b);
}

template<class T>
double distancePL(const Point<T> &p, const Line<T> &l) {
    return abs(cross(l.a - l.b, l.a - p)) / length(l);
}

template<class T>
double distancePS(const Point<T> &p, const Line<T> &l) {
    if (dot(p - l.a, l.b - l.a) < 0)
        return distance(p, l.a);
    if (dot(p - l.b, l.a - l.b) < 0)
        return distance(p, l.b);
    return distancePL(p, l);
}

template<class T>
Point<T> rotate(const Point<T> &a) {
    return Point(-a.y, a.x);
}

template<class T>
int sgn(const Point<T> &a) {
    return a.y > 0 || (a.y == 0 && a.x > 0) ? 1 : -1;
}

template<class T>
bool pointOnLineLeft(const Point<T> &p, const Line<T> &l) {
    return cross(l.b - l.a, p - l.a) > 0;
}

template<class T>
Point<T>
> lineIntersection(const Line<T> &l1, const Line<T> &l2) {
    return l1.a + (l1.b - l1.a) * (cross(l2.b - l2.a, l1.a - l2.a) / cross(l2.b - l2.a, l1.a - l1.b));
}

template<class T>
bool pointOnSegment(const Point<T> &p, const Line<T> &l) {
    return cross(p - l.a, l.b - l.a) == 0 &&
        min(l.a.x, l.b.x) <= p.x && p.x <= max(l.a.x, l.b.x)
        && min(l.a.y, l.b.y) <= p.y && p.y <= max(l.a.y, l.b.y);
}

```

```

template<class T>
bool pointInPolygon
(const Point<T> &a, const vector<Point<T>> &p) {
    int n = p.size(), t = 0;
    for (int i = 0; i < n; i++) {
        if (pointOnSegment(a, Line(p[i], p[(i + 1) % n]))) {
            return true;
        }
    }
    for (int i = 0; i < n; i++) {
        auto u = p[i];
        auto v = p[(i + 1) % n];
        if (u.x < a.x
            && v.x >= a.x && pointOnLineLeft(a, Line(v, u)))
            t ^= 1;
        if (u.x >= a.x
            && v.x < a.x && pointOnLineLeft(a, Line(u, v)))
            t ^= 1;
    }
    return t == 1;
}

// 0 : not intersect
// 1 : strictly intersect
// 2 : overlap
// 3 : intersect at endpoint
template<class T>
tuple<int, Point<T>, Point<T>> segmentIntersection
(const Line<T> &l1, const Line<T> &l2) {
    if (max(l1.a.x, l1.b.x) < min(l2.a.x, l2.b.x))
        return {0, Point<T>(), Point<T>()};
    if (min(l1.a.x, l1.b.x) > max(l2.a.x, l2.b.x))
        return {0, Point<T>(), Point<T>()};
    if (max(l1.a.y, l1.b.y) < min(l2.a.y, l2.b.y))
        return {0, Point<T>(), Point<T>()};
    if (min(l1.a.y, l1.b.y) > max(l2.a.y, l2.b.y))
        return {0, Point<T>(), Point<T>()};
    if (cross(l1.b - l1.a, l2.b - l2.a) == 0) {
        if (cross(l1.b - l1.a, l2.a - l1.a) != 0) {
            return {0, Point<T>(), Point<T>()};
        } else {
            auto maxx1 = max(l1.a.x, l1.b.x);
            auto minx1 = min(l1.a.x, l1.b.x);
            auto maxy1 = max(l1.a.y, l1.b.y);
            auto miny1 = min(l1.a.y, l1.b.y);
            auto maxx2 = max(l2.a.x, l2.b.x);
            auto minx2 = min(l2.a.x, l2.b.x);
            auto maxy2 = max(l2.a.y, l2.b.y);
            auto miny2 = min(l2.a.y, l2.b.y);
            Point<T> p1(max(minx1, maxx2), max(miny1, miny2));
            Point<T> p2(min(maxx1, maxx2), min(maxy1, maxy2));
            if (!pointOnSegment(p1, l1))
                swap(p1.y, p2.y);
            if (p1 == p2) {
                return {3, p1, p2};
            } else {
                return {2, p1, p2};
            }
        }
    }
    auto cp1 = cross(l2.a - l1.a, l2.b - l1.a);
    auto cp2 = cross(l2.a - l1.b, l2.b - l1.b);
    auto cp3 = cross(l1.a - l2.a, l1.b - l2.a);
    auto cp4 = cross(l1.a - l2.b, l1.b - l2.b);
    if ((cp1 > 0 && cp2 > 0) || (cp1 < 0 && cp2
        < 0) || (cp3 > 0 && cp4 > 0) || (cp3 < 0 && cp4 < 0))
        return {0, Point<T>(), Point<T>()};
    Point p = lineIntersection(l1, l2);
    if (cp1 != 0 && cp2 != 0 && cp3 != 0 && cp4 != 0) {
        return {1, p, p};
    } else {
        return {3, p, p};
    }
}

template<class T>
double distanceSS(const Line<T> &l1, const Line<T> &l2) {
    if (get<0>(segmentIntersection(l1, l2)) != 0)
        return 0.0;
    return min({distancePS(l1.a, l2), distancePS(l1
        .b, l2), distancePS(l2.a, l1), distancePS(l2.b, l1)});
}

template<class T>
bool segmentInPolygon
(const Line<T> &l, const vector<Point<T>> &p) {
    int n = p.size();
    if (!pointInPolygon(l.a, p)) return false;
    if (!pointInPolygon(l.b, p)) return false;
    for (int i = 0; i < n; i++) {
        auto u = p[i];
        auto v = p[(i + 1) % n];
        auto w = p[(i + 2) % n];
        auto [t, p1, p2] = segmentIntersection(l, Line(u, v));
        if (t == 1) return false;
        if (t == 0) continue;
        if (t == 2) {
            if (pointOnSegment(v, l) && v != l.a && v != l.b)
                if (cross(v - u, w - v) > 0)
                    return false;
        } else {
            if (p1 != u && p1 != v) {
                if (pointOnLineLeft(l.a, Line(v, u))
                    || pointOnLineLeft(l.b, Line(v, u)))
                    return false;
            }
        }
    }
}

```



```

    } else if (p1 == v) {
        if (l.a == v) {
            if (pointOnLineLeft(u, l)) {
                if (pointOnLineLeft(w, l)
                    && pointOnLineLeft(w, Line(u, v)))
                    return false;
            } else {
                if (pointOnLineLeft(w, l)
                    || pointOnLineLeft(w, Line(u, v)))
                    return false;
            }
        } else if (l.b == v) {
            if (pointOnLineLeft(u, Line(l.b, l.a))) {
                if (pointOnLineLeft(w, Line(l.b, l.a))
                    && pointOnLineLeft(w, Line(u, v)))
                    return false;
            } else {
                if (pointOnLineLeft(w, Line(l.b, l.a))
                    || pointOnLineLeft(w, Line(u, v)))
                    return false;
            }
        } else {
            if (pointOnLineLeft(u, l)) {
                if (pointOnLineLeft(w, Line(l.b, l.a))
                    || pointOnLineLeft(w, Line(u, v)))
                    return false;
            } else {
                if (pointOnLineLeft(w, l)
                    || pointOnLineLeft(w, Line(u, v)))
                    return false;
            }
        }
    }
}
return true;
}
template<class T>
vector<Point<T>> hp(vector<Line<T>> lines) {
    sort(lines.begin(), lines.end(), [&](auto l1, auto l2) {
        auto d1 = l1.b - l1.a;
        auto d2 = l2.b - l2.a;
        if (sgn(d1) != sgn(d2))
            return sgn(d1) == 1;
        return cross(d1, d2) > 0;
    });
    deque<Line<T>> ls;
    deque<Point<T>> ps;
    for (auto l : lines) {
        if (ls.empty()) {
            ls.push_back(l);
            continue;
        }
        while (!ps.empty() && !pointOnLineLeft(ps.back(), l))
            ps.pop_back(), ls.pop_back();
        while (!ps.empty() && !pointOnLineLeft(ps[0], l))
            ps.pop_front(), ls.pop_front();
        if (cross(l.b - l.a, ls.back().b - ls.back().a) == 0) {
            if (dot
                (l.b - l.a, ls.back().b - ls.back().a) > 0) {
                if (!pointOnLineLeft(ls.back().a, l)) {
                    assert(ls.size() == 1);
                    ls[0] = l;
                }
                continue;
            }
            return {};
        }
        ps.push_back(lineIntersection(ls.back(), l));
        ls.push_back(l);
    }
    while (!ps.empty() && !pointOnLineLeft(ps.back(), ls[0]))
        ps.pop_back(), ls.pop_back();
    if (ls.size() <= 2) return {};
    ps.push_back(lineIntersection(ls[0], ls.back()));
    return vector<Point<T>>(ps.begin(), ps.end());
}
using P = Point<ll>;

```

## 10.2 Convex Hull [f99ef6]

```

template<class T>
vector<Point<T>> convexHull(vector<Point<T>> a) {
    sort(a.begin(),
        a.end(), [](const Point<T> &l, const Point<T> &r) {
            return l.x == r.x ? l.y < r.y : l.x < r.x;
        });
    a.resize(unique(a.begin(), a.end()) - a.begin());
    if (a.size() <= 1) return a;
    vector<Point<T>> hull;
    for (int i = 0; i < 2; i++) {
        int t = hull.size();
        for (Point<T> p : a) {
            while (hull.size()
                - t >= 2 && cross(hull.back() - hull[hull.size()
                    - 2], p - hull[hull.size() - 2]) <= 0) {
                hull.pop_back();
            } // 要不要有等於要看點有沒有在邊上
            hull.push_back(p);
        }
        hull.pop_back();
    }
}

```

```

        reverse(a.begin(), a.end());
    }
    return hull;
}

```

## 10.3 Minimum Euclidean Distance [3020bc]

```

template<class T>
T distanceSquare(const Point<T> &a, const Point<T> &b) {
    return square(a - b);
}

void solve() {
    int n; cin >> n;
    constexpr ll inf = 8e18;
    vector<Point<ll>> a(n);
    for (int i = 0; i < n; i++) {
        ll x, y;
        cin >> x >> y;
        a[i] = Point<ll>(x, y);
    }
    struct sortY {
        bool operator
        ()(const Point<ll> &a, const Point<ll> &b) const {
            return a.y < b.y;
        }
    };
    struct sortXY {
        bool operator
        ()(const Point<ll> &a, const Point<ll> &b) const {
            if (a.x == b.x) return a.y < b.y;
            else return a.x < b.x;
        }
    };
    sort(a.begin(), a.end(), sortXY());
    vector<Point<ll>> t(n);
    auto devide = [&](auto &&self, int l, int r) -> ll {
        if (l == r) return inf;
        int m = (l + r) / 2;
        ll ans = min(self(self, l, m), self(self, m + 1, r));
        ll midval = a[m].x;
        ll p = 0;
        for (int i = l; i <= r; i++) {
            if ((midval - a[i].x) * (midval - a[i].x) <= ans) {
                t[p++] = a[i];
            }
        }
        sort(t.begin(), t.begin() + p, sortY());
        for (int i = 0; i < p; i++) {
            for (int j = i + 1; j < p; j++) {
                ans = min(ans, distanceSquare(t[i], t[j]));
                if ((t[i].y - t[j].y) * (t[i].y - t[j].y) > ans) break;
            }
        }
        return ans;
    };
    cout << devide(devide, 0, n - 1) << "\n";
}

```

## 10.4 Lattice Points [00db9d]

```

int main() {
    // Area 求法與 Polygon 內整數點數
    int n; cin >> n;
    vector<Point<ll>> polygon(n);
    for (int i = 0; i < n; i++) cin >> polygon[i];
    ll area = 0;
    for (int i = 0; i < n; i++) {
        area += cross(polygon[i], polygon[(i + 1) % n]);
    }
    area = abs(area);
    auto countBoundaryPoints
    = [&](const vector<Point<ll>> & polygon) -> ll {
        ll res = 0;
        int n = polygon.size();
        for (int i = 0; i < n; i++) {
            ll dx = polygon[(i + 1) % n].x - polygon[i].x;
            ll dy = polygon[(i + 1) % n].y - polygon[i].y;
            res += std::gcd(abs(dx), abs(dy));
        }
        return res;
    };
    ll res = countBoundaryPoints(polygon);
    ll ans = (area - res + 2) / 2;
    cout << ans << " " << res << "\n";
}

```

## 10.5 Minimum Cover Circle [00cc3f]

```

template<class T>
pair<T, Point<T>> MinCircular(vector<Point<T>> &a) {
    random_shuffle(a.begin(), a.end(), rng);
    int n = a.size();
    Point<T> c = a[0]; T r = 0;
    for (int i = 1; i < n; i++) {
        if (T(length(c - a[i]) - r) > 0.0) {
            c = a[i], r = 0;
            for (int j = 0; j < i; j++) {
                if (T(length(c - a[j]) - r) > 0.0) {
                    c = (a[i] + a[j]) / 2.0;
                    r = length(c - a[i]);
                    for (int k = 0; k < j; k++) {

```



```
        if (T(length(c - a[k]) - r) > 0.0) {
            Point<T> p = (a[j] + a[i]) / 2;
            Point<T> q = (a[j] + a[k]) / 2;
            c = lineIntersection(Line(p,
                p + rotate(a[j] - a[i])), Line
                (q, q + rotate(a[k] - a[j])));
            r = length(c - a[i]);
        }
    }
}
return make_pair(r, c);
}
```