

NC State University
Department of Electrical and Computer Engineering
ECE 463/563 (Prof. Rotenberg)
Project #1: Cache Design, Memory Hierarchy Design
REPORT TEMPLATE (Version 1.0)

By.

Robert Gerardi

NCSU Honor Pledge: "I have neither given nor received unauthorized aid on this project."

Student's electronic signature: **Robert Gerardi**
(sign by typing your name)

Course number: **563**


1. L1 cache exploration: SIZE and ASSOC

GRAPH #1 (total number of simulations: 55)

For this experiment:

- Benchmark trace: gcc_trace.txt
- L1 cache: SIZE is varied, ASSOC is varied, BLOCKSIZE = 32.
- L2 cache: None.
- Prefetching: None.

Plot L1 miss rate on the y-axis versus $\log_2(\text{SIZE})$ on the x-axis, for eleven different cache sizes: SIZE = 1KB, 2KB, ..., 1MB, in powers-of-two. (That is, $\log_2(\text{SIZE}) = 10, 11, \dots, 20$.) The graph should contain five separate curves (*i.e.*, lines connecting points), one for each of the following associativities: direct-mapped, 2-way set-associative, 4-way set-associative, 8-way set-associative, and fully-associative. All points for direct-mapped caches should be connected with a line, all points for 2-way set-associative caches should be connected with a line, *etc.*



Answer the following questions:

1. For a given associativity, how does increasing cache size affect miss rate?

Increasing the Cache size lowers the miss rate

2. For a given cache size, how does increasing associativity affect miss rate?

Increasing Associativity lowers miss rate


3. Estimate the *compulsory miss rate* from the graph and briefly explain how you arrived at this estimate.

compulsory miss rate = .0258 or 2.58%

How I arrived at this estimate: The values in my simulator do not go lower than that point, that where it seems to max out.

GRAPH #2 (no additional simulations with respect to GRAPH #1)

Same as GRAPH #1, but the y-axis should be AAT instead of L1 miss rate.



Answer the following question:

1. For a memory hierarchy with only an L1 cache and BLOCKSIZE = 32, which configuration yields the best (i.e., lowest) AAT and what is that AAT?


Configuration that yields the lowest AAT: **Fully Assoc, 2¹⁴ Cache Size**

Lowest AAT: **0.735**

GRAPH #3 (total number of simulations: 20)

Same as GRAPH #2, except make the following changes:

- Add the following L2 cache to the memory hierarchy: 16KB, 8-way set-associative, same block size as L1 cache.
- Vary the L1 cache size only between 1KB and 8KB (since L2 cache is 16KB).



Answer the following questions:

1. With the L2 cache added to the system, which L1 cache configuration yields the best (*i.e.*, lowest) AAT and what is that AAT?

L1 configuration that yields the lowest AAT with 16KB 8-way L2 added: **Direct Map with 2¹³ Size**

Lowest AAT: **0.7151**

2. How does the lowest AAT with L2 cache (GRAPH #3) compare with the lowest AAT without L2 cache (GRAPH #2)?

The lowest AAT with L2 cache is **.7151 ns** Less Than the lowest AAT without L2 cache.

3. Compare the *total area* required for the lowest-AAT configurations with L2 cache (GRAPH #3) versus without L2 cache (GRAPH #2).

Total area for lowest-AAT configuration with L2 cache =
0.010298466 mm² (L1 area) + **0.102584886 mm²** (L2 area) = **.112883352 mm²** (total area)

Total area for lowest-AAT configuration without L2 cache = **.063446019 mm²** (L1 area)

The total area of the lowest-AAT configuration with L2 cache is **43.7%** MORE than the total area of the lowest-AAT configuration without L2 cache.

FYI: How to calculate % difference of x with respect to y:

If $x > y$: x is $((x-y)/y * 100\%)$ more than y .
If $x < y$: x is $((y-x)/y * 100\%)$ less than y .


2. L1 cache exploration: SIZE and BLOCKSIZE

GRAPH #4 (total number of simulations: 24)

For this experiment:

- Benchmark trace: gcc_trace.txt
- L1 cache: SIZE is varied, BLOCKSIZE is varied, ASSOC = 4.
- L2 cache: None.
- Prefetching: None

Plot L1 miss rate on the y-axis versus $\log_2(\text{BLOCKSIZE})$ on the x-axis, for four different block sizes: $\text{BLOCKSIZE} = 16, 32, 64$, and 128 . (That is, $\log_2(\text{BLOCKSIZE}) = 4, 5, 6$, and 7 .) The graph should contain six separate curves (*i.e.*, lines connecting points), one for each of the following L1 cache sizes: $\text{SIZE} = 1\text{KB}, 2\text{KB}, \dots, 32\text{KB}$, in powers-of-two. All points for $\text{SIZE} = 1\text{KB}$ should be connected with a line, all points for $\text{SIZE} = 2\text{KB}$ should be connected with a line, *etc.*



Answer the following questions:

1. Do smaller caches prefer smaller or larger block sizes?

Smaller caches prefer **SMALLER** block sizes. For example, the smallest cache considered in Graph #4 (1KB) achieves its lowest miss rate with a block size of **16 B**.

2. Do larger caches prefer smaller or larger block sizes?

Larger caches prefer **LARGER** block sizes. For example, the largest cache considered in Graph #4 (32KB) achieves its lowest miss rate with a block size of **128 B**.

3. As block size is increased from 16 to 128, is the tension between *exploiting more spatial locality* and *cache pollution* evident in the graph? Explain.

Yes, the tension between *exploiting more spatial locality* and *cache pollution* is evident in the graph.

For example, consider the smallest (1KB) cache in Graph #4. Increasing block size from 16 B to 32 B is helpful (reduces miss rate) due to exploiting more spatial locality. But then increasing block size further, from 32 B to 128 B, is not helpful (increases miss rate) due to cache pollution having greater effect.


3. L1 + L2 co-exploration

GRAPH #5 (total number of simulations: 12)

For this experiment:

- Benchmark trace: gcc_trace.txt
- L1 cache: SIZE is varied, BLOCKSIZE = 32, ASSOC = 4.
- L2 cache: SIZE is varied, BLOCKSIZE = 32, ASSOC = 8.
- Prefetching: None.

Plot AAT on the y-axis versus $\log_2(\text{L1 SIZE})$ on the x-axis, for four different L1 cache sizes: L1 SIZE = 1KB, 2KB, 4KB, 8KB. (That is, $\log_2(\text{L1 SIZE}) = 10, 11, 12, 13$.) The graph should contain three separate curves (*i.e.*, lines connecting points), one for each of the following L2 cache sizes: 16KB, 32KB, 64KB. All points for the 16KB L2 cache should be connected with a line, all points for the 32KB L2 cache should be connected with a line, *etc.*



Answer the following question:

1. Which memory hierarchy configuration in Graph #5 yields the best (*i.e.*, lowest) AAT and what is that AAT?

Configuration that yields the lowest AAT: 16k L2 Size, 8k L1 Size,
Lowest AAT: .4115

4. Stream buffers study (ECE 563 students only)

TABLE #1 (total number of simulations: 5)

For this experiment:

- Microbenchmark: stream_trace.txt
- L1 cache: SIZE = 1KB, ASSOC = 1, BLOCKSIZE = 16.
- L2 cache: None.
- PREF_N (number of stream buffers): 0 (pref. disabled), 1, 2, 3, 4
- PREF_M (number of blocks in each stream buffer): 4

The trace “stream_trace.txt” was generated from the loads and stores in the loop of interest of the following microbenchmark:

```
#define SIZE 1000

uint32_t a[SIZE];
uint32_t b[SIZE];
uint32_t c[SIZE];

int main(int argc, char *argv[]) {
...
    // LOOP OF INTEREST
    for (int i = 0; i < SIZE; i++)
        c[i] = a[i] + b[i];    // per iteration: 2 loads (a[i], b[i]) and 1 store (c[i] = ...)
...
}
```

Fill in the following table and answer the following questions:

PREF_N, PREF_M	L1 miss rate
0,0 (pref. disabled)	0.2500
1,4	0.2500
2,4	0.2500
3,4	0.0010
4,4	0.0010

1. For this streaming microbenchmark, with prefetching disabled, do L1 cache size and/or associativity affect the L1 miss rate (feel free to simulate L1 configurations besides the one used for the table)? Why or why not?

With prefetching disabled, L1 cache size and/or associativity **DO NOT** affect L1 miss rate (for this streaming microbenchmark).

The reason: **They must all hit in the same set if the size or assoc does not affect the outcome.**

2. For this streaming microbenchmark, what is the L1 miss rate with prefetching disabled? Why is it that value, *i.e.*, what is causing it to be that value? Hint: each element of arrays a, b, and c, is 4 bytes (uint32_t).

The L1 miss rate with prefetching disabled is .25, because every 4 cycles, it misses and has to grab the next block, so it misses once and hits the next 3 bytes, $\frac{1}{4} = .25$ miss rate.

3. For this streaming microbenchmark, with prefetching disabled, what would the L1 miss rate be if you doubled the block size from 16B to 32B? (hypothesize what it will be and then check your hypothesis with a simulation)

The L1 miss rate with prefetching disabled and a block size of 32B is .125, because instead of missing $\frac{1}{4}$ times, it now misses $\frac{1}{8}$ times, so it cuts the miss rate in half.

4. With prefetching enabled, what is the minimum number of stream buffers required to have any effect on L1 miss rate? What is the effect on L1 miss rate when this many stream buffers are used: specifically, is it a modest effect or huge effect? Why are this many stream buffers required? Why is using fewer stream buffers futile? Why is using more stream buffers wasteful?

Minimum number of stream buffers needed to have any effect on L1 miss rate: 3

With this many stream buffers, the effect on L1 miss rate is huge. Specifically, the L1 miss rate is nearly 0%. We only miss on the first elements of The Loop (hence a total of 1 misses).

This many stream buffers are required because you need a buffer for a, b, and c.

Using fewer stream buffers is futile because you still have to wait on the other variables to get the values .

Using more stream buffers is wasteful because you only have 3 variables to prefetch, adding more is not needed.