
At t = 12 s, the analytical solution is 50.6175 (Example 1.1). The numerical results are:

step	v(12) absolute relative en	
2	51.6008	1.94%
1	51.2008	1.15%
0.5	50.9259	0.61%


where the relative error is calculated with

absolute relative error =
$$\left| \frac{\text{analytical} - \text{numerical}}{\text{analytical}} \right| \times 100\%$$

The error versus step size can be plotted as



Thus, halving the step size approximately halves the error.



(a) The force balance is

$$\frac{dv}{dt} = g - \frac{c'}{m}v$$

Applying Laplace transforms,

$$sV - v(0) = \frac{g}{s} - \frac{c'}{m}V$$

Solve for

$$V = \frac{g}{s(s+c'/m)} + \frac{v(0)}{s+c'/m}$$
(1)

The first term to the right of the equal sign can be evaluated by a partial fraction expansion,

$$\frac{g}{s(s+c'/m)} = \frac{A}{s} + \frac{B}{s+c'/m}$$
(2)

$$\frac{g}{s(s+c'/m)} = \frac{A(s+c'/m) + Bs}{s(s+c'/m)}$$

Equating like terms in the numerators yields

$$A + B = 0$$

$$g = \frac{c'}{m}A$$

Therefore,

$$A = \frac{mg}{c'} \qquad B = -\frac{mg}{c'}$$

Solution continued on next page...

These results can be substituted into Eq. (2), and the result can be substituted back into Eq. (1) to give

$$V = \frac{mg/c'}{s} - \frac{mg/c'}{s+c'/m} + \frac{v(0)}{s+c'/m}$$

Applying inverse Laplace transforms yields

$$v = \frac{mg}{c'} - \frac{mg}{c'} e^{-(c'/m)t} + v(0)e^{-(c'/m)t}$$

or

$$v = v(0)e^{-(c'/m)t} + \frac{mg}{c'} \left[1 - e^{-(c'/m)t}\right]$$

where the first term to the right of the equal sign is the general solution and the second is the particular solution. For our case, v(0) = 0, so the final solution is

$$v = \frac{mg}{c'} \left[1 - e^{-(c'/m)t} \right]$$

Alternative solution: Another way to obtain solutions is to use separation of variables,

$$\int \frac{1}{g - \frac{c'}{m}v} dv = \int dt$$

The integrals can be evaluated as

$$-\frac{\ln\left(g - \frac{c'}{m}v\right)}{c'/m} = t + C$$

where C = a constant of integration, which can be evaluated by applying the initial condition

$$C = -\frac{\ln\left(g - \frac{c'}{m}v(0)\right)}{c'/m}$$

Solution continued on next page...

which can be substituted back into the solution

$$-\frac{\ln\left(g - \frac{c'}{m}v\right)}{c'/m} = t - \frac{\ln\left(g - \frac{c'}{m}v(0)\right)}{c'/m}$$

This result can be rearranged algebraically to solve for v,

$$v = v(0)e^{-(c'/m)t} + \frac{mg}{c'} \left[1 - e^{-(c'/m)t}\right]$$

where the first term to the right of the equal sign is the general solution and the second is the particular solution. For our case, v(0) = 0, so the final solution is

$$v = \frac{mg}{c'} \left[1 - e^{-(c'/m)t} \right]$$

(b) The numerical solution can be implemented as


$$v(2) = 0 + \left[9.81 - \frac{11.5}{68.1}(0)\right] 2 = 19.62$$

$$v(4) = 19.62 + \left[9.81 - \frac{11.5}{68.1} (19.62) \right] 2 = 32.6136$$


The computation can be continued and the results summarized and plotted as:

t	v	dv/dt
0	0	9.81
2	19.6200	6.4968
4	32.6136	4.3026
6	41.2187	2.8494
8	46.9176	1.8871
10	50.6917	1.2497
12	53.1911	0.8276
®	58.0923	

Solution continued on next page...



Note that the analytical solution is included on the plot for comparison.




The first two steps yield

$$y(0.5) = 0 + \left[3 \frac{450}{1250} \sin^2(0) - \frac{450}{1250} \right] 0.5 = 0 + (-0.36) \ 0.5 = -0.18$$
$$y(1) = -0.18 + \left[3 \frac{450}{1250} \sin^2(0.5) - \frac{450}{1250} \right] 0.5 = -0.18 + (-0.11176) \ 0.5 = -0.23508$$

The process can be continued to give the following table and plot:

t	у	dy/dt	t	у	dy/dt
0	0.00000	-0.36000	5.5	1.10271	0.17761
0.5	-0.18000	-0.11176	6	1.19152	-0.27568
1	-0.23588	0.40472	6.5	1.05368	-0.31002
1.5	-0.03352	0.71460	7	0.89866	0.10616
2	0.32378	0.53297	7.5	0.95175	0.59023
2.5	0.59026	0.02682	8	1.24686	0.69714
3	0.60367	-0.33849	8.5	1.59543	0.32859
3.5	0.43443	-0.22711	9	1.75972	-0.17657
4	0.32087	0.25857	9.5	1.67144	-0.35390
4.5	0.45016	0.67201	10	1.49449	-0.04036
5	0.78616	0.63310			



Copyright © McGraw-Hill Education. This is proprietary material solely for authorized instructor use. Not authorized for sale or distribution in any manner. This document may not be copied, scanned, duplicated, forwarded, distributed, or posted on a website, in whole or part.

$$\sum M_{in} - \sum M_{out} = 0$$

Food + Drink + Air In + Metabolism = Urine + Skin + Feces + Air Out + Sweat

Drink = Urine + Skin + Feces + Air Out + Sweat - Food - Air In - Metabolism

Drink = 1.4 + 0.35 + 0.2 + 0.4 + 0.3 - 1 - 0.05 - 0.3 = 1.3 L


The first two steps can be computed as

$$T(1) = 70 + [-0.019(70 - 20)] 2 = 68 + (-0.95)2 = 68.1$$

 $T(2) = 68.1 + [-0.019(68.1 - 20)] 2 = 68.1 + (-0.9139)2 = 66.2722$

The remaining results are displayed below along with a plot of the results.

t	T	dT/dt	t	T	dT/dt
0	70.00000	-0.95000	12.00000	59.62967	-0.75296
2	68.10000	-0.91390	14.00000	58.12374	-0.72435
4	66.27220	-0.87917	16.00000	56.67504	-0.69683
6	64.51386	-0.84576	18.00000	55.28139	-0.67035
8	62.82233	-0.81362	20.00000	53.94069	-0.64487
10	61.19508	-0.78271			



Copyright © McGraw-Hill Education. This is proprietary material solely for authorized instructor use. Not authorized for sale or distribution in any manner. This document may not be copied, scanned, duplicated, forwarded, distributed, or posted on a website, in whole or part.

(a) For the constant temperature case, Newton's law of cooling is written as

$$\frac{dT}{dt} = -0.12(T - 10)$$

The first two steps of Euler's methods are

$$T(0.5) = T(0) - \frac{dT}{dt}(0) \times \Delta t = 37 + 0.12(10 - 37)(0.5) = 37 - 3.2400 \times 0.50 = 35.3800$$

 $T(1) = 35.3800 + 0.12(10 - 35.3800)(0.5) = 35.3800 - 3.0456 \times 0.50 = 33.8572$

The remaining calculations are summarized in the following table:

t	T_a	T	dT/dt
0:00	10	37.0000	-3.2400
0:30	10	35.3800	-3.0456
1:00	10	33.8572	-2.8629
1:30	10	32.4258	-2.6911
2:00	10	31.0802	-2.5296
2:30	10	29.8154	-2.3778
3:00	10	28.6265	-2.2352
3:30	10	27.5089	-2.1011
4:00	10	26.4584	-1.9750
4:30	10	25.4709	-1.8565
5:00	10	24.5426	-1.7451

(b) For this case, the room temperature can be represented as

$$T_a = 20 - 2t$$

where t = time (hrs). Newton's law of cooling is written as

$$\frac{dT}{dt} = -0.12(T - 20 + 2t)$$

Solution continued on next page...

The first two steps of Euler's methods are

$$T(0.5) = 37 + 0.12(20 - 37)(0.5) = 37 - 2.040 \times 0.50 = 35.9800$$


 $T(1) = 35.9800 + 0.12(19 - 35.9800)(0.5) = 35.9800 - 2.0376 \times 0.50 = 34.9612$

The remaining calculations are summarized in the following table:

t	T_a	T	dT/dt
0:00	20	37.0000	-2.0400
0:30	19	35.9800	-2.0376
1:00	18	34.9612	-2.0353
1:30	17	33.9435	-2.0332
2:00	16	32.9269	-2.0312
2:30	15	31.9113	-2.0294
3:00	14	30.8966	-2.0276
3:30	13	29.8828	-2.0259
4:00	12	28.8699	-2.0244
4:30	11	27.8577	-2.0229
5:00	10	26.8462	-2.0215

Comparison with (a) indicates that the effect of the room air temperature has a significant effect on the expected temperature at the end of the 5-hr period (difference = 26.8462 - 24.5426 = 2.3036°C).


(c) The solutions for (a) Constant T_a , and (b) Cooling T_a are plotted below:



```
>> TF = 32:3.6:93.2;
>> TC = 5/9*(TF-32);
>> rho = 5.5289e-8*TC.^3-8.5016e-6*TC.^2+6.5622e-5*TC+0.99987;
>> plot(TC,rho)
   1.001
   0.999
   0.998
   0.997
   0.996
   0.995
  0.994
                                      30
```

```
clear, clc
t = 10:10:60;
c = [3.4 2.6 1.6 1.3 1.0 0.5];
tf = 0:70;
cf = 4.84*exp(-0.034*tf);
plot(t,c,'d','MarkerEdgeColor','r','MarkerFaceColor','r')
hold on
plot(tf,cf,'--g')
xlim([0 75])
hold off

5
4.5
4
3.5
3
2.5
2
1.5
1
0.5
```




The following function implements the piecewise function:

```
function v = vpiece(t)
if t<0
    v = 0;
elseif t<8
    v = 10*t^2 - 5*t;
elseif t<16
    v = 624 - 3*t;
elseif t<26
    v = 36*t + 12*(t - 16)^2;
else
    v = 2136*exp(-0.1*(t-26));
end</pre>
```


Here is a script that uses vpiece to generate the plot

```
k=0;
for i = -5:.5:50
   k=k+1;
   t(k)=i;
   v(k)=vpiece(t(k));
end
plot(t,v)
```



Solution continued on next page...

```
% Script to generate a plot of temperature, pressure and density
% for the International Standard Atmosphere
clc,clf
h=[0 11 20 32 47 51 71 84.852];
gamma=[-6.5 0 1 2.8 0 -2.8 -2];
T=[15 -56.5 -56.5 -44.5 -2.5 -2.5 -58.5 -86.28];
p=[101325 22632 5474.9 868.02 110.91 66.939 3.9564 0.3734];
hint=[0:0.1:84.852];
for i=1:length(hint)
  [Tint(i),pint(i),rint(i)]=StdAtm(h,T,p,gamma,hint(i));
end
subplot(1,3,1)
plot(T,h,'o',Tint,hint),grid,xlabel('(a) Temperature(C)')
ylabel('altitude (km)')
subplot(1,3,2)
plot(p,h,'o',pint,hint)
grid,xlabel('(b) Pressure(atm)')
subplot(1,3,3)
plot(rint,hint),grid,xlabel('(c) Density(kg/m^3)')
[Tint(i),pint(i),rint(i)]=StdAtm(h,T,p,gamma,85);
function [Tint,pint,rint] = StdAtm(h,T,p,gamma,hi
R=8.3144621; M=0.0289644;
n=length(h);
if hi<h(1) | hi>h(n)
  error('Outside range')
else
  for i=1:n-1
    if hi<=h(i+1)</pre>
      Tint=T(i)+gamma(i)*(hi-h(i));
      pint=p(i)+(p(i+1)-p(i))/(h(i+1)-h(i))*(hi-h(i));
      rint=pint*M/(R*(Tint+273.15));
      break
    end
  end
end
end
Results:
Error using StdAtm (line
Outside range
Error in Prob0328StdAtmScript (line 20)
[Tint(i),pint(i),rint(i)]=StdAtm(h,T,p,gamma,85);
```



Copyright © McGraw-Hill Education. This is proprietary material solely for authorized instructor use. Not authorized for sale or distribution in any manner. This document may not be copied, scanned, duplicated, forwarded, distributed, or posted on a website, in whole or part.