

UNIVERSITY OF CALIFORNIA SAN DIEGO

Increasing the Signal Efficiency of  $H \rightarrow \gamma\gamma$  and  $HH \rightarrow b\bar{b}\gamma\gamma$  Analyses Using Machine Learning Techniques

A dissertation submitted in partial satisfaction of the  
requirements for the degree Doctor of Philosophy

in

Physics

by

Robert John Lee

Committee in charge:

Professor James G. Branson, Chair  
Professor Javier Duarte  
Professor Michael Gilson  
Doctor Marco Pieri  
Professor Yi-Zhuang You

2026

Copyright

Robert John Lee, 2026

All rights reserved.

The Dissertation of Robert John Lee is approved, and it is acceptable in quality and form for publication on microfilm and electronically.

University of California San Diego

2026

## DEDICATION

Probably no dedication.

## EPIGRAPH

True ease in writing comes from art, not chance,  
As those move easiest who have learn'd to dance.  
'T is not enough to no harshness gives offence,—  
The sound must seem an echo to the sense.

*Alexander Pope*

You write with ease to show your breeding,  
But easy writing's curst hard reading.

*Richard Brinsley Sheridan*

Writing, at its best, is a lonely life. Organizations for writers palliate the writer's loneliness, but I doubt if they improve his writing. He grows in public stature as he sheds his loneliness and often his work deteriorates. For he does his work alone and if he is a good enough writer he must face eternity, or the lack of it, each day.

*Ernest Hemingway*

## TABLE OF CONTENTS

|                                                                                   |       |
|-----------------------------------------------------------------------------------|-------|
| Dissertation Approval Page .....                                                  | iii   |
| Dedication .....                                                                  | iv    |
| Epigraph .....                                                                    | v     |
| Table of Contents .....                                                           | vi    |
| List of Figures .....                                                             | ix    |
| List of Tables .....                                                              | xiv   |
| Preface .....                                                                     | xv    |
| Acknowledgements .....                                                            | xvi   |
| Vita .....                                                                        | xvii  |
| Abstract of the Dissertation .....                                                | xviii |
| Introduction .....                                                                | 1     |
| Chapter 1    The Standard Model and Higgs Boson .....                             | 3     |
| 1.1    Quantum Electrodynamics (QED) .....                                        | 4     |
| 1.2    Quantum Chromodynamics (QCD) .....                                         | 4     |
| 1.3    Electroweak (EW) Theory .....                                              | 4     |
| 1.4    The Higgs Field and Higgs Boson .....                                      | 4     |
| 1.4.1    Motivation for the Higgs Field .....                                     | 5     |
| 1.4.2    Properties of the Higgs Potential .....                                  | 5     |
| 1.4.3    Production Modes of a Single Higgs Boson .....                           | 5     |
| 1.4.4    Decay Modes of a Single Higgs Boson .....                                | 7     |
| 1.5    Higgs Boson Decaying to Two Photons ( $H \rightarrow \gamma\gamma$ ) ..... | 9     |
| 1.5.1    Useful Properties for Analysis .....                                     | 9     |
| 1.5.2    Historical Results .....                                                 | 9     |
| 1.6    Di-Higgs Production and Properties .....                                   | 9     |
| 1.6.1    Di-Higgs Production Modes .....                                          | 9     |
| 1.6.2    Di-Higgs Decay Modes .....                                               | 9     |
| 1.6.3    Usefulness of the $HH \rightarrow b\bar{b}\gamma\gamma$ Channel .....    | 9     |
| Chapter 2    The LHC and CMS Detector .....                                       | 10    |
| 2.1    The Large Hadron Collider .....                                            | 10    |
| 2.1.1    LHC Design .....                                                         | 10    |
| 2.1.2    Collisions at the LHC .....                                              | 10    |
| 2.1.3    LHC Experiments .....                                                    | 10    |

|           |                                                                                      |    |
|-----------|--------------------------------------------------------------------------------------|----|
| 2.2       | The Compact Muon Solenoid Detector .....                                             | 11 |
| 2.2.1     | Beampipe and Inner Tracking System .....                                             | 13 |
| 2.2.2     | Electromagnetic Calorimeter .....                                                    | 15 |
| 2.2.3     | Hadron Calorimeter .....                                                             | 16 |
| 2.2.4     | Forward Calorimeter .....                                                            | 16 |
| 2.2.5     | The Muon Detector .....                                                              | 16 |
| Chapter 3 | Triggering and Offline Software .....                                                | 17 |
| 3.1       | Level-1 Triggers .....                                                               | 17 |
| 3.1.1     | Information Available to L1 Triggers .....                                           | 18 |
| 3.1.2     | The L1 Trigger Architecture .....                                                    | 19 |
| 3.1.3     | The L1 $e/\gamma$ Reconstruction .....                                               | 20 |
| 3.1.4     | The L1 Menu .....                                                                    | 21 |
| 3.2       | The Data Acquisition System (DAQ) .....                                              | 21 |
| 3.3       | High Level Trigger .....                                                             | 21 |
| 3.3.1     | HLT Event Reconstruction .....                                                       | 21 |
| 3.3.2     | HLT Trigger Rates and Timing .....                                                   | 21 |
| 3.3.3     | HLT Software and ConfDB .....                                                        | 21 |
| 3.4       | Analysis Software .....                                                              | 21 |
| 3.4.1     | Offline Reconstruction .....                                                         | 21 |
| 3.4.2     | The NanoAOD File Format .....                                                        | 21 |
| 3.4.3     | NanoAOD Event Reconstruction .....                                                   | 21 |
| 3.4.4     | HiggsDNA .....                                                                       | 21 |
| Chapter 4 | Boosted Decision Trees and XGBoost .....                                             | 22 |
| 4.1       | Gradient Descent Boosting .....                                                      | 22 |
| 4.2       | The Objective Function .....                                                         | 23 |
| 4.3       | XGBoost Software .....                                                               | 23 |
| Chapter 5 | Development of an MVA-Based High Level Trigger .....                                 | 24 |
| 5.1       | Limitations and Benefits of Current $H \rightarrow \gamma\gamma$ Trigger .....       | 24 |
| 5.2       | Development of a Boosted Decision Tree for Photon Candidate Classification ..        | 25 |
| 5.2.1     | XGBoost-Based BDT Software .....                                                     | 25 |
| 5.2.2     | Signal and Background Samples for Classification .....                               | 26 |
| 5.2.3     | Determination of Input Variables .....                                               | 27 |
| 5.2.4     | Hyperparameter Tuning .....                                                          | 32 |
| 5.3       | Determination of BDT Cuts .....                                                      | 34 |
| 5.4       | Final Implementation in HLT Menu .....                                               | 44 |
| Chapter 6 | MVA-Based Offline Preselection .....                                                 | 46 |
| 6.1       | Current Diphoton Preselection .....                                                  | 46 |
| 6.2       | Development of MVA-Based Offline Preselection .....                                  | 48 |
| 6.2.1     | Creation of Single Photon BDTs .....                                                 | 48 |
| 6.2.2     | Determination of Loose Single Photon MVA Cuts for $H \rightarrow \gamma\gamma$ ..... | 64 |

|           |                                                                                                   |     |
|-----------|---------------------------------------------------------------------------------------------------|-----|
| 6.2.3     | Creation of Diphoton BDT for $H \rightarrow \gamma\gamma$ . . . . .                               | 67  |
| 6.2.4     | Determination of Loose Single Photon MVA Cuts for $HH \rightarrow b\bar{b}\gamma\gamma$ . . . . . | 79  |
| 6.2.5     | Creation of Diphoton BDT for $HH \rightarrow b\bar{b}\gamma\gamma$ . . . . .                      | 81  |
| Chapter 7 | Evaluation of the MVA-HLT and Complementary Offline Selection . . . . .                           | 88  |
| 7.1       | Measurement of Trigger Rate . . . . .                                                             | 88  |
| 7.1.1     | Method of Rate Measurement . . . . .                                                              | 88  |
| 7.1.2     | Trigger Rate of MVA-HLT . . . . .                                                                 | 88  |
| 7.2       | Evaluation of MVA-HLT Efficiency on Selected Signal Samples . . . . .                             | 88  |
| 7.2.1     | Single Higgs MVA-HLT Acceptance . . . . .                                                         | 89  |
| 7.2.2     | DiHiggs MVA-HLT Acceptance . . . . .                                                              | 92  |
| 7.3       | Evaluation of Offline Selection Efficiency with MVA-HLT . . . . .                                 | 95  |
| 7.3.1     | Method of Signal Efficiency Measurement . . . . .                                                 | 95  |
| 7.3.2     | Single Higgs Offline Selection Acceptance . . . . .                                               | 95  |
| 7.3.3     | DiHiggs Offline Selection Acceptance . . . . .                                                    | 97  |
| Chapter 8 | Summary . . . . .                                                                                 | 100 |
| Chapter 9 | Acknowledgements . . . . .                                                                        | 101 |



## LIST OF FIGURES

|             |                                                                                                                                                                                                                                                               |    |
|-------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|
| Figure 5.1. | Plots of raw supercluster energy and $R_9$ . The signal MC is shown in dark blue for the barrel and light blue for the endcap, whereas the data (background) is shown in red for the barrel and pink for the endcap. ....                                     | 28 |
| Figure 5.2. | Plots of the $\sigma_{i\eta i\eta}$ and $\eta_{SC}$ . The signal MC is shown in dark blue for the barrel and light blue for the endcap, whereas the data (background) is shown in red for the barrel and pink for the endcap. ....                            | 29 |
| Figure 5.3. | Plots of the $\eta$ and $\phi$ widths. The signal MC is shown in dark blue for the barrel and light blue for the endcap, whereas the data (background) is shown in red for the barrel and pink for the endcap. ....                                           | 30 |
| Figure 5.4. | Plots of the H/E and isolation. The signal MC is shown in dark blue for the barrel and light blue for the endcap, whereas the data (background) is shown in red for the barrel and pink for the endcap. ....                                                  | 31 |
| Figure 6.1. | Plots of the Supercluster raw energy and $\eta_{SC}$ . The prompt signal is shown in dark blue for the barrel and light blue for the endcap, whereas the fake background is shown in red for the barrel and pink for the endcap. ....                         | 50 |
| Figure 6.2. | Plots of the $R_9$ and $S_4$ . The prompt signal is shown in dark blue for the barrel and light blue for the endcap, whereas the fake background is shown in red for the barrel and pink for the endcap. ....                                                 | 51 |
| Figure 6.3. | Plots of the $\sigma_{i\eta i\eta}$ and $\text{cov}(i\eta i\phi)$ . The prompt signal is shown in dark blue for the barrel and light blue for the endcap, whereas the fake background is shown in red for the barrel and pink for the endcap. ....            | 52 |
| Figure 6.4. | Plots of the $\eta$ and $\phi$ widths. The prompt signal is shown in dark blue for the barrel and light blue for the endcap, whereas the fake background is shown in red for the barrel and pink for the endcap. ....                                         | 53 |
| Figure 6.5. | Plots of the H/E and photon isolation. The prompt signal is shown in dark blue for the barrel and light blue for the endcap, whereas the fake background is shown in red for the barrel and pink for the endcap. ....                                         | 54 |
| Figure 6.6. | Plots of the charged isolations with respect to the chosen and worst vertices. The prompt signal is shown in dark blue for the barrel and light blue for the endcap, whereas the fake background is shown in red for the barrel and pink for the endcap. .... | 55 |

|              |                                                                                                                                                                                                                                                               |    |
|--------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|
| Figure 6.7.  | Plots of two endcap-specific variables: $\text{esEffSigmaRR}$ and $\text{esEnergyOverRawE}$ . The prompt signal is shown in light blue, whereas the fake background is shown in pink. ....                                                                    | 56 |
| Figure 6.8.  | Plots of the Supercluster raw energy and $\eta_{SC}$ . The prompt signal is shown in dark blue for the barrel and light blue for the endcap, whereas the fake background is shown in red for the barrel and pink for the endcap. ....                         | 58 |
| Figure 6.9.  | Plots of the $R_9$ and $S_4$ . The prompt signal is shown in dark blue for the barrel and light blue for the endcap, whereas the fake background is shown in red for the barrel and pink for the endcap. ....                                                 | 59 |
| Figure 6.10. | Plots of the $\sigma_{i\eta i\eta}$ and $\text{cov}(i\eta i\phi)$ . The prompt signal is shown in dark blue for the barrel and light blue for the endcap, whereas the fake background is shown in red for the barrel and pink for the endcap. ....            | 60 |
| Figure 6.11. | Plots of the $\eta$ and $\phi$ widths. The prompt signal is shown in dark blue for the barrel and light blue for the endcap, whereas the fake background is shown in red for the barrel and pink for the endcap. ....                                         | 61 |
| Figure 6.12. | Plots of the H/E and photon isolation. The prompt signal is shown in dark blue for the barrel and light blue for the endcap, whereas the fake background is shown in red for the barrel and pink for the endcap. ....                                         | 62 |
| Figure 6.13. | Plots of the charged isolations with respect to the chosen and worst vertices. The prompt signal is shown in dark blue for the barrel and light blue for the endcap, whereas the fake background is shown in red for the barrel and pink for the endcap. .... | 63 |
| Figure 6.14. | Plots of two endcap-specific variables: $\text{esEffSigmaRR}$ and $\text{esEnergyOverRawE}$ . The prompt signal is shown in light blue, whereas the fake background is shown in pink. ....                                                                    | 64 |
| Figure 6.15. | Acceptance of the MVA-HLT (blue) vs. the current standard diphoton HLT (green) for $M_{\gamma\gamma}$ ....                                                                                                                                                    | 65 |
| Figure 6.16. | Acceptance of the MVA-HLT (blue) vs. the current standard diphoton HLT (green) for $\eta_{SC}$ . Both the lead and sublead photons are plotted together. ..                                                                                                   | 66 |
| Figure 6.17. | Acceptance of the MVA-HLT (blue) vs. the current standard diphoton HLT (green) for $p_T$ . Both the lead and sublead photons are plotted together. ...                                                                                                        | 67 |
| Figure 6.18. | The two per-event diphoton input variables, $\sigma(M_{\gamma\gamma})/M_{\gamma\gamma}$ and $\cos(\Delta\phi)$ . The signal MC is in black, whereas the data events are in red. ....                                                                          | 69 |

|              |                                                                                                                                                                                                                                                             |    |
|--------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|
| Figure 6.19. | The lead and sublead $\gamma + \text{Jet}$ XGBoost BDT scores. The signal MC is in black, whereas the data events are in red. ....                                                                                                                          | 70 |
| Figure 6.20. | The lead and sublead Data/MC XGBoost BDT scores. The signal MC is in black, whereas the data events are in red. ....                                                                                                                                        | 71 |
| Figure 6.21. | The lead and sublead $\eta_{SC}$ . The signal MC is in black, whereas the data events are in red. ....                                                                                                                                                      | 72 |
| Figure 6.22. | The lead and sublead $p_T/M_{\gamma\gamma}$ . The signal MC is in black, whereas the data events are in red. ....                                                                                                                                           | 73 |
| Figure 6.23. | The lead and sublead electron veto. The signal MC is in black, whereas the data events are in red. ....                                                                                                                                                     | 74 |
| Figure 6.24. | Plots of the Supercluster raw energy and $\eta_{SC}$ . The signal MC is shown in dark blue for the barrel and light blue for the endcap, whereas the data (background) is shown in red for the barrel and pink for the endcap. ....                         | 75 |
| Figure 6.25. | Plots of the $R_9$ and $S_4$ . The signal MC is shown in dark blue for the barrel and light blue for the endcap, whereas the data (background) is shown in red for the barrel and pink for the endcap. ....                                                 | 76 |
| Figure 6.26. | Plots of the $\sigma_{i\eta i\eta}$ and $\text{cov}(i\eta i\phi)$ . The signal MC is shown in dark blue for the barrel and light blue for the endcap, whereas the data (background) is shown in red for the barrel and pink for the endcap. ....            | 77 |
| Figure 6.27. | Plots of the $\eta$ and $\phi$ widths. The signal MC is shown in dark blue for the barrel and light blue for the endcap, whereas the data (background) is shown in red for the barrel and pink for the endcap. ....                                         | 77 |
| Figure 6.28. | Plots of the H/E and photon isolation. The signal MC is shown in dark blue for the barrel and light blue for the endcap, whereas the data (background) is shown in red for the barrel and pink for the endcap. ....                                         | 78 |
| Figure 6.29. | Plots of the charged isolations with respect to the worst and chosen vertices. The signal MC is shown in dark blue for the barrel and light blue for the endcap, whereas the data (background) is shown in red for the barrel and pink for the endcap. .... | 78 |
| Figure 6.30. | Plots of the ES Eff. Sigma RR and ES Energy over Raw E. The signal MC is shown in dark blue for the barrel and light blue for the endcap, whereas the data (background) is shown in red for the barrel and pink for the endcap. ....                        | 79 |
| Figure 6.31. | Acceptance of the MVA-HLT (blue) vs. the current standard diphoton HLT (green) for $M_{\gamma\gamma}$ .....                                                                                                                                                 | 80 |

|              |                                                                                                                                                                                                                                                                 |    |
|--------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|
| Figure 6.32. | Acceptance of the MVA-HLT (blue) vs. the current standard diphoton HLT (green) for $\eta_{SC}$ .....                                                                                                                                                            | 80 |
| Figure 6.33. | Acceptance of the MVA-HLT (blue) vs. the current standard diphoton HLT (green) for $p_T$ .....                                                                                                                                                                  | 81 |
| Figure 6.34. | The two per-event diphoton input variables, $\sigma(M_{\gamma\gamma})/M_{\gamma\gamma}$ and $\cos(\Delta\phi)$ . The signal MC is in black, whereas the data events are in red.....                                                                             | 82 |
| Figure 6.35. | The lead and sublead $\gamma$ + Jet XGBoost BDT scores. The signal MC is in black, whereas the data events are in red. ....                                                                                                                                     | 83 |
| Figure 6.36. | The lead and sublead Data/MC XGBoost BDT scores. The signal MC is in black, whereas the data events are in red. ....                                                                                                                                            | 84 |
| Figure 6.37. | The lead and sublead $\eta_{SC}$ . The signal MC is in black, whereas the data events are in red. ....                                                                                                                                                          | 85 |
| Figure 6.38. | The lead and sublead $p_T/M_{\gamma\gamma}$ . The signal MC is in black, whereas the data events are in red. ....                                                                                                                                               | 86 |
| Figure 6.39. | The lead and sublead electron veto The signal MC is in black, whereas the data events are in red. ....                                                                                                                                                          | 87 |
| Figure 7.1.  | Acceptance of the MVA-HLT (dark blue) vs. the current standard diphoton HLT (green) for $M_{\gamma\gamma}$ . Events that pass the MVA-HLT but fail the standard HLT can be seen in light blue. ....                                                             | 90 |
| Figure 7.2.  | Acceptance of the MVA-HLT (dark blue) vs. the current standard diphoton HLT (green) for $\eta_{SC}$ . Both the lead and sublead photons are plotted together. Events that pass the MVA-HLT but fail the standard HLT can be seen in light blue. ....            | 91 |
| Figure 7.3.  | Acceptance of the MVA-HLT (dark blue) vs. the current standard diphoton HLT (green) for $p_T/M_{\gamma\gamma}$ . Both the lead and sublead photons are plotted together. Events that pass the MVA-HLT but fail the standard HLT can be seen in light blue. .... | 91 |
| Figure 7.4.  | Acceptance of the MVA-HLT (blue) vs. the current standard diphoton HLT (green) for $M_{\gamma\gamma}$ .....                                                                                                                                                     | 93 |
| Figure 7.5.  | Acceptance of the MVA-HLT (blue) vs. the current standard diphoton HLT (green) for $\eta_{SC}$ .....                                                                                                                                                            | 93 |
| Figure 7.6.  | Acceptance of the MVA-HLT (blue) vs. the current standard diphoton HLT (green) for $p_T/M_{\gamma\gamma}$ .....                                                                                                                                                 | 94 |

|              |                                                              |    |
|--------------|--------------------------------------------------------------|----|
| Figure 7.7.  | Both the lead and sublead photons are plotted together. .... | 95 |
| Figure 7.8.  | Both the lead and sublead photons are plotted together. .... | 96 |
| Figure 7.9.  | Both the lead and sublead photons are plotted together. .... | 96 |
| Figure 7.10. | Both the lead and sublead photons are plotted together. .... | 97 |
| Figure 7.11. | Both the lead and sublead photons are plotted together. .... | 98 |
| Figure 7.12. | Both the lead and sublead photons are plotted together. .... | 98 |

## LIST OF TABLES

|            |                                                                                                             |    |
|------------|-------------------------------------------------------------------------------------------------------------|----|
| Table 5.1. | E .....                                                                                                     | 27 |
| Table 5.2. | Chosen score cuts for BB and EE events .....                                                                | 36 |
| Table 5.3. | Signal efficiencies and background acceptances for both triggers, broken down by diphoton $\eta_{sc}$ ..... | 44 |
| Table 6.1. | E .....                                                                                                     | 47 |
| Table 6.2. | E .....                                                                                                     | 49 |
| Table 6.3. | E .....                                                                                                     | 68 |
| Table 7.1. | Signal efficiencies and background acceptances for both triggers, broken down by diphoton $\eta_{sc}$ ..... | 92 |
| Table 7.2. | Signal efficiencies and background acceptances for both triggers, broken down by diphoton $\eta_{sc}$ ..... | 94 |
| Table 7.3. | Signal efficiencies and background acceptances for both triggers, broken down by diphoton $\eta_{sc}$ ..... | 97 |
| Table 7.4. | Signal efficiencies and background acceptances for both triggers, broken down by diphoton $\eta_{sc}$ ..... | 99 |

## PREFACE

Probably no preface

## ACKNOWLEDGEMENTS

Acknowledgements



## VITA

- 2015–2018 Teaching Assistant, Department of Physics  
Arizona State University
- 2015–2018 Research Assistant  
Arizona State University Meson Physics Group
- 2018 Bachelor of Science  
Arizona State University Barret Honor's College
- 2018–2019 Teaching Assistant, Department of Physics  
University of California, San Diego
- 2019–2026 Graduate Student Researcher, University of California, San Diego
- 2026 Doctor of Philosophy, University of California, San Diego

## ABSTRACT OF THE DISSERTATION

Increasing the Signal Efficiency of  $H \rightarrow \gamma\gamma$  and  $HH \rightarrow b\bar{b}\gamma\gamma$  Analyses Using Machine Learning Techniques

by

Robert John Lee

Doctor of Philosophy in Physics

University of California San Diego, 2026

Professor James G. Branson, Chair

Abstract

# Introduction

First theorized in 1964, the Higgs field constitutes a vital component of the Standard Model (SM) of particle physics. The insertion of this field to the SM allowed a mechanism for the spontaneous breaking of the electroweak symmetry, a necessary fix to the versions of the antecedent theories of fundamental particles. This spontaneous symmetry breaking provides an avenue through which the fundamental particles may gain their masses; until the formulation of the Higgs fields, the prevailing version of the SM could not account for the existence of – let alone the values of – the masses of quarks and the force-carrying gauge bosons. Luckily, the prediction of the Higgs field proposed a corresponding bosonic particle to mediate the interactions of this field. As the fundamental particles predicted by the SM were discovered throughout the 20th century, the Higgs boson proved to be elusive, in fact eventually becoming the last undiscovered fundamental particle predicted by the SM.

Since the discovery of the Higgs boson in 2012, the Large Hadron Collider has undertaken continuously more precise measurements of its properties. As the amount of available data has accumulated, increasingly rare channels of analysis have become explorable. To enable these high-quality analyses, the hardware and software of the LHC and its detectors has had to be improved considerably. Due to the abundance of background processes created at the high energies achieved by the LHC, coupled with the relative rarity of the processes by which the Higgs boson is produced and decays, complex software is necessary to disentangle the signal processes.

This software is constructed using a layered approach, where each subsequent step in the processing of the data serves to further reduce the total amount of data events being analyzed,

while, ideally, preserving as many events considered signal as possible. The first stages of this data reduction are achieved by a set of triggers. These triggers are relatively coarse-grain, seeking to reject the most obvious background events and thereby reduce the amount of data being stored and analyzed by three to four orders of magnitude. Of course, given the large number of different final states of the Higgs boson decay, many different triggers must be developed to dig out the specific signal signature required for a specific analysis. Once these triggers are applied, further analysis software is used on the resulting data to produce final results of the measurements of the various properties of the desired physics process.

The goal of this paper is to examine the improvement of a specific set of these triggers and analysis-level cuts. While many channels of Higgs boson decay exist, the decay into two photons has been proven to be a major component of the analysis of the Higgs boson; this process provides a relatively clean decay signature, and occurs at a high enough rate to provide ample statistics for analysis.

# Chapter 1

## The Standard Model and Higgs Boson

Theory Citations: [7]: Short 1999 Overview of SM. [11]: 2024 review of particle physics. [2]: 2012 Higgs Discovery phys review letters publication. [3] 2013 JHEP Higgs discovery publication. [1] 2022 CMS Higgs 10 year review.

Detector Citations: [4] 2008 Early CMS Description. [8] 2024 Run3 CMS Description (use this mainly). [5] 2008 Overall LHC design.

Trigger Citations: [14] 2020 L1 Trigger review. [10] 2017 overall trigger structure. [9] 2024 review of Run2 HLT performance.

The standard model (SM) of particle physics is the quantum gauge field theory that describes all currently known physical interactions besides gravity. Early formulations considered there to be three distinct gauge theories that ruled interactions between physical objects: Quantum Electrodynamics (QED), which describes the electromagnetic force between charged objects; Quantum Chromodynamics (QCD), which describes the strong nuclear force; and Weak Theory, which describes the weak nuclear force.

Within the SM, there are two major forms of particle. Spin  $1/2$  particles, called fermions, comprise all matter as we know it, and include quarks and leptons. Integer spin particles, called bosons, act as the force carriers that mediate interactions between these fermions. QED posits the photon as the gauge boson, which mediates interactions between all electrically charged particles – including both charged leptons and quarks. QCD describes eight gluons as the force

mediators between color-charged quarks. The weak theory describes the massive  $W^\pm$  and  $Z^0$  bosons as the mediators of the weak force, which is responsible for radioactive decay.

As will be discussed in 1.3, experimental findings pointed early theorists towards the unification of the electromagnetic and weak forces into what is now known as the electroweak (EW) theory. The

## **1.1 Quantum Electrodynamics (QED)**

Use Gaillard, Grannis, and Sciulli

## **1.2 Quantum Chromodynamics (QCD)**

Use Gaillard, Grannis, and Sciulli AND PDG Physics summary page 153

## **1.3 Electroweak (EW) Theory**

Use Gaillard, Grannis, and Sciulli AND PDG Physics summary page 185


## **1.4 The Higgs Field and Higgs Boson**

Use PDG Physics summary page 211-218


### 1.4.1 Motivation for the Higgs Field

### 1.4.2 Properties of the Higgs Potential

### 1.4.3 Production Modes of a Single Higgs Boson




**Figure 1.1.** Feynman diagrams of known Higgs production modes. Reproduced from [CMS10YearReview]



**Figure 1.2.** Production cross sections for Higgs creation. Reproduced from [CMS10YearReview]




### 1.4.4 Decay Modes of a Single Higgs Boson



**Figure 1.3.** Feynman diagrams of known Higgs decay modes. Reproduced from [CMS10YearReview]

| Decay channel  | Branching fraction (%) |              |
|----------------|------------------------|--------------|
| bb             | 57.63                  | $\pm 0.70$   |
| WW             | 22.00                  | $\pm 0.33$   |
| gg             | 8.15                   | $\pm 0.42$   |
| $\tau\tau$     | 6.21                   | $\pm 0.09$   |
| cc             | 2.86                   | $\pm 0.09$   |
| ZZ             | 2.71                   | $\pm 0.04$   |
| $\gamma\gamma$ | 0.227                  | $\pm 0.005$  |
| $Z\gamma$      | 0.157                  | $\pm 0.009$  |
| ss             | 0.025                  | $\pm 0.001$  |
| $\mu\mu$       | 0.0216                 | $\pm 0.0004$ |



**Figure 1.4.** Decay branching fractions<sup>8</sup> for a single Higgs. Reproduced from [CMS10YearReview]


## 1.5 Higgs Boson Decaying to Two Photons ( $H \rightarrow \gamma\gamma$ )

### 1.5.1 Useful Properties for Analysis

### 1.5.2 Historical Results

## 1.6 Di-Higgs Production and Properties

### 1.6.1 Di-Higgs Production Modes



**Figure 1.5.** Feynman diagrams of known Higgs decay modes. Reproduced from [CMS10YearReview]

### 1.6.2 Di-Higgs Decay Modes

### 1.6.3 Usefulness of the $HH \rightarrow b\bar{b}\gamma\gamma$ Channel

# **Chapter 2**

## **The LHC and CMS Detector**

### **2.1 The Large Hadron Collider**

The Large Hadron Collider, which replaced the preexisting Large Electron-Positron Collider, was constructed between 2000 and 2008. Designed to reach new energy frontiers by colliding protons at up to 14 TeV, the LHC provided particles physicists with their most powerful tool yet to test the Standard Model and beyond. At the most basic level, these proton-proton collisions are achieved by crossing two counter-rotating proton beams at specific points. These counter-rotating beams are accelerated along the 26.7 km circumference of the LHC within a tunnel of 3.7 m internal diameter. Initial designs proposed two completely separated proton beam pipes, but it became clear that the space requirements of the existing CERN tunnel (constructed for LEP) precluded this possibility. As a result, a "two-in-one" superconducting magnet design was adopted that allowed the two beams to be transported in separate magnetic coils sharing the same mechanical and cryostat space.

#### **2.1.1 LHC Design**

#### **2.1.2 Collisions at the LHC**

#### **2.1.3 LHC Experiments**

Collisions at the LHC occur at 4 major interaction points, where 4 separate detectors have been constructed to allow independent measurements of target physics processes. Two of these


detectors, ATLAS and the Compact Muon Solenoid (CMS), are designed as general-purpose detectors with systems allowing the measurement of a broad range of physics processes. Since these detectors are constructed using different technologies and detector elements, the LHC is able to produce separate physics results that can be cross-checked. A major motivation for the construction of these experiments was the detection of the Higgs boson in its various decay modes.

## 2.2 The Compact Muon Solenoid Detector

The Compact Muon Solenoid is designed as a 22 m cylinder with a total diameter of 15 m. Centered on the beampipe where a proton-proton bunch crossing occurs, the detector consists of various layers of detector elements designed to track and measure different resultant particles. The general structure of the detector will be described beginning at the center and moving outward. A schematic of the detector can be seen in Figure 2.1. Later sections will provide additional detail on elements of particular interest for our  $H \rightarrow \gamma\gamma$  analyses.

After particles collide and are scattered, they first interact with the central beampipe that houses the incoming proton bunches. While this element does not provide any detecting capabilities, interactions between the outgoing particles and the material of the beampipe may cause additional scattering and particle production. Next, the particles enter the robust inner tracking system, designed to be able to reconstruct the path of charged particles through the detector. This inner tracking system is composed of an internal pixel detector surrounded by an external strip detector. These elements will be described in section 2.2.1.

The next detector element encountered is the Electromagnetic Calorimeter (ECal), which aims to measure the energies and locations of electrons and photons. Of course, given that the following analysis will be centered on photons, this detector element will be of great interest. This ECal is composed of scintillating  $PbWO_4$  crystals arranged into both a cylindrical ECal Barrel (EB) concentric with the beamline and two circular ECal Endcaps (EE) oriented orthogonally to



**Figure 2.1.** A full view of the CMS Detector, with each major system labeled. Reproduced from [CMSRun3Paper]

the beamline. A Preshower detector is inserted in front of the EE detectors. More details on this detector element will be provided in section 2.2.2.

Further from the beamline, the Hadronic calorimeter (HCal) aims to measure the locations and energies of charged and neutral hadronic particles using plastic scintillator tiles imbedded in a brass volume. Similarly to the ECal, the HCal is composed of a barrel (HB) region and two endcaps (EB). This detector will be described in more detail in section 2.2.3.

A superconducting solenoid encases all three of these internal regions, providing an internal magnetic field of 3.8T. This magnetic field allows the paths of charged particles to be bent, providing more precise measurement of their properties. While vital to the physics of the detector, this solenoid does not contain any detecting elements. Beyond this magnet lies the highly complicated Muon chambers, which will not be described for this analysis. Close to the

beamline but at the ends of the z-axis of the detector lies the forward calorimeter, which will also not be described for this analysis. The entire detector is shrouded in a steel return yoke.


### 2.2.1 Beampipe and Inner Tracking System

A major goal of the CMS detector is to reconstruct the tracks of charged particles. This allows the software to not only track and measure the flight of an individual particle, but it allows the primary interaction vertex (PV) to be measured more accurately. This is achieved by a two-layered approach; the pixel detectors closest to the beamline provide high-accuracy three-dimensional spatial information on the particles immediately after they leave the beampipe, while the strip detectors are used to reconstruct where the particle went after this precise initial location. Since the analysis of  $H \rightarrow \gamma\gamma$  is focused on photons, charged tracks are not expected for the final state particles of interest. This does not mean they are of no use to us, however – charged tracks can be used to exclude particles from our final state analysis, allowing us to reduce the number of resultant particles and increase the likelihood that the final particles analyzed are photons.

#### Pixel Detector

The pixel detectors achieve high spatial resolution by using 124 million channels each composed of a single pixel. As with most detector elements at CMS, the pixel detectors are formed by a barrel region (BPIX) and two circular disk endcap regions (FPIX). The barrels use 4 layers of silicon pixels, located at 29, 68, 109, and 160 mm from the beamline. The endcap detectors use 3 layers of pixels, at distances of 291, 396, and 516 mm from the center of the detector along the z-axis. This layout ensures that any charged particle will strike the pixel trackers 4 times at varying distances from the interaction vertex, allowing precise reconstruction of the track starting at the edge of the beampipe. [?Table of number of modules for each pixel detector? Table 1 Run3CMSDetector]

The individual pixels, of the same size in both the BPIX and FPIX, are housed on sensor




**Figure 2.2.** Longitudinal view of the pixel detector, where the beampipe is represented at the bottom of the image. Reproduced from [CMSRun3Paper]

modules with  $160 \times 416$  pixels each (with a total size of  $100 \times 150 \mu m^2$ ). This modular structure allows easy replacement of faulty modules, as well as allowing more efficient production. The BPIX contains 1184 such modules, across its 4 layers, whereas the FPIX contains 672 modules. Light-weight mechanical structures provide the mounting points for these modules, and include cooling apparatus.

### Strip Detector

The innermost pixel detector is rather small, only extending 160mm radially from the beamline, and 516mm along the beam direction from the interaction point. The majority of the tracking system is composed of the silicon strip tracker (SST). The SST contains 9.3 million silicon micro-strips grouped into 15,148 modules. While there are far fewer channels in the SST, the volume covered is much larger; once the origin of a particle track is pinpointed by the pixel detectors, the strip detectors are able to detect the particle as it travels through a large volume of the detector. The SST has a diameter of 2.5m and a length along the beamline of 5m, so it is clearly a more coarse-grain tracking sensor.





**Figure 2.3.** Full view of the tracker system. The inner pixel tracker is shown in green. Reproduced from [CMSRun3Paper]

### 2.2.2 Electromagnetic Calorimeter

Beyond the inner tracking system, the ECAL system is designed to measure the energies, locations, and arrival times of electrons and photons. Given that this paper will be dealing with a two-photon final state, the details of this detector are highly relevant. Similarly to the inner tracker, the ECAL is composed of modules of individual detector elements. Here, however, since the goal is to measure photons and electrons, scintillating material is required. As a result, the individual detector elements are composed of scintillating lead tungstate ( $PbWO_4$ ) crystals. These crystals were chosen because, in addition to being optically clear, they are radiation-hard. Given that the detector will be exposed to high levels of radiation for long continuous stretches, it is imperative that the crystals need not be replaced frequently. The photons from the scintillation of these crystals are detected by photodetectors. The photodetectors differ, however, between the barrel and endcap as explained in detail below.

#### ECal Barrel (EB)

The barrel component of the ECAL (EB) is designed, of course, with cylindrical symmetry. In the azimuthal direction,  $\phi$ , there are 360 crystals per "ring". The barrel detector covers

the pseudorapidity range of  $|\eta| < 1.479$ , and there are 180 crystals per "row" in this range. As a result, the EB consists of 61,200 total  $PbWO_4$  crystals. These crystals are tapered, such that the scintillated photons are funneled to the back of the crystal where two avalanche photodiodes (APDs) per crystal collect them. The cross-sectional area of the crystal faces is  $22 \times 22 \text{ mm}^2$ . The face of each crystal lies at a distance of 1.29m from the center of the beamline.

As with the tracker, the individual crystals are combined into submodules and modules, where readout and power-supplying electronics are consolidated. These submodules are of an "aveolar" structure, where the dividing walls between individual crystals are 0.1mm thick and are made of a combination of aluminum and fibre-epoxy resin. This leads to a total crystal-to-crystal distance of 0.35mm within each submodule. This provides sufficient granularity while still ensuring complete geometric coverage with a reasonable number of individual channels.

## **ECal Endcaps (EE)**

### **2.2.3 Hadron Calorimeter**

### **2.2.4 Forward Calorimeter**

### **2.2.5 The Muon Detector**

# Chapter 3

## Triggering and Offline Software

In Run3 of the LHC, the increased luminosity leads to an average of 60 collisions per bunch crossing (termed "Pileup") (REF?). Given that these bunch crossings occur at a rate of 40MHz (every 25ns) and can create a large number of individual particles, the processing and storage facilities are incapable of saving and analyzing every interaction generated in each bunch crossing. The triggering system, therefore, is designed to drastically reduce the number of output events while preserving as many events matching signal signatures as possible. Overall, the triggers aim to reduce the data rate from 40MHz down to just 5kHz. This reduction is achieved by a two-tier trigger system consisting of the Level 1 (L1) triggers and the High Level Triggers (HLT). Since there are many possible signal signatures depending on the analysis being conducted, there are many individual triggers at both L1 and HLT. Details of the L1 triggers will be given below in section 3.1, and the HLT will be described in great detail in section 3.3.

### 3.1 Level-1 Triggers

The Level 1 trigger is described in detail in [14], but the primary points are summarized in this section. As described in section 2.1.2, collisions in CMS during Run 3 occur at a rate of 40 million per second (40MHz). The goal of the L1 trigger is to select at most 100,000 of these events per second (100kHz) to pass on to the next level of the trigger, the HLT. The L1 trigger is designed to operate as quickly as possible, with a target latency of just 4  $\mu$ seconds. In order to

achieve this very low latency, minimal event reconstruction is done at L1; instead, this trigger performs minimal processing on the so-called trigger primitives (TP), which are the raw outputs from detector elements. The details of these TPs will be discussed below in section 3.1.1.

In order to process events as quickly as possible, software is eschewed in favor of an FPGA-based hardware system [10]. There are two of these systems corresponding to the two major detector systems: the L1 calorimeter trigger processes the information from both the Electron and Hadron Calorimeters, while the L1 muon trigger processes the information from the muon chambers. The calorimeter trigger system is of the greatest interest to this paper, as the photon candidates from  $H \rightarrow \gamma\gamma$  events are largely measured by the ECal with some additional information also being drawn from the HCal. In section 3.1.2, then, the calorimeter trigger system will be discussed in detail.

These two systems consist of many individual triggers, known as the L1 menu. This menu is designed to target specific physics objects, and consists of several triggers for each object. Muon triggers comprise nearly half of this menu. Additional triggers exist for both  $\tau$  leptons and the identification of jet objects. Finally there are triggers designed to measure electrons and photons (termed  $e/\gamma$  triggers). These triggers are, of course, the most important for  $H \rightarrow \gamma\gamma$  processes, and the identification of photon candidates is the first step in finding and measuring these signal processes. The details of the L1 menu, with particular emphasis on the  $e/\gamma$  triggers, are presented below in section 3.1.4.

### 3.1.1 Information Available to L1 Triggers

The inputs to the L1 trigger are entirely in the form of trigger primitives. For the calorimeter trigger, these TPs are in the form of energy deposition in a specific detector element [14]. The HCal and ECal, detailed in section 2.2.3 and 2.2.2, are only able to measure the energy deposited in their individual elements. So-called Trigger Towers (TTs) group together the ECal and HCal elements in a specific region of a detector. For the barrel detector, a 5x5 set of EB crystals is combined with the corresponding HB tower behind them into a single TT. This gives

a barrel resolution of  $\Delta\eta \times \Delta\phi = 0.087 \times 0.087$  radians. In the endcap, the presence of the HF detector complicates the TTs; the information from the EE, HE, and HF detectors must all be merged in a single TT per channel. Additionally, the geometry is complicated by the variable crystal size and spacing in the endcap. While the overall TT resolution consequentially varies in the endcap region, the maximum TT size is  $\Delta\eta \times \Delta\phi = 0.17 \times 0.17$  radians.

The L1 TPs for the muon triggers are considerably more complex, as there are more detector elements to consider. The cathode strip chambers, drift tubes, and resistive plate chambers described in section 2.2.5 all overlap and must be combined in each TT. Furthermore, the TPs in the muon L1 system are not merely energy depositions. Instead, the muon detector subsystems provide energy, coordinate, and quality information that is later used to reconstruct a track.


### 3.1.2 The L1 Trigger Architecture

The calorimeter L1 trigger consists of two distinct layers of processing. Layer-1 receives the inputs directly from the TPs listed above, and sorts and calibrates them rapidly. Layer-2 takes the outputs from Layer-1 and performs primitive calibration and reconstruction, which allows the trigger to roughly identify physics objects such as electrons,  $\tau$  leptons, and jets. A rather complex time-multiplexed hardware system is used in Layer-2, which allows the low, fixed latency necessary at the L1 trigger. Layer-2 consists of several separate reconstruction algorithms, of which primarily the  $e/\gamma$  reconstruction algorithm is of interest for the  $H \rightarrow \gamma\gamma$  trigger. Details of this reconstruction will be provided in the next section. Once the objects are reconstructed, they are passed to the next stage in the trigger system.

The muon L1 trigger has 3 separate muon track finders (MTFs) which aim to reconstruct tracks in three distinct regions of the detector (barrel, endcap, and overlap). In the barrel, only the DT and RPC TPs are used to reconstruct tracks. In the endcap, only the CSC and RPC TPs are used to achieve the same goal. In the overlap region, all three subdetectors are combined. These MTFs feed their outputs directly to the global muon trigger ( $\mu$ GMT), which receives up

to 108 muon tracks per event. The  $\mu$ GMT then sorts the tracks and removes duplicates. The final output of the muon triggers has at most 8 muon tracks.

Both the Layer-2 calorimeter trigger and the  $\mu$ GMT output to the Global Trigger ( $\mu$ GT). The  $\mu$ GT combines this information using a set of complex algorithms called the trigger menu described below in section 3.1.4. Six independent boards are used to distribute the processing of the L1 menu, and a final decision is rendered on whether to keep or discard an event. Below, in figure 3.1, a schematic of the full process from TPs to  $\mu$ GT is reproduced from [14].



**Figure 3.1.** A diagram of the L1 Trigger architecture, where the lefthand tree corresponds to the muon triggers and the righthand tree to the calorimeter triggers. Reproduced from [14].

### 3.1.3 The L1 $e/\gamma$ Reconstruction

Since photons and electrons have no associated tracking information, the only way that they can be identified is by their energy signatures.

### **3.1.4 The L1 Menu**

## **3.2 The Data Acquisition System (DAQ)**

## **3.3 High Level Trigger**

The final step of triggering before data is output for analysis, the HLT aims to reduce the rate from the 100kHz output by the L1 trigger down to a total of just 5kHz [9]. In contrast to the hardware-based L1 trigger, the HLT is a software-based suite of triggers that runs on a dedicated server of processors called the HLT filter farm.

### **3.3.1 HLT Event Reconstruction**

### **3.3.2 HLT Trigger Rates and Timing**

### **3.3.3 HLT Software and ConfDB**

## **3.4 Analysis Software**

### **3.4.1 Offline Reconstruction**

### **3.4.2 The NanoAOD File Format**

### **3.4.3 NanoAOD Event Reconstruction**

### **3.4.4 HiggsDNA**

# Chapter 4

## Boosted Decision Trees and XGBoost

The newly-proposed trigger and complementary offline selection – discussed in chapters 5 and 6, respectively – is based on a machine learning construct called a Boosted Decision Tree (BDT). This ML method provides a robust and relatively simple algorithm for binary classification problems, which works well both with the HLT and with subsequent offline classification and event selection. The theoretical details and structure of BDTs is described in section 4.1. The software package XGBoost (short for eXtreme Gradient Boosting) will be used for both the creation and evaluation of the BDTs employed at the trigger and offline analysis levels. This software is described in more detail in section 4.3.

### 4.1 Gradient Descent Boosting

The original description of boosted decision trees and gradient descent boosting is described in "Greedy Function Approximation: A Gradient Boosting Machine" by Jerome H. Friedman [6]. The following section is largely based on this seminal paper, with emphasis placed on the facets of the technique most relevant to this paper.

At its core, a binary classification problem is a function estimation problem; a function must be constructed that maps some input values onto a single output score. The general parlance is to label the input variables for a single event as  $\vec{x} = \{x_1, x_2, \dots, x_n\}$ , where  $n$  is the total number of selected input values. The output, however, is a single score, usually labeled  $y$ . There exists



some theoretical function,  $F^*(\vec{x})$  that directly maps  $\vec{x}$  onto  $y$ . This function cannot be known exactly for problems of moderate complexity, so an estimate of this function,  $\hat{F}(\vec{x})$ , is the goal of the gradient boosting process.

To quantify how closely the approximation  $\hat{F}(\vec{x})$  follows the true  $F^*(\vec{x})$ , some loss function must be defined. There are many forms of loss function, as will be described in section 4.2. The loss function is termed  $L(y, F(\vec{x}))$ , meaning that it quantifies how closely the approximate points,  $F(\vec{x})$ , follow the true classification values of the events,  $y$ . Given these definitions, the goal of the BDT algorithm can be written as given by Friedman [6].

$$F^* = \min_F E_{y, \vec{x}}[L(y, F(\vec{x}))] \quad (4.1)$$

## 4.2 The Objective Function

## 4.3 XGBoost Software

## Chapter 5

# Development of an MVA-Based High Level Trigger

### 5.1 Limitations and Benefits of Current $H \rightarrow \gamma\gamma$ Trigger

As discussed in section 3.3, the current  $H \rightarrow \gamma\gamma$  HLT uses hard cuts on kinematic, isolation, and showershape variables to select events. While cuts on some of these variables – such as  $R_9$  and H/E – serve to remove low quality photon candidates, others reduce the phase space of the trigger while not necessarily increasing the quality of the analysis. Principally, the current HLT makes rather tight cuts on the  $p_T$  of the two photon candidates. These cuts significantly reduce the trigger rate, as many background processes produce showers with low  $p_T$ . Many signal events, however, have at least one candidate with low  $p_T$ . It will be shown in section 5.3 that these  $p_T$  cuts significantly decrease the acceptance of simulated Monte Carlo signal events. Since many future analyses will be searching for either very rare processes or physics beyond our current understanding of the standard model, constraining the phase space of available information may affect the collaboration’s ability to probe novel processes.

The relative simplicity of the standard HLT, however, provides multiple benefits. Firstly, the numerical cuts can be closely examined and understood very easily. Though the cuts have been relatively stable in time, they may adjusted and reexamined with relative ease. The effects of cuts on individual variables can be quantified, which allows maximum transparency into how a decision is made on an event-by-event basis. Secondly, a decision for each event can be made

very rapidly. As discussed in section ??, minimizing computation time for each event is vital given the huge number of triggers deployed at the trigger farm. Since all of the quantities used by the current HLT are already being saved for each event, there is very little additional computation needed to arrive at a triggering decision. Any proposed changes to the  $H \rightarrow \gamma\gamma$  trigger must have minimal impact on decision speed given the stringent restrictions on computation time.

## 5.2 Development of a Boosted Decision Tree for Photon Candidate Classification

The HLT is a binary classification problem, where the two classes are signal events to keep and background events to discard. While the HLT is a per-event selection,  $H \rightarrow \gamma\gamma$  events contain two photon candidates. As described in 3.3, the current HLT first makes requirements on individual photons, then applies a final filter that considers both photons together. Our MVA-HLT uses a similar philosophy; a binary classifier can be used to calculate an identification score for each photon, then combined cuts can be made on these scores for two photon candidates. The process of creating the MVA-HLT, then, is twofold. Firstly, the single photon binary classifier must be constructed such that signal-like photon candidates are given a high score and background-like photon candidates are given a low score. Secondly, cuts on both photon candidate scores must be selected such that the signal efficiency is maximized while the data rate is minimized.

### 5.2.1 XGBoost-Based BDT Software

XGBoost is a commonly-used software package throughout CMS, as it excels at binary classification problems. Specifically, Boosted Decision Trees (BDTs) are used commonly in CMS software (REF?). BDTs provide a good balance between model complexity and transparency. By tuning a relatively small number of model hyperparameters, as discussed in section 5.2.4, model complexity can be controlled and understood. For the development of this BDT, the python version of XGBoost was used, though the final implementation of the model must be done in the

C-based CMSSW (as discussed in section 5.4).

### 5.2.2 Signal and Background Samples for Classification

The first – and perhaps most important – step in creating a binary classifier is selecting samples on which to train the BDT. It is important that the signal sample chosen accurately represents the type of events that should be kept at the HLT, while the background sample must encompass all possible source of background events.

#### Signal Samples

As discussed in (REF?), Monte Carlo simulations exist for various physics processes that contribute to  $H \rightarrow \gamma\gamma$ . While there are several common production modes for the Higgs boson (as discussed in section (REF?)), gluon fusion Higgs production (ggH) has the largest production cross section. In addition to the large cross section, ggH production has fewer associated productions when compared to VBF or ttH Higgs production. For these reasons, ggH signal MC provides a clean signal that maximizes the photon discrimination ability of a BDT.

In order to validate the performance of the model, the acceptance of these signal MC events must be quantified. As a result, half of the sample is used for training, while the other half is reserved for later validation. Events are split by event number into two separate categories: even event numbers are used for the training sample, and odd event numbers will be used for the validation of the model performance.

#### Background Samples

At the trigger level, background simulation poses a major challenge. Background events for  $H \rightarrow \gamma\gamma$  fall into three major categories: events containing two photons diphoton, events containing a photon and a jet, and events containing two jets. While it is possible to simulate these background sources, the simulation – especially of the jet-jet events – is challenging and therefore may not perfectly align with the real data. The most obvious resolution to this issue is to simply treat the data sample as background. While, of course, the goal of the trigger is to

**Table 5.1.** Table of input variable names, and a short description of each.

| Variable Name          | Description                                                                                   |
|------------------------|-----------------------------------------------------------------------------------------------|
| Raw Energy             | The total energy deposited in the 5x5 supercluster                                            |
| $R_9$                  | The proportion of the energy contained in the central 3x3 crystals relative to the raw energy |
| $\sigma_{i\eta i\eta}$ | The covariance in terms of crystal spacing ( $i_\eta$ )                                       |
| $\eta_{SC}$            | The eta coordinate of the center of the supercluster                                          |
| $\eta$ Width           | The supercluster width in $\eta$                                                              |
| $\phi$ Width           | The supercluster width in $\phi$                                                              |
| H/E                    | The ratio of the total supercluster energy measured in the HCal to that measured in the ECal  |
| ECalPFIso              | The isolation energy of the particle deposited in the ECal                                    |


preserve signal signatures from the data, it has been shown in chapter ?? that the overall expected count of signal events in this data sample is relatively low. As long as a clean signal sample is provided to the BDT, the incredibly small percentage of possible  $H \rightarrow \gamma\gamma$  events in the data should not appreciably mar the model’s ability to differentiate signal and background photon candidates. As with the signal MC, even event numbers are used for the training, while odd event numbers are reserved for later validation of model performance.

### 5.2.3 Determination of Input Variables

After signal and background samples are selected, input variables for the BDT must be chosen such that signal and background events can be separated. The most obvious starting place for this is by analogy to the current HLT; since cuts on the kinematic, isolation, and showershape variables have been successfully used in the preexisting trigger, a BDT should be able to use these variables to even greater effect. Below, in table 5.1, the chosen input variables are listed along with their definitions.

The chosen variables are largely showershape and isolation variables, as these can be used to differentiate a legitimate photon signature from a jet shower. A major goal of the BDT is to increase kinematic coverage; relying primarily on showershape variables ensures that the selection is not biased towards a specific kinematic region. Below are plots of the above input


variables, where the signal MC is shown in dark (barrel) and light (endcap) blue, while the data is shown in red (barrel) and pink (endcap). These distributions are self-normalized, so the y-axis value corresponds to the ratio of events in that bin versus the entire distribution.



**Figure 5.1.** Plots of raw supercluster energy and  $R_9$ . The signal MC is shown in dark blue for the barrel and light blue for the endcap, whereas the data (background) is shown in red for the barrel and pink for the endcap.

The raw supercluster energy gives a measure of the total energy deposited in the ECal supercluster. In figure 5.1a, it can be seen that the signal MC has a slightly higher center than the background in the barrel. This difference is more pronounced in the endcap, however, where the signal MC has a considerably higher average raw energy. The separation in these two detector regions is not major, however. The  $R_9$ , on the other hand, proves to be a very well-separated training variable. For both the barrel and endcap, the signal distributions seen in 5.1b are very well-peaked near 1. This means that most of the signal MC events have a very large percent of their energy deposited in the central 3x3 crystals of the supercluster. This is often the case for real photons, as their geometric extent is smaller than that of jets. The data, however, is a much broader distribution. While it peaks near 1, there are still many photon candidates with

$R_9$  approaching lower values. Since QCD jets tend to have a larger geometric extent, this is expected. As a result, this is a very strong discrimination variable for the binary classifier BDT.




**Figure 5.2.** Plots of the  $\sigma_{i\eta i\eta}$  and  $\eta_{SC}$ . The signal MC is shown in dark blue for the barrel and light blue for the endcap, whereas the data (background) is shown in red for the barrel and pink for the endcap.

The  $\sigma_{i\eta i\eta}$  is another showershape variable that has powerful discrimination abilities. As can be seen in figure 5.2a, the barrel and endcap are rather well-separated for both the MC and data. This is due to the difference in crystal positioning in the two detector regions; since the endcap crystals are larger with larger spacing as described in section 2.2.2, the  $\sigma$  in terms of the crystal spacing tends to be larger. Additionally, it is immediately obvious that the photon candidates from the signal MC are much more sharply peaked in both the barrel and endcap relative to the data events. Given that many of the data events contain QCD jets, this is to be expected.

The  $\eta_{SC}$  can help provide information on the kinematics of the event, as different reactions and decays will be arranged differently. While the barrel and endcap are self-normalized here, the relative difference in shapes for signal and background in both the barrel and endcap can


be examined. In the barrel, it is clear that the single Higgs signal MC tends to be more central, while the data sample eschews this region in favor of the higher- $\eta$  regions of the barrel. These kinematic differences are less pronounced in the endcap, where the signal MC and data shapes are relatively similar.



**Figure 5.3.** Plots of the  $\eta$  and  $\phi$  widths. The signal MC is shown in dark blue for the barrel and light blue for the endcap, whereas the data (background) is shown in red for the barrel and pink for the endcap.

Next, the  $\eta$  and  $\phi$  widths (in figure 5.3) are shower shape variables that provide further information of the geometric extent of the ECal energy deposition. As with the  $\sigma_{i\eta i\eta}$ , the expected shapes of these distributions are affected by the crystal geometry – as a result, the endcap and barrel distributions are expected to differ. Still, the signal MC and data can be seen to show some separation within the barrel and endcap. On average, the data has higher width in both  $\eta$  and  $\phi$  relative to the signal MC.





**Figure 5.4.** Plots of the H/E and isolation. The signal MC is shown in dark blue for the barrel and light blue for the endcap, whereas the data (background) is shown in red for the barrel and pink for the endcap.

The H/E in figure 5.4a is a powerful variable for separating photon-like ECal signatures from those originating from QCD jets. Measuring the ratio of how much energy is deposited in the HCal versus the ECal gives some idea of how likely to be a hadronically-produced signature the photon candidate is. Theoretically, a true photon would deposit purely in the ECal, leaving virtually 0 energy signature for the HCal behind it. As a result, real photons should have an H/E near 0. Clearly, the figure shows that this is largely true for the signal MC, whereas the data events – which are largely composed of jet-like candidates – have on average much higher H/E values. In fact, there are very few data events with an H/E in the first bin, while nearly 40% of signal events exhibit this behavior. As a result, this is a very strong separation value for the BDT.

The isolation, measured in units of energy (GeV), helps measure how much additional energy is deposited outside of the central supercluster. For jet-like events, this value is expected to be higher than true photon signatures; since QCD processes generally produce multiple wide jets together, it is expected that much energy will be deposited immediately near the supercluster.

Real photons, on the other hand, are more likely to provide a clean energy deposition with little additional surrounding sources of energy. As seen in figure 5.4b, this truth is borne out by the difference between the signal MC and the data. While there are still data events in the first bin near 0 isolation energy, there are nearly 3x as many events in this bin in the signal for both the barrel and endcap. This illustrates the power that this variable provides the BDT.

## 5.2.4 Hyperparameter Tuning

Once the input samples and variables are determined, the technical details of the model must be optimized. The structure of the BDTs is determined by the hyperparameters of the model as discussed in chapter 4. The most fundamental hyperparameters are the maximum depth, the learning rate, and the total number of trees in the model. The max depth and number of trees directly determine the complexity of the model. A model with more trees will, based on the boosted gradient descent method discussed in chapter 4, more precisely estimate the function that maps the chosen input variables from the training sample onto the correct labels of signal versus background. To mitigate the risks of overtraining the model, XGBoost early stopping is used to determine the number of trees. As the software adds additional trees to the ensemble, it measures the chosen objective function at each step on a testing sample not used in the training. Early stopping ends the training of the model when the chosen metric hasn't improved in a chosen number of rounds. For this training, 50 early stopping rounds were used and the area under the curve (AUC) was used as the target metric. So, then, this hyperparameter is essentially fixed while the others must be optimized.

The maximum depth controls the complexity of each individual tree in the ensemble. As discussed in chapter 4, the depth determines the number of layers each tree is able to employ. Deeper trees generally allow more precise mapping from input values to output scores at the cost of computation time; each layer of depth constitutes another set of weights that must be computed for each tree. Since it is vital that the computation time is minimized at the trigger level, this is a major consideration. Deeper trees also tend to overfit the training data more, as

there are essentially more degrees of freedom with which to fit the mapping function. So, the max depth must be kept as low as possible to avoid both overfitting and unreasonable computation time.

The learning rate controls the size of the individual feature weights from each new tree added to the ensemble. A higher learning rate allows each tree to have higher weights, which will therefore affect the model performance more drastically. Lowering the learning rate makes the model more conservative, as it reduces the overall change to the model predictions provided by each additional tree. Having a higher learning rate generally reduces the number of trees necessary to converge, but decreases the accuracy since statistical fluctuations within each tree can be assigned higher weights.

It was found that the max depth and learning rate are best optimized in tandem; as the trees become more complex (higher max depth), it was found that making the individual steps more conservative (lower learning rate) led to less overfitting and higher performance. As a result, a 2D grid search was used to optimize these two hyperparameters. A range of both max depth and learning rate was defined, then a model was trained for each combination. The resulting models were appraised in terms of not only their objective scores (AUC and logistic loss in this case, both described in chapter 4), but also in terms of the number of trees and the overall model size in megabytes. Since the model must be loaded into RAM at the trigger farm and then the weights applied to each photon in each incoming data event, a model taking up more space will increase both the computation time and memory load at the trigger level.


After many trials, the best balance of model performance, minimization of overfitting, and model size was found to be a max depth of 7 and a learning rate of 0.25. Experimentally, it was determined that many of the other hyperparameters had minimal impact on the model performance and size, so they were therefore left at their default values.

### 5.3 Determination of BDT Cuts

After the tuning and training of the model was optimized, a score is generated for each photon in each event. Each event may contain several photon candidates, but the job of the HLT is to determine if any pair of candidates exists that plausibly originates from  $H \rightarrow \gamma\gamma$ . Given that the BDT was trained such that photons originating from  $H \rightarrow \gamma\gamma$  MC are assigned a high score and background processes are given a low score, the photon candidates are first sorted by the output BDT score. Then, the highest two scores can be selected and the values analyzed for both signal MC and data events.

Since the HLT path simply renders a decision about whether an event contains a  $H \rightarrow \gamma\gamma$  process, cuts on the pairs of output scores must be chosen such that the number of signal events kept is maximized (high signal efficiency) while the total number of data events kept is minimized (low trigger rate).

Below, in figure 5.5, the high and low scores for signal MC are shown at left. Since these are purely signal events, it is expected that the scores to be clustered near 1. As can be seen, the higher of the two scores (along the x axis) tends to be above 0.9 for a large percentage of events. Meanwhile, while the lower of the two scores does cluster above 0.8, there is still a large band of score values extending down to 0. This means that there are many signal events for which one photon has a very high score, but the second photon has a lower score.



**Figure 5.5.** XGBoost output scores for two selected photon candidates in the Winter 2024 ggH signal MC. The higher of the two scores is plotted on the X-axis, while the lower of the two is plotted on the Y-axis.

Next, consider the scores of the data sample shown at right in in 5.5. Given the rarity of  $H \rightarrow \gamma\gamma$  events at the trigger level, it is expected that essentially all of these data events correspond to background processes. As a result, the vast majority of these data photon candidates should be assigned a BDT score close to zero. As can be see, the lower of the two photon scores very rarely extends above 0.1. Though the higher of the two scores is often close to 0, there are still many events where the value extends towards 1. Since this BDT is designed to indentify individual photon candidates, it can be inferred that many of these data events have one real photon (which is a major source of background as discussed in section 5.2.2).

As discussed in section 5.2.1, the single photon BDTs are trained separately for photon candidates in the barrel and those in the endcap. Due to the separate trainings – as well as the differences in kinematics and detector geometry – the score distributions for barrel and endcap photon candidates are not perfectly equivalent. As a result, the chosen cuts must be tuned separately for the barrel and endcap photons. This presents an issue, as diphoton events may contain two barrel photon candidates (BB), two endcap photon candidates (EE), or one photon


candidate in each region of the detector (BE). The simplest way to deal with this is to choose the single photon cuts by reference to the BB and EE distributions, then apply the chosen barrel and endcap cuts to all photons in either region.

Given the shapes of the output distributions in figure 5.5, it is clear that a single cut value for both photons will not achieve maximum signal efficiency. While many of the high score photons are clustered above 0.9, there are still many events with a second photon candidate that has a lower score. In order to preserve these signal events while still removing much of the background, cuts can be selected such that the cut value on the lower score depends on the higher score. For first photons with a very high score, a very loose cut can be applied to the second photon. As the score of the first photon decreases, the cuts on the second photon can be tightened. In the case where the first photon has a relatively low score, a tighter cut is applied on the second photon to help reduce the number of events with two bad photon candidates in the data while still preserving much of the signal. Since the data at the trigger level is strongly dominated by di-jet or single photon events, these cuts can drastically reduce the data rate while still preserving much of the signal. These cuts were experimentally determined, and are tabulated in table 5.2.


**Table 5.2.** Chosen score cuts for BB and EE events

| (a) Score cuts for BB events |                   | (b) Score cuts for EE events |                   |
|------------------------------|-------------------|------------------------------|-------------------|
| High Score                   | Minimum Low Score | High Score                   | Minimum Low Score |
| 0.92                         | 0.02              | 0.95                         | 0.04              |
| 0.85                         | 0.04              | 0.85                         | 0.08              |
| 0.30                         | 0.14              | 0.5                          | 0.20              |

Events that satisfy these requirements can be plotted on top of figures 5.5 . In figure 5.6 and 5.7 below, the selected events for BB and EE can be seen, respectively, in red. Yellow lines are added to the plots to demarcate the cuts. These plots contain both the signal MC (left) and the Data (right).



**Figure 5.6.** XGBoost output scores for two selected photon candidates in the Winter 2024 ggH signal MC (a), and 2023 Data (b). The higher of the two scores is plotted on the X-axis, while the lower of the two is plotted on the Y-axis.




**Figure 5.7.** XGBoost output scores for two selected photon candidates in the Winter 2024 ggH signal MC (a), and 2023 Data (b). The higher of the two scores is plotted on the X-axis, while the lower of the two is plotted on the Y-axis.

This choice of cuts, clearly, is able to preserve much of the signal MC while accepting


very few of the data events examined. While the overall signal efficiency and data rate are key metrics to appraise our MVA-HLT, it is also important to examine where in the kinematic phase space events are being gained relative to the standard diphoton HLT. While a more complete measurement of this will be shown in chapter 7, a preliminary analysis can be made with the cuts applied in this initial development framework.

Below, plots of selected kinematic variables are shown. The events accepted by the current diphoton HLT are shown in green, while the events accepted by the new MVA-HLT are shown in blue. As with the previous score plots, the Winter24 GGH signal MC will be shown at left, whereas the 2023 Data will be shown at right.





(a)




(b)

**Figure 5.8.** Diphoton mass for the signal MC (a) and data (b). Events accepted by the MVA-HLT are shown in blue, while events accepted by the standard HLT are shown in green.


Beginning with the mass, it can immediately be seen that MVA-HLT accepts 94.2% of signal MC events, which is an approximately 13.6% relative gain in signal efficiency compared to the 82.9% acceptance of the standard diphoton HLT. Additionally, the data rate appears considerably lower; while the standard HLT accepts 1.44% of the analyzed events, the MVA-HLT only accepts 0.86%, which corresponds to a 40.3% reduction in data rate.

One major consideration when examining the mass is the measured mass width of the accepted signal events. Generally, a more narrow peak is considered a cleaner signal. By treating the mass distribution as approximately gaussian, the width can be easily understood by measuring the standard deviation. Since the distribution is only approximately gaussian, it is safer to instead construct the quantity  $2\sigma_{effective}$ , which is simply the width (in  $GeV/c^2$ ) that contains 95% of the peak. Although this is not a statistically rigorous construct, it can be used to compare the approximate shapes of similar distributions in an internally consistent way. It can be seen that the  $2\sigma_{effective}$  is marginally increased for the MVA-HLT, reaching 6.58 compared to the 6.07 of the events accepted by the standard trigger. Some increase in width is to be expected, as accepting more events will necessarily bring the distribution closer to the "all" curve that has a wider width than either selection.

(Statments about the background mass distribution?)



(a)




(b)


**Figure 5.9.** Photon  $\eta$  for the signal MC (left) and data (right). Events accepted by the MVA-HLT are shown in blue, while events accepted by the standard HLT are shown in green.

Above, the next kinematic variable shown is the  $\eta_{sc}$  of both photons plotted together. As seen in both signal and background, the separation between the ECal Barrel (EB) and ECal Endcap (EE) can be seen at  $\eta_{sc} \approx \pm 1.5$ . For the signal, throughout the barrel, both the MVA-HLT and standard HLT accept photon candidates in relatively constant proportion to the total distribution, though the MVA-HLT has overall improved acceptance. While the MVA-HLT still has relatively constant acceptance in the EE, it can immediately be seen that the standard HLT is excluding many events in the lowest- $\eta_{sc}$  region of the endcap. Investigations have shown that this is due to the  $R_9$  cuts made within the trigger. This represents a reduction in kinematic coverage for the standard HLT, whereas the MVA-HLT is able to resolve this issue and maintain maximum kinematic coverage.

Considering the background, it can immediately be seen that the MVA-HLT has a relatively flat acceptance in both the EB and EE, while the standard HLT appears to accept more data at the extreme- $\eta_{sc}$  regions of the endcap. As can be seen from the MC, this region tends to contain less of the  $H \rightarrow \gamma\gamma$  signal events and therefore represents a lower signal to background ratio.



(a)



(b)

**Figure 5.10.** Photon  $E_T$  for the signal MC (left) and data (right). Events accepted by the MVA-HLT are shown in blue, while events accepted by the standard HLT are shown in green.

Finally, consider the transverse energy of the photon candidates,  $E_T$ . Here, both candidates are again shown on the same plot, which explains the double-peaking behavior in the background distribution. The standard diphoton HLT contains cuts at 30 and 22  $GeV/c^2$  for the lead and sublead photon, respectively. The sublead cut can clearly be seen in both the signal, at left, and the background at right. While the new MVA-HLT selection accepts more of these low- $E_T$  photons, it is clear that little of the gain comes from this kinematic region. Below about 30  $GeV/c^2$ , both selections tend to cut out many photons from the total distribution. In the case of the MVA-HLT, this is likely due to those photon candidates being of lower quality and therefore being assigned a lower BDT score.

Below, in table 5.3, the acceptance percentages are given for the 3 different diphoton  $\eta_{sc}$  configurations, as well as the total acceptance for both signal and background, compared to the standard HLT cuts.

**Table 5.3.** Signal efficiencies and background acceptances for both triggers, broken down by diphoton  $\eta_{sc}$

| (a) Signal Efficiencies |            |             | (b) Data Acceptances |            |             |
|-------------------------|------------|-------------|----------------------|------------|-------------|
| Region                  | MVA-HLT(%) | Std. HLT(%) | Region               | MVA-HLT(%) | Std. HLT(%) |
| B-B                     | 95.93      | 89.32       | B-B                  | 0.65       | 1.06        |
| B-E                     | 91.91      | 74.10       | B-E                  | 1.20       | 2.17        |
| E-E                     | 89.46      | 76.85       | E-E                  | 0.58       | 1.07        |
| All                     | 93.86      | 82.64       | All                  | 0.88       | 1.56        |

## 5.4 Final Implementation in HLT Menu

As discussed in section 3.3.3, triggering and event reconstruction is handled by the distributed CMSSW software framework. As a result, any proposed trigger developments must be deployed in a central CMSSW release. While the software strategy is the same as the original python implementation, the code must of course be rewritten in C and adapted to work within the trigger.

As described in section 3.3, the HLT operates on all photon candidates in an event, then

simply renders an event-by-event decision if any pair of photons satisfy the chosen conditions. As a result, the first step of the implementation is to create a module that calculates the BDT score for each photon candidate in every event. Once these scores are stored within the trigger path, another module must be constructed to check if any possible pair of photon candidates passes the two-fold cuts described above. Importantly, due to the constraints on storage space, the scores of the individual photon candidates cannot be saved to the event. As a result, the only output from the MVA-HLT is a decision on whether the event should be accepted or rejected.

Luckily, these two modules are the only software additions required to add the BDT to the trigger menu. Beyond that, standard modules can be used (with some modifications to the cuts made) within ConfDB to construct the entire trigger path as discussed in section ?? . The first step of the HLT path is to require the necessary L1 triggers. The standard L1 suite required by the existing HLT is used here, which consists of a combination of single and double EGamma triggers as described in section 3.1.

In order to reduce the amount of MVA scores that must be calculated, the very loose kinematic cuts are applied to all photon candidates in the event as the first step. While these cuts are quite loose, they still serve to reduce the number of candidates considered. Since many data events may have many photon candidates, this will help reduce the time taken to calculate the BDT scores. (Is this true? Do individual photon candidates get removed at the HLT level, or just events?)

With the preliminary cuts in place, the module that calculates the scores is placed in the HLT path, followed by the module that makes the cuts as described in section . Finally, a combined module is created that combines these BDT cuts on both photons with a mass cut of  $M_{\gamma\gamma} > 90 \text{ GeV}/c^2$ . So, then, the whole HLT path serves to check if there is any possible pair of photon candidates that passes the loose kinematic cuts, the pairwise BDT cuts, and the  $M_{\gamma\gamma}$  cut. If any pair satisfies these conditions, a flag is added to the event and all photon candidates are kept at the RAW level.

# Chapter 6

## MVA-Based Offline Preselection

As discussed in chapter 3, the HLT is one of the first steps in selecting data and MC events for analysis. Once a decision has been rendered by the HLT, the event is read out and saved in either the appropriate data stream or in the corresponding MC sample. Once these files are read in by the analysis software – in this case HiggsDNA as described in section 3.4.4 – further selection cuts are made to create a final analysis sample on which measurements can be made.

### 6.1 Current Diphoton Preselection

The current diphoton selection is created by direct analogy to the standard diphoton HLT; firstly,  $p_T$ , showershape, and isolation cuts are made on individual photons in an event, then the single photons are paired together and cuts are made on the resulting diphoton. In the case of the HLT, a simple diphoton mass cut is made. At the offline analysis level, however, the diphoton cuts are made on  $p_T/M_{\gamma\gamma}$ .

The  $H \rightarrow \gamma\gamma$  preselection is described in detail in [12]. First, loose cuts of  $p_T > 20\text{GeV}/c$ ,  $R_9 > 0.5$ ,  $H/E < 0.08$ , and  $idMVA > 0.9$  are applied to each photon candidate. Additionally, the  $|\eta_{sc}|$  is constrained to be below 2.5, and the gap region between the EB and EE is excluded ( $1.444 < |\eta_{sc}| < 1.556$ ). Additionally, the electron veto is required to exclude photons originating from electron tracks. Beyond that, the remaining isolation and showershape cuts are only applied



**Table 6.1.** Table showing the cuts applied by the standard preselection for  $H \rightarrow \gamma\gamma$ .

| Region | $R_9$      | H/E      | idMVA     | $\sigma_{i\eta i\eta}$ | Pho Iso (GeV) | Track Iso (GeV) |
|--------|------------|----------|-----------|------------------------|---------------|-----------------|
| Barrel | [0.5,0.85] | $< 0.08$ | $' > 0.9$ | $> 0.015$              | $< 4.0$       | $< 4.0$         |
|        | $> 0.85$   | $< 0.08$ | $> 0.9$   | –                      | –             | –               |
| Endcap | [0.5,0.9]  | $< 0.08$ | $> 0.9$   | $> 0.035$              | $< 4.0$       | $< 4.0$         |
|        | $> 0.9$    | $< 0.08$ | $> 0.9$   | –                      | –             | –               |

on low- $\eta$  photons. Above  $R_9 = 0.85$  in the barrel and  $R_9 = 0.90$  in the endcap, no further preselection cuts are applied. For photons below these  $R_9$  thresholds, cuts are applied on the  $\sigma_{i\eta i\eta}$ , photon isolation, and track isolation. Finally, the electron veto (described in REF) is required for each photon candidate. This veto decision is designed to identify and remove energy signatures associated with a track, which are likely to be electrons.

Once these single photon preselection cuts are applied, all remaining photon candidates are paired together into a collection of diphotons. For each pair, the higher of the two photons must satisfy  $p_T > 30\text{GeV}/c$ . Paired with the baseline requirement of  $p_T > 20\text{GeV}/c$ , these cuts closely mimic the 30 and 22 GeV/c cuts applied at the trigger level. Then, the  $p_T/M_{\gamma\gamma}$  cuts are applied to the diphoton pairs. At this point, many of the possible photon combinations have been removed. A final diphoton combination must be selected, however, as HiggsDNA is designed to output a single photon pair of photons. The remaining pairs in the event are sorted by their diphoton  $p_T$ , and the pair with the highest value is written out into the event [12]. These cuts, in their totality, are shown in table 6.1

There is no explicit  $M_{\gamma\gamma}$  cut applied within the preselection, as the possibility for high- and low-mass Higgs analysis is left open. For the purposes of comparing this preselection to the new MVA-based selection, only the standard mass Higgs is considered. So, a loose cut of  $90 < M_{\gamma\gamma} < 180\text{GeV}/c^2$  is applied to all resulting diphotons.

## 6.2 Development of MVA-Based Offline Preselection

Since the offline selection is designed to cover the HLT used, it is clear that applying the preexisting preselection described above on top of the MVA-HLT is a suboptimal strategy. In fact, since these cuts mirror the standard HLT quite closely, it is expected that applying the standard preselection on top of the MVA-HLT would likely reduce or even entirely remove the signal efficiency gains obtained by the new trigger. As a result, an alternative set of preselection cuts must be proposed that allows the trigger-level gains to be realized at the offline analysis level.

Just as the standard preselection cuts are designed to not only cover the standard HLT but work in much the same way, a new preselection can be created with maximum similarity to the MVA-HLT. One major complication of this is that the same BDTs cannot be used for both the trigger and offline selection. Since the reconstruction differs for the NanoAOD vs the RAW, the input variable distributions will be different enough that the models are not directly comparable. Instead, a new BDT-based preselection framework must be developed and its coverage of the MVA-HLT must be analyzed.

### 6.2.1 Creation of Single Photon BDTs

#### A $\gamma + Jet$ BDT

As discussed in section 6.1, there already exists an MVA within the standard preselection. While this idMVA is now a centralized part of the NanoAOD format, historical preselections used an MVA trained on  $\gamma + Jet$  MC (REF?). Events in  $\gamma + Jet$  MCs will contain one real (prompt) photon and one jet that looks like a photon, termed a "fake". This MC provides a very easy-to-use training sample, as one can simply use the prompt  $\gamma$  as the signal photon and the fake as the background photon. This standard  $\gamma + Jet$  idMVA is usually only used to make relatively loose cuts as part of the much broader preselection cuts as described above.

The original idMVA was trained using many of the variables from the preselection as

**Table 6.2.** Table of input variable names for the offline  $\gamma + Jet$  MVA, and a short description of each. The final two variables are only used for training the endcap.


| Variable Name                      | Description                                                                                   |
|------------------------------------|-----------------------------------------------------------------------------------------------|
| Raw Energy                         | The total energy deposited in the 5x5 supercluster                                            |
| $R_9$                              | The proportion of the energy contained in the central 3x3 crystals relative to the raw energy |
| $S_4$                              | The proportion of the energy contained in the central 2x2 crystals relative to the raw energy |
| $\sigma_{i\eta i\eta}$             | The covariance in terms of crystal spacing ( $i_\eta$ )                                       |
| $cov(i\eta i\phi)$                 | The covariance between the $\eta$ and $\phi$ coordinates                                      |
| $\eta_{SC}$                        | The eta coordinate of the center of the supercluster                                          |
| $\eta$ Width                       | The supercluster width in $\eta$                                                              |
| $\phi$ Width                       | The supercluster width in $\phi$                                                              |
| H/E                                | The ratio of the total supercluster energy measured in the HCal to that measured in the ECal  |
| PhoIso03                           | The photon isolation                                                                          |
| Charge Iso<br>w.r.t. Worst Vertex  | The charged isolation for the worst vertex determined by the vertexing algorithm              |
| Charge Iso<br>w.r.t. Chosen Vertex | The charged isolation for the chosen vertex determined by the vertexing algorithm             |
| $\rho$                             | The event energy density                                                                      |
| esEffSigmaRR                       | temp                                                                                          |
| esEnergyOverRawE                   | temp                                                                                          |

input variables. These same input variables were used as a starting point for a new  $\gamma + Jet$  MVA, with the addition of H/E. By adding this variable to the inputs, the new  $\gamma + Jet$  MVA contains the same information available to the standard preselection described above. Additionally, this allows the offline selection model to more closely mirror the MVA-HLT. The input variables used are shown below in table 6.2. As with the MVA-HLT, the barrel and endcap models are trained separately, with individual photons selected based on their location in the detector.

As with the trigger level BDT, the separation between the signal and background in the various input variables can be examined. For the subsequent plots (6.1-6.7), the prompt and fake will be shown for both the barrel and endcap, as the trainings are separated. The prompt photons will be shown in dark and light blue for the barrel and endcap, respectively. The fake distributions will be shown in red and pink for the barrel and endcap, respectively. All the input

variable distributions have been normalized to 1, so that their shapes can be directly compared.


The SC raw energy, in 6.1a, shows rather clear separation for both the barrel and endcap. It can be seen that the prompt photons tend, on average, to have higher total supercluster energy than the fake photons. The separation in  $\eta_{SC}$ , however, is primarily seen in the endcap, where the fake photons tend towards the higher values. Since the BDT works by creating correlations between variables, and the  $\eta_{SC}$  is a strongly kinematic-dependent variable, it will still be shown to be a relatively powerful discrimination variable.



**Figure 6.1.** Plots of the Supercluster raw energy and  $\eta_{SC}$ . The prompt signal is shown in dark blue for the barrel and light blue for the endcap, whereas the fake background is shown in red for the barrel and pink for the endcap.


Next, the energy ratios,  $R_9$  and  $S_4$  can be examined. It is expected that a real (prompt) photon will have relatively well-localized energy; since the photon is a relatively clean signal in the detector, it is expected that most of the energy will be deposited in the center of the supercluster. It is clear that this is the case for both the barrel and endcap, as seen in figure 6.2. Since the fake photon corresponds to a jet, it is expected that the energy deposition will be more spread in the supercluster, which can also be seen in the plots. As a result,  $R_9$  and  $S_4$  can be

relatively powerful discrimination variables.




**Figure 6.2.** Plots of the  $R_9$  and  $S_4$ . The prompt signal is shown in dark blue for the barrel and light blue for the endcap, whereas the fake background is shown in red for the barrel and pink for the endcap.

The next showershape variables,  $\sigma_{i\eta i\eta}$  and  $\text{cov}(i\eta i\phi)$ , provide information about the energy depositions in terms of the crystal spacing.  $\sigma_{i\eta i\eta}$  quantifies the standard deviation of the energy deposited in terms of the  $\eta$  crystals in the supercluster.  $\text{Cov}(i\eta i\phi)$ , on the other hand, quantifies the covariance between the energy deposited in the  $\eta$  and  $\phi$  directions. Since these measurements both depend on the crystal size and spacing, their values differ considerably between the barrel and endcap. This can be seen clearly in figure 6.3. In the barrel, the  $\sigma_{i\eta i\eta}$  and  $\text{cov}(i\eta i\phi)$  both prove to be very good discrimination variables; the fake photons tend to have considerably larger spread in both measures compared to the prompt photons. In the endcap, the signal  $\sigma_{i\eta i\eta}$  is still clearly well-separated from the background, though the separation in  $\text{cov}(i\eta i\phi)$  is much smaller.




**Figure 6.3.** Plots of the  $\sigma_{i\eta i\eta}$  and  $\text{cov}(i\eta i\phi)$ . The prompt signal is shown in dark blue for the barrel and light blue for the endcap, whereas the fake background is shown in red for the barrel and pink for the endcap.

Similarly to the  $\sigma_{i\eta i\eta}$  and  $\text{cov}(i\eta i\phi)$ , the  $\eta$  and  $\phi$  widths are powerful showershape variables that provide some measure of how well-localized the energy deposition is. It is expected that these values are different for the barrel and endcap, as the crystal size and spacing are different in the two different regions of the detector. This can be seen in both plots in figure 6.4. Additionally, the separation between prompt and fake photons can be clearly seen, especially in  $\eta$  width.



**Figure 6.4.** Plots of the  $\eta$  and  $\phi$  widths. The prompt signal is shown in dark blue for the barrel and light blue for the endcap, whereas the fake background is shown in red for the barrel and pink for the endcap.


The measure of the HCal energy vs the ECal energy,  $H/E$ , provides a powerful measure of whether the energy deposition more closely matches an electromagnetic process – such as a photon or electron – or a hadronic process such as a jet. It is expected that most photons will have a value consistent with 0, as they should deposit all of their energy into the ECal. There is, of course, some level of energy leakage that ensures that even photons often do not have an  $H/E$  of identically 0. Clearly, however, the prompt photons in both the barrel and endcap strongly peak near 0 and fall off rather quickly below this. Note that figure a is a log plot, so that the secondary peak below 0 is down by more than a factor of 10 relative to the primary peak at 0. Since the fake photons are jet signatures designed to mimic a prompt signature, they still exhibit a strong peak near 0. It can be seen, however, that the distribution extends to much higher values of  $H/E$  overall.



**Figure 6.5.** Plots of the H/E and photon isolation. The prompt signal is shown in dark blue for the barrel and light blue for the endcap, whereas the fake background is shown in red for the barrel and pink for the endcap.


The charge isolation variables are the next input variables, and represent the isolation energy (in GeV) relative to a specific vertex. The vertexing described in section 3.4.1 provides multiple vertices at the NanoAOD level. Isolations are measured relative to both the worst possible vertex (figure 6.6a), and the final chosen vertex (figure 6.6b). While the chosen vertex often has 0 isolation energy, the worst vertex very rarely does. In both cases, however, the separation between signal and background is clear for both the barrel and endcap. The charge isolation w.r.t. worst vertex, specifically, shows very clear and powerful separation.





**Figure 6.6.** Plots of the charged isolations with respect to the chosen and worst vertices. The prompt signal is shown in dark blue for the barrel and light blue for the endcap, whereas the fake background is shown in red for the barrel and pink for the endcap.

The final two variables in the model are only used in the endcap models. In fact, these variables only exist for endcap events.



**Figure 6.7.** Plots of two endcap-specific variables: esEffSigmaRR and esEnergyOverRawE. The prompt signal is shown in light blue, whereas the fake background is shown in pink.


Comparing to the MVA-HLT variables shown in 5.1, it can be seen that a few variables have been added at the offline selection level. The photon isolation is analogous to the ECalIso used at the trigger level, but is calculated differently (how?). The two charged isolations used are entirely new additions, as the MVA-HLT is calculated before any complex vertexing is implemented. (Why are both used?). (Statements on rho, and the endcap variables)

The hyperparameter optimization at the offline level was performed very similarly to the MVA-HLT; the max depth and learning rate were varied in tandem until an optimal point was found. The same process of early stopping within XGBoost was used, as well. The hyperparameters were, however, found to be quite different from the trigger-level optimization. Since there are considerably more input variables used (13/15 for the barrel/endcap versus the 8 for the trigger), the max depth was necessarily higher. Consequently, the learning rate was also made lower. The optimum hyperparameters were, then, found to be a maximum depth of 18 and a learning rate of 0.06.

### **A Data/MC BDT for $H \rightarrow \gamma\gamma$**


While the above  $\gamma + Jet$  BDT can help differentiate real photon candidates from fakes, it cannot, in principle, properly differentiate a photon candidate coming from a signal process from a photon candidate coming from a background process. Since the EGamma trigger selections will already cut out many events with jet-like photon candidates, much of the  $H \rightarrow \gamma\gamma$  preselection is aimed at removing real photons coming from non-resonant processes (or even non-Higgs resonances). For the standard preselection, the  $p_T$  and  $p_T/M_{\gamma\gamma}$  cuts achieve this.

Furthermore, the  $\gamma + Jet$  BDT does not properly mirror the MVA-HLT; since the trigger-level BDT was training using Higgs MC as the signal and real data as the background, the offline selection should employ a similar strategy. So, in the same way that the trigger was trained using signal photon candidates originating from a ggH MC sample and background photon candidates originating from the data. The same input variables used in the  $\gamma + Jet$  BDT were then used to train and optimize the new model. These input variables are plotted in the same way as for the previous section, with the barrel and endcap signal being shown in dark and light blue, respectively. Meanwhile, the barrel and endcap background will be shown in red and pink.




**Figure 6.8.** Plots of the Supercluster raw energy and  $\eta_{SC}$ . The prompt signal is shown in dark blue for the barrel and light blue for the endcap, whereas the fake background is shown in red for the barrel and pink for the endcap.

Similarly to the  $\gamma + \text{Jet}$  distributions, a clear difference can be seen in 6.8a between the barrel and endcap distributions of the signal and background. In contrast, however, the difference between signal and background is less pronounced for the data and signal MC. As a result, this will be a less powerful discrimination variable for this new BDT. The features of the  $\eta_{SC}$  distributions for the data and MC differ considerably more than those for the  $\gamma + \text{Jet}$  prompt and fake distributions, however. Particularly in the barrel, it can be seen that the signal MC tends to be much more central, whereas the data peaks strongly towards to high- $\eta$  regions of the barrel. The endcap distributions, however, are much more similar than they were for the  $\gamma + \text{Jet}$ .




**Figure 6.9.** Plots of the  $R_9$  and  $S_4$ . The prompt signal is shown in dark blue for the barrel and light blue for the endcap, whereas the fake background is shown in red for the barrel and pink for the endcap.

As with the  $\gamma + \text{Jet}$  distributions, the  $R_9$  (figure 6.9a) and  $S_4$  (figure 6.9b) variables for the signal tend to be much more strongly peaked near 1 compared to the background.




**Figure 6.10.** Plots of the  $\sigma_{i\eta i\eta}$  and  $\text{cov}(i\eta i\phi)$ . The prompt signal is shown in dark blue for the barrel and light blue for the endcap, whereas the fake background is shown in red for the barrel and pink for the endcap.

In figure 6.10, it can be seen that the signal and background distributions are quite similar for both  $\sigma_{i\eta i\eta}$  and  $\text{cov}(i\eta i\phi)$ . Compared to the  $\gamma + \text{Jet}$  BDT, this means that these showershape variables will be much less powerful. Likely, due to the MVA-HLT selection applied, many of the more jet-like photons have already been removed from this training sample.



**Figure 6.11.** Plots of the  $\eta$  and  $\phi$  widths. The prompt signal is shown in dark blue for the barrel and light blue for the endcap, whereas the fake background is shown in red for the barrel and pink for the endcap.


The  $\eta$  and  $\phi$  widths in figure 6.11 show similar separation between signal and background relative to the  $\gamma$  + Jet distributions.



**Figure 6.12.** Plots of the H/E and photon isolation. The prompt signal is shown in dark blue for the barrel and light blue for the endcap, whereas the fake background is shown in red for the barrel and pink for the endcap.


The H/E and photon isolation in figure 6.12 show decent separation between the signal MC and data in both the barrel and endcap. The barrel and endcap for the data are quite similar for H/E, while the signal MC shows considerably more variation between the two detector elements. Overall, H/E remains a quite powerful discrimination variable in these new samples. Similarly, clear differences can be seen between the signal and background in the photon isolation.





**Figure 6.13.** Plots of the charged isolations with respect to the chosen and worst vertices. The prompt signal is shown in dark blue for the barrel and light blue for the endcap, whereas the fake background is shown in red for the barrel and pink for the endcap.

In figure 6.13, it can immediately be seen that the two charge isolations are quite similar for the signal and background in both the barrel and endcap. While the values tend to extend a bit higher for the background overall, the shapes are far more similar between the signal and background classes relative to the  $\gamma + \text{Jet}$  distributions.



**Figure 6.14.** Plots of two endcap-specific variables: esEffSigmaRR and esEnergyOverRawE. The prompt signal is shown in light blue, whereas the fake background is shown in pink.


The same process of hyperparameter optimization as the previous models was used. Notably, the signal MC and data show much more similarity in the input variable distributions relative to the  $\gamma$  + Jet samples. As a result, the model must become a bit more complex to achieve the desired discrimination power. The same experimental optimization process led to a maximum depth of 18 paired with a learning rate of 0.025. While the maximum depth is the same as that of the  $\gamma$  + Jet model, the learning rate is quite a bit lower than the 0.06 used for that BDT.

## 6.2.2 Determination of Loose Single Photon MVA Cuts for $H \rightarrow \gamma\gamma$

The preexisting preselection first makes decently loose cuts on individual photons, then tighter  $p_T$  and  $p_T/M_{\gamma\gamma}$  cuts on selected diphoton combinations. A very similar strategy can be used for the BDT-based offline selection. Firstly, loose cuts on the above BDT scores can be applied to the individual photon candidates, which will reduce the number of possible diphoton combinations and cut out many events with no reasonable photon candidates. Then, with the list of individual photons cleaned up a bit, a tighter selection can be applied to the resulting diphoton

objects for the selection of a final pair of photons.


So, then, the aim is to choose a loose set of cuts on the  $\gamma + Jet$  and Data/MC BDT scores before applying a tighter final selection on the resulting diphoton combinations. One great advantage of a BDT-based approach is the ease with which these cuts can be adjusted and optimized; while a many-variable preselection has several different cuts to optimize, a binary classifier BDT only has a single output score on which to make cuts. While the goal of this current offline selection is to demonstrate an example analysis that leverages the increased signal efficiency of the MVA-HLT, the existence of these single photon scores allows very easy tuning of the photon preselection for any given analysis. The example cuts chosen below were designed to reduce the signal efficiency by about 2%, which primarily serves to reduce the number of possible photon combinations for final selection; ultimately, the diphoton cuts described in 6.2.3 will be the primary final selection used to achieve the desired data rate.



**Figure 6.15.** Acceptance of the MVA-HLT (blue) vs. the current standard diphoton HLT (green) for  $M_{\gamma\gamma}$


Clearly, as seen in figure 6.15, these chosen single photon cuts (in blue) leave the signal MC relatively untouched. The final chosen signal efficiency for this gluon fusion  $H \rightarrow \gamma\gamma$  is

98.3%, which is much higher than the standard single photon preselection efficiency of 78.5%. Of course, it can be seen that the background rate is much higher – while the standard preselection cuts achieve a background rejection of 96.8%, the loose single photon BDT cuts only achieve an 85.9% rejection.



**Figure 6.16.** Acceptance of the MVA-HLT (blue) vs. the current standard diphoton HLT (green) for  $\eta_{SC}$ . Both the lead and sublead photons are plotted together.

Maximizing the kinematic acceptance of the signal events in  $\eta_{SC}$  is a key consideration to any photon selection. In figure 6.16, the acceptance of the different single photon selections is shown. Given that the signal acceptance is so high for these loose single photon cuts, it can be seen immediately that there are no regions of the detector shown for which the acceptance is problematic. Considering the preselection (yellow), however, a relative drop in efficiency can be seen in the low- $\eta$  regions at the start of the endcap (near  $|\eta| = 1.5$ ). Investigations showed that the hard  $R_9$  cuts placed on the photons by the standard preselection are responsible for this relative dip in efficiency. Utilizing the  $R_9$  in the BDT, as opposed to these hard cuts, ensures that the kinematic coverage for the loose single photon BDT selection is better than that of the standard preselection.



**Figure 6.17.** Acceptance of the MVA-HLT (blue) vs. the current standard diphoton HLT (green) for  $p_T$ . Both the lead and sublead photons are plotted together.

A major advantage to these loose single photon cuts can be seen in figure 6.17. Clearly, the standard preselection cuts considerably reduce the signal MC kinematic phase space by making relatively tight cuts of  $p_T^{Lead} > 35 \text{ GeV}/c^2$  and  $p_T^{Sub} > 25 \text{ GeV}/c^2$ . While this also leads to a considerable reduction in data rate, the loss of good Higgs events with low- $p_T$  photons may impact future analyses with different kinematics. By comparison, the loose single photon cuts, being based entirely on the single photon BDT scores, do not noticeably impact the  $p_T$  distributions of either the signal or background.

### 6.2.3 Creation of Diphoton BDT for $H \rightarrow \gamma\gamma$

With the single photon preselection cuts determined, an additional selection must be placed on the diphoton objects. The most obvious continuation of the current strategy is to create an additional MVA that now works on diphoton quantities. Previous analysis strategies have, in fact, employed a diphoton MVA for the classification of events [12]. A new diphoton BDT can be constructed in reference to this, with the aim of making final cuts on this score such that the

**Table 6.3.** Table of diphoton BDT input variable names, and a short description of each.

| Variable Name                                                  | Description                                            |
|----------------------------------------------------------------|--------------------------------------------------------|
| $p_T^{Lead}/M_{\gamma\gamma}$ and $p_T^{Sub}/M_{\gamma\gamma}$ | The mass-normalized $p_T$ for each photon              |
| $\eta_{sc}^{Lead}$ and $\eta_{sc}^{Sub}$                       | The supercluster $\eta$ for each photon                |
| $BDT_{\gamma+jet}^{Lead}$ and $BDT_{\gamma+jet}^{Sub}$         | The $\gamma + jet$ BDT score for each photon           |
| $BDT_{Data/MC}^{Lead}$ and $BDT_{Data/MC}^{Sub}$               | The Data/MC BDT score for each photon                  |
| Lead and Sublead Electron Veto                                 | A boolean to reject photons originating from electrons |
| $\cos(\Delta\phi)$                                             | The cosine of the $\phi$ separation of the two photons |
| $\sigma(M_{\gamma\gamma})/M_{\gamma\gamma}$                    | A relative mass resolution estimate                    |


background rate is controlled while maintaining maximum signal efficiency.

While the goal of the single photon BDTs is to reject individual candidates that appear to not be photons, the diphoton BDT aims to properly differentiate diphton candidates coming from  $H \rightarrow \gamma\gamma$  from both events that do not contain two real photons and events with two real photons originating from background processes. As a result, the inputs to this model will consist primarily of lead and sublead single photon variables. By providing both the lead and sublead values to one model, correlations can be found that ensure that selected events contain two real photons with the necessary kinematics to possibly comprise a signal event. Below, in table 6.3, each of the input variables is listed and described. These were largely adopted from the Run2 Diphoton photonID, with a few differences.

Since the goal of this model is to differentiate signal diphoton combinations from those in the background, signal MC and data can again be used for the signal and background for the BDT, as with the data/MC BDT described above. Again, the input variable distributions can be examined to see the separation between signal and background class events.

The first two variables are related directly to the kinematics of the diphoton object, and therefore are not split into lead and sublead values. The first,  $\sigma(M_{\gamma\gamma})/M_{\gamma\gamma}$ , provides a relative invariant mass resolution estimate of the diphoton combination. It can clearly be seen in figure 6.18a, that there is great separation between the signal MC and data events. The signal MC tends to have a much lower  $\sigma(M_{\gamma\gamma})/M_{\gamma\gamma}$ , which corresponds to a higher mass resolution. This

is to be expected, as the two selected photons in the  $H \rightarrow \gamma\gamma$  are much more likely to come from a resonant process than those in the data. The  $\cos(\Delta\phi)$ , however, does not exhibit the same strong separation. This variable aims to measure the separation in  $\phi$  of the two selected photon candidates. Based on the other selections at play, however, it seems that this variable will not be a strong discrimination variable.




**Figure 6.18.** The two per-event diphoton input variables,  $\sigma(M_{\gamma\gamma})/M_{\gamma\gamma}$  and  $\cos(\Delta\phi)$ . The signal MC is in black, whereas the data events are in red.

The next two pairs of input variables are the single photon BDT scores. Firstly, the  $\gamma + \text{Jet}$  single photon BDT scores are shown below in figure 6.19. As with all XGBoost BDT binary classification scores, a value near 0 shows that the algorithm has identified the photon as being part of the background class, while a score near 1 corresponds to an event identified as part of the signal class. For the signal MC, it can be seen that the scores peak very well near 1. This is to be expected, as the signal MC photons here are matched to a generated photon and therefore guaranteed to be a real photon. This effect is clear for both the lead and sublead photons.

Clearly, however, the background photons in red are not constrained entirely near 0. In fact, there are two peaks in both the lead and sublead score distributions. While many of the


background photon candidates can easily be assigned a score near 0, there are also a large number for which the  $\gamma + \text{Jet}$  scores are not adequate to differentiate the background from the signal. This likely due, at least in part, to the composition of the data overall. While many of the data events consist of dijet QCD background, there are likely many events for which one or even two real photons have been selected. This is exacerbated by the triggers required for this training sample; here, since either the MVA-HLT trigger or the standard diphoton trigger must be passed to enter the training sample, the odds of a data event containing one or two real photons is much higher than it would be for other data samples. This demonstrate why the  $\gamma + \text{Jet}$  BDT alone is not adequate to correctly differentiate between signal and background events.



**Figure 6.19.** The lead and sublead  $\gamma + \text{Jet}$  XGBoost BDT scores. The signal MC is in black, whereas the data events are in red.

Secondly, the data/MC scores for both the lead and sublead photons are shown in figure 6.20 on a logarithmic scale. As expected, there is clear separation between the signal MC in black and the data in red. It is expected that the signal MC distributions will largely cluster near 1, which corresponds to a positive identification as signal. While this is true for both the lead and sublead scores, the identification of the background is perhaps a stronger effect. It can be seen






**Figure 6.20.** The lead and sublead Data/MC XGBoost BDT scores. The signal MC is in black, whereas the data events are in red.

that the data events are very closely clustered near 0. Very few of the background events, on the other hand, are placed near a score of 1.

Similarly to the  $\gamma + \text{Jet}$  single photon BDT, then, it is clear that this data/MC BDT is not adequate alone to differentiate signal and background. The diphoton BDT, then, is a crucial step of the signal and background selection; by having access to both the single photon BDTs, the diphoton BDT can construct correlations that allow the final model to be considerably more discerning than input scores it uses. As will be shown in chapter 7, this works to great effect.


While the single photon quality scores given by the single photon BDTs are quite helpful, the diphoton kinematics are additionally a very strong source of discrimination power. As seen for both the lead (figure 6.21a) and sublead (figure 6.21a)  $\eta_{SC}$  distributions, the shape of the single Higgs signal MC in black and the data in red are quite different. Due to the kinematics of the Higgs production, as discussed in 1, the signal MC tends to be much more central in the barrel detector (closer to perpendicular to the beamline). Meanwhile, in the endcaps, the amount of signal photons rapidly drops as the edges of the chosen  $\eta_{SC}$  range are approached. Due to this

good separation between signal and background, the  $\eta_{SC}$  of the lead and sublead photon provide good discrimination power to the binary classifier BDT.



**Figure 6.21.** The lead and sublead  $\eta_{SC}$ . The signal MC is in black, whereas the data events are in red.

The other diphoton kinematic quantities used by the diphoton BDT are the  $p_T/M_{\gamma\gamma}$  of the two selected photons. This mass-normalized measure of the photon candidates' transverse momentum is used in the standard diphoton preselection given its great discrimination power. Of course, if hard cuts on a variable are successful in separating signal from background, a BDT should be able to leverage the information to even greater effect. Furthermore, as with the  $p_T$  cuts, removing the hard cuts on this variable considerably improve the kinematic coverage of the offline selection. In figure 6.22, a clear separation between the signal and background events can be seen for both the lead and sublead photon candidates. Paired with the corresponding  $\eta_{SC}$  values, this lends considerable kinematic discrimination power to the diphoton BDT.




**Figure 6.22.** The lead and sublead  $p_T/M_{\gamma\gamma}$ . The signal MC is in black, whereas the data events are in red.

Finally, the electron veto values can be used to help differentiate between photons and electrons in the final selection. As discussed in section 3.4.1, photons and electrons are quite hard to differentiate purely from ECal information. The electron veto was designed to leverage charged track information to provide a conversion-safe way to reject electrons from photon candidates [13]. This quantity has not historically been deployed in the diphotonMVA; since the standard preselection generally makes a hard requirement on the electron veto, there is no need to use it in the diphotonMVA. By adding the lead and sublead electron veto decision to the diphoton BDT, however, the information can be correlated with the other variables provided to more elegantly reject electrons in the data while still maximizing the signal efficiency.

The values of the electron veto are shown in figure 6.23. Since this is just a veto decision, the variable is saved as a boolean. As a result, the plots show a value of 0 for false (failing the electron veto) and 1 for true (passing the electron veto). A very clear separation can be seen between the signal MC (black) and data (red). Very few of the selected signal MC lead or sublead photon candidates fail the electron veto, whereas there are a considerable portion of the data

events that fail. It can be seen, however, that there are still many data events that pass the electron veto.




**Figure 6.23.** The lead and sublead electron veto. The signal MC is in black, whereas the data events are in red.

As with the other two BDTs, the hyperparameters must of course be optimized once the input variables are selected. This was, again, a relatively experimental process. Given the reduced number of input variables relative to the single photon BDTs, lower maximum depths were explored. A max depth of 10 was selected in conjunction with a learning rate of 0.1. This lower max depth and higher learning rate allows the model to still leverage the reduced number of input variables without considerable overtraining.

#### A Data/MC BDT for $HH \rightarrow b\bar{b}\gamma\gamma$


Of course, since the Data/MC and diphoton BDTs are trained using signal MC and data, they should be retrained for samples with markedly different input features. As discussed in chapter 1, the kinematics of the  $HH \rightarrow b\bar{b}\gamma\gamma$  differ considerably from the  $H \rightarrow \gamma\gamma$ . Therefore, the same process of training and evaluation must be repeated for these new samples. While the same

data samples are used for this updated analysis, the  $HH \rightarrow b\bar{b}\gamma\gamma$  workflow applies additional cuts to the  $b\bar{b}$  object as discussed in section 3.4.4. The same input variable distributions for the Data/MC BDT are displayed in figures 6.24-6.30 for these new samples. Major differences between the single and DiHiggs samples will be noted.




**Figure 6.24.** Plots of the Supercluster raw energy and  $\eta_{SC}$ . The signal MC is shown in dark blue for the barrel and light blue for the endcap, whereas the data (background) is shown in red for the barrel and pink for the endcap.

A major difference in  $\eta_{SC}$  exists relative to the single H, as seen in figure 6.24. While the signal MC is relatively similar in the barrel, the endcap is far more concentrated at lower- $\eta$  values. The data, on the other hand, is considerably more flat in both the endcap and barrel due to the changed kinematics based on the requirements placed on finding a  $b\bar{b}$  pair. On the whole, this leads the  $\eta_{SC}$  being used more strongly by the DiHiggs Data/MC BDT. Since less of the MC is in the extreme regions of the endcap, it will be shown that the selection is biased away from selecting data in these regions.




**Figure 6.25.** Plots of the  $R_9$  and  $S_4$ . The signal MC is shown in dark blue for the barrel and light blue for the endcap, whereas the data (background) is shown in red for the barrel and pink for the endcap.


Relative to the data selected by the single Higgs workflow, the DiHiggs data selection has considerably lower values on average of both the  $R_9$  and  $S_4$ . This leads to a clearer separation between the signal and background for both the barrel and endcap events.




**Figure 6.26.** Plots of the  $\sigma_{in\eta in}$  and  $cov(in\eta in\phi)$ . The signal MC is shown in dark blue for the barrel and light blue for the endcap, whereas the data (background) is shown in red for the barrel and pink for the endcap.



**Figure 6.27.** Plots of the  $\eta$  and  $\phi$  widths. The signal MC is shown in dark blue for the barrel and light blue for the endcap, whereas the data (background) is shown in red for the barrel and pink for the endcap.




(a) H/E




(b) Photon Isolation

**Figure 6.28.** Plots of the H/E and photon isolation. The signal MC is shown in dark blue for the barrel and light blue for the endcap, whereas the data (background) is shown in red for the barrel and pink for the endcap.




(a) Chg. Iso. W.r.t. Worst Vertex



(b) Chg. Iso. W.r.t. Chosen Vertex

**Figure 6.29.** Plots of the charged isolations with respect to the worst and chosen vertices. The signal MC is shown in dark blue for the barrel and light blue for the endcap, whereas the data (background) is shown in red for the barrel and pink for the endcap.







**Figure 6.30.** Plots of the ES Eff. Sigma RR and ES Energy over Raw E. The signal MC is shown in dark blue for the barrel and light blue for the endcap, whereas the data (background) is shown in red for the barrel and pink for the endcap.

## 6.2.4 Determination of Loose Single Photon MVA Cuts for $HH \rightarrow b\bar{b}\gamma\gamma$

Given the difference in the resulting output BDT score distributions, the loose single photon cuts must be reexamined for the DiHiggs sample. As previously mentioned, this readjustment of the cuts is a relatively straightforward process. Again, the general goal was to achieve an approximately 98% signal efficiency. Relative to the single H cuts, both the  $\gamma$  + Jet and Data/MC cuts are numerically tighter. The chosen cuts yielded a total signal efficiency of 97.35% and a corresponding data acceptance of 14.7%. While both of these values are fractionally lower than that of the single Higgs, there is still ample signal efficiency with which to realize the gains from the trigger level. On the other hand, the preselection yields a signal efficiency of 67.78%, which is considerably lower than that of the single Higgs.




(a) Signal MC  $M_{\gamma\gamma}$




(b) Data  $M_{\gamma\gamma}$

**Figure 6.31.** Acceptance of the MVA-HLT (blue) vs. the current standard diphoton HLT (green) for  $M_{\gamma\gamma}$



(a) Signal MC  $\eta_{sc}$




(b) Data  $\eta_{sc}$

**Figure 6.32.** Acceptance of the MVA-HLT (blue) vs. the current standard diphoton HLT (green) for  $\eta_{sc}$

Relative to the singleH selection, the DiHiggs data acceptance is relatively unchanged.

Of course, given the very high signal efficiency of this selection, there is little effect on the signal acceptance. A relevant kinematic difference can be seen, however; the DiHiggs signal MC tends to be far more central in the barrel, with very little extending into the endcap. This highlights, again, why retraining both the single photon Data/MC BDT and the diphoton BDT is so crucial for this sample.




**Figure 6.33.** Acceptance of the MVA-HLT (blue) vs. the current standard diphoton HLT (green) for  $p_T$

The scale of the accepted  $p_T$  values is quite skewed by the very large bin content of the overflow bin (above 200 GeV/c). This points to another important kinematic difference – given the more central photon distribution in  $\eta_{SC}$ , the photon candidates tend to have higher  $p_T$  values on average.


### 6.2.5 Creation of Diphoton BDT for $HH \rightarrow b\bar{b}\gamma\gamma$

The final step is to consider the recreation of the diphoton BDT for the DiHiggs process. It will be shown in figures 6.34-6.39 that both the kinematic variables and the input BDT score distributions are significantly different relative to the single Higgs.




**Figure 6.34.** The two per-event diphoton input variables,  $\sigma(M_{\gamma\gamma})/M_{\gamma\gamma}$  and  $\cos(\Delta\phi)$ . The signal MC is in black, whereas the data events are in red.

While the  $\sigma(M_{\gamma\gamma})/M_{\gamma\gamma}$  distributions are relatively similar to their single Higgs counterparts, there are minor differences in the  $\cos(\Delta\phi)$ . The single Higgs for both the data and signal MC was strongly peaked at -1, with a very similar shape for both samples. In the DiHiggs, however, there is far better separation between the signal and background; the data is still relatively well clustered at -1, but the signal MC has a sloped shape favoring higher values (especially increasing approaching 1). This, again, is due to the kinematics of the DiHiggs production.  $\cos(\Delta\phi) = -1$  corresponds to a  $\Delta\phi = \pi$ , whereas  $\cos(\Delta\phi) = 1$  corresponds to a  $\Delta\phi = 0$ . As expected, then, the DiHiggs signal is more likely to have a lower separation in  $\phi$ . So, the discrimination power of this variable should have increased relative to the single Higgs.




**Figure 6.35.** The lead and sublead  $\gamma$  + Jet XGBoost BDT scores. The signal MC is in black, whereas the data events are in red.

Next, there are clear differences in the  $\gamma$  + Jet BDT score distributions for the DiHiggs. The signal MC, surprisingly, has a relatively similar distribution in scores. The score peaks strongly at 1 for the signal in both the lead and sublead photon candidate. The data, however, has moved closer to 0. Especially in the sublead photon candidate, the peak near 0 is taller than the peak near 1. In the single Higgs, the two peaks were of a more similar size. Even though this  $\gamma$  + Jet BDT was not retrained, it appears to perform better on separating DiHiggs signal MC from data.




**Figure 6.36.** The lead and sublead Data/MC XGBoost BDT scores. The signal MC is in black, whereas the data events are in red.

The single photon Data/MC BDT scores are quite well-separated for the lead photon, perhaps moreso than they were for the single Higgs sample. Clearly, as well, the sublead scores for the data are very well-placed near 0. Again, in conjunction with the  $\gamma$  + Jet scores shown in figure 6.35, these data/MC BDT scores will have strong discrimination power.



**Figure 6.37.** The lead and sublead  $\eta_{SC}$ . The signal MC is in black, whereas the data events are in red.


As mentioned for the selection of the single photon cuts, the  $\eta_{SC}$  distributions for the diHiggs samples are more separated than those of the single Higgs. Especially in the lead photon candidate, there is very little data in the center of the barrel, while the signal MC sees its strongest peak in this region. The endcap shapes are rather different for the lead photon, but much more similar for the sublead photon. Again, due to the difference in kinematics relative to the single Higgs, these differences are to be expected.



**Figure 6.38.** The lead and sublead  $p_T/M_{\gamma\gamma}$ . The signal MC is in black, whereas the data events are in red.

While the separation between the signal and background for both lead and sublead  $p_T/M_{\gamma\gamma}$  is still quite good (as seen in figure 6.38), the distributions for the signal MC are quite different than those for the single Higgs. Specifically, the values tend to be, on average, a bit higher for both the lead and sublead. Additionally, the spread of the values for the signal MC is quite a bit higher, which likely reduces the discrimination power of the  $p_T/M_{\gamma\gamma}$  for the diHiggs samples.





**Figure 6.39.** The lead and sublead electron veto The signal MC is in black, whereas the data events are in red.

Finally, the electron veto values look very similar to those of the single Higgs data and MC. Shown in figure 6.39, it is still the case that the signal MC has both photons passing the veto in  $\sim 95\%$  of cases. Again, this will prove a very useful discrimination variable.

For this final BDT, the same steps of hyperparameter optimization and training were followed. It was found that, for the diHiggs diphoton BDT, the same hyperparameters could be used as for the single Higgs version of the same BDT.

# Chapter 7

## Evaluation of the MVA-HLT and Complementary Offline Selection

### 7.1 Measurement of Trigger Rate

As discussed in chapter 5, the first main consideration for any HLT is the trigger rate, usually measured in Hz. There are two main corresponding numbers: the total rate measures the total number of events being accepted by the trigger, whereas the pure rate measures the number of events being accepted by a trigger that would not be accepted by any other trigger.

#### 7.1.1 Method of Rate Measurement

#### 7.1.2 Trigger Rate of MVA-HLT

### 7.2 Evaluation of MVA-HLT Efficiency on Selected Signal Samples

Once it has been verified that the trigger rate is within the limits posed by the collaboration, the next major task is ensuring that the signal efficiency for the MVA-HLT is a noticeable improvement over the standard HLT. Since the reconstruction, calibrations, and corrections are different at the NanoAOD level, the measurements made at the RAW level in section 5.3 must be verified on independent analysis-level (NanoAOD) samples.


As in section 5.3, plots can be made of selected input variables and the resulting accepted

distributions can be compared for the MVA-HLT versus the standard diphoton HLT. For these subsequent plots, the acceptance of MVA-HLT will be shown in dark blue, while the acceptance of the standard HLT will be shown in dark blue. Additionally, the light blue curve will show events that pass the MVA-HLT but fail the standard HLT. Therefore, the light blue curve will our signal gain directly.

### 7.2.1 Single Higgs MVA-HLT Acceptance

Beginning with the  $M_{\gamma\gamma}$  distribution (fig. 7.1), it can be seen that the MVA-HLT (blue) has considerably improved signal MC acceptance compared to the standard HLT. In fact, there is a 9.7% relative signal efficiency gain (97.32% vs 88.68%) when considering both the barrel and endcap events together. This is a bit lower than the 13.6% signal gain seen at the RAW trigger level (93.86% vs 82.64%). This is partly due to the improvement in overall signal efficiency for the standard HLT at the NanoAOD level. Because the NanoAOD reconstruction is improved relative to that at the trigger RAW level, it is expected that the overall signal efficiency at this level will be improved. Overall, however, it can be seen that the  $H \rightarrow \gamma\gamma$  signal efficiency is very high for the MVA-HLT, as desired.

Another major advantage of the MVA-HLT is the reduction in data rate. As demonstrated in section 7.1, the MVA-HLT has approximately half the trigger rate of the standard trigger. This is approximately confirmed by data distribution shown in 7.1b. For all  $\eta_{SC}$ , the total data acceptance is 22.41% compared to thr 42.62% of the standard HLT. The light blue curve, additionally, can be used as a proxy for seeing the pure rate measured in section 7.1; about 13.4% of the data passes the MVA-HLT but fails the standard HLT.




**Figure 7.1.** Acceptance of the MVA-HLT (dark blue) vs. the current standard diphoton HLT (green) for  $M_{\gamma\gamma}$ . Events that pass the MVA-HLT but fail the standard HLT can be seen in light blue.


Next, the acceptance in the trigger in  $\eta_{SC}$  7.2 can be considered. The MVA-HLT has relatively consistent acceptance in  $\eta_{SC}$ , whereas the standard trigger shows holes in the acceptance in the lowest- $\eta$  regions of the endcap. Investigations have shown that the  $R_9$  cuts of the standard trigger are responsible for this inefficiency. As seen in the light blue curve, the MVA-HLT is able to close this gap and provide more consistent kinematic coverage. Otherwise, the gain relative to the standard MVA-HLT is relatively flat throughout the barrel and the rest of the endcap. These features shown that the kinematic coverage is improved relative to that of the standard HLT.

The acceptance of the data, shown in figure 7.2b, shows a few relevant features. Whereas the standard HLT accepts more data in the center of the barrel and cuts out more of the barrel above  $|\eta_{SC}| > 1.0$ . The MVA-HLT, on the other hand, exhibits the opposite features. In the data, the standard HLT closely matches the shape of the full distribution in black, including considerable acceptance in the high- $\eta$  horns. The MVA-HLT is relatively flat throughout the

enecap, though it does also accept a small amount more data in the high- $\eta$  horns.



**Figure 7.2.** Acceptance of the MVA-HLT (dark blue) vs. the current standard diphoton HLT (green) for  $\eta_{sc}$ . Both the lead and sublead photons are plotted together. Events that pass the MVA-HLT but fail the standard HLT can be seen in light blue.



**Figure 7.3.** Acceptance of the MVA-HLT (dark blue) vs. the current standard diphoton HLT (green) for  $p_T/M_{\gamma\gamma}$ . Both the lead and sublead photons are plotted together. Events that pass the MVA-HLT but fail the standard HLT can be seen in light blue.

Finally, the results of the signal MC efficiency and the data acceptance are tabulated in table 7.1. The different  $\eta_{SC}$  configurations are separated here – B-B and E-E events correspond to both photons being located in the barrel and endcap, respectively, while the B-E events have one photon in the barrel and the other in the endcap. Immediately, it can be seen that the MVA-HLT has relatively constant signal acceptance for each region, varying by a total of 3.45% between the B-E events (95.2%) and the B-B events (93.39%). Meanwhile, the standard HLT has considerably reduced signal efficiency in the B-E. This allows the MVA-HLT to have a relative efficiency gain of 17.1% in this region. This is another way in which the kinematic coverage of the MVA-HLT is greatly improved relative to the standard HLT.


**Table 7.1.** Signal efficiencies and background acceptances for both triggers, broken down by diphoton  $\eta_{sc}$

| (a) Signal Efficiencies |            |             | (b) Data Acceptances |            |             |
|-------------------------|------------|-------------|----------------------|------------|-------------|
| Region                  | MVA-HLT(%) | Std. HLT(%) | Region               | MVA-HLT(%) | Std. HLT(%) |
| B-B                     | 98.65      | 93.39       | B-B                  | 21.07      | 37.27       |
| B-E                     | 95.20      | 81.27       | B-E                  | 23.11      | 46.57       |
| E-E                     | 96.70      | 86.24       | E-E                  | 22.26      | 32.32       |
| All                     | 97.32      | 88.68       | All                  | 22.41      | 42.62       |


Overall, it can be seen that the MVA-HLT achieves the desired result at the NanoAOD analysis level. The signal efficiency is about 9.7% higher for the  $H \rightarrow \gamma\gamma$  signal MC relative to the standard HLT. The overall efficiency sits at 97.3%, which allows virtually all of the signal MC to be considered for subsequent analyses. In addition, no holes in kinematic coverage can be seen, meaning that the MVA-HLT is able to more-completely cover the full range of possible physics that can be gleaned from  $H \rightarrow \gamma\gamma$  processes.

## 7.2.2 DiHiggs MVA-HLT Acceptance

Where the MVA-HLT can shine best, however, is for more rare processes like the  $HH \rightarrow b\bar{b}\gamma\gamma$ .




(a) Signal MC  $M_{\gamma\gamma}$




(b) Data  $M_{\gamma\gamma}$

**Figure 7.4.** Acceptance of the MVA-HLT (blue) vs. the current standard diphoton HLT (green) for  $M_{\gamma\gamma}$




(a) Signal MC  $\eta_{sc}$




(b) Data  $\eta_{sc}$

**Figure 7.5.** Acceptance of the MVA-HLT (blue) vs. the current standard diphoton HLT (green) for  $\eta_{sc}$



(a) Signal MC  $p_T/M_{\gamma\gamma}$



(b) Data  $p_T/M_{\gamma\gamma}$

**Figure 7.6.** Acceptance of the MVA-HLT (blue) vs. the current standard diphoton HLT (green) for  $p_T/M_{\gamma\gamma}$

**Table 7.2.** Signal efficiencies and background acceptances for both triggers, broken down by diphoton  $\eta_{sc}$

(a) Signal Efficiencies

| Region | MVA-HLT(%) | Std. HLT(%) |
|--------|------------|-------------|
| B-B    | 98.90      | 91.01       |
| B-E    | 97.25      | 81.10       |
| E-E    | 98.26      | 89.18       |
| All    | 94.45      | 88.45       |

(b) Data Acceptances


| Region | MVA-HLT(%) | Std. HLT(%) |
|--------|------------|-------------|
| B-B    | 14.73      | 28.12       |
| B-E    | 18.26      | 37.24       |
| E-E    | 15.51      | 24.77       |
| All    | 16.86      | 33.24       |




## 7.3 Evaluation of Offline Selection Efficiency with MVA-HLT

### 7.3.1 Method of Signal Efficiency Measurement


### 7.3.2 Single Higgs Offline Selection Acceptance



**Figure 7.7.** Both the lead and sublead photons are plotted together.




(a) Signal MC  $\eta_{sc}$




(b) Data  $\eta_{sc}$

**Figure 7.8.** Both the lead and sublead photons are plotted together.



(a) Signal MC  $p_T/M_{\gamma\gamma}$



(b) Data  $p_T/M_{\gamma\gamma}$

**Figure 7.9.** Both the lead and sublead photons are plotted together.

**Table 7.3.** Signal efficiencies and background acceptances for both triggers, broken down by diphoton  $\eta_{sc}$


(a) Signal Efficiencies

| Region | BDT(%) | SA(%) |
|--------|--------|-------|
| B-B    | 94.56  | 81.95 |
| B-E    | 85.43  | 52.12 |
| E-E    | 91.63  | 63.63 |
| All    | 91.27  | 70.53 |


(b) Data Acceptances

| Region | BDT(%) | SA(%) |
|--------|--------|-------|
| B-B    | 2.50   | 2.30  |
| B-E    | 0.77   | 0.80  |
| E-E    | 1.08   | 1.71  |
| All    | 1.25   | 1.25  |

### 7.3.3 DiHiggs Offline Selection Acceptance




(a) Signal MC  $M_{\gamma\gamma}$




(b) Data  $M_{\gamma\gamma}$

**Figure 7.10.** Both the lead and sublead photons are plotted together.




(a) Signal MC  $\eta_{sc}$




(b) Data  $\eta_{sc}$

**Figure 7.11.** Both the lead and sublead photons are plotted together.



(a) Signal MC  $p_T/M_{\gamma\gamma}$



(b) Data  $p_T/M_{\gamma\gamma}$

**Figure 7.12.** Both the lead and sublead photons are plotted together.

**Table 7.4.** Signal efficiencies and background acceptances for both triggers, broken down by diphoton  $\eta_{sc}$

(a) Signal Efficiencies

| Region | BDT(%) | SA(%) |
|--------|--------|-------|
| B-B    | 97.23  | 73.43 |
| B-E    | 88.38  | 53.83 |
| E-E    | 89.88  | 57.02 |
| All    | 94.68  | 67.78 |

(b) Data Acceptances

| Region | BDT(%) | SA(%) |
|--------|--------|-------|
| B-B    | 3.12   | 2.42  |
| B-E    | 0.76   | 0.86  |
| E-E    | 1.50   | 1.71  |
| All    | 1.46   | 1.46  |

# **Chapter 8**

## **Summary**

## **Chapter 9**

# **Acknowledgements**

Appendix

# Bibliography

- [1] The CMS Collaboration. “A portrait of the Higgs boson by the CMS experiment ten years after the discovery”. In: *Nature* 607.7917 (2022), pp. 1–1. ISSN: 1476-4687. DOI: 10.1038/s41586-022-04892-x.
- [2] The CMS Collaboration. “Observation of a new boson at a mass of 125 GeV with the CMS experiment at the LHC”. In: (2012). DOI: 10.1016/j.physletb.2012.08.021. eprint: arXiv:1207.7235.
- [3] The CMS Collaboration et al. “Observation of a new boson with mass near 125 GeV in pp collisions at  $\sqrt{s} = 7$  and 8 TeV”. In: *Journal of High Energy Physics* 2013.6 (2013). ISSN: 1029-8479. DOI: 10.1007/jhep06(2013)081. URL: [http://dx.doi.org/10.1007/JHEP06\(2013\)081](http://dx.doi.org/10.1007/JHEP06(2013)081).
- [4] The CMS Collaboration et al. “The CMS experiment at the CERN LHC”. In: *Journal of Instrumentation* 3.08 (2008), pp. 1–1. ISSN: 1748-0221. DOI: 10.1088/1748-0221/3/08/S08004. URL: <http://dx.doi.org/10.1088/1748-0221/3/08/S08004>.
- [5] Lyndon Evans and Philip Bryant. “LHC Machine”. In: *Journal of Instrumentation* 3.08 (2008), pp. 1–1. ISSN: 1748-0221. DOI: 10.1088/1748-0221/3/08/S08001. URL: <http://dx.doi.org/10.1088/1748-0221/3/08/S08001>.
- [6] Jerome H. Friedman. “Greedy function approximation: A gradient boosting machine.” In: *The Annals of Statistics* 29.5 (Oct. 2001). ISSN: 0090-5364. DOI: 10.1214/aos/1013203451. URL: <http://dx.doi.org/10.1214/aos/1013203451>.



- [7] Mary K. Gaillard, Paul D. Grannis, and Frank J. Sciulli. “The Standard Model of Particle Physics”. In: (1998). DOI: 10.1103/RevModPhys.71.S96. eprint: arXiv:hep-ph/9812285.
- [8] A. Hayrapetyan et al. “Development of the CMS detector for the CERN LHC Run 3”. In: *Journal of Instrumentation* 19.05 (May 2024), pp. 1–1. ISSN: 1748-0221. DOI: 10.1088/1748-0221/19/05/p05064. URL: <http://dx.doi.org/10.1088/1748-0221/19/05/P05064>.
- [9] A. Hayrapetyan et al. “Performance of the CMS high-level trigger during LHC Run 2”. In: *Journal of Instrumentation* 19.11 (Nov. 2024), pp. 1–1. ISSN: 1748-0221. DOI: 10.1088/1748-0221/19/11/p11021. URL: <http://dx.doi.org/10.1088/1748-0221/19/11/P11021>.
- [10] V. Khachatryan et al. “The CMS trigger system”. In: *Journal of Instrumentation* 12.01 (Jan. 2017), pp. 1–1. ISSN: 1748-0221. DOI: 10.1088/1748-0221/12/01/p01020. URL: <http://dx.doi.org/10.1088/1748-0221/12/01/P01020>.
- [11] S. Navas et al. “Review of Particle Physics”. In: *Phys. Rev. D* 110 (3 2024), pp. 1–1. DOI: 10.1103/PhysRevD.110.030001.
- [12] A. M. and Sirunyan et al. “Measurements of Higgs boson properties in the diphoton decay channel in proton-proton collisions at  $\sqrt{s} = 13$  TeV”. In: *Journal of High Energy Physics* 2018.11 (Nov. 2018). ISSN: 1029-8479. DOI: 10.1007/jhep11(2018)185. URL: [http://dx.doi.org/10.1007/JHEP11\(2018\)185](http://dx.doi.org/10.1007/JHEP11(2018)185).
- [13] A.M. Sirunyan et al. “Electron and photon reconstruction and identification with the CMS experiment at the CERN LHC”. In: *Journal of Instrumentation* 16.05 (May 2021), P05014. ISSN: 1748-0221. DOI: 10.1088/1748-0221/16/05/p05014. URL: <http://dx.doi.org/10.1088/1748-0221/16/05/P05014>.
- [14] A.M. Sirunyan et al. “Performance of the CMS Level-1 trigger in proton-proton collisions at  $\sqrt{s} = 13$  TeV”. In: *Journal of Instrumentation* 15.10 (Oct. 2020), pp. 1–1. ISSN: 1748-0221. DOI: 10.1088/1748-0221/15/10/p10017. URL: <http://dx.doi.org/10.1088/1748-0221/15/10/P10017>.