Advanced Mobility Architectures and Environmental Survivability Systems for Mercurian and Interstellar Applications: A Technical Feasibility Review

1. Executive Summary and Strategic Context

The trajectory of human presence in the solar system is currently defined by a transition from transient exploration to permanent industrialization. While the focus of the early 21st century has been the characterization of Mars, the logistical and energetic requirements of a Kardashev Type I civilization necessitate the exploitation of the inner solar system, specifically the high-energy environment of Mercury. This report provides a comprehensive engineering analysis of the mobility systems required to operate on the Hermean surface—an environment characterized by extreme thermal cycling, intense radiation flux, and a regolith morphology significantly more hostile than that of the Moon or Mars.

The central subject of this analysis is the **Active Adaptive Grouser System (AAGS)**, colloquially referred to as the "Wheel of Nails." This concept represents a fundamental departure from the passive pneumatic or rigid-elastic tires that have dominated planetary rover design since the Apollo era. By utilizing radially actuated linear motors to dynamically alter the wheel's geometry, the AAGS addresses the critical failure modes observed in the Mars Science Laboratory (MSL) mission: the catastrophic fatigue and puncture of wheel skins by sharp, cemented ventifacts. The proposed system enables a rover to mechanically "sense" sharp regolith edges and retract the contacting grouser element effectively "stepping over" the hazard rather than rolling through it.

Furthermore, this report situates the mobility platform within a necessary ecosystem of survivability technologies. The operation of complex electromechanical actuators on Mercury requires the integration of **Transparent Aluminum Oxynitride (ALON)** for radiation-hardened optical apertures and **Polyimide Aerogels** for thermal isolation. Energetic sustainability is addressed through **Molten Salt Thermal Energy Storage (TES)**, leveraging the extreme solar flux to bridge the long Mercurian night. Finally, the report extrapolates

these technologies to their ultimate application: serving as the foundational hardware for interstellar precursor missions to habitable exoplanets such as **Proxima Centauri b** and **Teegarden's Star b**, where autonomous terrain adaptation will be the deciding factor in mission success.

---

2. The Mobility Crisis in Planetary Exploration: Historical Failures and Environmental Realities

To understand the necessity of the "Wheel of Nails," one must first analyze the limitations of current mobility paradigms when subjected to the geologic realities of terrestrial planets. The design lineage of planetary rovers—from the wire-mesh tires of the Lunar Roving Vehicle (LRV) to the aluminum semi-monocoques of the Mars Exploration Rovers (MER)—relied on the assumption that the regolith was primarily unconsolidated soil with occasional, avoidable obstacles. The mission of the Mars Science Laboratory (*Curiosity*) shattered this assumption.

2.1. The "Curiosity" Syndrome: Passive Wheel Fatigue

The wheels of the *Curiosity* rover are constructed from a solid block of aluminum, machined to a skin thickness of 0.75 mm, with stiffening rings and 19 grousers (cleats) for traction.[1] This design relied on the skin to flex slightly to absorb impact energy. However, the Martian terrain in Gale Crater presented a specific geological feature known as "ventifacts"—rocks honed by aeolian abrasion into immobile, pyramidal spikes.

When a passive rigid wheel encounters such an obstacle, the entire weight of the rover (approx. 900 kg for MSL) is concentrated onto the point of the rock. The thin skin, unable to deform sufficiently, suffers puncture. As the wheel rotates, these punctures propagate into cracks, eventually threatening the structural integrity of the wheel and the grousers themselves.[1] By 2021, *Curiosity* had sustained significant grouser failures, necessitating a radical alteration of its driving strategy to avoid "gator-back" terrain.[1]

This failure mode highlights a fundamental deficiency in passive suspension: **a passive wheel cannot distinguish between a load-bearing surface and a damaging hazard.** It must bear the load regardless of the contact geometry.

2.2. The Mercurian Surface: A Hostile Operating Theater

Mercury presents a surface environment that exacerbates every failure mode observed on Mars.

- **Regolith Morphology:** Unlike the Moon, which is weathered primarily by micrometeoroids, Mercury is subjected to intense solar wind sputtering and heavy ion bombardment due to its proximity to the Sun and weak magnetosphere.[2] This creates a regolith that is potentially sharper and more chemically reactive. The lack of an atmosphere preserves the angularity of impact ejecta, creating fields of razor-sharp cemented breccia that would shred thin aluminum tires.
- **Thermal Extremes:** The surface temperature on Mercury cycles between 100 K (night) and 700 K (day).[3] Standard elastomers used in terrestrial tires would instantly sublimate or embrittle. Even the aluminum used in Mars rovers would experience significant thermal softening at peak daytime temperatures, accelerating fatigue failure.
- **Topological Uncertainty:** The "active" nature of Mercury's surface interaction with the solar wind implies that localized surface charging and plasma precipitation could affect soil mechanics, potentially creating areas of surprisingly low bearing capacity (dust traps) adjacent to bedrock.[2]

2.3. The Requirement for Active Adaptation

The convergence of these factors necessitates a mobility system that is **active** rather than passive. The rover must be able to change its contact geometry in real-time. It must offer the high flotation of a continuous track for soft dust, the point-loading capability of a claw for climbing crater rims, and the compliance of a legged robot to avoid sharp hazards. The **Active Adaptive Grouser System (AAGS)** is the engineering embodiment of these requirements.

---

3. Engineering Architecture of the Active Adaptive Grouser System (AAGS)

The "Wheel of Nails" concept replaces the static rim of a wheel with a radial array of linear actuators. Each actuator effectively functions as a spoke that can change its length,

transforming the wheel from a circle into an adaptive polygon.

3.1. Linear Actuator Topology and Selection

The core of the AAGS is the linear actuator driving each "nail." The selection of this component is critical, as it must provide high force, precise positioning, and withstand the vacuum/thermal environment.

3.1.1. Ball Screw Actuators vs. Roller Screws

While pneumatic and hydraulic systems are common in terrestrial heavy machinery, they are unsuitable for Mercury due to the risk of fluid boiling, freezing, or seal failure in a hard vacuum.[4] Electromechanical screw actuators are the preferred solution.

- **Ball Screw Actuators:** These utilize recirculating ball bearings to minimize friction between the screw and the nut. They offer high efficiency ($>90\%$) and can support substantial static loads ($>30 \text{ kN}$).[5] They are ideal for high-duty-cycle applications where energy conservation is paramount.
- **Planetary Roller Screws:** For the extreme shock loads of a rover wheel (e.g., dropping off a rock), roller screws are superior. They provide more contact points than ball screws, offering higher stiffness and resistance to Brinelling (denting of the races).[4]
- **Mechanism Design:** The optimal design for the AAGS is a **Planetary Roller Screw** driven by a high-torque **Brushless DC (BLDC) Motor**. The motor provides the rotational energy, which the screw converts into the linear extension of the nail. The system must include an **electromagnetic brake** to hold the nail in position without consuming power when the rover is stationary.[5]

3.1.2. Linear Motor (Direct Drive) Options

For applications requiring faster response times (milliseconds), direct-drive **Permanent Magnet Synchronous Linear Motors (PMSLM)** are an alternative.[6] Unlike screw actuators, which are mechanically geared, linear motors move the payload directly using magnetic fields.

- **Advantage:** Extremely fast retraction. If a sensor detects a sharp rock, a linear motor can

retract the nail in $<20 \text{ ms}$, virtually eliminating impact force.
- **Disadvantage:** Lower force density and higher power consumption to hold a load against gravity.
- **Hybrid Approach:** A hybrid system could use a lead screw for the main load-bearing extension and a compliant magnetic spring for high-frequency vibration isolation.[6]

3.2. Control Strategy: The "Virtual Rim"

The AAGS is not just a mechanical assembly; it is a software-defined wheel. The control system creates a "virtual rim" by coordinating the extension of the actuators.[7]

3.2.1. Mode A: Obstacle Swallow (The Bed of Nails Effect)

This is the primary defense against sharp regolith edges.

1. **Sensing:** Each nail tip is equipped with a high-temperature piezoelectric force sensor.
2. **Detection:** As the wheel rotates, the controller monitors the force profile of each contacting nail. A normal ground contact produces a gradual rise in force. A contact with a sharp, immobile edge produces a near-instantaneous spike (Dirac delta function).
3. **Reaction:** The control algorithm (using Active Disturbance Rejection Control - LADRC) identifies the spike and immediately commands the specific actuator to **retract**.[6]
4. **Outcome:** The sharp rock enters the space created by the retracted nail. The load is instantly redistributed to the adjacent nails, which are contacting the surrounding regolith. The sharp edge exerts zero force on the rover structure, preventing puncture.

3.2.2. Mode B: Active Traction (Peristaltic Gait)

In soft, unconsolidated regolith (like the "sand traps" that claimed the *Spirit* rover), slip is the primary failure mode. Fixed grousers can churn the soil, digging a hole.

1. **Action:** The AAGS alters its gait. The leading nails extend to maximize penetration depth, effectively acting as anchors.
2. **Retraction:** As the wheel rotates and a nail moves to the rear, it actively **retracts** before lifting off the ground.
3. **Physics:** This prevents the "excavation" effect where the exiting grouser lifts soil and

throws it backward. By retracting *while still in the ground*, the nail minimizes soil disturbance, maintaining the shear strength of the regolith for the next wheel pass.[7] This mimics the efficient walking motion of a rimless wheel.[10]

3.2.3. Mode C: Variable Diameter and Ride Height

The rover can dynamically adjust its ground clearance.

- **Scenario:** Traversing a field of small boulders.
- **Action:** All actuators extend simultaneously, increasing the wheel diameter from (for example) 0.5 meters to 0.8 meters. This increases the approach angle, allowing the rover to climb over larger obstacles without grounding its chassis.[11]
- **Slope Leveling:** On steep crater rims, the downhill wheels can extend and the uphill wheels retract, keeping the chassis level. This prevents tip-over and maintains the optimal orientation for communications antennas and solar arrays.[12]

3.3. Structural Design of the "Nail" End-Effector

The tip of the actuator must withstand the direct abrasion of the regolith.

- **Geometry:** A simple needle point provides poor flotation. The design utilizes a **Tapered Grouser with a Footpad**. The footpad provides surface area for soft sand, while the central tapered spine provides the "bite" for hard rock.
- **Compliance:** To protect the delicate internal screw mechanism from shock, the nail assembly includes a **Series Elastic Element (SEA)**—a heavy-duty die spring or compliant titanium flexure located between the actuator rod and the ground tip.[11] This passively absorbs high-frequency impacts ($>100 \text{ Hz}$) that are too fast for the active control loop to address.

3.4. Comparative Performance Analysis

Performance	Passive Rigid	Active AAGS	Technical

Metric	Wheel (MSL/M2020)	"Wheel of Nails"	Justification
Puncture Resistance	**Low**. Thin skin vulnerable to point loads.	**High**. Active retraction eliminates point loads.	Distributed actuation allows local deformation without material yield.[1]
Soft Soil Traction	**Moderate**. Fixed grousers cause excavation.	**High**. Retraction gait prevents digging.	Active control of entry/exit angles optimizes soil shear mechanics.[7]
Obstacle Clearance	**Fixed**. Dependent on wheel radius.	**Variable**. Radius can increase by 50%.	Linear extension capability.[11]
Energy Efficiency	**High**. Passive rolling.	**Low**. Constant actuator power required.	Requires advanced power systems (see Sec. 5).
Complexity/Mass	**Low**. Simple structure.	**High**. Multiple motors/controllers per wheel.	Trade-off for survivability in extreme environments.

---

4. Materials Science for Survivability: Hardening the Machine

The implementation of the AAGS on Mercury requires materials that can maintain structural and optical integrity in an environment that destroys conventional engineering materials.

4.1. Transparent Radiation Shielding: Aluminum Oxynitride (ALON)

The AAGS relies on vision systems (LiDAR, stereo cameras) to map the terrain and preemptively identify hazards. These sensors are vulnerable to micrometeoroid pitting and radiation-induced darkening (browning).

Aluminum Oxynitride (ALON), a transparent ceramic with the composition $(AlN)_x \cdot (Al_2O_3)_{1-x}$, is the enabling material for these optical apertures.[13]

- **Mechanical Hardness:** ALON has a Knoop hardness of $\sim 1800 \text{ kg/mm}^2$, which is 4 times harder than fused silica glass and 85% as hard as sapphire.[13] This makes it virtually impervious to "sandblasting" by high-velocity regolith dust, ensuring that camera lenses remain clear over multi-year missions.
- **Radiation Stability:** Unlike borosilicate glass, which develops color centers (defects that absorb light) under gamma and proton irradiation, ALON maintains high transparency from the UV ($0.2 \mu m$) to the Mid-IR ($5.0 \mu m$).[13] This broad transmission window is critical for the rover's multispectral mineralogy instruments.
- **Structural Application:** ALON's high strength (Compressive strength 2.68 GPa) allows it to be used not just for windows, but as transparent structural armor. The rover's sensor mast could be encased in a seamless ALON dome, providing ballistic protection against micrometeoroids while allowing 360° visibility.[14]

4.2. Thermal Insulation: Transparent Polyimide Aerogels

The linear actuators located in the wheel hubs are exposed to surface temperatures up to 700 K. However, the permanent magnets in the motors will demagnetize (pass their Curie point) at such temperatures. Active cooling is energy-expensive; passive insulation is preferred.

Polyimide Aerogels represent a breakthrough in this domain.[15]

- **Structure:** Unlike brittle silica aerogels, polyimide aerogels are cross-linked polymer networks that are mechanically robust, flexible, and foldable. They are 500 times stronger than traditional aerogels.[16]
- **Performance:** They offer extremely low thermal conductivity ($\sim 0.014 \text{ W/mK}$) while maintaining high optical transparency.
- **Implementation:** The linear actuators can be wrapped in a blanket of transparent polyimide aerogel. This allows for radiative heat dissipation from the motors during the cooler phases while blocking the immense conductive and convective heat load from the Mercurian surface. The transparency allows visual inspection cameras to monitor the internal health of the actuators (lubricant status, gear wear) without removing the

insulation.[17]

4.3. Graded-Z Shielding for Electronics

The central computer controlling the AAGS must be shielded from the intense flux of solar energetic particles (SEPs) found in Mercury's magnetospheric cusps. A single-material shield (like lead) is dangerous because high-energy protons striking high-Z atoms produce secondary radiation (Bremsstrahlung) that is often more penetrating than the primary particle.

Graded-Z Shielding is the required architecture [18]:

1. **Outer Layer (Low-Z):** A hydrogen-rich material to scatter and slow down protons. On Mercury, where polyethylene would melt, **Lithium Hydride (LiH)** or high-temperature polymers are used.
2. **Middle Layer (High-Z): Tantalum** or **Tungsten** to attenuate the gamma rays and X-rays.
3. **Inner Layer (Low-Z):** A final layer of **Boron Carbide (B_4C)** or similar material to absorb any thermalized neutrons generated by the interaction, preventing them from causing single-event upsets (SEUs) in the CPU.[19]

4.4. Active Magnetic Shielding (M2P2)

Given the unlimited solar energy available on Mercury, the rover can employ **Active Magnetic Shielding**. Based on the Mini-Magnetospheric Plasma Propulsion (M2P2) concept, the rover deploys a solenoid to generate a magnetic field and injects a small amount of plasma to "inflate" the field lines.[20] This creates a magnetic bubble significantly larger than the physical spacecraft, deflecting solar wind plasma and protecting the sensitive electronics and potentially biological payloads from ionizing radiation.

---

5. Energy Infrastructure: Powering the Active Rover

The AAGS is energetically demanding. While a passive rover might require 100 W for mobility, an active rover with 24-36 linear actuators holding position and actively damping

vibrations could draw peaks of $5\text{--}10 \text{ kW}$. Standard Radioisotope Thermoelectric Generators (RTGs) are insufficient. The mission requires a high-density power infrastructure.

5.1. Solar Concentrator Power Stations

Mercury's solar constant ($6.2\text{--}14.4 \text{ kW/m}^2$) makes it the ideal location for **Concentrated Solar Power (CSP)**.

- **Design:** The rover would deploy stationary or towable parabolic troughs. These concentrators focus sunlight onto a receiver tube containing a heat transfer fluid.[21]
- **Efficiency:** Unlike photovoltaics, which degrade in high heat, thermal engines (Stirling or Brayton cycles) become *more* efficient as the temperature difference (ΔT) increases. A solar concentrator on Mercury can easily achieve working fluid temperatures $>1000^\circ \text{C}$.[22]
- **Regolith Sintering (ISRU):** The optical train of the concentrator can be decoupled from the engine and focused directly onto the regolith. At temperatures $>1100^\circ \text{C}$, the regolith sinters into a ceramic; at $>1400^\circ \text{C}$, it melts into magma.[23] This allows the rover to act as a mobile foundry, 3D-printing its own roads or landing pads to stabilize the loose terrain, thereby reducing the energy cost of transport for future logistical flows.[24]

5.2. Molten Salt Thermal Energy Storage (TES)

The critical challenge on Mercury is the diurnal cycle: roughly 88 Earth days of searing heat followed by 88 days of deep freeze. Batteries cannot bridge this gap. **Molten Salt** systems store energy as heat.

- **Chemistry:** Standard "Solar Salt" (Nitrates) freezes at $\sim 220^\circ \text{C}$. For Mercury, a ternary or quaternary eutectic mixture (e.g., $LiNO_3-NaNO_3-KNO_3-Ca(NO_3)_2$) is engineered to have a low melting point ($\sim 65^\circ \text{C}$) while remaining stable up to 500°C.[25]
- **Operational Cycle:**
  - **Day:** The solar concentrator melts the salt, raising it to 500°C. It is stored in a heavily insulated tank.
  - **Night:** The hot salt is pumped through a heat exchanger. It provides thermal maintenance for the rover's lubricants and drives a Stirling engine to generate

electricity for the active suspension and scientific instruments.[27]
    - **Capacity:** Molten salt has a high volumetric heat capacity ($>3000 \text{ kJ/m}^3\text{K}$). A few cubic meters of salt can power a rover through the long night.

5.3. Ionic Liquids for Heat Transfer

For thermal loops that must operate across the widest possible range (e.g., cooling the linear motors during the day and heating them at night), **Ionic Liquids (ILs)** are superior to water or oils.

- **Properties:** ILs like imidazolium-based salts have negligible vapor pressure (they won't boil off in a vacuum leak), high thermal stability, and liquid ranges spanning from -80°C to $>300^\circ \text{C}$.[26]
- **Application:** They serve as the hydraulic fluid for any active cooling systems and potentially as the lubricant for the ball screw actuators, providing wear protection without outgassing.[28]

5.4. Geothermal Heat Rejection

While the surface of Mercury is hot, the subsurface temperature stabilizes a few meters down to the average internal temperature ($\sim 400 \text{ K}$).

- **Mechanism:** The rover can use its active "nails" to drill or push heat exchange probes into the subsurface.
- **Geo-exchange:** During the peak of the day (700 K), the subsurface (400 K) acts as a heat sink. The rover pumps its waste heat into the ground, significantly reducing the load on its radiators and allowing the linear actuators to operate continuously without overheating.[29]

---

6. Beyond Mercury: The Interstellar Precursor

The engineering solutions required for Mercury—active adaptation, extreme radiation shielding, and autonomous energy management—are direct analogues to the technologies

required for **Interstellar Precursor Missions**.

6.1. Exoplanetary Targets and Transit Physics

Current surveys identify several nearby exoplanets as prime targets for exploration [30]:

- **Proxima Centauri b (4.24 ly):** Earth-mass, habitable zone, but subjected to intense stellar flares. Requires the active shielding and radiation-hardened materials (ALON) validated on Mercury.
- **Teegarden's Star b (12.5 ly):** High Earth Similarity Index (0.90). Orbiting a stable, quiet star. An ideal target for searching for biosignatures.[32]
- **Ross 128 b (11 ly):** Another temperate world around a quiet red dwarf, potentially offering easier atmospheric characterization.[34]

Propulsion and Arrival:
The Breakthrough Starshot initiative proposes accelerating gram-scale probes to $0.2c$ using gigawatt-class laser arrays.35

- **Transit Time:** At $0.2c$, a probe reaches Proxima b in ~ 22 years.
- **The Mobility Link:** Upon arrival, a high-speed flyby yields limited data. Deceleration requires magnetic sails or photon braking. Once on the surface, a "micro-rover" cannot rely on wheels that might get stuck in unknown alien regolith. The **AAGS concept scales down**. A MEMS-based "chip-rover" could use piezoelectric "nails" to grip the surface of Proxima b, navigating with the same active logic used on Mercury.[36]

6.2. Optical Beam Steering and Communications

Data return from 4 light-years away requires tightly collimated laser beams. Mechanical gimbals are too heavy and prone to failure for interstellar probes.

- **Solution:** The "mirror array" technologies researched for the AAGS sensors [37] translate directly to **Optical Phased Arrays (OPAs)**.
- **Technology:** An OPA on the interstellar probe can steer the communications laser beam back to Earth with micro-radian precision by adjusting the phase of light emitted from thousands of nano-antennas, with no moving parts. This technology would be flight-tested on the Mercury rover to maintain high-bandwidth links with Earth despite the vibrations of the active suspension.[38]

7. Societal Implications: Building a Type I/II Civilization

The development of the "Wheel of Nails" rover and its supporting infrastructure on Mercury is not an isolated scientific endeavor. It represents the first step in the industrialization of the inner solar system, a prerequisite for advancing humanity on the **Kardashev Scale**.[39]

7.1. The Mercury Foundry

The deployment of solar concentrators capable of melting regolith [23] transforms the rover from an explorer into a builder.

- **Dyson Swarm Precursors:** Mercury is rich in metals and silicon. An armada of active rovers could mine materials and use solar heat to manufacture the components for a Dyson Swarm (a Type II civilization structure). The rovers would build the launch loops and power stations necessary to disassemble the planet and harvest the Sun's full energy output.[40]
- **Energy Abundance:** Mastering energy storage (Molten Salt) and transmission on Mercury provides the blueprint for solving Earth's energy crises, enabling a true Type I planetary civilization.

8. Conclusion and Recommendations

The "Wheel of Nails" is a response to the unforgiving physics of the inner solar system. It rejects the passivity of traditional design in favor of active, intelligent mechanical adaptation.

Key Technical Recommendations:

1. **Adopt Active Compliance:** Future rover wheels for hazardous terrain must utilize radial linear actuators (Planetary Roller Screws) to permit real-time shape-shifting and obstacle avoidance.
2. **Implement ALON Optics:** Replace all fused silica sensor windows with Aluminum Oxynitride to ensure mission longevity against abrasion and radiation.
3. **Deploy Molten Salt TES:** Utilize eutectic nitrate/salt mixtures for thermal management to enable continuous operation through the Mercurian night.

4. **Validate Interstellar Tech:** Use the Mercury mission profile to flight-test Optical Phased Arrays and Active Magnetic Shielding, retiring risk for future missions to Proxima Centauri b.

By creating a machine that can walk on nails, traverse fire, and see through radiation, we do more than explore a planet; we forge the tools necessary for our species to become an interstellar civilization.

Appendix: Comparative Data Tables

Table A: Linear Actuator Technologies for AAGS

Actuator Type	Force Density	Efficiency	Back-Drive Risk	Vacuum Suitability	Recommended Application
Ball Screw	High	$>90\%$	High (Needs Brake)	Moderate (Lubrication)	**General Mobility**
Roller Screw	**Very High**	$80\text{--}90\%$	Medium	**High**	**Heavy Shock Loads**
Lead Screw	Medium	$30\text{--}50\%$	**Low (Self-Locking)**	High (Dry Lube)	Holding Position / Safety
Linear Motor	Low	Variable	N/A	High	High-Speed Retraction (Reflex)

Data synthesized from.[4]

Table B: Nearby Exoplanet Targets for Future Mobility

Planet	Distance (ly)	Mass (ME)	Equilibrium Temp (K)	Habitability Potential
Proxima Centauri b	4.24	1.27	234	High (Liquid Water possible)
Barnard's Star b	5.96	3.2	105	Low (Frozen)
Ross 128 b	11.0	1.40	301	**Very High** (Quiet Star)
Teegarden's Star b	12.5	1.05	300	**Highest ESI (0.90)**
Wolf 1061 c	14.1	3.4	223	Moderate

Data synthesized from.[30]

Works cited

1. Assessing Mars Curiosity Rover Wheel Damage - JPL Robotics - NASA, accessed November 30, 2025, https://www-robotics.jpl.nasa.gov/media/documents/fmwi-rankin-2022-0225-final.pdf
2. How the solar wind interacts with Mercury's surface? - Tech Explorist, accessed November 30, 2025, https://www.techexplorist.com/solar-wind-interacts-mercury-surface/69669/
3. (PDF) Properties of Solar Wind Structures at Mercury's Orbit - ResearchGate, accessed November 30, 2025, https://www.researchgate.net/publication/344045826_Properties_of_Solar_Wind_Structures_at_Mercury's_Orbit
4. Understanding linear actuator technology - Linear Motion Tips, accessed November 30, 2025, https://www.linearmotiontips.com/understanding-linear-actuator-technology/

5. Heavy Duty Linear Actuators with Stroke 12v, 36v inch - Venture Mfg Co., accessed November 30, 2025, https://www.venturemfgco.com/heavy-duty-linear-actuators/
6. Height Control and Experimental Study of Linear Motor-Based Active Suspension Systems, accessed November 30, 2025, https://www.mdpi.com/2079-9292/14/12/2482
7. Diagram of a wheeled rover with assistive grouser mechanism - ResearchGate, accessed November 30, 2025, https://www.researchgate.net/figure/Diagram-of-a-wheeled-rover-with-assistive-grouser-mechanism-a-Assistive-grouser-angle_fig1_308181447
8. The Effect of Assistive Anchor-Like Grousers on Wheeled Rover Performance over Unconsolidated Sandy Dune Inclines - PMC - PubMed Central, accessed November 30, 2025, https://pmc.ncbi.nlm.nih.gov/articles/PMC5038780/
9. Design of wheels with grousers for planetary rovers traveling over loose soil - ResearchGate, accessed November 30, 2025, https://www.researchgate.net/publication/259092053_Design_of_wheels_with_grousers_for_planetary_rovers_traveling_over_loose_soil
10. (PDF) Development of a rimless wheel robot with telescopic legs for step adaptability, accessed November 30, 2025, https://www.researchgate.net/publication/379319791_Development_of_a_rimless_wheel_robot_with_telescopic_legs_for_step_adaptability
11. NoteBot: Fully retractable spoke-wheel robot based on a compliant mechanism | Request PDF - ResearchGate, accessed November 30, 2025, https://www.researchgate.net/publication/396711102_NoteBot_Fully_retractable_spoke-wheel_robot_based_on_a_compliant_mechanism
12. An Active Suspension System for a Planetary Rover, accessed November 30, 2025, https://www.dfki.de/fileadmin/user_upload/import/7261_20140617_iSAIRAS14_CordesEtAl_ActiveSuspensionPlanetaryRover.pdf
13. Aluminium oxynitride - Wikipedia, accessed November 30, 2025, https://en.wikipedia.org/wiki/Aluminium_oxynitride
14. Aluminum oxynitride manufacturing process - ConRo, accessed November 30, 2025, https://www.conro.com/Blog/Aluminum-oxynitride-manufacturing-process/
15. Optically Transparent Polyimide Aerogels | T2 Portal - NASA Technology Transfer Program, accessed November 30, 2025, https://technology.nasa.gov/patent/LEW-TOPS-117
16. Durable Polyimide Aerogels | T2 Portal - NASA Technology Transfer Program, accessed November 30, 2025, https://technology.nasa.gov/patent/LEW-TOPS-133
17. Optically Transparent Polyimide Aerogels - Tech Briefs, accessed November 30, 2025, https://www.techbriefs.com/component/content/article/33593-lew-tops-117
18. Radiation protection - Wikipedia, accessed November 30, 2025, https://en.wikipedia.org/wiki/Radiation_protection
19. FAST AND THERMAL NEUTRON REMOVAL CROSS-SECTION FOR CERAMIC GLASS ALUMINUM OXYNITRIDE - DergiPark, accessed November 30, 2025, https://dergipark.org.tr/en/download/article-file/4035269

20. Tapping the Energy of the Solar Wind for Spacecraft Propulsion R. M. Winglee Geophysics - University of Washington, accessed November 30, 2025, https://earthweb.ess.washington.edu/space/M2P2/m2p2.org.PDF
21. Heat Supply to Industrial Processes via Molten Salt Solar Concentrators - MDPI, accessed November 30, 2025, https://www.mdpi.com/1996-1073/17/18/4541
22. geothermal energy - SMU, accessed November 30, 2025, https://www.smu.edu/-/media/site/dedman/academics/programs/geothermal-lab/documents/teachermaterials/tx_geo_history_virtus.pdf
23. Feasibility Study and Prospects Analysis of Lunar Regolith Forming Based on Concentrated Solar Energy - ResearchGate, accessed November 30, 2025, https://www.researchgate.net/publication/390331104_Feasibility_Study_and_Prospects_Analysis_of_Lunar_Regolith_Forming_Based_on_Concentrated_Solar_Energy
24. Published at Acta Astronautica - Feasibility study and prospects analysis of lunar regolith forming based on concentrated solar energy - SolarPACES, accessed November 30, 2025, https://www.solarpaces.org/published-at-acta-astronautica-feasibility-study-and-prospects-analysis-of-lunar-regolith-forming-based-on-concentrated-solar-energy/
25. Development of Molten Salt Heat Transfer Fluid With Low Melting Point and High Thermal Stability | Request PDF - ResearchGate, accessed November 30, 2025, https://www.researchgate.net/publication/229005256_Development_of_Molten_Salt_Heat_Transfer_Fluid_With_Low_Melting_Point_and_High_Thermal_Stability
26. Ionic Liquids as Thermal Fluids - Semantic Scholar, accessed November 30, 2025, https://pdfs.semanticscholar.org/e4f6/08b8f91d8cddefd01fa5d2652891b8ab510c.pdf?skipShowableCheck=true
27. Molten Salt Storage - Stanford University, accessed November 30, 2025, http://large.stanford.edu/courses/2015/ph240/dodaro2/
28. Ionic liquids in space technology | IoLiTec, accessed November 30, 2025, https://iolitec.de/en/node/675
29. Geothermal - Colorado Geological Survey, accessed November 30, 2025, https://coloradogeologicalsurvey.org/energy/e-geothermal/
30. List of nearest exoplanets - Wikipedia, accessed November 30, 2025, https://en.wikipedia.org/wiki/List_of_nearest_exoplanets
31. Nearest exoplanets - Stellar Catalog, accessed November 30, 2025, https://www.stellarcatalog.com/exoplanets.php?list=2
32. Teegarden's Star b - Grokipedia, accessed November 30, 2025, https://grokipedia.com/page/Teegarden's_Star_b
33. Teegarden's Star b - Wikipedia, accessed November 30, 2025, https://en.wikipedia.org/wiki/Teegarden%27s_Star_b
34. Potentially habitable world found just 11 light years away | Science | The Guardian, accessed November 30, 2025, https://www.theguardian.com/science/across-the-universe/2017/nov/15/potentially-habitable-world-found-just-11-light-years-away-ross-128-b
35. Breakthrough Starshot - Wikipedia, accessed November 30, 2025,

https://en.wikipedia.org/wiki/Breakthrough_Starshot
36. Swarming Proxima Centauri: Optical Communications Over Interstellar Distances - arXiv, accessed November 30, 2025, https://arxiv.org/html/2309.07061v2
37. Optical multi-beam steering and communication using integrated acousto-optics arrays - PMC - PubMed Central, accessed November 30, 2025, https://pmc.ncbi.nlm.nih.gov/articles/PMC12081728/
38. Integrated Optical Phased Arrays for Beam Forming and Steering - MDPI, accessed November 30, 2025, https://www.mdpi.com/2076-3417/11/9/4017
39. Kardashev scale - Wikipedia, accessed November 30, 2025, https://en.wikipedia.org/wiki/Kardashev_scale
40. Society, Economy & Government of a Type II Civilization [closed] - Worldbuilding Stack Exchange, accessed November 30, 2025, https://worldbuilding.stackexchange.com/questions/103494/society-economy-government-of-a-type-ii-civilization
41. The Kardashev scale is often cited in many sci-fi books and movies. But what is it? - Medium, accessed November 30, 2025, https://medium.com/@ruizrivera.alejandro/the-unmanned-aerial-phenomenon-uap-formerly-ufo-is-a-very-hot-topic-nowadays-13b0c9f6af75
42. Linear actuators - Choose between several models today - Linak-US.com, accessed November 30, 2025, https://www.linak-us.com/products/linear-actuators/
43. Electric Linear Actuators | Tolomatic, accessed November 30, 2025, https://www.tolomatic.com/products/electric-linear-actuators/
44. Wolf 1061c - Wikipedia, accessed November 30, 2025, https://en.wikipedia.org/wiki/Wolf_1061c
45. Ross 128 b - Wikipedia, accessed November 30, 2025, https://en.wikipedia.org/wiki/Ross_128_b