

CSc 134

Database Management and File Organization

9. Indexing Structures for Files

Ying Jin

Computer Science Department

California state University, Sacramento

Single-level ordered indexes

- Structure
 - Ordered index file
 - Small, easy to do binary search
 - A list of pointers to disk blocks
- Dense index vs. sparse (nondense) index
 - Dense: One index entry for every record of data files.
 - Sparse: Has index entries for only some of the search values.
- Primary index
- Clustering index
- Secondary index

Primary Indexes

- Specified on the *ordering key field* of an ordered file of records.
- Ordering key field is used to **physically** order the file records on disk.
- Index file consists of index entry (or index record)
- index entry: <primary key, pointer to disk block>
- index entry i: <K(i), P(i)>
- 1 index entry --- 1 block in the data file
- Anchor record of the block (block anchor): first record in each block of the data file.
- Dense index or sparse index 😊?

Access a record

- Load blocks of index files
- Search in index files
- load corresponding data file

Average time to access a record

- B: block size, R: record size, r: total number of records.
- blocking factor $bfr = \lfloor B/R \rfloor$ records per block
- A file has b block: $b = (r/bfr)$
- A file with **b** block, binary search to find a specific record needs to access $\log_2 b$ block
 - Linear search $b/2$.
- Example1
 - $r=30,000, B=1024, R=100$.
 - How many block accesses are needed for a binary search on the data file?

Example 1 (Cont.)

- Use primary index
 - ordering key field: $V=9$ bytes, a block pointer $P=6$ bytes.

Insertion and Deletion

- Insertion
 - Solution 1
 - Move space for the new record
 - May change some index entries
 - Solution 2
 - Using an unordered overflow file
 - Solution 3
 - Linked list of overflow records
- Deletion
 - Deletion markers.

Clustering Indexes

- Files are physically ordered on non-key field – clustering field
- Clustering field does not required to have distinct value.
- Clustering index
- <index field, pointer>
 - 1 entry for each **distinct value** of the clustering field.
 - a pointer to the **first block** in the data file that has a record with that value for its clustering field.
- Figure

Insertion


- Make insertion more efficient:
It is common to reserve a whole block (or a cluster of contiguous blocks) for each value of the clustering field.
- Figure

Secondary Indexes

- Provide a secondary means of accessing a file for which some primary access already exists
- Index entry
 - index field: nonordering field of the data file
 - pointer: either a block pointer or a record pointer

Secondary indexes

- Secondary key: Index field has a distinct value for every record
- One index entry for each record in the data file
- e.g. Block pointer (figure)
 - Load and search index block
 - Load appropriate block
 - A search for the desired record within the block
- Dense index




Example 2

- $r = 30,000$, $R=100$, $B=1024$, $b=3000$
- Linear search
 - Require $b/2=3000/2 = 1500$ block accesses on the average
- Secondary index on non-ordering key field
 $v=9$, $P=6$

Secondary index on a non-key field

- Numerous records in the data file can have the same value for the indexing field
- Options for implementation
 1. Several index entries with the same $K(i)$ value – one for each record.
 2. Variable-length records for the index entries
 $\langle K(i), \langle P(i,1), \dots, P(i,k) \rangle \rangle$
 3. $\langle K(i), P(i) \rangle$ points to a block of record pointers (figure)
If some $K(i)$ occurs in **too many** records (pointers cannot fit in one block), **a cluster or linked list of blocks** is used. Figure

Option 3




Multilevel Indexes

- Idea

- If the first level needs more than one block of disk storage → require a second level index
- If the second level needs more than one block of disk storage → require a third level index
- ...
- Repeat the preceding process until all the entries of some index level t fit in a single block

TWO-LEVEL INDEX

DATAFILE



Multilevel indexes (Cont.)

- bfr_i is called **fan-out** of the multilevel index.
Referred as **fo**.
- In any level, $bfr_i = fo$ (# of record per block)
 - Reason: all index entries are the same size
- r_1 : total number of records in level 1
- the 1st level needs (r_1/fo) block
= # of entries needed at the 2nd index level
= $r_2 = (r_1/fo)$

Multilevel indexes (Cont.)

- the 2nd level needs $(r2/fo)$ block
= # of entries needed at the 3rd index level
= $r3 = (r2/fo)$
- **Approximately** t level index, such that $r1/((fo)^t) \geq 1$
- A multilevel index with $r1$ first-level entries will have approximately t level, where
$$t = \log_{fo} (r1)$$

B-Tree

- All leaf nodes are at the same level
- Figure
- Internal node of a B-tree
 $\langle P_1, \langle K_1, Pr_1 \rangle, P_2, \langle K_2, Pr_2 \rangle, \dots, \langle K_{q-1}, Pr_{q-1} \rangle, P_q \rangle$
 P_i – tree pointer
 Pr_i – data pointer (a pointer to the record whose search key field value = K_i , or to the data file block containing that record)

B-Tree (Cont.)

- Within each node, $K_1 < K_2 < \dots < K_{q-1}$
- For all search key field values X in the subtree pointed at by P_i
 - $K_{i-1} < X < K_i$, where $1 < i < q$
 - $X < K_i$, where $i=1$
 - $K_{i-1} < X$, where $i=q$;
- Leaf nodes have the same structure as internal nodes except that all of their tree pointers are null

B⁺ Tree

- Data pointers are stored only at the leaf nodes of the tree
- The leaf nodes have an entry for every value of the search field, along with a data pointer to the record (or block) if the search field is a key field
- The structure of leaf nodes differs from the structure of internal nodes
- Internal nodes of a B+ tree (figure)

Leaf node of a B⁺ tree

- $\langle \langle K_1, Pr_1 \rangle, \langle K_2, Pr_2 \rangle, \dots \langle K_{q-1}, Pr_{q-1} \rangle, P_{next} \rangle$

Pr_i is a data pointer

P_{next} points to the next leaf node of the B⁺ tree

- $K_1 < K_2 < \dots < K_{q-1}$
- Figure



These slides are based on the textbook:

R. Elmaseri and S. Navathe, *Fundamentals of Database Systems*, 6th Edition, Addison-Wesley.
Chapter 18.