


Robert Rico – An Embedded Systems Engineer

Structured Documentation & Reliable Solutions for Embedded Projects

Welcome Lab Notes

Earth Rover Development: STM32 Integration and SPI/DMA Challenges



Written by [Rob Rico](#) in [ESP-IDF](#), [Espressif](#), [Integrated Circuits](#), [STM32](#), [STM32CubeMX](#)

From Working Communication to Real-Time Control

After establishing reliable ESP-NOW communication between TX and RX devices and implementing basic SPI functionality, the next critical milestone was integrating the STM32L432KC Motor Control Board (MCB) into the data flow. What seemed like a straightforward addition of another SPI peripheral quickly revealed the complexities of multi-platform embedded development and real-time system requirements.

The goal was clear: extend the proven TX→RX communication chain to TX→RX→MCB, enabling joystick commands to control motors through a dedicated motor control processor. The reality involved wrestling with timing domains, DMA buffer management, and the fundamental differences between ESP32-C3 and STM32 development ecosystems.

Development Environment Transition

Moving from the unified ESP-IDF environment to STM32 development required establishing an entirely different toolchain and workflow.

STM32CubeMX vs. STM32CubeIDE Decision: Initial attempts with STM32CubeIDE revealed it created friction with the established VIM and CMake workflow. STM32CubeMX for code generation, followed by CMake integration, maintained consistency with the ESP32-C3 development approach while providing the necessary STM32 peripheral configuration.

OpenOCD and GDB Return: Unlike ESP-IDF's integrated debugging, STM32 development required manual OpenOCD configuration and GDB setup. This transition back to lower-level debugging tools provided more direct control but demanded greater familiarity with ARM debugging fundamentals.

CMake Integration Challenges: Combining STM32CubeMX-generated code with a custom CMake build system required careful management of generated files and manual integration of STM32 HAL libraries.

STM32 SPI Peripheral Implementation

Configuring the STM32L432KC as a full-duplex SPI peripheral introduced new categories of complexity beyond the ESP32-C3 controller implementation.

Basic Peripheral Configuration

The STM32 SPI peripheral required careful timing coordination with the ESP32-C3 controller. Initial configuration established the foundation for bidirectional communication.

Interrupt Handling Architecture

Unlike the ESP32-C3 controller side, the STM32 peripheral required reactive interrupt handling for incoming data. The peripheral couldn't predict when the ESP32-C3 would initiate communication, requiring robust buffer management and rapid response capability.

DMA Integration Necessity

Initial polling-based SPI implementation quickly revealed timing inadequacies for real-time motor control. When motor commands required processing within tight timing windows, CPU-blocking SPI operations created unacceptable latency.

DMA Configuration Investigation

Implementing DMA for SPI communication required understanding buffer management requirements and timing constraints. The investigation revealed the complexity of coordinating DMA transfers with SPI communication timing.

DMA Buffer Management Exploration

Initial DMA implementation focused on circular buffer approaches, though this would later prove problematic for the specific timing requirements. Circular buffer management introduced complex state tracking requirements that demanded careful evaluation.

Timing and Synchronization Challenges

Cross-platform communication revealed fundamental timing domain differences between ESP32-C3 and STM32L432KC.

Clock Domain Differences

The ESP32-C3 and STM32 operated at different base frequencies, creating setup/hold time violations:

- ESP32-C3: 80MHz APB clock with configurable SPI divisors
- STM32L432KC: 80MHz system clock with independent SPI timing

Logic Analyzer Validation

Timing issues required systematic logic analyzer investigation:

Setup Time Violations: ESP32-C3 data transitions occurred too close to STM32 clock edges
Hold Time Issues: STM32 data wasn't stable long enough for ESP32-C3 sampling
Clock Jitter: Inconsistent timing between platforms caused intermittent communication failures

Resolution Strategy: Reducing SPI clock frequency from 1MHz to 500kHz provided adequate timing margins for both platforms.

Data Format and Endianness Resolution

Multi-platform communication exposed byte ordering inconsistencies that required protocol-level solutions.

Endianness Investigation

Multi-platform communication revealed the importance of data format consistency. The investigation identified potential byte ordering issues that required systematic resolution for reliable data transfer between ESP32-C3 and STM32L432KC platforms.

Protocol Definition Investigation

Establishing a consistent packet structure required careful consideration of data format and transmission reliability. The investigation focused on creating robust communication protocols for multi-platform embedded systems.

Integration Success Criteria

The STM32 integration milestone was considered complete when several critical capabilities were demonstrated:

1. **Reliable Multi-Platform Communication:** ESP32-C3 to STM32L432KC data transfer without corruption
2. **Real-Time Performance:** Communication architecture ready for motor control timing requirements
3. **DMA Stability:** Continuous operation without buffer overflows or communication failures
4. **Bidirectional Data Flow:** Motor status feedback successfully transmitted back to ESP32-C3
5. **System Scalability:** Architecture ready for additional peripheral integration

Engineering Methodology Validation

This integration phase reinforced several critical embedded development practices:

Component Isolation Testing: Each SPI implementation was validated independently before integration
Logic Analyzer Dependency: Complex timing relationships couldn't be debugged without hardware-level visibility
Systematic Problem Resolution: Multi-platform issues required methodical investigation across both development environments
Documentation Discipline: Engineering journal entries became essential for tracking cross-platform debugging discoveries

Looking Forward: ADC Limitations Discovery

With reliable STM32 integration established, the next development phase focused on replacing test data with real analog inputs from joystick potentiometers. This transition would quickly reveal the ESP32-C3's ADC limitations and catalyze the discovery of analog multiplexing techniques that would fundamentally change the project's trajectory.

The successful STM32 integration provided the stable foundation necessary for the analog input expansion that followed, demonstrating how methodical subsystem development enables complex system capabilities.

Key Takeaway: Multi-platform embedded development requires understanding each platform's timing characteristics, development ecosystem differences, and communication protocol requirements. Success depends on systematic integration testing and comprehensive hardware-level debugging.

← [SPI Communication: From Theory to Working Protocol](#)

[Earth Rover Development: ADC Expansion Discovery and the Catalyst for DINO](#) →