

SQL Introduction

SQL SELECT (I)

SQL SELECT (II)

SQL ORDER BY

SQL GROUP BY

SQL LIKE

SQL Wildcards

SQL UNION

SQL Subquery

SQL ANY and ALL

SQL CASE

SQL HAVING

SQL EXISTS

SQL JOIN

SQL DATABASE & TABLE

SQL Insert, Update and Delete

SQL Constraints

SQL Additional Topics

- Related Topics
- SQL UNION

SQL Subquery

SQL Comments

SQL SELECT

SQL SELECT INTO Statement

SQL IN Operator

# SQL ANY and ALL

In this tutorial, we'll learn about SQL ANY and ALL operators with the help of examples.

## SQL ANY

SQL `ANY` compares a value of the first table with all values of the second table and returns the row if there is a match with any value.

For example, if we want to find teachers whose age is similar to any of the student's age, we can use

```
SELECT *
FROM Teachers
WHERE age = ANY (
  SELECT age
  FROM Students
);
```

Here, the sub query

```
SELECT age
FROM Students
```

returns all the ages from the `Students` table. And, the condition

```
WHERE age = ANY (...)
```

compares the student ages (returned by subquery) with the teacher's age. If there is any match, the corresponding row of the `Teachers` table is selected.



## SQL ALL

SQL `ALL` compares a value of the first table with all values of the second table and returns the row if there is a match with all values.

For example, if we want to find teachers whose age is greater than all students, we can use

```
SELECT *
FROM Teachers
WHERE age > ALL (
  SELECT age
  FROM Students
);
```


Here, the sub query

```
SELECT age
FROM Students
```

returns all the ages from the `Students` table. And, the condition

```
WHERE age > ALL (...)
```

compares the student ages (returned by subquery) with the teacher's age. If the teacher's age is greater than all student's ages, the corresponding row of the `Teachers` table is selected.




## ANY and ALL with Comparison Operators

We can use any [comparison operators](#) like `=`, `>`, `<`, etc. with the `ANY` and `ALL` keywords.

Let's see an example where we want teachers whose age is less than any student.

```
SELECT *
FROM Teachers
WHERE age < ANY (
  SELECT age
  FROM Students
);
```

Here, the SQL command selects rows if `age` in the **outer query** is less than any `age` in a **subquery**.



Previous Tutorial:  
SQL Subquery

Next Tutorial:  
SQL CASE →

Did you find this article helpful?

😊

😞

### Related Tutorials

- Programming

SQL UNION
- Programming

SQL Comments
- Programming

SQL Subquery
- Programming

SQL IN Operator