

SQL Introduction

SQL SELECT (I)

SQL SELECT (II)

SQL JOIN

SQL DATABASE & TABLE

SQL Insert, Update and Delete

SQL Constraints

SQL Additional Topics

SQL Constraints

SQL Not Null Constraint

SQL Unique Constraints

SQL Primary Key

SQL Foreign Key

SQL Check

SQL Default

SQL Create Index

# SQL Constraints

In this tutorial, we'll learn about constraints in SQL with the help of examples.

In a database table, we can add rules to a column known as **constraints**. These rules control the data that can be stored in a column.

For example, if a column has `NOT NULL` constraint, it means the column cannot store `NULL` values.

The constraints used in SQL are:

Constraint	Description
<code>NOT NULL</code>	values cannot be null
<code>UNIQUE</code>	values cannot match any older value
<code>PRIMARY KEY</code>	used to uniquely identify a row
<code>FOREIGN KEY</code>	references a row in another table
<code>CHECK</code>	validates condition for new value
<code>DEFAULT</code>	set default value if not passed
<code>CREATE INDEX</code>	used to speedup the read process

**Note:** These constraints are also called integrity constraints.

## NOT NULL Constraint

The `NOT NULL` constraint in a column means that the column cannot store `NULL` values. For example,

```
CREATE TABLE Colleges (  
  college_id INT NOT NULL,  
  college_code VARCHAR(20) NOT NULL,  
  college_name VARCHAR(50)  
);
```

Here, the `college_id` and the `college_code` columns of the `Colleges` table won't allow `NULL` values.

To learn more, visit [SQL NOT NULL Constraint](#).

## UNIQUE Constraint

The `UNIQUE` constraint in a column means that the column must have unique value. For example,

```
CREATE TABLE Colleges (  
  college_id INT NOT NULL UNIQUE,  
  college_code VARCHAR(20) UNIQUE,  
  college_name VARCHAR(50)  
);
```

Here, the value of the `college_code` column must be unique. Similarly, the value of `college_id` must be unique as well as it cannot store `NULL` values.

To learn more, visit [SQL UNIQUE Constraint](#).

## PRIMARY KEY Constraint

The `PRIMARY KEY` constraint is simply a combination of `NOT NULL` and `UNIQUE` constraints. It means that the column value is used to uniquely identify the row. For example,

```
CREATE TABLE Colleges (  
  college_id INT PRIMARY KEY,  
  college_code VARCHAR(20) NOT NULL,  
  college_name VARCHAR(50)  
);
```

Here, the value of the `college_id` column is a unique identifier for a row. Similarly, it cannot store `NULL` value and must be `UNIQUE`.

To learn more, visit [SQL PRIMARY KEY](#).

## FOREIGN KEY Constraint

The `FOREIGN KEY` (`REFERENCES` in some databases) constraint in a column is used to reference a record that exists in another table. For example,

```
CREATE TABLE Orders (  
  order_id INT PRIMARY KEY,  
  customer_id int REFERENCES Customers(id)  
);
```

Here, the value of the `college_code` column references the row in another table named `Customers`.

It means that the value of `customer_id` in the `Orders` table must be a value from the `id` column of the `Customers` table.

To learn more, visit [SQL FOREIGN KEY](#).

## CHECK Constraint

The `CHECK` constraint checks the condition before allowing values in a table. For example,

```
CREATE TABLE Orders (  
  order_id INT PRIMARY KEY,  
  amount int CHECK (amount >= 100)  
);
```

Here, the value of the `amount` column must be **greater than or equal to 100**. If not, the SQL statement results in an error.

To learn more, visit [SQL CHECK Constraint](#).

## DEFAULT Constraint

The `DEFAULT` constraint is used to set the default value if we try to store `NULL` in a column. For example,

```
CREATE TABLE College (  
  college_id INT PRIMARY KEY,  
  college_code VARCHAR(20),  
  college_country VARCHAR(20) DEFAULT 'US'  
);
```

Here, the default value of the `college_country` column is **US**.

If we try to store the `NULL` value in the `college_country` column, its value will be **US**.

To learn more, visit [SQL DEFAULT Constraint](#).

## CREATE INDEX Constraint

If a column has `CREATE INDEX` constraint, it's faster to retrieve data if we use that column for data retrieval. For example,

```
-- create table  
CREATE TABLE Colleges (  
  college_id INT PRIMARY KEY,  
  college_code VARCHAR(20) NOT NULL,  
  college_name VARCHAR(50)  
);  
  
-- create index  
CREATE INDEX college_index  
ON Colleges(college_code);
```

Here, the SQL command creates an index named `customers_index` on the `Customers` table using `customer_id` column.

**Note:** We cannot see the speed difference with less records in a table. However, we can easily notice the speed difference between using indexes and not using indexes.

To learn more, visit [SQL CREATE INDEX](#).

Previous Tutorial:

[SQL Delete and Truncate Rows](#)

Next Tutorial:

[SQL Not Null Constraint](#)

Did you find this article helpful?

😊

😞

### Related Tutorials

- Programming

SQL UNIQUE Constraint
- Programming

SQL NOT NULL Constraint
- Programming

SQL PRIMARY KEY
- Programming

SQL DEFAULT Constraint