

**M16878/4 CABLE - SHIELDED, PTFE TAPE JACKET**



PTFE insulated conductors (Type E - MIL-W-16878/4), color coded, cabled for 2 or more conductors, braided with silver-plated copper (90% minimum coverage), with an PTFE Teflon® tape overall jacket.

Conductor: Silver Plated Copper  
Insulation: Extruded PTFE  
Jacket: PTFE Tape  
Temp Rating: 200°C  
Voltage Rating: 600 Volts R.M.S.

Blake Part Number	AWG	Stranding	Number of Conductors	Nom. O.D. Over Conductor Inches	Finished Cable Nominal O.D. Inches
BCB-9671TJ	16	19/29	1	0.053	0.120
BCB-9672TJ	16	19/29	2	0.053	0.203
BCB-9673TJ	16	19/29	3	0.053	0.215
BCB-9674TJ	16	19/29	4	0.053	0.235
BCB-9675TJ	16	19/29	5	0.053	0.250
BCB-9676TJ	16	19/29	6	0.053	0.270
BCB-9681TJ	14	19/27	1	0.067	0.135
BCB-9682TJ	14	19/27	2	0.067	0.233
BCB-9683TJ	14	19/27	3	0.067	0.248
BCB-9684TJ	14	19/27	4	0.067	0.272
BCB-9685TJ	14	19/27	5	0.067	0.300
BCB-9686TJ	14	19/27	6	0.067	0.320
BCB-9691TJ	12	19/25	1	0.084	0.154
BCB-9692TJ	12	19/25	2	0.084	0.271
BCB-9693TJ	12	19/25	3	0.084	0.290
BCB-9694TJ	12	19/25	4	0.084	0.319

Cable Configurations up to 10 conductors.

\*Jackets can be made in all colors.