

AMS-DTL-23053/12 CLASS 1



M23053/12 is a PTFE heat shrink tubing. M23053/12 has the ability to withstand extreme heat and external chemicals, PTFE Shrink Tubing also boasts a low friction rating and a very low level of moisture absorption. M23053/12 has an operating temperature of -67°C to 250°C and classes 1-4 have a 2:1 shrink ratio and class 5 has a 4:1 shrink ratio.

MIL-DTL-23053/12
UL Recognized
RoHS Compliant

Class 1 - Heavy Wall – Shelf Life 4 Years

Blake Part Number	Expanded I.D. (in)	Recovered I.D. Max (in)	Nom. Recovered Wall Thickness (in)
BT-1200-101-X	0.166	0.130	0.030
BT-1200-102-X	0.250	0.193	0.030
BT-1200-103-X	0.333	0.257	0.030
BT-1200-104-X	0.415	0.320	0.030
BT-1200-105-X	0.498	0.383	0.030
BT-1200-106-X	0.580	0.448	0.030
BT-1200-107-X	0.666	0.510	0.030
BT-1200-108-X	0.748	0.572	0.030
BT-1200-109-X	0.830	0.637	0.030
BT-1200-110-X	0.915	0.700	0.032
BT-1200-111-X	1.000	0.764	0.040
BT-1200-112-X	1.170	0.891	0.045
BT-1200-113-X	1.330	1.020	0.050

X = Color: See Page BCC-1