

**AA-59569 Silver Plated Copper Tubular Braid**



Made in compliance with MIL-SPEC QQ-B-575 (as revised). Braid is formed so as to maintain coverage of 90% shielding, (70% for 0.78 and smaller), over the nominal diameters specified.

**Silver Plated:** Individual wires are silver plated copper wires, conforming to ASTM B298 standard, with 40 micro inches minimum of silver plating. Excellent for use at temperatures exceeding 200°C or where special resistance to corrosion is required

Blake Part Number	Nominal Inside Diameter (inch)	AWG of Individual Ends	Carriers	# of Wires Per Strand	Total # of Individual Ends	Approximate AWG Equivalent	Approx. Current Carrying Cap. (amps)
BBD-10329T	0.562	30	48	10	480	3	145.0
BBD-10330T	0.656	30	48	16	768	1	190.0
BBD-10331T	0.781	36	48	18	864	7	88.0
BBD-10332T	0.781	34	48	11	528	7	88.0
BBD-10333T	0.781	32	48	7	336	7	88.0
BBD-10334T	0.875	30	48	7	336	5	100.0
BBD-10335T	1.000	30	48	8	384	4	120.0
BBD-10336T	1.125	30	48	9	432	4	130.0
BBD-10337T	1.375	30	48	11	528	3	150.0
BBD-10338T	1.500	30	48	12	576	2	165.0