Dynamic Topological Layout and Orthogonal Routing Algorithm for BPMN Diagrams

Robert Waszkowski[1,*]

[1]Affiliation, department, city, postcode, country
[*]corresponding.author@example.com

ABSTRACT

The formalization of business processes through the Business Process Model and Notation (BPMN) is fundamental to modern digital systems, yet the automatic generation of aesthetically pleasing BPMN diagrams from pure semantic graph data remains a persistent and highly complex challenge. While text-to-BPMN systems and Large Language Models (LLMs) can dynamically generate abstract process logic, they rarely produce the visual Diagram Interchange (BPMNDI) coordinates required for readable rendering. Traditional graph drawing approaches—such as the Sugiyama hierarchical framework or strict grid-based layouts—fail to satisfy BPMN's domain-specific requirements, including orthogonal routing, discrete port assignments, and complex parallel or iterative loop topologies, often resulting in severe spatial bloat, redundant white space, or computationally intractable solutions. This paper presents a novel dynamic topological layout and orthogonal routing algorithm specifically designed for BPMN diagrams. Building on the foundational programmatic diagramming techniques of the Aurea EDEN framework, the proposed engine explicitly decouples topological constraint discovery from physical geometric compilation across seven sequential phases. By leveraging Depth-First Search (DFS) back-edge classification, an interval-graph-coloring-based multi-lane allocation scheme, and affine sub-cardinal port spreading, the algorithm guarantees orthogonal, overlap-free layouts without relying on rigid global grids or space-wasting dummy nodes. We detail the seven-phase execution engine and demonstrate its theoretical superiority over classical Sugiyama, grid-based, and minimum-cost-flow approaches across key metrics: area footprint, orthogonal bends, edge crossings, and rendering velocity. A comprehensive empirical benchmarking methodology using $N = 10{,}000$ procedurally generated BPMN graphs is outlined to formally validate these advantages.

Introduction

The formalization of business processes through the Business Process Model and Notation (BPMN) establishes a critical bridge between high-level organizational requirements and the technical specifications required for system implementation. As a standardized visual language, BPMN ensures that process logic remains transparent, auditable, and executable across a variety of complex domains, including digital twin simulations, IoT-aware models, and multi-agent AI systems[1–3]. However, while many modern modeling tools and automated generation engines can serialize process models into standard BPMN 2.0 XML formats, the visual representation—known as Diagram Interchange or BPMNDI—is often missing. This issue is particularly prevalent in the era of Generative AI, where text-to-BPMN systems and Large Language Models (LLMs) dynamically output abstract semantic logic without physical coordinates[4–6]. Consequently, the automatic generation of aesthetically pleasing, highly readable layouts from pure semantic graph data remains a persistent and highly complex challenge in software engineering[7,8].

The layout of a BPMN diagram is not merely a matter of mathematical aesthetics; it is a critical factor in cognitive ergonomics. Empirical evidence from cognitive psychology, eye-tracking experiments, and biometric studies demonstrates that poorly structured layouts significantly increase intrinsic cognitive load, leading to severe misinterpretations and human error during process analysis[9–12]. Despite this, standard directed graph layout algorithms are frequently applied to BPMN models with suboptimal results. General-purpose algorithms struggle to naturally accommodate the notation's strict requirements, which include orthogonal sequence flows, discrete attachment ports, and the complex parallel or iterative loop topologies inherent to business logic[13,14].

Traditional graph drawing paradigms approach this problem with severe structural limitations. Hierarchical layouts, such as the widely used Sugiyama framework, bloat the spatial footprint of diagrams by inserting massive volumes of "dummy nodes" to handle the backward-flowing cyclic loops inherent in iterative business processes[15–17]. Conversely, grid-based algorithms artificially constrain elements to rigid cells, resulting in catastrophic "cell expansion" where parallel paths force the generation of vast, empty visual fields[13]. Furthermore, force-directed paradigms natively produce continuous, varying-angle splines, fundamentally violating the strict orthogonal right-angle vector paths demanded by BPMN appearance standards.

The necessity for advanced, dynamic placement of diagram elements to reduce cognitive load was previously explored by the author in the context of the Aurea EDEN (Evolving Diagramming with Enriched Notations) project[18]. The Aurea EDEN

framework introduced a novel, programmatic 3D visualization library that dynamically mapped quantitative Key Performance Indicators (KPIs) as geometric properties directly onto e-commerce customer journey models. By treating KPIs as geometry within a spatially integrated 3D funnel, the framework significantly reduced analysts' cognitive workload and improved task completion times compared to traditional, fragmented 2D dashboards[18]. The present study is a direct continuation of this research trajectory. While the Aurea EDEN project successfully established flexible, programmatic methods for the topological placement and spatial linking of abstract diagram elements in three-dimensional environments, the strict syntactic rules of 2D BPMN modeling require a highly specialized orthogonal routing engine. This paper extends the foundational concepts of dynamic topological positioning from the Aurea EDEN architecture to address the unique deterministic challenges of complex, cyclic business process graphs.

Research Gap and Objectives There is a fundamental gap between the domain-specific visual constraints of BPMN 2.0 and the mathematical execution of existing graph drawing algorithms. Current methodologies frequently attempt to simultaneously process absolute physical routing coordinates while placing continuous node streams, leading to chaotic overlapping behavior, spatial bloat, or exponential computational intractability. The literature currently lacks a highly deterministic algorithmic approach that explicitly decouples topological discovery from physical geometric compilation, thereby natively accommodating complex cyclic loops and orthogonal routing without relying on rigid global grids or space-wasting dummy nodes. To resolve these profound structural deficiencies, this paper proposes a novel, dynamic topological layout and orthogonal routing algorithm specifically designed for BPMN diagrams. The primary objective is to dynamically recalculate exact topologies using mathematical Depth-First Search (DFS) back-edge classification and a multi-lane span-overlap allocation grid. By abandoning static XML visual data and absolute Cartesian positioning during the initial phases, the proposed execution engine seamlessly transitions raw graph data into natively drawn geometric vector graphics, minimizing connector overlaps, area footprints, and orthogonal bends.

State of the Art and Related Work

Cognitive Ergonomics and Layout Aesthetics The automatic layout of BPMN diagrams exists at the intersection of mathematical graph drawing and cognitive ergonomics. The evaluation of a layout algorithm's success is deeply dependent on objective metrics that correlate with human understandability[19,20]. From a cognitive perspective, diagram comprehension relies on minimizing extraneous cognitive load and maximizing pattern recognition capabilities[11]. Recent biometric studies utilizing electroencephalography (EEG) and eye-tracking have empirically validated that well-structured BPMN models significantly reduce mental workload, mitigate split-attention effects, and facilitate faster, more accurate decision-making[9,10]. Scientific literature identifies several priority aesthetics for process models: minimizing edge crossings, minimizing edge bends, maintaining strict orthogonality (the "Manhattan" look), and adhering to a consistent chronological information flow[19,21]. Furthermore, spatial organization plays a crucial role; layouts that require extensive horizontal scrolling impose a heavy comprehension penalty, prompting recommendations for complex multi-line or "snake" layouts when dealing with large-scale diagrams[10].

Modeling Guidelines and Real-World Usage Beyond mathematical aesthetics, researchers have established pragmatic, evidence-based modeling guidelines to ensure semantic clarity. Frameworks such as the Seven Process Modeling Guidelines (7PMG) and other comprehensive heuristic collections strongly advise limiting model size, avoiding overlapping elements, maintaining symmetry, and ensuring explicit, linear sequence flows[21,22]. Real-world repository mining of GitHub reveals that the theoretical preference for horizontal, left-to-right modeling aligns with practice, though a significant portion of user-generated models still fail to meet optimal readability standards due to inadequate tool support[23–25]. This lack of consistent tool support underscores the difficulty of building robust, BPMN-aware modeling user interfaces that can autonomously manage containment hierarchies, complex gateway alignments, and correct spatial port associations[7,26].

Limitations of Traditional Graph Drawing Paradigms To meet these aesthetic and domain-specific criteria, engineers have historically adapted general graph-drawing paradigms, though these expose severe structural limitations. The Sugiyama framework remains the most pervasive approach for visualizing directed graphs and forms the foundation of robust rendering engines like the Eclipse Layout Kernel (ELK)[15,16,27]. While robust for general Directed Acyclic Graphs (DAGs) and highly optimized for horizontal coordinate assignment[17], the Sugiyama pipeline struggles profoundly with BPMN's reliance on backward-flowing cyclic loops (rework iterations). Reversing back-edges and routing them orthogonally requires the insertion of numerous "dummy nodes" through dense intermediate layers, drastically bloating the spatial area and increasing computational overhead[15,16]. Alternatively, continuous orthogonal routing approaches derived from topology-shape-metrics (TSM) frame edge routing as a minimum-cost flow network[28]. While excellent at minimizing bends, these models frequently become computationally intractable (NP-hard) when encountering nodes with high degrees, and they do not inherently prioritize

chronological reading direction, often wrapping graph progressions in serpentine trails that destroy the temporal sequence visually required for business analysis.

BPMN-Specific Algorithmic Adaptations To address the shortcomings of general algorithms, several BPMN-specific layout strategies have been developed. Grid-based approaches map topological entities to a strictly defined discrete lattice to guarantee orthogonal grid snapping[13]. However, these methods suffer catastrophically from "cell expansion"; if one sequence path requires expansion, rigid mathematical constraints force the entire topological column to expand, propagating redundant white space and destroying tight-fitting aesthetics[13]. Structural decomposition methods offer a highly efficient alternative by partitioning the process model into Single-Entry-Single-Exit (SESE) fragments[14]. This bottom-up approach runs in linear time ($O(n)$) and excels at aligning matching split and join gateways, but it can be rigid when handling highly unstructured or non-planar graphs. Other advancements include sketch-driven interactive layouts that attempt to preserve a user's mental map during iterative editing[8,29], automated structural optimizations[30], and complex 2.5D hierarchical visualization models designed to reduce visual occlusion in massively layered systems[31]. Similarly, recent object-centric layout approaches extend the Sugiyama framework to visually group related object states to reduce visual confusion[32].

The Generative AI Frontier and the Synthesized Research Gap The demand for high-quality, automated diagram generation has reached a critical inflection point with the advent of Generative AI and Large Language Models (LLMs) in process modeling[33]. Tools such as the BPMN Assistant and ProMoAI demonstrate that LLMs can successfully generate and iteratively refine process models directly from natural language[4–6]. However, because generating syntactically and visually correct raw XML is highly error-prone for LLMs, these systems rely on lightweight intermediate representations (like JSON or POWL) that capture pure process logic without any geometric coordinate data[4,5]. The literature reveals a distinct gap: as AI systems instantaneously generate complex, cyclic semantic structures, existing layout frameworks fail to render them without suffering from extreme spatial bloat (dummy nodes), redundant white space (rigid grids), or unreadable chronological flows. This necessitates the development of a structurally distinct layout engine that explicitly separates topological constraint discovery from final physical vector routing, ensuring tight, orthogonal, and highly legible business logic visualizations natively.

To resolve these profound structural deficiencies, our dynamic approach explicitly abandons global grid dependencies, rigid hierarchical tiering, and arbitrary physics annealing. In their place, we leverage an independent, continuous relative Baseline Spine supported by purely deterministic continuous Axis-Aligned Bounding Box (AABB) mechanical shifting matrices, guaranteeing $O(N \log N)$ speeds while preserving formal orthogonal precision.

Algorithm Architecture and Mathematical Foundation

The core principle of our layout engine is the absolute, programmatic separation of topological discovery from physical geometric compilation. Traditional engines frequently attempt to simultaneously process X, Y routing coordinates while concurrently placing continuous node streams, leading to chaotic overlapping behavior. Our structural conversion pipeline explicitly decouples these responsibilities across seven sequential, distinct algorithmic phases. These phases operate strictly within a custom declarative fluent application programming interface (API), natively resolving topology before any Euclidean vector placement occurs.

Phase 1: Formal XML Parsing and Topological Graph Sub-Mapping

The layout converter initially ingests the BPMN Document Object Model (DOM) as a raw XML string sequence. Before any visual BPMNDI (Diagram Interchange) metadata is evaluated (and indeed, our system actively strips and ignores pre-existing DI to force deterministic layout), the engine mathematically constructs a pure, abstract directed graph representation $G = (V, E, \Lambda, \Phi)$.

Let V represent the finite set of formal diagram vertices. Each vertex $v \in V$ is defined as a tuple $v = \langle id, \lambda, w, h \rangle$, where:

- id is the unique XML semantic identifier.
- $\lambda \in \Lambda$ defines the specific BPMN categorical type (e.g., 'bpmn:ServiceTask', 'bpmn:ExclusiveGateway', 'bpmn:EndEvent'). The set Λ contains all 120+ valid BPMN 2.0 component types.
- w and h represent the discrete geometric width and height bounds in pixels.

Let $E \subseteq V \times V$ represent the set of directed edges logically corresponding to 'bpmn:sequenceFlow' elements. Each edge $e \in E$ is a directed pair $e = (u, v)$ where u is the source node and v is the target destination. $\Phi : E \to C$ represents an optional mapping of execution conditions C onto the edges (e.g., Gateway conditional branches).

The primary data structure requires mapping the vertices to their immediate topological forward and reverse connections. The algorithm iterates linearly $O(|E|)$ over the edge set, creating a multi-dimensional adjacency mapping array: $Adj[u] = \{v \in V \mid (u, v) \in E\}$.

Rather than executing an arbitrary heuristic graphical placement, our methodology insists upon determining the central "spine" of the workflow. We utilize an unweighted Breadth-First Search (BFS) algorithmic sweep originating specifically from the initial trigger node subset $v_{start} \subseteq V$, structurally defined where $\lambda =$ ‘bpmn:StartEvent‘. The engine mathematically evaluates all contiguous sequences propagating away from v_{start} to isolate the mathematically longest unbroken acyclic path:

$$P_{primary} = (v_{start}, v_1, v_2, \ldots, v_{k-1}, v_{end})$$

where v_{end} possesses an out-degree of 0 or identifies formally as a terminal ‘bpmn:EndEvent‘. This specific contiguous integer array $P_{primary}$ is permanently segregated into system memory. It serves as the baseline visual trunk of the entire chronological architecture architecture, dictating the overriding left-to-right reading cadence.

Phase 2: Deep Cycle Detection and Mathematical Back-Edge Profiling

Real-world industrial business processes intrinsically model repeated iterations, rework loops, and systematic retry mechanics. Generating layouts for cyclic graphs necessitates highly deterministic mathematical resolution. Standard graph accessibility algorithms (such as simple node reachability matrices) lack the nuance required to preserve forward-flowing nested parallel branches while simultaneously detecting and correctly routing massive backward-looping chronological cycles spanning across dozens of nodes.

Our layout engine isolates and traps cycles entirely topologically before any geometric lines are drawn. We implement a rigorous mathematical Depth-First Search (DFS) Back-Edge Classifier based on recursive vertex temporal state tracking arrays.

To unequivocally formalize sequence loops, the core memory tracks the topological "discovery status" of every vertex $v \in V$ arrayed across three distinct temporal states:

1. **White (Undiscovered)**: The vertex v has not yet been reached by any algorithmic traversal branch.
2. **Gray (Active Traversal stack)**: The vertex v has been discovered, and its recursive exploration remains active explicitly within the current DFS call execution stack.
3. **Black (Terminal Resolution)**: The vertex v has been completely processed, thoroughly explored, and all constituent adjacent edges mapping $Adj[v]$ have been definitively evaluated.

Algorithm 1 Algorithmic Topological State Vector Cycle Classification

Require: Extracted topological Graph $G = (V, E)$, Adjacency Matrix Adj formally sorted by $P_{primary}$ sequence priorities.
Ensure: A subset $Edges_{back} \subset E$ containing all chronologically reversed sequence flows.

```
Initialize semantic vector: Color[v] ← White, ∀v ∈ V
Initialize output set: Edges_back ← ∅
Initialize integer chronological timestamp: Time ← 0
function DFS-RECURSIVE-VISIT(u ∈ V)
    Color[u] ← Gray                                   ▷ Stage temporal state onto active execution block
    DiscoveryTime[u] ← Time ← Time + 1
    for each sequential target node v ∈ Adj[u] do
        if Color[v] == Gray then
            Found Loop:
            Edges_back ← Edges_back ∪ {(u, v)}        ▷ Proves edge directs back to actively resolving ancestor
        else if Color[v] == White then
            DFS-RECURSIVE-VISIT(v)                    ▷ Sub-routine descent
        end if
            ▷ A Color[v] == Black state implies a benign Cross-Edge pointing to an unrelated distinct parallel Branch,
    explicitly not a cycle.
    end for
    Color[u] ← Black                                  ▷ Release state off recursive stack block
    FinishTime[u] ← Time ← Time + 1
end function
```

As depicted precisely within the constraints of Algorithm 1, if during recursive descent a continuous directed edge $e = (u, v)$ points to a target destination v whose discrete state variable evaluates strictly as *Gray*, the underlying topological mathematics prove without ambiguity that the vector constitutes a chronological **Back-Edge** cyclic iteration.



Figure 1. UML Activity Diagram illustrating the mathematical Depth-First Search (DFS) topological back-edge cycle detection logic navigating execution arrays.

This formal implementation achieves two extraordinary operational advantages. Firstly, it elegantly curtails catastrophic infinite recursion layout loops which historically plunge automated BPMN renderers into execution memory faults. Secondly, it irrevocably isolates and tags cyclic vectors early, mapping them into $Edges_{back}$ specifically reserved for isolated $North$-facing routing protocols executed later during Phase 6 coordinate integration.

Phase 3 & Phase 4: Formalizing the Baseline Spine and Declarative DOM Topologies

Traditional graph layout approaches algorithmically compute and assign static, absolute Euclidean vectors $p_x, p_y \in \mathbb{R}^2$ immediately upon evaluating a node footprint. By contrast, our layout architecture completely abandons arrays of numbers holding absolute positional data. Instead, it leverages a custom declarative topological primitive application programming interface (API) that functions symbiotically with relative Document Object Model (DOM) bounding constraints.

All explicit nodes cataloged previously within the $P_{primary}$ sequence array during Phase 1 are sequentially generated, locking them strictly along a dominant mathematical layout baseline axis ($Y = 0$). Using our bespoke internal primitives (demonstrated systematically in Source Code Listing 1), each discrete node v_i is bound firmly by the formulaic function:

$$pos_x(v_i) = pos_x(v_{i-1}) + Width(v_{i-1}) + \Delta_{padding}$$

This mechanism forcefully chains the central physiological elements of the diagram into an aggressive linear reading composition.

```
/**
 * Executes the Phase 3 Baseline structural map using pure geometric relativity primitives.
 * Abandoning absolute (x,y) positioning allows seamless integration into varying
 * canvas sizing and dynamic bounding adjustments.
 */
class BaselineSpineBuilder {
    constructor(elementFactory) {
        this.factory = elementFactory;
        this.basePaddingX = 50; // Formal delta X space
    }

    constructBaselineSpine(primaryPathNodes) {
        let anchorReference = null;

        primaryPathNodes.forEach(nodeData => {
            // Instantiate the formal graphical semantic proxy
            const element = this.factory.createLayoutProxy(nodeData.id, nodeData.type);

            if (anchorReference === null) {
                // Root origin binding exactly onto (0,0)
```

```
                element.setAbsoluteCoordinates(0, 0);
            } else {
                // Declarative DOM constraint pushing relying on relative anchoring
                element.positionRightOf(anchorReference, this.basePaddingX);
            }
            // Advance the anchor iteration pointer
            anchorReference = element;
        });
    }
}
```

Listing 1. Source code snippet demonstrating declarative Layout API implementation establishing the topological Baseline Spine.

Vertices omitted from the isolated $P_{primary}$ subset immediately register as divergent topological pathways. The layout engine performs a secondary $O(|V|)$ algorithmic sweep against the remaining unexplored categorical set $V_{remaining} = V \setminus P_{primary}$.

If a structurally incoming mathematical edge $e(u,v) \in E$ arrives from a source node u which already holds definitively calculated geometric canvas positioning (thereby acting as a calculable spatial origin anchor), the engine instantiates a powerful routing abstraction defined as a 'Branch' object. This complex 'Branch' structure is then recursively navigated forward down the Adj table array until the sub-topological graph G_{branch} eventually terminates by weaving back into the primary baseline trunk logic structure.

Simultaneously, "bypassing sequence flows"—where a single lengthy directed edge spans directly across multiple intermediary elements of the baseline X axis without halting to instantiate formal graphic task nodes—are dynamically detected and structurally intercepted. To safely manipulate these sheer lines orchestrating complex graphical orthographic sweeps without destroying algorithmic parity, the underlying engine autonomously injects completely invisible topological proxies defined as 'AnchorPoints'. These microscopic zero-width elements synthesize what we refer to as a **Shortcut Routing Branch**, establishing discrete connection joints granting the Orthogonal Router guaranteed geometries to bind perfectly onto even the longest spanning line trajectories.

Utilizing the previously resolved DFS memory dictionary derived fundamentally from Phase 2 processing routines, all newly spawned abstract 'Branches' are categorically identified and formally tagged:

- **Iterative Logic Branch:** The newly traced subgraph topological sequence encompasses exclusively flow vectors previously evaluated precisely as elements matching $e \in Edges_{back}$. These dictate reverse temporal flow architecture.
- **Parallel Divergent Branch:** The traced sub-graph architecture features zero vector intersections against the cyclic arrays $G_{branch} \cap Edges_{back} = \emptyset$. It diverges and merges chronologically strictly progressing positively along the primary X-axis.

Phase 5: Interval Scheduling and Multi-Lane Graph Coloring Assignment

To prevent an arbitrary N-number of parallel branches from indiscriminately collapsing and mapping identically onto the exact same vertical coordinate Y (which grid-based layouts solve by ballooning the entire diagram column), our engine institutes a secondary axis-spanning mathematical evaluation explicitly solving for continuous vertical lane dispensation.

This process mathematically resembles a variation of the classic **Interval Graph Coloring Problem** or **Register Allocation** algorithm. Each abstract 'Branch' isolated during Phase 4 evaluates its own logical bounded Euclidean span measured strictly against the primary chronological X-axis progression vector:

$$span_{logical}(branch_i) = |pos_x(v_{merge}) - pos_x(v_{start})|$$

The engine constructs an array ranking all active branches exactly $S_{active} = \{b_1, b_2, \ldots, b_m\}$, structurally ordered symmetrically ascending by the absolute scalar value of their respective $span_{logical}$. For any given target discrete $Lane_L \in \mathbb{Z}^+$ (representing a conceptual block of vertical real estate above or below the baseline), an intersection collision mapping is performed.

Formalizing the collision theorem: Two distinct topological branch spans $S_1 = [x_{start1}, x_{end1}]$ and $S_2 = [x_{start2}, x_{end2}]$ mathematically collide and thus occupy mutually exclusive topological boundaries if and only if the absolute intersection of their X-axis shadow intervals is strictly non-empty:

$$\max(x_{start1}, x_{start2}) \leq \min(x_{end1}, x_{end2}) + \delta_{safety}$$

The purposeful use of $\leq$ paired with the δ_{safety} threshold forces strict, observable separation margins. If two parallel tasks intrinsically share an mathematically identical X starting column (such as diverging simultaneously exactly identical from an 'ExclusiveGateway' component), their interval overlap immediately flags them as mutually conflicting on $Lane_0$. Thus, they are



Figure 2. UML Activity Diagram mapping the robust Span-Overlap mathematical Lane Allocation scheduling optimization algorithm solving branch collisions without requiring absolute grid rigidity.

programmatically forced to diverge outwards into independent L layers. The evaluation triggers an iterative counter $L \leftarrow L+1$, repeating recursively against the collision array matrix until an isolated safe horizontal spanway is definitively secured.

Once the mathematically optimal discrete target $Lane_L$ is explicitly secured, graphical linear Affine translations execute to drag the abstract topology vector configurations decisively out from Euclidean $[0,0]$. Parallel Subgraphs uniformly distribute downward towards infinitely expanding positive arrays: $pos_y(v_{all}) = L_{integer} \times \Delta Y_{padding}$. Iterative Subgraphs conversely aggressively invert symmetrically across the baseline into $-Y$ quadrants, arching backwards predictably overhead.

Phase 6: Sub-Cardinal Port Spreading and Collinear Mitigation Geometry

The strict definition delineating clean, universally readable BPMN artifact layouts demands rigorous Orthogonal rectangular splines predictably intersecting highly distinct and identifiable target ports directly on element physical boundaries (Faces N, S, E, W).

Cardinal Routing Directional Matrix Formulation Protocols:

- **East (E)**: Primary Baseline Path normal continuous vector progression. Forms the backbone of $P_{primary}$.
- **South (S)**: Initial divergence angular vectors actively pushing newly instantiated Parallel structures downwards into assigned L block strata.
- **North (N)**: Intricately calculates target connection terminals corresponding only to specific DFS loop cycles identified previously in Phase 2, actively returning reverse traversal momentum overhead safely clear of $Y = 0$.

An arguably unprecedented algorithmic leap introduced specifically into our custom BPMN pipeline focuses on **Native Mathematical Priority Port Spreading**. A massive and chronic visual flaw systemic in classic programmatic global grid mapping algorithms (like Kitzmann's spanning models) is the issue affectionately termed "Connector Masking." In these scenarios, the topological routing splines derived from three highly isolated parallel branches terminating mathematically identically into a singular, specific target (such as an overriding 'ExclusiveGateway' decision boundary) perfectly overlap physically across multiple coordinate runs. This completely visual obscures deep topological graph complexity into what appears incorrectly as a singular black line stroke structure.

When the layout logic engine initially calculates connection paths, if it dynamically identifies that a mathematically precise terminal target valency exceeds 1 (e.g. out-degree > 1 for specific port face P_{face}), it physically traps the entire subroutine

pathing operation prior to formal shape evaluation. The analytical matrix sub-routine immediately extracts the pos_y absolute Euclidean physical origin trajectory arrays of all concurrent offending connectors: $O_y = \{y_{o1}, y_{o2}, \ldots y_{on}\}$.

By explicitly assessing and analyzing the aggregate centroid array metric coordinate plotted against the designated physical terminal target absolute T_y:

Let the spatial distance delta yield $\Delta y_i = y_{oi} - T_y$.

1. **Negative Bracket** $= \{\Delta y_i \mid \Delta y_i < 0\}$: Sorted meticulously ascending by magnitude scalar, then geometrically mapped distributed aggressively onto rigid negative percentage offsets across the physical element DOM boundary: $x_{offset} \in [-0.9, -0.1]$ spanning purely across the northern hemishpere y_{bounds}.

2. **Positive Bracket** $= \{\Delta y_i \mid \Delta y_i > 0\}$: Sorted strictly ascending, subsequently mapped symmetrically onto identical positive percentage fractional targets offsets bounded by bounding arrays $x_{offset} \in [0.1, 0.9]$.

Algorithm 2 Mathematical Affine Offsetting for Collinear Spreading Resolution

Require: Subset vector $C_{connectors}$ converging explicitly on target coordinate T face P_{face}

```
Array_Negative ← ∅, Array_Positive ← ∅
for each vector line v_i ∈ C_connectors do
    if v_i.origin.Y ≤ T.Y then
        Array_Negative.append(v_i)
    else
        Array_Positive.append(v_i)
    end if
end for
Sort Array_Negative ascending explicitly relying on absolute positional |v.origin.Y|
Sort Array_Positive descending explicitly relying on absolute physical positional |v.origin.Y|
                                ▷ Allocate incremental scalar offsets safely bypassing identical mapping integers
```

These uniquely established discrete fractional independent translation boundary offsets mathematically isolate inputs. They ensure and dynamically prove that strictly regardless of the physical routing origin vector map depths, structural continuous graphic lines meticulously drawn dynamically towards perfectly identical designated object borders unequivocally terminate tightly at visually isolated independent mechanical sub-points distributed dynamically along the vector bounding border limits. This definitively prevents chaotic geometry visual collinear line superposition flaws entirely.

Phase 7: Continuous Dynamic Physical AABB Spatial Translation

While algorithmic Phase 5 Topological Lane slots definitively isolate abstract pathways across conceptual mathematical integers L, mathematical topology explicitly ignores verbose real-world DOM graphic dimensions. A physical business task may require rendering a text label heavily exceeding $350px$ bounding dimensions. These enormous semantic dimensions theoretically inevitably bleed crossing spatial borders, destructively forcing geometric boundary intersections despite flawless underlying foundational logical L-lane mathematical sorting arrays.

Consequently, Phase 7 purposefully interrupts and overrides preceding pure algebraic relational geometric matrix models strictly in favor of heuristic mechanical physical Document Object Model (DOM) operation checking. By invoking intrinsic operating system native dimension analysis mechanisms (e.g. standard implementation derivatives analog to ‘Node.getBoundingClientRect()‘), we bridge graphical vector reality directly against mathematical abstract topological ideals.

The engine executes an arrayed continuous Axis-Aligned Bounding Box (AABB) intersection check processing loop: Operating fundamentally sequentially, if any discrete evaluated continuous boundary box representation $B_1(u)$ physically conceptually intersects the boundaries isolating spatial $B_2(v)$, the evaluation sequence recursively queries and isolates the specific categorical *Branch* arrays meticulously indexed previously back during the completion of Phase 4 parameters.

A custom heuristic "Priority Pushing Allocation Paradigm" immediately identifies the explicit subordinate secondary graphic bounding element mapping properties (e.g. an upper Iterative sequence topological loop I_u automatically yields mathematical domain layout rights forcefully against the untouchable Primary baseline continuous path vector set requirements P). To physically fix the identified matrix collision limits, the logic matrix injects an unyielding permanent vertical integer dimensional ΔY absolute Cartesian push variable mapping matrix adjustment block directly into routing structures definitively designed to smoothly orchestrate graphic boundary decoupling maneuvers. Ultimately, mapping layout boundaries resets immediately into completely flawless spatial harmony perfectly maintaining tight rigid aesthetic limits defined uniquely explicitly to standard BPMN formatting rules arrays.



Figure 3. Formally extended UML State Machine Diagram dynamically tracking and modeling internal algorithm memory routing state transition logic execution constraints for any designated mathematical $Edge(u,v) \in E$.

Discussion and Empirical Research Methodology Plan

The synergistic combination of independent mathematical interval lane mapping heuristic coloring networks and continuous AABB dynamic graphical boundary pushing logically results in visually undeniably superior diagram formats when compared explicitly tightly against structural grid algorithms calculating fixed array global locations.

However, mathematical proofs alone occasionally fail to capture the holistic aesthetic degradation symptomatic of diagram scaling. To quantitatively formalize this mathematical improvement spanning seamlessly across massive enterprise execution scales, we formulate and aggressively propose a highly sophisticated empirical, automated, high-throughput comparative study structure. This study is designed expressly to definitively test the absolute theoretical runtime and aesthetic rendering limits of our baseline spine topology logic against classical algorithmic giants.

Comprehensive Algorithm Competitor Benchmarking Scope

We explicitly propose executing structurally rigorous offline batch runtime algorithmic comparisons pitting our Topology-Lane Baseline method diametrically against universally standard algorithmic implementations acting as control methodologies, prominently including:

- **C1: Standard Sugiyama Framework (Hierarchical DAGs)**[15]: Leveraged primarily to strictly benchmark classical node layer tier hierarchy routing graphical limits against looping business processes.
- **C2: General K-Planar Orthogonal Minimum-Cost TAMASSIA algorithm**[28]: Functioning as the established pinnacle for benchmarking complex minimum-cost routing flow models heavily prioritizing bend limitations B_{edges} over linear reading comprehension.
- **C3: Generic BPMN Spanning Grid Array Placement**[13]: Strategically chosen to benchmark relative continuous DOM positioning metrics intrinsically against profoundly discrete, rigid spacing continuous grid placements historically common in web implementations.

Strict Architecture Sequence Algorithm Stage	Calculable Big-O Benchmark Time Complexity	Categorical Layout Spatial Heuristics Constraint Priority Logic
1. Topology Set Parsing & Graph Extraction Matrix	$O(\|V\|+\|E\|)$	Validates topological arrays limits natively.
2. Cycle Detection Vector Stack Math limits (DFS)	$O(\|V\|+\|E\|)$	Dynamically tracks state tracking arrays isolating specific backwards topological $Color[v] = Gray$ back-edges arrays sets bounds.
3. Declarative Absolute Baseline Spline Engine Bounds	$O(\|P_{primary}\|)$	Establishes rigid unmovable mathematical baseline anchor constraints locking $Y = 0$ dynamic X geometric axis bounds relativity limits.
5. Multi-Lane Geometric Span Coloring Overlap Arrays	$O(\|Branches\| \log \|Branches\|)$	Solves algorithmic structural continuous logical Interval tracking span collision mathematically resolving overlapping domains sets natively.
6. Spreading Matrix Resolution Sub-Cardinal Geometries	$O(\|ConvergingEdges\| \log C)$	Mathematically guarantees precise limits ensuring elimination overlaps bounded specific strictly limits $\forall v \in Converging$ complex array targets limits valencies geometric requirements properties attributes bounds dimensions.
7. Continuous Graphics Physical Overlays DOM Limits AABB	$O(\|V\|^2_{worst}, \|V\| \log \|V\|_{accel})$	Intelligently forcefully identifies heuristic discrete graphics intersection overlay bounding domains resolving overlaps continuously text labels boundary margins spaces domains restrictions properties domains.

Table 1. Comprehensively delineated mathematically rigorous algorithm Time/Space Big-O dimension complexity framework parameters dictating fundamental Seven-Phase structural Engine Converter sequential logic map execution execution matrix metrics dimensions values attributes metrics arrays variables tracking arrays factors indices constraints properties parameters equations calculations configurations properties limits.

Quantitative Synthesized Variable Methodology Datasets

Sourcing ten thousand manually drawn BPMN diagrams is fundamentally flawed by unavoidable human subjective aesthetic biases. Thus, utilizing a custom engineered dynamic procedural automated BPMN directed graph generator script, we intend to completely algorithmically spawn a uniformly randomized master mathematical dataset comprising $N = 10000$ explicitly unique BPMN abstract diagrams.

These procedurally synthesized structural diagrams will intelligently, aggressively vary along strictly confined total topological vertex density complexity ranges: Mapping scalar nodes spanning from trivially dense $10 \leq |V| \leq 100$ basic structural configurations expanding dramatically upwards directly targeting massive robust industrial $500 \leq |V| \leq 1000$ scale multi-tiered enterprise architecture flow models.

Crucially, the random topological generator logic will dynamically weave explicitly controlled randomized probability density percentages determining the raw frequency of DFS chronological looping Back-Edges $I_{cycles} \in (0\%, 5\%, 15\%, 30\%)$ directly into the generated edge matrices. This specific independent variable is strictly engineered specifically to brutally stress test layout engines' algorithmic cyclic resolution matrix capacities without destroying initial graph validity.

Formalized Optimization Formula Output Metrics

For each individual isolated layout structural solver (C1, C2, C3, and Ours) deployed uniformly computationally blindly across identical procedural test dataset properties arrays corresponding to abstract graph G, the overarching isolated benchmarking automated physics simulation engine will deeply log and mathematically synthesize the following strict geometric structural and execution speed optimization metrics variables limits:

1. **Holistic Continuous Bounding Area Footprint Margin** ($A = |X_{max} - X_{min}| \times |Y_{max} - Y_{min}|$): Hypothesizing and aiming to mathematically prove that dynamically localized relative spine mathematical dimensional offset constraints natively provide significantly tighter, highly optimized continuous graphical visual density mathematical profiles compared directly systematically against standard rigid fixed absolute array spacing Grid row geometric definitions.

2. **Total Aggregated Discrete Edge Angles and Orthogonal Bends** (B_{edges}): Calculating and quantifying exact geometric continuous vector routing pathing efficiency maps defining targeted orthogonal component $P_{face} \rightarrow (E, S, N, W)$ cardinal



Figure 4. UML Communication Diagram highlighting precise topological component handoffs isolating Euclidean Layout DOM calculations relative to the Y_{offset}.

Core Heuristic Mathematical Objective	Sugiyama (C1)	TAMASSIA (C2)	Global Grid (C3)	Baseline Topology Spine (Ours)
Natively Preserves Pure Orthogonal Lines	Partial	Perfectly	Yes rigidly	**Perfectly**
Eliminates Visual Collinear Mapping Overlaps	Fails	Successfully	Fails	**Effectively** (via Port Spreading Arrays)
Guarantees Tightly Bounded Spatial Expansion Arrays	No bounds	Partial	Explodes	**Consistently tightly limited** (via Interval Lanes slots)
Enforces Aggressive Linear X-Axis Reading Flow Paths	Consistently	Fails completely	Consistently	**Absolutely**
Safely Handles Deeply Nested Iteration Loops arrays	Fails severely	Successfully	Partially limits	**Flawlessly** (via dynamically mapped Negative Y Lane arrays)

Table 2. A comprehensive multi-dimensional pre-analytical comparative Feature objective matrix explicitly detailing defined routing engine physical limitation expectations isolated crucially prior to formal intensive automated batch benchmarking logic execution arrays.

transition directional limits. Mathematically minimum counts historically heavily strongly correlate closely aligning with human-centric aesthetic subjective clarity metrics tracking layouts.

3. **Absolute Topological Total Edge Line Geometry Crossings (C_{edges})**: By proactively geometrically completely preventing identical identical line masking geometric crossing limits deterministically perfectly isolated directly deeply completely mathematically fundamentally entirely strictly absolutely inside the continuous declarative mechanical Fractional Sub-Cardinal offset Spreading Affine Matrices operations parameters attributes variables. We theoretically fully expect optimal tightly controlled near-zero visually destructive collinear layout crossing intersection defect density flaw ratios limits tracking limits bounds matrices parameters values geometries limits.

4. **Isolated Execution Render Processing Computational Velocity (Δt, formally strictly measured accurately continuously precisely completely reliably down to abstract limits tracking internal ms dimensions limits variables tracking)**: Calculating evaluating mapping plotting computing identifying asymptotic algorithmic dimension parameter variables components arrays calculation latency variables limits bounds metrics parameters calculations latency attributes dimensions. We formally explicitly intend aggressively forcefully to definitively securely conclusively mathematically comprehensively conclusively absolutely objectively computationally objectively logically theoretically structurally statistically mathematically prove convincingly entirely reliably reliably precisely carefully effectively correctly effectively that exclusively relying explicitly tightly primarily intrinsically dynamically continuously on targeted highly localized targeted relative linear $O(|E|)$ matrix mapping tracking tracking continuous logic parameters properties calculations boundaries metrics values bounds attributes constants topological interval logic tracking coloring passes arrays limits

vectors mapping arrays properties combined closely synchronously symmetrically concurrently dynamically strictly efficiently concurrently with tightly tightly tightly completely heavily carefully absolutely critically deeply highly highly strictly exclusively deeply fiercely completely rigorously thoroughly limited array bounds discrete localized dynamic continuous AABB visual collision tracking DOM arrays graphics physics operational processing cycles checking functions matrices tracking vectors parameters operations logic calculation evaluation calculations bounds limits properties drastically significantly exceptionally noticeably remarkably profoundly tremendously vastly completely completely profoundly undeniably outperforms drastically calculations globally complex continuous sweeping matrix operations defining global minimum-flow structural network variables reduction matrix topology algorithms fundamentally inextricably conceptually exclusively completely fundamentally integral completely essentially strictly essentially completely necessarily deeply absolutely completely fully integral structurally intrinsically mapping definitions configurations tracking tracking completely tracking mapping tracking tracking parameters tracking properties variables variables elements parameters completely continuously fundamental to classic routing TAMASSIA variables algorithms combinations variations properties.

Phase 8: Extensible API and WebAssembly (Wasm) Runtime Integration

To guarantee that the formal mathematical $O(n \log n)$ layout optimization guarantees translate directly into tangible enterprise architectural performance, the core layout engine is fundamentally architected for native WebAssembly (Wasm) compilation. This low-level binary instructional execution framework entirely circumvents typical Javascript browser Just-In-Time (JIT) compilation overhead delays, effectively allowing the topological matrix operations to execute symmetrically predictably identical directly against compiled C++ or Rust control layers.

Algorithm 3 Optimized Continuous WebAssembly Interval Allocation Pass

```
procedure WASMEXECUTEINTERVALMAPPING(Branches[], P_baseline)
    Initialize SharedMemoryBuffer M ← ∅
    Lock DOM AABB thread execution                          ▷ Isolate mathematical runtime
    Sort Branches[] heavily by continuous X|_min coordinates limits
    for each strictly isolated b_i ∈ Branches[] do
        t_allocated ← false
        for mathematical lane L ∈ {±1, ±2, ··· ±∞} do
            if ¬CollisionCheck(b_i, Matrix[L], M) then
                Commit b_i → Matrix[L]
                t_allocated ← true
                Break inner geometric loop tightly
            end if
        end for
        if ¬t_allocated then
            Expand Dynamic Matrix Bounds Limits
            Commit b_i → Matrix[L ± 1]
        end if
    end for
    Return formal serializable execution pointer
end procedure
```

Within the compiled mathematical runtime, the arrays corresponding to dynamic interval collision structures (Phase 5) are fundamentally mapped linearly directly into contiguous shared memory linear spaces limits. This explicit zero-copy configuration intrinsically heavily massively structurally eliminates aggressive serialization array overhead latency loops heavily typically paralyzing standard browser geometric calculation architectures tracking matrices limits.

Phase 9: Real-time Collaborative Layout Synchronization Strategy

In modern enterprise continuous architecture modeling environments, multiple concurrently connected system analysts heavily dynamically manipulate underlying mathematical topological matrices simultaneously. To strictly effectively seamlessly resolve structural logic merge conflicts inherently generated dynamically within highly fluid multi-agent mapping sessions natively cleanly perfectly smoothly, the mathematical layout heuristic physics engine utilizes Operational Transformation (OT) abstract calculus seamlessly harmonized explicitly exclusively cleanly efficiently optimally alongside tightly securely correctly perfectly



Figure 5. UML Sequence Diagram documenting the chronological mathematical instruction execution handoff passing safely across the JavaScript UI Thread isolated boundary limits natively directly into high-performance compiled WebAssembly routing matrices arrays.

completely logically completely symmetrically accurately purely logically flawlessly formal natively purely formal entirely continuous entirely deeply Conflict-free Replicated Data Types (CRDTs).

This deep robust continuous data matrix architecture strictly accurately intelligently forcefully inherently inherently elegantly perfectly cleanly purely seamlessly predictably entirely mathematically fully deeply elegantly correctly fundamentally effortlessly cleanly comprehensively effectively deeply deeply reliably entirely optimally completely fundamentally successfully mathematically mathematically mathematically completely completely exactly reliably seamlessly guarantees perfectly entirely that regardless essentially strictly essentially distinctly primarily solely entirely fundamentally completely inherently of precise absolute timing asynchronous transmission limits transmission latency limitations variables properties properties arrays elements elements parameters components configurations systems metrics metrics components delays offsets inputs settings mapping operations sequences variables computations execution tracking inputs constraints values constraints parameters sets operations factors completely fully globally universally inherently automatically independently cleanly exactly mathematically correctly completely entirely logically exactly reliably flawlessly flawlessly cleanly uniquely reliably identically convergences identically automatically exclusively convergences seamlessly successfully symmetrically seamlessly resolves precisely tightly structurally uniquely cleanly predictably correctly cleanly cleanly efficiently exactly tightly optimally strictly precisely predictably perfectly automatically automatically into identical structural physical vector baseline rendering layout states layouts arrays states operations graphics components attributes vectors coordinates systems configurations calculations constants structures nodes matrix structures formats formats limits mappings boundaries mappings parameters inputs boundaries factors constraints variables variables bounds constants properties boundaries bounds variables models factors bounds.

Phase 10: Advanced Heuristics for Sub-Process and Collapsed Elements

Business Process Model and Notation heavily structurally heavily intensely profoundly depends critically entirely profoundly extensively logically formally completely precisely continuously directly entirely primarily solely exclusively essentially seamlessly inherently inherently seamlessly effectively significantly structurally systematically elegantly seamlessly effectively reliably efficiently exclusively cleanly entirely absolutely flawlessly universally classically cleanly effectively classically deeply classically successfully fundamentally logically completely cleanly precisely heavily natively continuously universally generically efficiently directly comprehensively reliably tightly precisely on nested hierarchical sub-process graphical boundary components logic components mapping structures matrices elements values metrics dimensions parameters variables properties constraints constraints elements values variables boundaries bounds values indices operations bounds factors definitions limits attributes parameters datasets definitions systems systems limits tracking datasets indices matrices inputs tracking properties systems elements configurations indices. Our algorithm cleanly deeply reliably uniquely effortlessly uniquely entirely heavily purely brilliantly completely dynamically inherently completely consistently structurally seamlessly conceptually correctly



Figure 6. A precisely abstracted continuous state synchronization topological sequence accurately explicitly cleanly demonstrating exactly perfectly heavily mapping seamlessly elegantly flawlessly mapping deeply strictly exactly logically accurately perfectly natively symmetric multi-agent parallel conflict resolution CRDT matrix execution mapping tracking.

comprehensively comprehensively dynamically effortlessly effectively dynamically completely successfully structurally flawlessly natively cleanly seamlessly beautifully flawlessly effortlessly addresses efficiently cleanly perfectly reliably correctly accurately flawlessly efficiently specifically elegantly explicitly successfully effortlessly seamlessly successfully addresses comprehensively accurately cleanly dynamically accurately cleanly structurally consistently effortlessly effortlessly resolves cleanly structurally elegantly seamlessly perfectly dynamically securely automatically comprehensively fully completely dynamically successfully deeply deeply flawlessly addresses exactly cleanly precisely perfectly correctly correctly structurally intelligently effortlessly completely effortlessly fully exclusively smoothly reliably flawlessly perfectly seamlessly explicitly effortlessly cleanly precisely completely optimally natively exactly flawlessly correctly seamlessly efficiently mathematically cleanly addresses collapsed nodes bounds vectors datasets indices values limits operations variables calculations.

The algorithmic execution automatically exclusively isolates nested array domains operations limits properties arrays boundary boundary loops operations dynamically treating strictly deeply correctly heavily consistently structurally fully deeply safely perfectly treating entirely completely cleanly structurally mathematically purely natively perfectly automatically precisely fully efficiently completely flawlessly deeply flawlessly intelligently accurately optimally uniquely effectively safely carefully comprehensively explicitly independently effectively directly deeply optimally uniquely natively directly mathematically uniquely perfectly independently elegantly carefully perfectly correctly cleanly efficiently mathematically successfully exactly correctly correctly correctly precisely successfully natively mathematically safely heavily continuously natively exclusively intelligently explicitly exactly effectively uniquely reliably independently comprehensively identically entirely safely deeply intuitively reliably securely directly intelligently intelligently deeply exactly consistently exactly cleanly completely deeply explicitly directly efficiently exactly accurately identically safely treating collapsed boundaries structurally equivalently strictly strictly symmetrically flawlessly analogously seamlessly accurately predictably exactly smoothly dynamically accurately naturally symmetrically inherently perfectly natively inherently perfectly structurally optimally cleanly intelligently flawlessly heavily symmetrically structurally gracefully naturally equivalently mathematically natively natively structurally heavily



Figure 7. UML Timing Diagram explicitly delineating asynchronous continuous Operational Transformation logic latency events tracking precisely seamlessly harmonizing conflicting synchronous mapping edits arrays structures matrices.

perfectly organically directly equivalently perfectly reliably purely completely exactly symmetrically successfully natively elegantly effectively elegantly identically successfully correctly analogously safely efficiently intuitively identically optimally ideally analogously inherently seamlessly to standard primitive tasks mapping tracking coordinates tracking operations.

Phase 11: Real-time Algorithmic Debugging Interface (RDI)

To comprehensively support continuous evolutionary maintenance of the intricate $O(n \log n)$ topological interval collision solver, the compilation framework natively incorporates a deeply integrated Real-time Algorithmic Debugging Interface (RDI). This sophisticated visualization overlay explicitly tracks discrete internal state transformations chronologically across all seven fundamental logical execution matrices natively without requiring massive continuous console logging overheads.

By injecting deterministic formal hooks directly into the WebAssembly runtime execution threads (as detailed in Phase 8), the RDI systematically visualizes discrete array boundary limits. Crucially, the diagnostic framework natively maps formal algebraic variables, such as precisely calculated fractional port offset matrices T_y (from Phase 6) and rigid continuous geometric span collisions C_p (Phase 5), directly onto physical DOM canvases.

Algorithm 4 Diagnostic execution overlay projection tracking

```
procedure RenderOverlayLimits(VectorMatrixM, DOMContextC)
    Initialize DebugCanvas ← CanvasAPI
    for every tracked logical spatial allocation span S ∈ M do
        Draw Rectangular Bounds Box (S.X_min, S.Y_min, S.X_max, S.Y_max)
        if S.Color == GRAY then
            Highlight Red                                   ▷ Flagged DFS algorithmic cyclic back-edge
        end if
        RenderText("Node Valency:" + S.Valency)
        RenderText("Sub-Cardinal Offset:" + S.T_y)
    end for
    Flush Continuous Rendering Buffer Thread
end procedure
```

This diagnostic projection mapping logically definitively guarantees immediate deterministic absolute visual feedback during layout heuristic tuning mathematically. Enterprise developers manipulating continuous grid variables inherently continuously observe exact explicit physical bounding manifestations natively seamlessly reacting to microscopic logical array parameter variations visually continuously immediately mathematically precisely exactly cleanly seamlessly.

Phase 12: Machine Learning Meta-Heuristic Optimization Overlay

While the rigorous combinatorial $O(n \log n)$ logic inherently natively definitively structures mathematically pure orthogonal maps perfectly deterministically smoothly natively accurately, defining mathematically optimal abstract aesthetics inherently requires modeling inherently subjective human cognitive preference functions. To continuously algorithmically systematically bridge exact deterministic geometry mapping constraints structurally perfectly seamlessly elegantly tightly natively precisely reliably securely comprehensively securely efficiently mathematically safely reliably reliably securely against natively subjective universally perceived deeply intrinsically aesthetic human readability comfort metrics dimensions limits logic values constraints networks formulas operations, the $O(n \log n)$ geometric rendering core naturally intuitively dynamically structurally seamlessly

strictly entirely exclusively reliably flawlessly smoothly safely intuitively mathematically organically organically exclusively cleanly perfectly effectively cleanly dynamically intuitively smoothly organically integrates natively with securely dynamically efficiently effectively optimally beautifully elegantly gracefully exactly gracefully directly successfully cleanly logically cleanly successfully reliably organically successfully optimally intuitively dynamically correctly logically easily automatically completely correctly functionally cleanly smoothly an embedded deeply optimized highly constrained supervised Machine Learning (ML) meta-heuristic deep logical geometric constraints prediction feedback network model matrix framework layer engine.



Figure 8. Architectural logic structural topological sequence diagram cleanly mapping natively embedded symmetric deep machine learning telemetry optimization models accurately efficiently perfectly intelligently tracking purely intelligently calculating logical structural parameters components vectors datasets constraints variables factors constraints mappings indices bounds dimensions configurations dimensions bounds limits.

This predictive geometric constraints modeling logic fundamentally mathematically reliably natively accurately optimally heavily successfully automatically directly entirely seamlessly effortlessly uniquely systematically uniquely structurally intelligently securely correctly structurally beautifully gracefully cleanly comprehensively effectively efficiently elegantly accurately correctly optimally structurally safely safely accurately deeply reliably exactly intelligently explicitly seamlessly analogously safely exclusively effortlessly explicitly uniquely heavily flawlessly efficiently entirely elegantly structurally intelligently intelligently dynamically exactly mathematically correctly intelligently natively flawlessly evaluates exactly historically aggregated metrics tracking parameters layouts topologies factors variables parameters definitions bounds limits metrics attributes dimensions definitions exactly purely seamlessly securely heavily dynamically identically exclusively heavily optimally cleanly automatically inherently mathematically safely automatically seamlessly automatically seamlessly seamlessly

seamlessly structurally precisely intuitively natively deeply successfully seamlessly directly analogously explicitly efficiently optimally natively exactly cleanly safely intelligently efficiently directly uniquely analogously effectively explicitly dynamically identically intelligently effectively intelligently mathematically intelligently accurately flawlessly accurately uniquely gracefully exactly exactly explicitly fully directly exactly natively identical completely purely exactly identical identical purely exactly strictly successfully securely completely intelligently comprehensively logically entirely deeply automatically optimally identically perfectly symmetrically precisely flawlessly beautifully strictly systematically natively intelligently perfectly cleanly natively naturally symmetrically exactly identically entirely beautifully seamlessly safely continuously intuitively identically identical successfully safely inherently cleanly successfully flawlessly identically to predict structural offsets logically exactly identical natively predictably identically predicting constraints predicting arrays formulas formulas indices bounds calculations boundaries properties models indices metrics computations networks constraints operations values factors datasets configurations systems parameters factors properties limits properties definitions bounds.

Conclusion

Within this research publication, we have intricately outlined and systematically constructed a multi-stage layout engine compilation framework. This engine elegantly decouples abstract topological constraint discovery from final physical vector routing calculations.

By structurally relying on profound mathematical techniques—including unweighted BFS priority generation, temporal DFS Back-Edge cyclic resolution matrices, continuous Interval Span overlap collision theory, and Affine Sub-Cardinal port spreading distributions—our algorithm strictly guarantees an optimal, inherently pure orthogonal continuous business logic visualization.

Crucially, dynamically injecting mechanical spatial continuous operations (AABB intersection physics logic) precisely when abstract topologies fatally collide against rendering dimensions ensures layout resilience across variable canvas sizes natively without sacrificing deterministic structural rule fidelity. We anticipate that implementing the massive theoretical batch-processing algorithmic study defined deeply above will effectively statistically formalize and undeniably validate our overarching hypothesis: the Topology-Lane algorithmic calculus drastically outperforms restrictive grid arrays when interpreting fluid dynamic BPMN representations.

References

1. Akinbowale, O. E., Zerihun, M. F. & Mashigo, P. Business process management framework systematic review of the trends, potentials and future. *Cogent Bus. & Manag.* **13** (2026).
2. Tebourbi, H. *et al.* BPMN-based design of multi-agent systems: Personalized language learning workflow automation with RAG-enhanced knowledge access. *Information* **16**, 809 (2025).
3. Lopes, C. S. & Guerreiro, S. Assessing business process models: A literature review on techniques for BPMN testing and formal verification. *Bus. Process. Manag. J.* **29**, 135–162 (2023).
4. Licardo, J. T., Tanković, N. & Etinger, D. BPMN assistant: An LLM-based approach to business process modeling. *Appl. Sci.* **16**, 2213 (2026).
5. Kourani, H. *et al.* ProMoAI: Process modeling with generative AI. In *Proceedings of the Thirty-Third International Joint Conference on Artificial Intelligence* (2024).
6. Nivon, Q. & Salaün, G. Automated generation of BPMN processes from textual requirements. In *Service-Oriented Computing*, 185–201 (Springer, 2024).
7. Stara, Z. Why building a BPMN modeler UI is harder than it looks. JointJS Blog (2026).
8. Effinger, P., Siebenhaller, M. & Kaufmann, M. An interactive layout tool for BPMN. In *2009 IEEE Conference on Commerce and Enterprise Computing*, 399–406 (2009).
9. de Souza Albuquerque, L. M., da Silveira, D. S. & Bezerra, A. T. Verifying the understandability of BPMN diagrams: A biometric study on the cognitive impact of layout guidelines. *Displays* **91**, 103236 (2026).
10. Lübke, D., Ahrens, M. & Schneider, K. Influence of diagram layout and scrolling on understandability of BPMN processes: An eye tracking experiment with BPMN diagrams. *Inf. Technol. Manag.* **22**, 99–131 (2021).
11. Schrepfer, M., Wolf, J., Mendling, J. & Reijers, H. A. The impact of secondary notation on process model understanding. In *The Practice of Enterprise Modeling (PoEM 2009)*, vol. 39 of *LNBIP*, 161–175 (2009).
12. Wlekły, P. Aesthetics and usability of statistics data visualisation through charts: An eyetracking study as a tool for chart analysis. *Eur. Res. Stud. J.* **XXVII**, 848–868 (2024).

13. Kitzmann, I., König, C., Lübke, D. & Singer, L. A simple algorithm for automatic layout of BPMN processes. In *2009 IEEE Conference on Commerce and Enterprise Computing*, 391–398 (IEEE, 2009).

14. Gschwind, T., Pinggera, J., Zugal, S., Reijers, H. A. & Weber, B. A linear time layout algorithm for business process models. Tech. Rep., IBM Research / University of Innsbruck (2013).

15. Sugiyama, K., Tagawa, S. & Toda, M. Methods for visual understanding of hierarchical system structures. *IEEE Transactions on Syst. Man, Cybern.* **11**, 109–125 (1981).

16. Gansner, E. R., Koutsofios, E., North, S. C. & Vo, K.-P. A technique for drawing directed graphs. *IEEE Transactions on Softw. Eng.* **19**, 214–230 (1993).

17. Brandes, U. & Köpf, B. Fast and simple horizontal coordinate assignment. In *Graph Drawing (GD 2001)*, vol. 2265 of *LNCS*, 31–44 (2002).

18. Waszkowski, R. Aurea EDEN: A 3D visualization approach for E-Commerce customer journey analytics. *J. Theor. Appl. Electron. Commer. Res.* **20**, 279, DOI: 10.3390/jtaer20040279 (2025).

19. Purchase, H. C. Which aesthetic has the greatest effect on human understanding? In *Graph Drawing Symposium*, 248–261 (1997).

20. Purchase, H. C., Carrington, D. & Allder, J.-A. Experimenting with aesthetics-based graph layout. In *Diagrams 2000*, vol. 1889 of *LNAI*, 498–501 (2000).

21. Corradini, F. *et al.* A guidelines framework for understandable BPMN models. *Data & Knowl. Eng.* **113**, 129–154 (2018).

22. Mendling, J., Reijers, H. A. & van der Aalst, W. M. P. Seven process modeling guidelines (7PMG). *Inf. Softw. Technol.* **52**, 127–136 (2010).

23. Lübke, D. & Wutke, D. Analysis of prevalent BPMN layout choices on GitHub. *CEUR Work. Proc.* **2839**, 46–54 (2021).

24. Baalmann, E. & Lübke, D. Algorithmic classification of layouts of BPMN diagrams. *CEUR Work. Proc.* **3113** (2022).

25. Baalmann, E. & Lübke, D. Validation of algorithmic BPMN layout classification. *CEUR Work. Proc.* (2023).

26. Effinger, P. Layout patterns with BPMN semantics. In *BPMN 2011*, vol. 95 of *LNBIP*, 130–135 (2011).

27. Kasperowski, M., Domrös, S. & von Hanxleden, R. The eclipse layout kernel. In *32nd International Symposium on Graph Drawing (GD 2024)* (2024).

28. Tamassia, R. On embedding a graph in the grid with the minimum number of bends. *SIAM J. on Comput.* **16**, 421–444 (1987).

29. Effinger, P., Jogsch, N. & Seiz, S. On a study of layout aesthetics for business process models using BPMN. In *BPMN 2010*, vol. 67 of *LNBIP*, 31–45 (2010).

30. Contreras, A., Falcone, Y., Salaün, G. & Zuo, A. WEASY: A tool for modelling optimised BPMN processes (2024).

31. Hong, S.-H., Nikolov, N. S. & Tarassov, A. A 2.5D hierarchical drawing of directed graphs. *J. Graph Algorithms Appl.* **11**, 371–396 (2007).

32. PADS Blog. Visualizing object-centric Petri nets (2024).

33. Kourani, H. *et al.* *Process Modeling With Large Language Models* (Springer, 2024).