

Renewable sources, nuclear power, and energy storage alternatives to reduce UIUC Campus CO₂ emissions

Roberto Fairhurst Agosta
ref3@illinois.edu

NPRE 498 - Energy Storage - Spring 2021
University of Illinois at Urbana-Champaign





Objectives

- Propose electricity generation alternatives for decreasing CO₂ emissions on UIUC campus.
 - Objective aligned with Illinois Climate Action Plan (iCAP) objectives.
- Understand the components of UIUC campus grid.
- Determine current CO₂ emissions in two representative months of the year.
- Calculate CO₂ emissions for different scenarios, including:
 - Increase in **wind** generation capacity.
 - Increase in **solar** generation capacity.
 - Addition of a **nuclear reactor** to UIUC campus grid.
 - Compare different electricity storage alternatives.

iCAP [1]



- American College and University Presidents' Climate Commitment (2008)
- Become carbon neutral as soon as possible, no later than 2050.
- Development of the iCAP (2010)
- Comprehensive roadmap toward a sustainable campus.
- iCAP list of goals, objectives, and potential strategies for several topical areas:
 - Energy Conservation and Building Standards
 - Energy generation, Purchasing, and Distribution
 - Transportation
 - Water and Stormwater usage
 - Purchasing, Waste, and Recycling (Zero Waste)
 - Agriculture, Land Use, Food, and Sequestration

UIUC Campus Grid [2]




Figure. FY19 Electricity generation distribution.


ABBOTT Power Plant [3-4]



- Built in 1940.
- Supplies 70-75% of the campus energy demand.
- Types of energy sources:
 - Two gas turbines (natural gas or fuel oil)
 - Three gas-fired boilers (natural gas or fuel oil)
 - Three coal-fired boilers
- Cogeneration facility: steam and electricity
 - High-pressure steam spins a turbine to drive a generator and produce electricity.
 - Low-pressure exhaust steam for space heating, water heating, and space cooling.
 - Electrical capacity 85 MW.
- Free tours.



Rail Splitter Wind Farm [5-6]




- Operation began in 2009.
- Located in Tazewell and Logan Counties.
- Power output: 100.5 MW.
- 67 turbines of 1.5 MW.
- Power purchase agreement:
 - November 2016 - October 2026
 - 8.6% of the total wind generation

Solar Farm 1.0 [7-8]

- Operation began in 2015.
- Power output: 4.68 MWac.
- Total modules: 18,867.
- Land usage: 20.8 acres.
- Power purchase agreement: 2015-2025.
- Solar Farm 2.0: 12.32 MWdc, 54 acres.



Small Modular Reactors and Microreactors [9-10]




- UIUC Grid demand < 80 MW.
- Limited on-site preparation requirements.
- Factory-fabricated components.
- Components shipped out to generation site.
- Black starts and islanding operation mode.
- Passive safety systems, minimizing electrical parts.


Li-ion Batteries [11-15]



- Charge-Discharge Efficiency: 80-90%
- Rechargeable battery
- First prototype developed in 1985
- High energy density and low self-discharge
- Can cause explosions and fires
- Capacity fading over hundreds to thousands of cycles
- Applications:
 - Portable Power Packs: Laptops and cellphones
 - Electric Vehicles (EVs)
 - Uninterruptible Power Supply (UPS):
computers, communication technology, medical
technology
 - Solar power storage
- World largest Li-ion: 150 MW



Electrolysis [16]



- Commercial use since 1890.
- Most common technologies:
 - Alkaline-based
 - Proton exchange membrane (PEM)
 - Solid Oxide (SOEC)
- Low temperature electrolysis (LTE)
- High temperature electrolysis (HTE)


Equation:

- $\Delta H = \Delta G + T\Delta S$
- ΔH : Specific total energy
- ΔG : Specific electrical energy
- $T\Delta S$: Specific thermal energy


Scenario 0 - Business as usual




- We will focus in a summer month (June) and a winter month (January)
- Data available from F&S per request [17]
- Abbott: 0.26 tCO₂/MW(th)h [1-2]
- Imports: 0.825 tCO₂/MWh [1-2]



Scenario 0 - Results




10^3 MT CO_2	Abbott	Imports	Total
Winter	6.6	8.5	15.1
Summer	4.8	16.7	21.5



Scenario 1



- Dispatch model
 - Wind and Solar
 - Storage
 - Abbott
 - Import
- Increase in Wind and Solar capacity
- Net Demand (ND) = Demand - Wind - Solar
- Necessity for storage mechanisms




Scenario 1 - Results



- Capacity increase by 10, Wind: 100.5 MW, Solar: 46.8 MW




Scenario 1 - Results




Scenario 2

- Dispatch model
 - Wind and Solar
 - Nuclear Reactor
 - Storage
 - Abbott
 - Import
- Increase in Wind and Solar capacity
- Increase in Reactor Capacity
- Net Demand (ND) = Demand - Wind - Solar - Reactor
- Necessity for storage mechanisms
- HTE at 3.5 MPa



Scenario 2 (2)





	γ	P_{EH2}	P_{TH2}
LTE	1	$\neq 0$	0
HTE	(0-1)	$\neq 0$	$\neq 0$

- $P_E = \eta \beta P_{TH}$
- $P_{EH2} = \eta \gamma (1 - \beta) P_{TH}$
- $P_{TH2} = (1 - \gamma) (1 - \beta) P_{TH}$
- $\eta = \eta(T_0)$
- η : conversion efficiency
- T_0 : reactor outlet temperature
- $\beta = P_E / \eta / (P_E / \eta + P_{TH2} / (1 - \gamma))$
- $\gamma = P_{EH2} / \eta / (P_{EH2} / \eta + P_{TH2})$



Scenario 2 - Results





- Capacity increase by 10, Wind: 100.5 MW, Solar: 46.8 MW, Reactor: 10 MWth



Scenario 2 - Results - Summer



Scenario 2 - Results - Winter





Conclusions

- UIUC campus grid is a good example of a diverse microgrid.
- Winter CO₂ emissions are lower to Summer CO₂ emissions.
 - Total demand is lower as well.
 - Future work may include the same analysis using February dataset.
- Decreasing the imported electricity considerably reduces CO₂ emissions.
- Abbott steam production may limit max electric capacity.
- Increase in renewables capacity linearly decreases CO₂ emissions if no storage mechanism is needed.
- In Scenario 1, increasing wind and solar capacity requires:
 - Battery of around 70 MW.
 - Hydrogen plant that can support 1400 kg/h.
- Larger reactor capacities reduce further the CO₂ emissions.
- Larger reactor outlet temperature increases storage efficiency.
- HTE-H₂ production is limited by the size of the reactor, secondary method required.
- Li-ion is the most efficient storage mechanism.

Acknowledgements



I would like to thank Sam Dotson and Lucas Woodrich for putting together most of the data that was used in this work.

This research was performed using funding received from the DOE Office of Nuclear Energy's University Program (Project 20-19693, DE-NE0008972) 'Evaluation of micro-reactor requirements and performance in an existing well-characterized micro-grid'.

References

- [1] - <https://icap.sustainability.illinois.edu/files/project/2634/2015iCAPweb.pdf>
- [2] - <https://icap.sustainability.illinois.edu/files/project/5293/iCAP-2020-FINAL-WEB.pdf>
- [3] - <https://fs.illinois.edu/services/utilities-energy/production/abbott-power-plant>
- [4] - https://fs.illinois.edu/docs/default-source/utilities-energy/abbottbrofinal.pdf?sfvrsn=90b1f9ea_4
- [5] - <https://icap.sustainability.illinois.edu/files/project/2235/RailSplitter-Wind%20Farm-9.6.16.pdf>
- [6] - <https://fs.illinois.edu/services/utilities-energy/production/renewable-energy>
- [7] -
https://fs.illinois.edu/docs/default-source/utilities-energy/solar-farm-project-fact-sheet_with-faqs_104171bbba4c36b8160c2ad00ff2500358aeb.pdf?sfvrsn=813ac4ea_0
- [8] - <https://icap.sustainability.illinois.edu/project/solar-farm-20>
- [9] - <https://www.energy.gov/ne/downloads/ultimate-fast-facts-guide-nuclear-energy>
- [10] - <https://twitter.com/govnuclear/status/1282822874865242117>

References (2)

- [11] - <http://large.stanford.edu/courses/2010/ph240/sun1/>
- [12] -
<https://www.ornl.gov/news/new-class-cobalt-free-cathodes-could-enhance-energy-density-next-gen-lithium-ion-batteries>
- [13] - <https://relionbattery.com/blog/the-seven-top-uses-for-rechargeable-lithium-ion-batteries>
- [14] - https://en.wikipedia.org/wiki/Lithium-ion_battery#Battery_life
- [15] - <https://www.tesla.com/videos/powerpack-hornsdale?redirect=no>
- [16] - Fairhurst-Agosta R. MULTI-PHYSICS AND TECHNICAL ANALYSIS OF HIGH-TEMPERATURE GAS-COOLED REACTORS FOR HYDROGEN PRODUCTION. MS Thesis. University of Illinois at Urbana-Champaign. 2020. <https://www.ideals.illinois.edu/handle/2142/109439>
- [17] - UIUC F&S. Private Communications. 2019. 2020.



Thank you!

Questions?