ANY-1 v3 Instruction Set

© 2021 Robert Finch

Table of Contents

Instruction Formats

ANY1 has relatively few instruction formats. The instruction format is a fixed 36-bits in size. It is highly desirable to keep the instruction size to a minimum as minimally sized instructions have better entropy characteristics. The instruction format contains more decode information than is present in some instruction sets. Particularly there are register type codes associated with register spec fields. This is to keep the size of the instruction decoder hardware to a minimum. Otherwise, a ginormous decoder would be required to handle all possible combinations of instructions and types of registers. A vector machine that supports multiple primitive data types leads to a design that potentially has a lot of variation of instructions.

Register Specifiers

The seven-bit register specifier field of an instruction looks like:

2625	24 20
Tb_2	Rb_5

Register specifiers are always located at the same fixed positions in all instructions. This increases performance and minimizes decoding hardware.

Register specifiers contain a one or two-bit type code and a five-bit register number. The meaning of the type code is in the following table:

Ty_2	Meaning
0	Scalar register
1	Vector register
2,3	Six-bit constant value (bit 0 of Ty is the high order bit of the constant) Not available for Ra, Rt register specs

Note that allowing either scalar or vector registers to be specified in the register spec eliminates the need for special classes of instructions to handle scalar-scalar, vector-scalar, or vector-vector operations.

For signed operations the six-bit constant is treated as a signed value and extended to 64-bits. For unsigned operations (BLTU, BGEU, SLTU, SGEU,…) the six-bit constant is treated as an unsigned value and zero extended to 64-bits.

Constant Interpretation for Float Instructions

For floating point instructions specifying a constant treats the constant as a positive six-bit floating point constant which is extended to 64-bits before use. The exponent specifies a three-bit range of -3 to +4.

Bits 3 to 4	Bits 0 to 2
3-bit Exponent	3-bit significand

The significand has a hidden leading one bit.

Vector Instruction Indicator

The processing core needs to know if an instruction is a vector instruction before it is fully decoded. Depending on if the instruction is a vector instruction, it may be re-decoded and sent into the pipeline multiple times. The processor needs to know very quickly and simply at the instruction fetch stage if the instruction is a vector operation. So, to help things along ANY1 encodes this information in bit 7 of all instructions. See the sample instruction below.

Immediate Format:

35	20	19	18	14	13	12	8	7	6	0
Constant_{16}		Ta	Ra_5		Tt	Rt_5		v	09h_8	

Root Opcode

The root opcode determines the class of instructions executed. Some commonly executed instructions are also encoded at the root level to make more bits available for the instruction. The root opcode is always present in all instructions as the lowest seven bits of the instruction.

35	20	19	18	14	13	12	8	7	6	0
Constant_{16}		Ta	Ra_5		Tt	Rt_5		v	09h_8	

Target Register Spec

Most instructions have a target register. The register spec for the target register is always in the same position, bits 8 to 13 of an instruction. The Tt field specifies the target register is a scalar (0) or vector (1) register.

35	20	19	18	14	13	12	8	7	6	0
Constant_{16}		Ta	Ra_5		Tt	Rt_5		v	09h_8	

Extended Immediate

The extended immediate instructions extend an immediate constant from bit 11 of the following instruction. Five root opcodes are reserved for extended immediates. See the EXIn description.

35	8	7	0
$\text{Constant}_{38..11}$		50_8	

35	8	7	0
$\text{Constant}_{66..39}$		51_8	

35		8	7	0
$Constant_{94..67}$			52_8	

35		8	7	0
$Constant_{122..95}$			53_8	

35		8	7	0
$Constant_{150..123}$			54_8	

Register Formats

R1 (one source register)

With just one source register spec there is room available in the instruction to encode the vector mask register for vector instructions. This avoids the needs for an instruction modifier.

35	29	28	24	23	21	20	19	18	14	13	12	8	7	6	0
$func_7$		$\sim_5$		m_3		z	Ta	Ra_5		Tt	Rt_5		v	$01h_7$	

R2 (two source register)

35	29	28	27	26	25	24	20	19	18	14	13	12	8	7	6	0
$func_7$		$\sim_2$		Tb_2		Rb_5		Ta	Ra_5		Tt	Rt_5		v	$02h_7$	

Branch Instructions

Branch instructions make use of bits 8 to 13 and 27 to 35 to specify a 15-bit branch displacement for a range of ±71kB. The displacement is in terms of count of instructions skipped over. Note there are no vector branch instructions. Opcodes that would encode to vector branching are reserved for future use.

35 27	2625	24 20	19	18 14	13 8	7	6 0
$Const_9$	Tb_2	Rb_5	Ta	Ra_5	$Const_6$	0	$4xh_8$

Instruction Modifiers

IMOD Instruction Modifier - 58

This modifier adds two register spec fields allowing an instruction to use up to four source registers. It also allows a vector mask register to be optionally specified. Rounding mode for instructions supporting rounding is also possible to specify.

35 31	30 28	27	2625	24 20	19	18 14	1312	11 9	8	7 0
$\sim_5$	Rm_3	Tc	Td_2	Rd_6	Tc	Rc_5	A	m_3	z	$58h_8$

A: 00 = ignore mask and round
      01 = apply vector mask
      10 = apply rounding
      11 = apply both vector mask and rounding.

Branch Modifier – 5A

The branch modifier adds a link register to allow storing a return address. This allows conditional subroutine calls. Also, present is a branch target register spec. This allows conditional branching relative to a value in a register. Fifteen additional bits of branch displacement are provided, making the total branch displacement 30 bits (or ±2.4GB).

35 21	2019	18 14	13	12 8	7 6	0
$Constant_{15}$	Tc_2	Rc_5	Tt	Rt_5	0	$5Ah_7$

Instruction Modifier

31 29	28 26	25 14	1312	11 9	8	7 0
C_3	Rm_3	$Constant_{12}$	A	m_3	z	$5Bh_8$

Stride Modifier – 5C

The stride modifier is used with vector load / store instructions to specify the stride of the operation.

35 21	2019	18 14	1312	11 9	8	7 0
$Const_{15}$	Tc_2	Rc_5	A	m_3	z	$5Ch_8$

z: 1 = zero vector element if mask bit clear, 0 = vector element unchanged (ignored for scalar ops)
m_3: vector mask register (ignored for scalar operations).
Rm_3: rounding mode

Sz_4	Size	Qualifier	Alt Qualifier
0	byte	.b	
1	wyde	.w	
2	tetra	.t	.s (single)
3	octa	.o	.d (double)
4	hexi	.h	.q (quad)
8	SIMD byte	.bp	
9	SIMD wyde	.wp	
10	SIMD tetra	.tp	.sp
11	SIMD octa	.op	.dp
12	SIMD hexi	.hp	.qp

Example Instruction

add.int.o x1,x2,x3   ; scalar add of integers x2,x3

add.int.o v1,v2,v3,vm0 ; vector add of integers v2,v3

add.int.o v1,v2,x4,vm0 ; vector add scalar integers v2,x4

add.fp.o v1,v2,v3,vm0   ; vector add float-point double v2,v3

Instructions

Arithmetic / Logical

ABS – Absolute Value

Description:

This instruction takes the absolute value of a register and places the result in a target register.

Integer Instruction Format: R1

Both the source and target registers are treated as integer values.

35	29	28 24	23 21	20	19	18 14	13	12 8	7	6 0
$06h_7$		$\sim_5$	m_3	z	Ta	Ra_5	Tt	Rt_5	v	$01h_7$

v: 0 = scalar, 1 = vector op

Float Instruction Format: R1

Both the source and target registers are treated as float values.

35	29	28 24	23 21	20	19	18 14	13	12 8	7	6 0
$20h_7$		$\sim_5$	m_3	z	Ta	Ra_5	Tt	Rt_5	v	$34h_7$

Decimal Float Instruction Format: R1

Both the source and target registers are treated as decimal float values.

35	29	28 24	23 21	20	19	18 14	13	12 8	7	6 0
$20h_7$		$\sim_5$	m_3	z	Ta	Ra_5	Tt	Rt_5	v	$30h_7$

Operation:

If Ra < 0
    Rt = -Ra
else
    Rt = Ra

Vector Operation

for x = 0 to VL - 1

if (Vm[x]) Rt[x] = Ra[x] < 0 ? -Ra[x] : Ra[x]

Execution Units: I, F, D, P

Clock Cycles: 1

Exceptions: none

Notes:

> For sign-magnitude formats this instruction simply clears the MSB of the number. No rounding occurs.

ADD - Addition

Description:

Add two values. The first operand must be in a register. The second operand may be in a register or may be an immediate value specified in the instruction.

Operation:

Rt = Ra + Imm

or

Rt = Ra + Rb

Vector Operation

for x = 0 to VL - 1

if (Vm[x]) Vt[x] = Va[x] + Vb[x]

else if (z) Vt[x] = 0

Integer Instruction Format: RI

35 20	19	18 14	13	12 8	7	6 0
$Constant_{16}$	Ta	Ra_5	Tt	Rt_5	v	$04h_7$

1 clock cycle / N clock cycles (N = vector length)

Integer Instruction Format: R2

35 29	2827	2625	24 20	19	18 14	13	12 8	7	6 0
$04h_7$	$\sim_2$	Tb_2	Rb_5	Ta	Ra_5	Tt	Rt_5	v	$02h_7$

1 clock cycle / N clock cycles (N = vector length)

Float Instruction Format: R2

35 29	2827	2625	24 20	19	18 14	13	12 8	7	6 0
$04h_7$	$\sim_2$	Tb_2	Rb_5	Ta	Ra_5	Tt	Rt_5	v	$35h_7$

25 clock cycles / N * 25 clock cycles (N = vector length)

Decimal Float Instruction Format: R2

35 29	2827	2625	24 20	19	18 14	13	12 8	7	6 0
$04h_7$	$\sim_2$	Tb_2	Rb_5	Ta	Ra_5	Tt	Rt_5	v	$31h_7$

25 clock cycles / N * 25 clock cycles (N = vector length)

Posit Instruction Format: R2

35 29	2827	2625	24 20	19	18 14	13	12 8	7	6 0
$04h_7$	$\sim_2$	Tb_2	Rb_5	Ta	Ra_5	Tt	Rt_5	v	$39h_7$

25 clock cycles / N * 25 clock cycles (N = vector length)

Vector Mask Instruction Format: R2 (MADD)

35 29	28 25	24 22	21 18	17 15	14 11	10 8	7 0
$04h_7$	0_4	Vmb_3	0_4	Vma_3	0_4	Vmt_3	$3Eh_8$

1 clock cycle

Exceptions: none

AND – Bitwise And

Description:

Perform a bitwise 'and' operation between operands. The first operand must be in a register. The second operand may be in a register or may be an immediate value specified in the instruction. The immediate constant is one extended before use.

Integer Instruction Format: RI

35 20	19	18 14	13	12 8	7	6 0
$Constant_{16}$	Ta	Ra_5	Tt	Rt_5	v	$08h_7$

1 clock cycle / N clock cycles (N = vector length)

Integer Instruction Format: R2

35 29	2827	2625	24 20	19	18 14	13	12 8	7	6 0
$08h_7$	$\sim_2$	Tb_2	Rb_5	Ta	Ra_5	Tt	Rt_5	v	$02h_7$

1 clock cycle / N clock cycles (N = vector length)

Vector Mask Instruction Format: R2 (MADD)

35 29	28 25	24 22	21 18	17 15	14 11	10 8	7 0
$00h_7$	0_4	Vmb_3	0_4	Vma_3	0_4	Vmt_3	$3Eh_8$

1 clock cycle

Operation:

Rt = Ra & Imm

or

Rt = Ra & Rb

Vector Operation

for x = 0 to VL - 1

if (Vm[x]) Vt[x] = Va[x] & Vb[x]

else if (z) Vt[x] = 0

Exceptions: none

BMM – Bit Matrix Multiply

BMM Rt, Ra, Rb

Description:

The BMM instruction treats the bits of register Ra and register Rb as an 8x8 matrix and performs a bit matrix multiply of the two registers and stores the result in the target register. An alternate mnemonic for this instruction is MOR.

Instruction Format: R2

35	29	2827	2625	24	20	19	18	14	13	12	8	7	6	0
$func_7$		$\sim_2$	Tb_2	Rb_5		Ta	Ra_5		Tt	Rt_5		v	$02h_7$	

Fn_7	Function
30h	MOR
31h	MXOR
32h	MORT (MOR transpose)
33h	MXORT (MXOR transpose)

Operation:

for I = 0 to 7
     for j = 0 to 7
          Rt.bit[i][j] = (Ra[i][0]&Rb[0][j]) | (Ra[i][1]&Rb[1][j]) | … | (Ra[i][15]&Rb[15][j])

Clock Cycles: 1

Execution Units: Integer ALU

Exceptions: none

Notes:

The bits are numbered with bit 63 of a register representing I,j = 0,0 and bit 0 of the register representing I,j = 7,7.

BYTNDX – Byte Index

Description:

This instruction searches Ra, which is treated as an array of eight bytes, for a byte value specified by Rb or an immediate value and places the index of the byte into the target register Rt. If the byte is not found -1 is placed in the target register. A common use would be to search for a null byte. The index result may vary from -1 to +7. The index of the first found byte is returned (closest to zero).

If a vector BYTNDX instruction is issued and the target is a scalar register then the instruction searches all the vector elements and returns a value which varies from -1 to +511 in the scalar register. Thus, BYTNDX may be used to determine the length of a null termination string in the vector register.

Instruction Format: R2

35 32	3127	2625	24 20	19	18 14	13	12 8	7	6 0
0_4	$\sim_5$	Tb_2	Rb_5	Ta	Ra_5	Tt	Rt_5	v	$1Ah_7$

35 32	31	20	19	18 14	13	12 8	7	6 0
1_4	$Constant_{12}$		Ta	Ra_5	Tt	Rt_5	v	$1Ah_7$

R2 Supported Formats: .o

Clock Cycles: 1

Execution Units: Integer ALU

Operation:

Rt = Index of (Rb in Ra)

Exceptions: none

CMP – Compare

Description

Compare two registers or a register and an immediate value and return the relationship between them.

Integer Instruction Format: R2

Both values are treated as signed numbers.

35 29	2827	2625	24 20	19	18 14	13	12 8	7	6 0
$20h_7$	$\sim_2$	Tb_2	Rb_5	Ta	Ra_5	Tt	Rt_5	v	$02h_7$

1 clock cycle

Operation:

Rt = Ra < Rb ? –1 : Ra = Rb ? 0 : 1

Vector Operation

for x = 0 to VL - 1

if (Vm[x]) Vt[x] = Va[x] < Vb[x] ? –1 : Va[x]=Vb[x] ? 0 : 1

Float Instruction Format: R2 (FCMP)

Both values are treated as double precision (64-bit) floating point numbers. The result is returned as a float value of -1.0, 0.0 or +1.0. If the comparison is unordered 2.0 is returned.

35 29	2827	2625	24 20	19	18 14	13	12 8	7	6 0
$10h_7$	$\sim_2$	Tb_2	Rb_5	Ta	Ra_5	Tt	Rt_5	v	$35h_7$

1 clock cycle

Float Instruction Format: R2 (FCMPB)

Both values are treated as double precision (64-bit) floating point numbers. The value returned is a bit vector as outlined in the table below. Note that the less than status is returned in both bits 1 and 63 so that a BLT may be used.

35 29	2827	2625	24 20	19	18 14	13	12 8	7	6 0
$15h_7$	$\sim_2$	Tb_2	Rb_5	Ta	Ra_5	Tt	Rt_5	v	$35h_7$

1 clock cycle

The float comparison returns a bit vector containing the status of all possible relationships. This may then be tested with the BBS instruction.

Rt bit	Meaning
0	= equal
1	< less than
2	<= less than or equal
3	< magnitude less than
4	unordered
5 to 7	zero (reserved)
8	< > not equal
9	>= greater than or equal
10	> greater than
11	>= magnitude greater than or equal
12	ordered
13 to 62	zero (reserved)
63	less than

Decimal Float Instruction Format: R2 (DFCMP)

Both values are treated as double precision (64-bit) decimal floating point numbers. The result is returned as a float value of -1.0, 0.0 or +1.0. If the comparison is unordered 2.0 is returned.

35 29	2827	2625	24 20	19	18 14	13	12 8	7	6 0
$10h_7$	$\sim_2$	Tb_2	Rb_5	Ta	Ra_5	Tt	Rt_5	v	$31h_7$

1 clock cycle

CNTPOP – Count Population

CNTPOP r1,r2
CNTPOP v1,v2
CNTPOP r1,vm2
Description:

Count the number of ones and place the count in the target register.

Vector Operation

for x = 0 to VL - 1

if (Vm[x]) Vt[x] = popcnt(Va[x])

Instruction Format: R1

35	29	28	24	23	21	20	19	18	14	13	12	8	7	6	0
$02h_7$		$\sim_5$		m_3		z	Ta	Ra_5		Tt	Rt_5		v	$01h_7$	

Vector Mask Instruction Format: R1

35	26	25	22	21	18	17	15	14	13	12	8	7	0
$0Dh_{10}$		$\sim_4$		0_5		Vm_3		Tt_2		Rt_5		$3Eh_8$	

Execution Units: integer ALU

Exceptions: none

CNTLZ – Count Leading Zeros

Description:

Count the number of leading zeros (starting at the MSB) in Ra and place the count in the target register.

Instruction Format: R1

35 29	28 24	23 21	20	19	18 14	13	12 8	7	6 0
$00h_7$	$\sim_5$	m_3	z	Ta	Ra_5	Tt	Rt_5	v	$01h_7$

Vector Mask Instruction Format: R1

35 26	25 22	21 18	17 15	1413	12 8	7 0
$00h_{10}$	$\sim_4$	0_5	Vm_3	Tt_2	Rt_5	$3Eh_8$

R1 Supported Formats: .o

Clock Cycles: 1

Execution Units: Integer ALU

Exceptions: none

COM – Ones Complement

Description:

Bitwise complement all the bits in the register. 1's become 0's and 0's become 1's.

Instruction Format: R1

35　　　29	28 24	23 21	20	19	18　14	13	12　8	7	6　　0
$03h_7$	$\sim_5$	m_3	z	Ta	Ra_5	Tt	Rt_5	v	$01h_7$

1 clock cycle

Operation

Rt = ~Ra

Vector Operation

for x = 0 to VL-1

if (Vm[x]) Vt[x] = ~Va[x]

else if (z) Vt[x] = 0

else Vt[x] = Vt[x]

Exceptions: none

DEP – Deposit

Description:

Insert to a bitfield. Rc specifies the bitfield offset, Rd specifies the width of the bitfield. Rb specifies the data to insert. Ra contains the original source data. The least significant Rd minus one bits of Rb are inserted into Ra at the position specified by Rc. The final result is placed into Rt.

This instruction may also be used to perform a left shift of a single register by specifying x0 for Ra.

Formats Supported: R4

31 29	28 26	25 20	19 14	1312	11 9	8	7 0
DT_3	Rm_3	Rc_6	Rd_6	A	m_3	z	$59h_8$

31 26	25 20	19 14	13 8	7 0
3_6	Rb_6	Ra_6	Rt_6	$1Ch_8$

DT_3	Meaning
00	Rc,Rd are both regs
01	Rc is a six bit immediate, Rd is a reg
10	Rd is a six bit immediate, Rc is a reg
11	Both Rc, Rd are six bit immediates

Operation Size: .o

Execution Units: integer ALU

Exceptions: none

Example:

DIF – Difference

Description:

This instruction computes the difference between two signed values in registers Ra and Rb and places the result in a target Rt register. The difference is calculated as the absolute value of Ra minus Rb.

Instruction Format: R2

35 29	2827	2625	24 20	19	18 14	13	12 8	7	6 0
$18h_7$	$\sim_2$	Tb_2	Rb_5	Ta	Ra_5	Tt	Rt_5	v	$02h_7$

Supported Formats: .o

Clock Cycles: 1

Execution Units: Integer

Operation:

Rt = Abs(Ra - Rb)

Exceptions: none

DIV[O][Z] – Division

Description:

Divide two operand values and place the result in the target register. The first operand must be in a register specified by the Ra field of the instruction. The second operand may be a register specified by the Rb field of the instruction or an immediate value. Both operands are treated as signed values. The register form of this instruction may cause a divide by zero exception if enabled in the instruction.

Instruction Format: RI

35 20	19	18 14	13	12 8	7	6 0
$Constant_{16}$	Ta	Ra_5	Tt	Rt_5	v	$10h_7$

Instruction Format: R2

35 29	2827	2625	24 20	19	18 14	13	12 8	7	6 0
$10h_7$	OZ_2	Tb_2	Rb_5	Ta	Ra_5	Tt	Rt_5	v	$02h_7$

Float Instruction Format: R2

35 29	2827	2625	24 20	19	18 14	13	12 8	7	6 0
$09h_7$	$\sim_2$	Tb_2	Rb_5	Ta	Ra_5	Tt	Rt_5	v	$35h_7$

Execution Units: ALU

Clock Cycles: 20

Exceptions: none

DIVR – Division

Description:

> This instruction is supplied as division is not commutative. Divide two operand values and place the result in the target register. The first operand must be an immediate value. The second operand must be a register specified by the Ra field of the instruction. Both operands are treated as signed values. This instruction allows a constant to be divided by a register value "reverse" to how the DIV instruction works.

Integer Instruction Format: RI

35	20	19	18	14	13	12	8	7	6	0
$Constant_{16}$		Ta	Ra_5		Tt	Rt_5		v	$21h_7$	

Execution Units: ALU

Clock Cycles: 20

Exceptions: none

DIVSU – Division Signed-Unsigned

Description:

Divide two operand values and place the result in the target register. The first operand must be in a register specified by the Ra field of the instruction. The second operand may be either a register specified by the Rb field of the instruction, an immediate value. The first operand is treated as a signed value, the second operand as unsigned.

Instruction Format: RI

35 20	19	18 14	13	12 8	7	6 0
$Constant_{16}$	Ta	Ra_5	Tt	Rt_5	v	$12h_7$

Instruction Format: R2

35 29	2827	2625	24 20	19	18 14	13	12 8	7	6 0
$12h_7$	OZ_2	Tb_2	Rb_5	Ta	Ra_5	Tt	Rt_5	v	$02h_7$

Execution Units: ALU

Clock Cycles: 20

Exceptions: none

DIVU – Division Unsigned

Description:

Divide two operand values and place the result in the target register. The first operand must be in a register specified by the Ra field of the instruction. The second operand may be either a register specified by the Rb field of the instruction, an immediate value. Both operands are treated as unsigned values.

Instruction Format: RI

35 20	19	18 14	13	12 8	7	6 0
$Constant_{16}$	Ta	Ra_5	Tt	Rt_5	v	$11h_7$

Instruction Format: R2

35 29	2827	2625	24 20	19	18 14	13	12 8	7	6 0
$11h_7$	$\sim_2$	Tb_2	Rb_5	Ta	Ra_5	Tt	Rt_5	v	$02h_7$

Execution Units: ALU

Clock Cycles: 20

Exceptions: none

EOR – Bitwise Exclusive Or

Description:

This is an alternate mnemonic for the XOR instruction. Perform a bitwise exclusive or operation between operands. The first operand must be in a register. The second operand may be a register or immediate value. The immediate constant is zero extended before use.

EXIn – Extended Immediate

Description:

These instructions are used to extend the constant field of the following instruction. The constant is extended from bit eleven. Multiple constant extensions may be present to extend a constant up to 64 bits. When multiple extensions are present they should be placed in order least significant to most significant. (EXI0 first, EXI1 second, EXI2 third). The constant extensions sign-extend to the width of the machine.

Constant extensions may be applied for most instructions with a constant field.

Interrupts are locked out between the modifier and the following instruction.

Instruction Format: EXI

35	8	7	0
$Constant_{38..11}$		50_8	

35	8	7	0
$Constant_{66..39}$		51_8	

35	8	7	0
$Constant_{94..67}$		52_8	

35	8	7	0
$Constant_{122..95}$		53_8	

35	8	7	0
$Constant_{150..123}$		54_8	

EXT –Extract Bitfield

Description:

A bitfield is extracted from the source by shifting the source to the right and 'and' masking. The result is sign extended to the width of the machine. This instruction may be used to sign extend a value from an arbitrary bit position. The width specified should be one less than the desired width. The source is value is contained in the register pair Ra, Rb. The field width is specified by Rc and field offset by Rd.

Instruction Format: R4

35	31	30	28	27	26	25	24	20	19	18	14	13	12	11	9	8	7	0
$\sim_5$		Rm_3		Tc	Td_2		Rd_6		Tc	Rc_5		A		m_3		z	$58h_8$	

35	29	28	27	26	25	24	20	19	18	14	13	12	8	7	6	0
$04h_7$		$\sim_2$		Tb_2		Rb_5		Ta	Ra_5		Tt	Rt_5		v	$1Ch_7$	

Execution Units: Integer ALU

Exceptions: none

Notes:

EXTU –Extract Bitfield Unsigned

Description:

A bitfield is extracted from the source by shifting the source to the right and 'and' masking. The result is zero extended to the width of the machine. This instruction may be used to zero extend a value from an arbitrary bit position. The width specified should be one less than the desired width. The source is a 128-bit value which is the concatenation of Rb and Ra. Rc contains the field offset, Rd the width.

Instruction Format: R4

35 31	30 28	27	2625	24 20	19	18 14	1312	11 9	8	7 0
$\sim_5$	Rm_3	Tc	Td_2	Rd_6	Tc	Rc_5	A	m_3	z	$58h_8$

35 29	2827	2625	24 20	19	18 14	13	12 8	7	6 0
$05h_7$	$\sim_2$	Tb_2	Rb_5	Ta	Ra_5	Tt	Rt_5	v	$1Ch_7$

Execution Units: Integer ALU

Exceptions: none

Notes:

FDP – Fused Dot Product

Description:

Calculate the dot product x = (a * b) + (c * d). The operations are fused together meaning no rounding occurs until the final product is produced.

Instruction Format: R4

35 31	30 28	27	2625	24 20	19	18 14	1312	11 9	8	7 0
$\sim_5$	Rm_3	Tc	Td_2	Rd_6	Tc	Rc_5	A	m_3	z	$58h_8$

35 29	2827	2625	24 20	19	18 14	13	12 8	7	6 0
$37h_7$	$\sim_2$	Tb_2	Rb_5	Ta	Ra_5	Tt	Rt_5	v	$03h_7$

FFO –Find First One

Description:

A bitfield contained in Ra is searched beginning at the most significant bit to the least significant bit for a bit that is set. The index into the bitfield of the bit that is set is stored in Rt. If no bits are set, then Rt is set equal to -1. The field offset is specified by Rc, the field width by Rd.

Instruction Format: R4

35 31	30 28	27	2625	24 20	19	18 14	1312	11 9	8	7 0
$\sim_5$	Rm_3	Tc	Td_2	Rd_6	Tc	Rc_5	A	m_3	z	$58h_8$

35 29	2827	2625	24 20	19	18 14	13	12 8	7	6 0
$06h_7$	$\sim_2$	$\sim_2$	$\sim_5$	Ta	Ra_5	Tt	Rt_5	v	$1Ch_7$

DT_3	Meaning
00	Rc,Rd are both regs
01	Rc is a six bit immediate, Rd is a reg
10	Rd is a six bit immediate, Rc is a reg
11	Both Rc, Rd are six bit immediates

Clock Cycles:

Execution Units: Integer

Exceptions: none

MAX – Maximum Value

Description:

Determines the maximum of two values in registers Ra, Rb and places the result in the target register Rt.

Integer Instruction Format: R2

35 29	2827	2625	24 20	19	18 14	13	12 8	7	6 0
$29h_7$	$\sim_2$	Tb_2	Rb_5	Ta	Ra_5	Tt	Rt_5	v	$02h_7$

Float Instruction Format: R2

35 29	2827	2625	24 20	19	18 14	13	12 8	7	6 0
$03h_7$	$\sim_2$	Tb_2	Rb_5	Ta	Ra_5	Tt	Rt_5	v	$35h_7$

Operation:

IF Ra > Rb

      Rt = Ra

else

      Rt = Rb

MIN – Minimum Value

Description:

Determines the minimum of two values in registers Ra, Rb and places the result in the target register Rt.

Integer Instruction Format: R2

35 29	2827	2625	24 20	19	18 14	13	12 8	7	6 0
$28h_7$	$\sim_2$	Tb_2	Rb_5	Ta	Ra_5	Tt	Rt_5	v	$02h_7$

Float Instruction Format: R2

35 29	2827	2625	24 20	19	18 14	13	12 8	7	6 0
$02h_7$	$\sim_2$	Tb_2	Rb_5	Ta	Ra_5	Tt	Rt_5	v	$35h_7$

Operation:

IF Ra < Rb
       Rt = Ra
else
       Rt = Rb

MOD – Instruction Modifier

Description:

Used to modify the operation of the following instruction. Modifiers 50h to 52h are used to supply additional constant bits and are described as EXI instructions.

Interrupts are locked out between the modifier and the following instruction.

Instruction Format: 58/D8 (IMOD)

35 31	30 28	27	2625	24 20	19	18 14	1312	11 9	8	7 0
$\sim_5$	Rm_3	Tc	Td_2	Rd_6	Tc	Rc_5	A	m_3	z	$58h_8$

A[0]: 1 = apply vector mask, 0=ignore mask spec
A[1]: 1 = apply rounding mode. 0 = ignored rounding mode spec

There are three basic additional elements supplied for the following instruction.

1) A vector mask specification, used only by vector instructions.
2) Two additional source registers
3) A rounding mode specification, useful only to applicable instructions

Two additional register fields allow up to four source operands for the following instruction. If these registers are not required they should be specified as #0.

Application of the vector mask and rounding mode are optional. Two bits in the 'A' field indicate which of these modifiers is applied.

Instruction Format: 5A (BRMOD)

35 21	2019	18 14	13	12 8	7	6 0
$Constant_{15}$	Tc_2	Rc_5	Tt	Rt_5	0	$5Ah_7$

The 5A modifier applies to branch instructions to both extend the range of a branch and allow branch-to-register, and branch-and-link capability. When the 5A modifier is present, the Rc register overrides the use of the IP in calculating the branch target address. The target address is then the sum of register Rc and a constant supplied in the instruction.

The constant field of the 5A modifier adds an additional fifteen bits to the branch displacement. This allows branching extended to ±2.4GB.

The Rt field may be set to the address of the instruction following the branch, to allow conditional branch to subroutine capability.

Instruction Format: 5C/DC (STRIDE)

35 21	2019	18 14	1312	11 9	8	7 0
$Const_{15}$	Tc_2	Rc_5	A	m_3	z	$5Ch_8$

This format is used with vector load and store instructions to supply stride information and extend the address range of the load / store. Any additional constant modifiers (EXI0, EXI1, EXI2) should be placed before the stride modifier.

MUL[O] – Multiply

Description:

Multiply two values. The first operand must be in a register. The second operand may be in a register or may be an immediate value specified in the instruction. Both the operands are treated as signed values, the result is a signed result. The register form of the instruction may cause an overflow exception if the overflow enable bit in the instruction is set.

Integer Instruction Format: RI

35　　　　　　　20	19	18　　14	13	12　　8	7	6　　　　0
$Constant_{16}$	Ta	Ra_5	Tt	Rt_5	v	$06h_7$

4 clock cycles

Integer Instruction Format: R2

35　　29	2827	2625	24　20	19	18　14	13	12　8	7	6　　0
$06h_7$	O_2	Tb_2	Rb_5	Ta	Ra_5	Tt	Rt_5	v	$02h_7$

4 clock cycles

Exceptions: overflow (if enabled)

Float Instruction Format: R2

35　　29	2827	2625	24　20	19	18　14	13	12　8	7	6　　0
$08h_7$	O_2	Tb_2	Rb_5	Ta	Ra_5	Tt	Rt_5	v	$35h_7$

25 clock cycles

Execution Units: ALU

Vector Operation

> for x = 0 to VL - 1
>
> > if (Vm[x]) Vt[x] = Va[x] * Vb[x]

Exceptions: none

MULF – Fast Unsigned Multiply

Description:

Multiply two values. The first operand must be in a register. The second operand may be in a register or may be an immediate value specified in the instruction. Both the operands are treated as unsigned values. The result is an unsigned result. The fast multiply multiplies only the low order 24 bits of the first operand times the low order 16 bits of the second. The result is a 40-bit unsigned product.

Integer Instruction Format: RI

35	20	19	18 14	13	12 8	7	6 0
$Constant_{16}$		Ta	Ra_5	Tt	Rt_5	v	$15h_7$

1 clock cycle / N clock cycles (N = vector length)

Integer Instruction Format: R2

35 29	2827	2625	24 20	19	18 14	13	12 8	7	6 0
$1Ch_7$	$\sim_2$	Tb_2	Rb_5	Ta	Ra_5	Tt	Rt_5	v	$02h_7$

1 clock cycle / N clock cycles (N = vector length)

Execution Units: ALU

Clock Cycles: 1

Exceptions: none

MULU – Unsigned Multiply

Description:

Multiply two values. The first operand must be in a register. The second operand may be in a register or may be an immediate value specified in the instruction. Both the operands are treated as unsigned values, the result is a unsigned result.

Integer Instruction Format: RI

35 20	19	18 14	13	12 8	7	6 0
$Constant_{16}$	Ta	Ra_5	Tt	Rt_5	v	$0Eh_7$

4 clock cycles

Integer Instruction Format: R2

35 29	2827	2625	24 20	19	18 14	13	12 8	7	6 0
$0Eh_7$	$\sim_2$	Tb_2	Rb_5	Ta	Ra_5	Tt	Rt_5	v	$02h_7$

4 clock cycles

Exceptions: none

Vector Operation

for x = 0 to VL - 1

if (Vm[x]) Vt[x] = Va[x] * Vb[x]

Exceptions: none

MUX – Multiplex

Description:

The MUX instruction performs a bit-by-bit copy of a bit of Rb to the target register if the corresponding bit in Ra is set, or a copy of a bit from Rc if the corresponding bit in Ra is clear.

Instruction Format: R2

35 31	30 28	27	2625	24 20	19	18 14	1312	11 9	8	7 0
$\sim_5$	$\sim_3$	Tc	$\sim_2$	$\sim_6$	Tc	Rc_5	A	m_3	z	$58h_8$

35 29	2827	2625	24 20	19	18 14	13	12 8	7	6 0
$04h_7$	$\sim_2$	Tb_2	Rb_5	Ta	Ra_5	Tt	Rt_5	v	$03h_7$

Exceptions: none

Execution Units: integer ALU

NABS –Negative Absolute Value

Description:

Take the negative absolute value of the number in register Ra and place the result into target register Rt. No rounding of the number occurs.

Integer Instruction Format: R1

Both the source and target registers are treated as integer values.

31 26	25 20	19 14	13 8	7 0
7_6	$\sim_6$	Ra_6	Rt_6	$01h_8$

Integer Vector Format: R1

31 26	2524	23 21	20	19 14	13 8	7 0
$07h_6$	$\sim_2$	m_3	z	Va_6	Vt_6	$81h_8$

Float Instruction Format: R1

Both the source and target registers are treated as float values.

31 26	25 20	19 14	13 8	7 0
$21h_6$	$\sim_6$	Ra_6	Rt_6	$34h_8$

Float Vector Format: R1

31 26	2524	23 21	20	19 14	13 8	7 0
$21h_6$	$\sim_2$	m_3	z	Va_6	Vt_6	$B4h_8$

Operation:

If Ra < 0
   Rt = Ra
else
   Rt = -Ra

Clock Cycles: 1

Execution Units: Integer, Floating Point

NEG - Negate

Description:

This is an alternate mnemonic for the SUBF instruction where the constant is zero.

Instruction Format: R2

31	20	19	14	13	8	7	0
0_{12}		Ra_6		Rt_6		$05h_8$	

Vector Instruction Format: R2

31	20	19	14	13	8	7	0
0_{12}		Va_6		Vt_6		$85h_8$	

Scalar Operation

Rt = 0 - Rb

Vector Operation

for x = 0 to VL - 1

if (Vm[x]) Vt[x] = 0 - Vb[x]

else if (z) Vt[x] = 0

else Vt[x] = Vt[x]

Notes

For sign-magnitude operations the sign bit is inverted, no subtract occurs. The result is not rounded.

NOT – Logical Not

Description:

This instruction takes the logical 'not' value of a register and places the result in a target register. If the source register contains a non-zero value, then a zero is loaded into the target. Otherwise, if the source register contains a zero a one is loaded into the target register.

NOT reduces the value to a single bit Boolean.

Integer Instruction Format: R1

35　　　29	28 24	23 21	20	19	18　14	13	12　8	7	6　　0
$04h_7$	$\sim_5$	m_3	z	Ta	Ra_5	Tt	Rt_5	v	$01h_7$

1 clock cycle

Operation:

Rt = !Ra

Exceptions: none

OR – Bitwise Or

Description:

Perform a bitwise or operation between operands. The immediate constant is zero extended before use.

Integer Instruction Format: RI

35	20	19	18 14	13	12 8	7	6 0
$Constant_{16}$		Ta	Ra_5	Tt	Rt_5	v	$09h_7$

1 clock cycle / N clock cycles (N = vector length)

Integer Instruction Format: R2

35 29	2827	2625	24 20	19	18 14	13	12 8	7	6 0
$09h_7$	$\sim_2$	Tb_2	Rb_5	Ta	Ra_5	Tt	Rt_5	v	$02h_7$

1 clock cycle / N clock cycles (N = vector length)

Vector Mask Instruction Format: R2 (MADD)

35 29	28 25	24 22	21 18	17 15	14 11	10 8	7 0
$01h_7$	0_4	Vmb_3	0_4	Vma_3	0_4	Vmt_3	$3Eh_8$

1 clock cycle

Operation

Rt = Ra | Immediate

OR

Rt = Ra | Rb

Vector Operation

for x = 0 to VL-1

if (Vm[x]) Vt[x] = Va[x] | Vb[x] | Vc[x]

Exceptions: none

PERM – Permute Bytes

Description:

This instruction allows any combination of bytes in a source register to be copied to a target register. The low order twenty-four bits of register Rb or a 12-bit immediate constant are used to identify which source bytes are copied to the destination. The twenty-four-bit value is composed of eight three-bit fields. Field S0 indicates the source byte for target byte position 0. S1 indicates the source byte for target byte position 1. S2 to S7 work similarly for the remaining target bytes. There are many interesting possibilities with this instruction. A single source byte could be copied to all target byte positions for instance. Or the order of bytes in a word could be reversed.

Integer Instruction Format: RI

The immediate format is normally used with a constant extension word as 24 bits are required to resolve the target positions.

31 20	19 14	13 8	7 0
$Constant_{12}$	Ra_6	Rt_6	$17h_8$

1 clock cycle

Integer Instruction Format: R2

31 26	25 20	19 14	13 8	7 0
$17h_6$	Rb_6	Ra_6	Rt_6	$02h_8$

1 clock cycle

Execution Units: integer ALU

Clock Cycles: 1

Exceptions: none

PTRDIF – Difference Between Pointers

Description:

Subtract two values then shift the result right. Both operands must be in a register. The right shift is provided to accommodate common object sizes. It may still be necessary to perform a divide operation after the PTRDIF to obtain an index into odd sized or large objects. Rc may vary from zero to thirty-one. This instruction always uses a modifier to supply Rc or an immediate constant.

Integer Instruction Format: R3

31 29	28 26	25 20	19 14	13 12	11 9	8	7 0
DT_3	0_3	0_6	Rc_6	A	m_3	z	$59h_8$

31 26	25 20	19 14	13 8	7 0
$18h_6$	Rb_6	Ra_6	Rt_6	$03h_8$

1 clock cycle

Integer Vector Instruction Format: R3

31 29	28 26	25 20	19 14	13 12	11 9	8	7 0
DT_3	0_3	0_6	Vc_6	A	m_3	z	$B9h_8$

31 26	25 20	19 14	13 8	7 0
$18h_6$	Vb_6	Va_6	Vt_6	$83h_8$

1 clock cycle

Operation:

$$Rt = Abs(Ra - Rb) >> Rc$$

Clock Cycles: 1

Execution Units: Integer

Exceptions:

None

SEQ – Set if Equal

Description:

The set instruction places a 1 or 0 in the target register based on the relationship between the two source operands. If operand Ra is equal to a second operand in register (Rb) or an immediate constant then the target register is set to a one, otherwise the target register is set to a zero. Comparing float values returns an integer.

For floating-point operations positive and negative zero are considered equal.

If a vector operation is taking place then the target register is one of the vector mask registers.

Instruction Format: RI

31 20	19 14	13 8	7 0
$Constant_{12}$	Ra_6	Rt_6	$26h_8$

Instruction Format: R2

Integer:

31 26	25 20	19 14	13 8	7 0
$26h_6$	Rb_6	Ra_6	Rt_6	$02h_8$

Float:

31 26	25 20	19 14	13 8	7 0
$11h_6$	Rb_6	Ra_6	Rt_6	$35h_8$

Vector Instruction Format: RI

31 20	19 14	13 8	7 0
$Constant_{12}$	Va_6	Vt_6	$A6h_8$

Vector Instruction Format: R2

Integer:

31 26	25 20	19 14	13 8	7 0
$26h_6$	Vb_6	Va_6	Vt_6	$82h_8$

Float:

31 26	25 20	19 14	13 8	7 0
$11h_6$	Rb_6	Ra_6	Rt_6	$B5h_8$

SGE – Set if Greater Than or Equal

Description:

The set instruction places a 1 or 0 in the target register based on the relationship between the two source operands. If operand Ra is greater than or equal to a second operand in register (Rb) then the target register is set to a one, otherwise the target register is set to a zero. The operands are treated as signed values.

There is no immediate form to this instruction. An immediate equivalent may be achieved using the SGT instruction and adjusting the constant by one.

Instruction Format: R2

Integer:

31 26	25 20	19 14	13 8	7 0
$2Dh_6$	Rb_6	Ra_6	Rt_6	$02h_8$

Float:

The float version is an alternate mnemonic for SLE where the operands have been swapped.

31 26	25 20	19 14	13 8	7 0
$13h_6$	Ra_6	Rb_6	Rt_6	$35h_8$

SGEU – Set if Greater Than or Equal Unsigned

Description:

The set instruction places a 1 or 0 in the target register based on the relationship between the two source operands. If operand Ra is greater than or equal to a second operand in register (Rb) then the target register is set to a one, otherwise the target register is set to a zero. The operands are treated as signed values.

There is no immediate form to this instruction. An immediate equivalent may be achieved using the SGTU instruction and adjusting the constant by one.

Instruction Format: R2

31 26	25 20	19 14	13 8	7 0
$2Fh_6$	Rb_6	Ra_6	Rt_6	$02h_8$

SGT – Set if Greater Than

Description:

The set instruction places a 1 or 0 in the target register based on the relationship between the two source operands. If operand Ra is greater than a second operand which is a constant supplied in the instruction, then the target register is set to a one, otherwise the target register is set to a zero. The operands are treated as signed values.

There is no register form of this instruction. The register equivalent operation may be performed using the SLT instruction and swapping the registers.

Instruction Format: RI

31 20	19 14	13 8	7 0
$Constant_{12}$	Ra_6	Rt_6	$29h_8$

Integer Instruction Format: R2 (SLT)

31 26	25 20	19 14	13 8	7 0
$2Ch_6$	Ra_6	Rb_6	Rt_6	$02h_8$

Float Instruction Format: R2 (SLT)

31 26	25 20	19 14	13 8	7 0
$12h_6$	Ra_6	Rb_6	Rt_6	$35h_8$

Vector Instruction Format: RI

31 20	19 14	13 8	7 0
$Constant_{12}$	Va_6	Vt_6	$A9h_8$

Integer Vector Instruction Format: R2 (SLT)

31 26	25 20	19 14	13 8	7 0
$2Ch_6$	Va_6	Vb_6	Vt_6	$82h_8$

Float Vector Instruction Format: R2 (SLT)

31 26	25 20	19 14	13 8	7 0
$12h_6$	Va_6	Vb_6	Vt_6	$B5h_8$

SGTU – Set if Greater Than Unsigned

Description:

The set instruction places a 1 or 0 in the target register based on the relationship between the two source operands. If operand Ra is greater than a second operand which is a constant supplied in the instruction, then the target register is set to a one, otherwise the target register is set to a zero. The operands are treated as signed values.

There is no register form of this instruction. The register equivalent operation may be performed using the SLTU instruction and swapping the registers.

Instruction Format: RI

31 20	19 14	13 8	7 0
$Constant_{12}$	Ra_6	Rt_6	$2Bh_8$

Integer Instruction Format: R2 (SLTU)

31 26	25 20	19 14	13 8	7 0
$2Eh_6$	Ra_6	Rb_6	Rt_6	$02h_8$

SIGN – Sign (Compare to Zero)

Synopsis

Take sign of value. This is an extended Mnemonic for the CMP instruction.

Description

The sign of a register is placed in the target register Rt.

Instruction Format: R1

Integer:

31 26	25 20	19 14	13 8	7 0
$2Ah_6$	0_6	Ra_6	Rt_6	$02h_8$

Float:

31 26	25 20	19 14	13 8	7 0
$10h_6$	0_6	Ra_6	Rt_6	$35h_8$

Operation:

Rt = Ra < 0 ? –1 : Ra = 0 ? 0 : 1

Vector Operation

for x = 0 to VL - 1

if (Vm[x]) Vt[x] = Va[x] < 0 ? –1 : Va[x]=0 ? 0 : 1

SLL –Shift Left Logical

Description:

Left shift an operand value by an operand value and place the result in the target register. Zeros are shifted into the least significant bits. The first operand must be in a register specified by the Ra. The second operand may be either a register specified by the Rb field of the instruction, or an immediate value.

Instruction Formats: R2

31 26	25 20	19 14	13 8	7 0
$19h_6$	Rb_6	Ra_6	Rt_6	$02h_8$

Instruction Formats: R2I

31 26	25 20	19 14	13 8	7 0
$1Ah_6$	Imm_6	Ra_6	Rt_6	$02h_8$

Vector Instruction Formats: R2

31 26	25 20	19 14	13 8	7 0
$19h_6$	Vb_6	Va_6	Vt_6	$82h_8$

Vector Instruction Formats: R2I

31 26	25 20	19 14	13 8	7 0
$1Ah_6$	Imm_6	Va_6	Vt_6	$82h_8$

Vector Mask Instruction Format: R2 (MSLL)

31 26	25 20	19 17	16 14	13 11	10 8	7 0
$0Eh_6$	imm_6	0_3	Vma_3	0_3	Vmt_3	$80h_8$

1 clock cycle

Operation Size: .o

Execution Units: integer ALU

Exceptions: none

Example:

SLLP –Shift Left Logical Pair

Description:

Left shift a pair of operand values by an operand value and place the result in the target register. The upper 64 bits of the result are placed in the target register. Zeros are shifted into the least significant bits. The operand pair must be in registers specified by the Ra and Rc field of the instruction. The third operand may be either a register specified by the Rb field of the instruction, or an immediate value.

This instruction may also be used to perform a left rotate of a single register by specifying the same register for Ra and Rc.

Instruction Formats: R3

31 29	28 26	25 20	19 14	1312	11 9	8	7 0
DT_3	Rm_3	Rd_6	Rc_6	A	m_3	z	$59h_8$

31 26	25 20	19 14	13 8	7 0
$10h_6$	Rb_6	Ra_6	Rt_6	$03h_8$

31 26	25 20	19 14	13 8	7 0
$11h_6$	Imm_6	Ra_6	Rt_6	$03h_8$

Operation Size: .o

Execution Units: integer ALU

Exceptions: none

Example:

SLT – Set if Less Than

Description:

The set instruction places a 1 or 0 in the target register based on the relationship between the two source operands. If operand Ra is less than a second operand in either a register (Rb) or a constant supplied in the instruction, then the target register is set to a one, otherwise the target register is set to a zero. The operands are treated as signed values.

The register form of the instruction may also be used to test for greater than by swapping the operands around.

Instruction Format: RI

31 20	19 14	13 8	7 0
$Constant_{12}$	Ra_6	Rt_6	$28h_8$

Integer Instruction Format: R2

31 26	25 20	19 14	13 8	7 0
$2Ch_6$	Rb_6	Ra_6	Rt_6	$02h_8$

Integer Vector Instruction Format: RI

31 20	19 14	13 8	7 0
$Constant_{12}$	Ra_6	Rt_6	$A8h_8$

Integer Vector Instruction Format: R2

31 26	25 20	19 14	13 8	7 0
$2Ch_6$	Rb_6	Ra_6	Rt_6	$82h_8$

Float Instruction Format: R2

31 26	25 20	19 14	13 8	7 0
$12h_6$	Rb_6	Ra_6	Rt_6	$35h_8$

Float Vector Instruction Format: R2

31 26	25 20	19 14	13 8	7 0
$12h_6$	Rb_6	Ra_6	Rt_6	$B5h_8$

Float Vector Set Mask Register:

31 26	25 20	19 14	13 11	10 8	7 0
$36h_6$	Rb_6	Ra_6	2_3	Vmt_3	$B5h_8$

SLE – Set if Less Than or Equal

Description:

The set instruction places a 1 or 0 in the target register based on the relationship between the two source operands. If operand Ra is less than or equal to a second operand in register (Rb) then the target register is set to a one, otherwise the target register is set to a zero. The operands are treated as signed values.

There is no immediate form to this instruction. An immediate equivalent may be achieved using the SLT instruction and adjusting the constant by one.

Instruction Format: R2

Integer:

The integer register form of instruction is an alternate mnemonic for SGE where the operands have been swapped.

31 26	25 20	19 14	13 8	7 0
$2Dh_6$	Ra_6	Rb_6	Rt_6	$02h_8$

Float:

31 26	25 20	19 14	13 8	7 0
$13h_6$	Rb_6	Ra_6	Rt_6	$35h_8$

Integer Vector:

The integer register form of instruction is an alternate mnemonic for SGE where the operands have been swapped.

31 26	25 20	19 14	13 8	7 0
$2Dh_6$	Va_6	Vb_6	Vt_6	$82h_8$

Float Vector:

31 26	25 20	19 14	13 8	7 0
$13h_6$	Vb_6	Va_6	Vt_6	$B5h_8$

Float Vector Set Mask Register:

31 26	25 20	19 14	13 11	10 8	7 0
$36h_6$	Vb_6	Va_6	3_3	Vmt_3	$B5h_8$

SLEU – Set if Less Than or Equal

Description:

The set instruction places a 1 or 0 in the target register based on the relationship between the two source operands. If operand Ra is less than or equal to a second operand in register (Rb) then the target register is set to a one, otherwise the target register is set to a zero. The operands are treated as unsigned values.

This instruction is an alternate mnemonic for the SGEU instruction where the operands have been swapped.

There is no immediate form to this instruction. An immediate equivalent may be achieved using the SLTU instruction and adjusting the constant by one.

Instruction Format: R2

31 26	25 20	19 14	13 8	7 0
$2Fh_6$	Ra_6	Rb_6	Rt_6	$02h_8$

SLTU – Set if Less Than Unsigned

Description:

The set instruction places a 1 or 0 in the target register based on the relationship between the two source operands. If operand Ra is less than a second operand in either a register (Rb) or a constant supplied in the instruction, then the target register is set to a one, otherwise the target register is set to a zero. The operands are treated as unsigned values.

The register form of the instruction may also be used to test for greater than by swapping the operands around.

Instruction Format: RI

31 20	19 14	13 8	7 0
$Constant_{12}$	Ra_6	Rt_6	$2Ah_8$

Integer Instruction Format: R2

31 26	25 20	19 14	13 8	7 0
$2Eh_6$	Rb_6	Ra_6	Rt_6	$02h_8$

Integer Vector Instruction Format: R2

31 26	25 20	19 14	13 8	7 0
$2Eh_6$	Ra_6	Rb_6	Rt_6	$82h_8$

SNE – Set if Not Equal

Description:

The set instruction places a 1 or 0 in the target register based on the relationship between the two source operands. If operand Ra is not equal to a second operand in register (Rb) or an immediate constant then the target register is set to a one, otherwise the target register is set to a zero.

For floating-point operations positive and negative zero are considered equal.

Integer Instruction Format: RI

31 20	19 14	13 8	7 0
$Constant_{12}$	Ra_6	Rt_6	$27h_8$

Integer Instruction Format: R2

31 26	25 20	19 14	13 8	7 0
$27h_6$	Rb_6	Ra_6	Rt_6	$02h_8$

Integer Vector Instruction Format: RI

31 20	19 14	13 8	7 0
$Constant_{12}$	Va_6	Vt_6	$A7h_8$

Integer Vector Instruction Format: R2

31 26	25 20	19 14	13 8	7 0
$27h_6$	Vb_6	Va_6	Vt_6	$82h_8$

Integer Vector Set Mask Register:

31 26	25 20	19 14	13 11	10 8	7 0
$36h_6$	Vb_6	Va_6	1_3	Vmt_3	$82h_8$

Float Vector Set Mask Register:

31 26	25 20	19 14	13 11	10 8	7 0
$36h_6$	Vb_6	Va_6	1_3	Vmt_3	$B5h_8$

SQRT – Square Root

Description:

This instruction takes the square root of a register and places the result in a target register.

Integer Instruction Format: R1

Both the source and target registers are treated as integer values.

31 26	25 20	19 14	13 8	7 0
8_6	$\sim_6$	Ra_6	Rt_6	$01h_8$

Integer Vector Format: R1

31 26	2524	23 21	20	19 14	13 8	7 0
$08h_6$	$\sim_2$	m_3	z	Va_6	Vt_6	$81h_8$

Float Instruction Format: R1

Both the source and target registers are treated as float values.

31 26	25 20	19 14	13 8	7 0
$08h_6$	$\sim_6$	Ra_6	Rt_6	$34h_8$

Float Vector Format: R1

31 26	2524	23 21	20	19 14	13 8	7 0
$08h_6$	$\sim_2$	m_3	z	Va_6	Vt_6	$B4h_8$

SRA –Shift Right Arithmetic Pair

Description:

This is an alternate mnemonic for the signed field extract EXT instruction.

Right shift a pair of operand values by an operand value and place the result in the target register. The lower 64 bits of the result are placed in the target register. The sign bit is shifted into the most significant bits. The operand pair must be in registers specified by the Ra and Rb field of the instruction. The third operand may be either a register specified by the Rc field of the instruction, or an immediate value.

Instruction Format: R4

31 29	28 26	25 20	19 14	1312	11 9	8	7 0
DT_3	Rm_3	63_6	Rc_6	A	m_3	z	$59h_8$

31 26	25 20	19 14	13 8	7 0
4_6	Rb_6	Ra_6	Rt_6	$1Ch_8$

DT_3	Meaning
10	Rd is a six bit immediate, Rc is a reg
11	Both Rc, Rd are six bit immediates

Operation Size: .o

Execution Units: integer ALU

Exceptions: none

Example:

SRL –Shift Right Logical

Description:

Right shift an operand value by an operand value and place the result in the target register. Zeros are shifted into the most significant bits. The first operand must be in a register specified by the Ra. The second operand may be either a register specified by the Rb field of the instruction, or an immediate value.

Instruction Formats: R2

31 26	25 20	19 14	13 8	7 0
$21h_6$	Rb_6	Ra_6	Rt_6	$02h_8$

Instruction Formats: R2I

31 26	25 20	19 14	13 8	7 0
$22h_6$	Imm_6	Ra_6	Rt_6	$02h_8$

Vector Mask Instruction Format: R2 (MSRL)

31 26	25 20	19 17	16 14	13 11	10 8	7 0
$0Fh_6$	imm_6	0_3	Vma_3	0_3	Vmt_3	$80h_8$

1 clock cycle

Operation Size: .o

Execution Units: integer ALU

Exceptions: none

Example:

SRLP –Shift Right Logical Pair

Description:

This is an alternate mnemonic for the unsigned field extract EXTU instruction.

Right shift a pair of operand values by an operand value and place the result in the target register. The lower 64 bits of the result are placed in the target register. Zeros are shifted into the most significant bits. The operand pair must be in registers specified by the Ra and Rb field of the instruction. The third operand may be either a register specified by the Rc field of the instruction, or an immediate value.

This instruction may also be used to perform a right rotate of a single register by specifying the same register for Ra and Rb.

Instruction Format: R4

31 29	28 26	25 20	19 14	1312	11 9	8	7 0
DT_3	Rm_3	63_6	Rc_6	A	m_3	z	$59h_8$

31 26	25 20	19 14	13 8	7 0
5_6	Rb_6	Ra_6	Rt_6	$1Ch_8$

DT_3	Meaning
10	Rd is a six bit immediate, Rc is a reg
11	Both Rc, Rd are six bit immediates

Operation Size: .o

Execution Units: integer ALU

Exceptions: none

Example:

SUB - Subtract

Description:

Subtract two values. Both operands must be in a register.

Instruction Format: R2

31 26	25 20	19 14	13 8	7 0
5_6	Rb_6	Ra_6	Rt_6	$02h_8$

Scalar Operation

Rt = Ra - Rb

Vector Operation

for x = 0 to VL - 1

if (Vm[x]) Vt[x] = Va[x] - Vb[x]

else if (z) Vt[x] = 0

else Vt[x] = Vt[x]

SUBF – Subtract From

Description:

Subtract two values. The first operand must be in a register. The second operand must be an immediate value specified in the instruction. There is no register form for this instruction.

Instruction Format: RI

31	20	19	14	13	8	7	0
$Constant_{12}$		Ra_6		Rt_6		$05h_8$	

Operation:

Rt = Imm - Ra

Exceptions: none

U21NDX – UTF21 Index

Description:

This instruction searches Ra, which is treated as an array of three UTF21 values, for a value specified by Rb and places the index of the value into the target register Rt. If the UTF21 value is not found -1 is placed in the target register. A common use would be to search for a null. The index result may vary from -1 to +2. The index of the first found value is returned (closest to zero).

Integer Instruction Format: RI

The RI instruction format may be used with an immediate extension word for full 21-bit constants.

31 20	19 14	13 8	7 0
$Constant_{12}$	Ra_6	Rt_6	$23h_8$

1 clock cycle

Instruction Format: R2

31 26	25 20	19 14	13 8	7 0
$23h_6$	Rb_6	Ra_6	Rt_6	$02h_8$

Supported Formats: .o

Clock Cycles: 1

Execution Units: Integer ALU

Operation:

Rt = Index of (Rb in Ra)

Exceptions: none

WYDNDX – Wyde Index

Description:

This instruction searches Ra, which is treated as an array of four wydes, for a wyde value specified by Rb and places the index of the wyde into the target register Rt. If the wyde is not found -1 is placed in the target register. A common use would be to search for a null wyde. The index result may vary from -1 to +3. The index of the first found wyde is returned (closest to zero).

Integer Instruction Format: RI

The RI instruction format may be used with an immediate extension word for full 16-bit constants.

35	22	21 20	19 15	14 13	12 8	7	6 0
$Constant_{14}$		Ta_2	Ra_5	Tt_2	Rt_5	v	$1Bh_7$

1 clock cycle

Instruction Format: R2

35 29	28 27	26 22	21 20	19 15	14 13	12 8	7	6 0
$1Bh_7$	Tb_2	Rb_5	Ta_2	Ra_5	Tt_2	Rt_5	v	$02h_7$

R2 Supported Formats: .o

Clock Cycles: 1

Execution Units: Integer ALU

Operation:

Rt = Index of (Rb in Ra)

Exceptions: none

XOR – Bitwise Exclusive Or

Description:

Perform a bitwise exclusive or operation between operands. The first operand must be in a register. The second operand may be a register or immediate value. A third operand must be in a register. The immediate constant is zero extended before use.

Integer Instruction Format: RI

35 20	19	18 14	13	12 8	7	6 0
$Constant_{16}$	Ta	Ra_5	Tt	Rt_5	v	$0Ah_7$

1 clock cycle / N clock cycles (N = vector length)

Integer Instruction Format: R2

35 29	2827	2625	24 20	19	18 14	13	12 8	7	6 0
$0Ah_7$	$\sim_2$	Tb_2	Rb_5	Ta	Ra_5	Tt	Rt_5	v	$02h_7$

1 clock cycle / N clock cycles (N = vector length)

Vector Mask Instruction Format: R2 (MADD)

35 29	28 25	24 22	21 18	17 15	14 11	10 8	7 0
$02h_7$	0_4	Vmb_3	0_4	Vma_3	0_4	Vmt_3	$3Eh_8$

1 clock cycle

Operation

Rt = Ra ^ Immediate

OR

Rt = Ra ^ Rb

Vector Operation

for x = 0 to VL-1

if (Vm[x]) Vt[x] = Va[x] ^ Vb[x] ^ Vc[x]

else if (z) Vt[x] = 0

else Vt[x] = Vt[x]

Exceptions: none

ZXB –Zero Extend Byte

Description:

Zero extend byte.

Integer Instruction Format: R1

Both the source and target registers are treated as integer values.

31 26	25 20	19 14	13 8	7 0
$0Ch_6$	$\sim_6$	Ra_6	Rt_6	$01h_8$

Clock Cycles: 1

Execution Units: Integer ALU

Exceptions: none

Notes:

ZXW –Zero Extend Wyde

Description:

Integer Instruction Format: R1

Both the source and target registers are treated as integer values.

31 26	25 20	19 14	13 8	7 0
$0Dh_6$	$\sim_6$	Ra_6	Rt_6	$01h_8$

Integer Vector Format: R1

31 26	2524	23 21	20	19 14	13 8	7 0
$0Dh_6$	$\sim_2$	m_3	z	Va_6	Vt_6	$81h_8$

Clock Cycles: 1

Execution Units: Integer ALU

Exceptions: none

Notes:

ZXT –Zero Extend Tetra

Description:

Integer Instruction Format: R1

Both the source and target registers are treated as integer values.

31 26	25 20	19 14	13 8	7 0
$0Eh_6$	$\sim_6$	Ra_6	Rt_6	$01h_8$

Integer Vector Format: R1

31 26	2524	23 21	20	19 14	13 8	7 0
$0Eh_6$	$\sim_2$	m_3	z	Va_6	Vt_6	$81h_8$

Clock Cycles: 1

Execution Units: Integer ALU

Exceptions: none

Notes:

Graphics

BLEND – Blend Colors

Description:

This instruction blends two colors whose values are in Ra and Rb according to an alpha value in Rc. The resulting color is placed in register Rt. The alpha value is an eight-bit value assumed to be a binary fraction less than one. The color values in Ra and Rb are assumed to be RGB888 format colors. The result is a RGB888 format color. The high order eight bits of the result register are set to the high order eight bits of Ra. Note that a close approximation to 1.0 – alpha is used. Each component of the color is blended.

Instruction Format: R3

31 29	28 26	25 20	19 14	13 12	11 9	8	7 0
DT_3	0_3	0_6	Rc_6	0	m_3	z	$58h_8$

31 26	25 20	19 14	13 8	7 0
$30h_6$	Rb_6	Ra_6	Rt_6	$03h_8$

Operation:

Rt.R = (Ra.R * alpha) + (Rb.R * ~alpha)

Rt.G = (Ra.G * alpha) + (Rb.G * ~alpha)

Rt.B = (Ra.B * alpha) + (Rb.B * ~alpha)

Clock Cycles: 2

TRANSFORM – Transform Point

Description:

The point transform instruction transforms a point from one location to another using a transform function. The transform function has 12 co-efficients in the form of a matrix to used in the calculation.

Points are represented in 16.16 fixed-point format.

31 26	25 20	19 14	13 8	7 0
$11h_9$	0_6	Ra_6	Rt_6	$01h_8$

Clock Cycles: 2

RW_COEEF – Read/Write Co-efficient

Description:

RW_COEFF reads and writes a coefficient value to be used for the transform matrix. Ra contains the number of the coefficient to read or write. Rb contains the new value for the coefficient.

Instruction Format: R2

31 26	25 20	19 14	13 8	7 0
$3Eh_9$	Rb_6	Ra_6	Rt_6	$02h_8$

Co-efficient Matrix:

AA	AB	AC	AT
BA	BB	BC	BT
CA	CB	CC	CT

Regno in Ra	Coefficient Accessed
0	AA
1	AB
2	AC
3	AT
4	BA
5	BB
6	BC
7	BT
8	CA
9	CB
10	CC
11	CT
12	CMD – bit 0, 1=transform, 0 = pass through

Memory Operations

CACHE – Cache Command

CACHE Cmd, d[Rn]

Description:

This instruction commands the cache controller to perform an operation. Commands are summarized in the command table below. Commands may be issued to both the instruction and data cache at the same time. The address of the cache line to be invalidated is passed in Ra if needed.

Instruction Formats: CACHE

31 28	27 20	19 14	13 11	10 8	7 0
$15_{3..0}$	$Const_8$	Ra_6	DC_3	IC_3	$60h_8$

Commands:

IC_3	Mne.	Operation
0	NOP	no operation
1	invline	invalidate line associated with given address
2	invall	invalidate the entire cache (address is ignored)
3 to 7		reserved

DC_3	Mne.	Operation
0	NOP	no operation
1	enable	enable cache (instruction cache is always enabled)
2	disable	not valid for the instruction cache
3	invline	invalidate line associated with given address
4	invall	invalidate the entire cache (address is ignored)
5 to 7		reserved

Notes:

LDx – Load

Description:

Load a value from memory into a register.

Formats Supported:

Register Indirect with Displacement

This mode may make use of immediate prefixes to extend the range.

35 32	31 20	19	18 14	13	12 8	7 0
$Func_{3..0}$	$Const_{12}$	Ta	Ra_5	Tt	Rt_5	$60h_8$

Scalar Indexed Form (LD)

The effective address (EA) is calculated as the sum of Ra plus Rb multiplied by a scale.

35 32	3130	29 27	2625	24 20	19	18 14	13	12 8	7 0
$Func_4$	$\sim_2$	Sc_3	Tb_2	Rb_5	Ta	Ra_5	Tt	Rt_5	$61h_8$

z: 1= zero extend, 0 = sign extend

S	Multiplier
0	1
1	operand size

Operation:

Rt = Memory[d + Ra + Rb * Sc]

Vector forms

Stridden Form (LDS)

31 21	20	19 14	1312	11 9	8	7 0
$Const_{11}$	I	Rc_6	A	m_3	z	$5Ch_8$

31 28	27 20	19 14	13 8	7 0
$Func_{3..0}$	$Const_8$	Ra_6	Rt_6	$E2h_8$

Data is loaded from memory addresses separated by the stride amount specified by register field Rc, beginning with the sum of Ra and an immediate value. If the vector mask bit is clear and the 'z' bit is set in the instruction then the corresponding element of the vector register is loaded with zero. If the vector mask bit is clear and the 'z' bit is clear in the instruction then the corresponding element of the vector register is left unchanged (no value is loaded from memory).

Elements are loaded only up to the length specified in the vector length register.

Vm[x]	z	Result

0	0	Vt[x] = Vt[x] (unchanged)
0	1	Vt[x] = 0 (set to zero)
1	0	Vt[x] = memory, sign extended
1	1	Vt[x] = memory, zero extended

$Func_4$	Operation Size
0	byte
1	wyde
2	tetra
3	octa
4	hexi (double octa)
5	quad octa
6	reserved
7	pointer
…	reserved
15	cache cmd

Operation:

for x = 0 to vector length
      if (Vm[x])
            Vt[x] = Memory[d+Ra + Rb * x]
      else
            Vt[x] = z ? 0 : Vt[x]

Indexed Form

Data is loaded from memory addresses beginning with the sum of Ra and a vector element from Vc.

31 21	20	19 14	1312	11 9	8	7 0
$Const_{11}$	0	Vc_6	A	m_3	z	DCh_8

31 28	27 20	19 14	13 8	7 0
$Func_{3..0}$	$Const_8$	Ra_6	Rt_6	$E3h_8$

Operation:

n = 0
for x = 0 to vector length
      if (Vm[x])
            Vt[x] = Memory[d + Ra + Vb[x]]
      else
            Vt[x] = z ? 0 : Vt[x]

Exceptions: none

LDB – Load Byte (8 bits)

Description:

Data is loaded from the memory address which is the sum of an immediate value and the sum of Ra and Rb times a scale. The value loaded is sign extended from bit 7 to the machine width.

Formats Supported: LD

Operation:

Rt = Memory$_8$[d + Ra + Rb*Sc]

Exceptions: none

LDBZ – Load Byte, Zero Extend (8 bits)

Description:

Data is loaded from the memory address which is the sum of an immediate value and the sum of Ra and Rb times a scale. The value loaded is zero extended from bit 8 to the machine width.

Formats Supported: LD

Operation:

Rt = Memory$_8$[d + Ra + Rb*Sc]

Exceptions: none

LDO – Load Octa (64 bits)

Description:

Data is loaded into Rt from the memory address which is the sum of an immediate value and the sum of Ra and Rb scaled.

Formats Supported: RR,RI

Operation:

Rt = Memory$_{64}$[d + Ra + Rb*Sc]

Execution Units: Mem

Exceptions: none

LDT – Load Tetra (32 bits)

Description:

> Data is loaded from the memory address which is the sum of Ra and an immediate value or the sum of Ra and Rb scaled. The value loaded is sign extended from bit 31 to the machine width.

Formats Supported: RR,RI

Operation:

> $Rt = Memory_{32}[d + Ra + Rb*Sc]$

Execution Units: Mem

Exceptions: none

LDTZ – Load Tetra, Zero Extend (32 bits)

Description:

> Data is loaded from the memory address which is the sum of Ra and an immediate value or the sum of Ra and Rb scaled. The value loaded is zero extended from bit 8 to the machine width.

Formats Supported: RR,RI

Operation:

> $Rt = Memory_{32}[d + Ra + Rb*Sc]$

Execution Units: Mem

Exceptions: none

LDW – Load Wyde (16 bits)

Description:

> Data is loaded from the memory address which is the sum of Ra and an immediate value or the sum of Ra and Rb scaled. The value loaded is sign extended from bit 15 to the machine width.

Formats Supported: LD

Operation:

> $Rt = Memory_{16}[d + Ra + Rb*Sc]$

Execution Units: Mem

Exceptions: none

LDWZ – Load Wyde, Zero Extend (16 bits)

Description:

> Data is loaded from the memory address which is the sum of Ra and an immediate value or the sum of Ra and Rb scaled. The value loaded is zero extended from bit 16 to the machine width.

Formats Supported: LD

Operation:

> $Rt = Memory_{16}[d + Ra + Rb*Sc]$

Execution Units: Mem

Exceptions: none

LEA – Load Effective Address

Description:

This instruction computes the effective address for a load/store operation. The data type tag for the target register is set to indicate it contains a pointer.

Formats Supported:

Scalar Indexed Form (LD)

31 28	27	26	25 20	19 14	13 8	7 0
$Func_{3..0}$	1	S	Rb_6	Ra_6	Rt_6	$61h_8$

Operation:

$Rt = d + Ra + Rb * Sc$

Vector forms

Stridden Form (LDS)

63 50	4948	47 44	4341	40	39 32	31 24	23 16	15 8	7 0
$Const_{21..8}$	U_2	Sz_4	m_3	z	$Const_{7..0}$	Rb_8	Ra_8	Rt_8	$69h_8$

Vm[x]	z	Result
0	0	Vt[x] = Vt[x] (unchanged)
0	1	Vt[x] = 0 (set to zero)
1	0	Vt[x] = memory address
1	1	Vt[x] = memory address

U_2	Unit
0	integer
1	floating-point
2	decimal-float
3	posit

Sz_4	Operation Size
0	byte
1	wyde
2	tetra
3	octa
4	hexi

Operation:

for x = 0 to vector length
  if (Vm[x])
    Vt[x] = d + Ra + Rb * x
  else
    Vt[x] = z ? 0 : Vt[x]

Indexed Form

63	48	47 44	4341	40	39 32	31 24	23 16	15 8	7 0
$Const_{23..8}$		Sz_4	m_3	z	$Const_{7..0}$	Vb_8	Ra_8	Rt_8	$6Ah_8$

Operation:

n = 0
for x = 0 to vector length
  if (Vm[x])
    Vt[x] = d + Ra + Vb[x]
  else
    Vt[x] = z ? 0 : Vt[x]

Exceptions: none

STx – Store

Description:

Store values to memory. Either the contents of a scalar or vector register or a six-bit immediate constant may be stored. Both scalar and vector store operations are possible.

Formats Supported:

Register Indirect with Displacement

35 32	3127	2625	24 20	19	18 14	13 8	7 0
$Func_{3..0}$	C_5	Tb_2	Rb_5	Ta	Ra_5	$Const_6$	$70h_8$

Scalar Indexed Form (ST)

The effective address (EA) is calculated as the sum of Ra plus Rc multiplied by a scale.

35 31	30 28	27	2625	24 20	19	18 14	1312	11 9	8	7 0
$\sim_5$	Rm_3	Tc	Td_2	Rd_6	Tc	Rc_5	A	m_3	z	$58h_8$

35 32	3130	29 27	2625	24 20	19	18 14	13 8	7 0
$Func_4$	$\sim_2$	Sc_3	Tb_2	Rb_6	Ta	Ra_6	$\sim_6$	$71h_8$

Sc	Multiplier
0	1
1	Store size

Operation:

Memory[d+Ra + Rb * Sc] = Rs

Vector forms

Stridden Form (STS)

35 21	2019	18 14	1312	11 9	8	7 0
$Const_{15}$	Tc_2	Rc_5	A	m_3	z	$5Ch_8$

31 28	2726	25 20	19 14	13 8	7 0
$Func_{3..0}$	C_2	Rb_6	Ra_6	$Const_6$	$F2h_8$

Data is stored to memory addresses separated by the stride amount specified by register field Rc, beginning with the sum of Ra and an immediate value. If the vector mask bit is clear and the 'z' bit is set in the instruction then memory for the corresponding element of the vector register is

stored with zero. If the vector mask bit is clear and the 'z' bit is clear in the instruction then memory corresponding to the element of the vector register is left unchanged (no value is stored to memory).

Elements are loaded only up to the length specified in the vector length register.

Vm[x]	z	Result
0	0	Memory = Memory (unchanged)
0	1	Memory = 0 (set to zero)
1	0	memory = Vt[x]
1	1	memory = Vt[x]

Sz_4	Operation Size
0	byte
1	wyde
2	tetra
3	octa
4	hexi
5,6	reserved
7	pointer

Operation:

for x = 0 to vector length
      if (Vm[x])
              Memory[d+Ra + Rb * x] = Vt[x]
      else
              Memory[d+Ra + Rb * x] = z ? 0 : Memory[d+Ra + Rb * x]

Indexed Form

Data is stored to memory addresses beginning with the sum of Ra and a vector element from Vb.

35 21	20 19	18 14	13 12	11 9	8	7 0
$Const_{15}$	Tc_2	Rc_5	A	m_3	z	$5Ch_8$

31 28	27 26	25 20	19 14	13 8	7 0
$Func_{3..0}$	C_2	Rb_6	Ra_6	$Const_6$	$F3h_8$

Operation:

n = 0
for x = 0 to vector length
      if (Vm[x])

$$Memory[d + Ra + Vb[x]] = Vt[x]$$

else

$$Memory = z \: ? \: 0 : Memory$$

Exceptions: none

STB – Store Byte (8 bits)

Description:

This instruction stores a byte (8 bit) value to memory.

Instruction Format: ST

Register Indirect Operation:

$Memory_8[d + Ra] = Rb$

Indexed Operation:

$Memory_8[Ra + Rc*Sc] = Rb$

STBZ – Store Byte and Zero (8 bits)

Description:

This instruction stores a byte (8 bit) value to memory. After the byte is stored to memory the register is zeroed out.

Instruction Format: ST

Register Indirect Operation:

$Memory_8[d + Ra] = Rb$
$Rb = 0$

Indexed Operation:

$Memory_8[Ra + Rc*Sc] = Rb$
$Rb = 0$

STO – Store Octa (64 bits)

Description:

This instruction stores an octa-byte (64 bit) value to memory. The memory address is calculated as the sum of an immediate constant and the sum of Ra and Rb scaled.

Instruction Format: ST

Operation:

$Memory_{64}[d + Ra + Rb*Sc] = Rs$

STOZ – Store Octa and Zero (64 bits)

Description:

This instruction stores an octa-byte (64 bit) value to memory. The memory address is calculated as the sum of an immediate constant and the sum of Ra and Rb scaled. After the tetra is stored to memory the register is zeroed out.

Instruction Format: ST

Operation:

$Memory_{64}[d + Ra + Rb*Sc] = Rs$

$Rs = 0$

STPTR – Store Pointer (64 bits)

Description:

This instruction stores an octa-byte (64 bit) value to memory. The memory address is calculated as the sum of an immediate constant and the sum of Ra and Rb scaled. STPTR begins a series of stores to memory addresses scaled by eight bits, until the address zero is reached. The first store proceeds normally, for the second and subsequent stores a byte store operation takes place with the value zero being to memory.

The purpose of the STPTR instruction is to allow a code dense implementation of a write barrier that indicates where in memory a pointer is stored with increasing resolution.

This instruction assumes that card memory used to record pointer locations is located at the low end of the memory system.

Instruction Format: ST

Operation:

$ea = d + Ra + Rb*Sc$
$Memory_{64}[ea] = Rs$
while $ea <> 0$
$\quad\quad ea = ea >> 8$
$\quad\quad Memory_8[ea] = 0$

STT – Store Tetra (32 bits)

Description:

This instruction stores a tetra-byte (32 bit) value to memory. The memory address is calculated as the sum of an immediate constant and the sum of Ra and Rb scaled.

Instruction Format: ST

Operation:

$Memory_{32}[d + Ra + Rb*Sc] = Rs$

STTZ – Store Tetra and Zero (32 bits)

Description:

This instruction stores a tetra-byte (32 bit) value to memory. The memory address is calculated as the sum of an immediate constant and the sum of Ra and Rb scaled. After the tetra is stored to memory the register is zeroed out.

Instruction Format: ST

Operation:

$Memory_{32}[d + Ra + Rb*Sc] = Rs$

$Rs = 0$

STW – Store Wyde (16 bits)

Description:

This instruction stores a byte (16 bit) value to memory. The memory address is calculated as the sum of an immediate constant and the sum of Ra and Rb scaled.

Instruction Format: ST

Operation:

$Memory_{16}[d + Ra + Rb*Sc] = Rs$

STWZ – Store Wyde and Zero (16 bits)

Description:

This instruction stores a byte (16 bit) value to memory. The memory address is calculated as the sum of an immediate constant and the sum of Ra and Rb scaled. After the wyde is stored to memory the register is zeroed out.

Instruction Format: ST

Operation:

Memory$_{16}$[d + Ra + Rb*Sc] = Rs

Rs = 0

Flow Control (Branch Unit) Operations

Branches

Displacement

The conditional branch displacement is in terms of instruction count skipped over to increase the range a branch may cover. A displacement of one represents nine nybbles. Code using conditional branches must be sequentially laid out in memory, instructions adjacent to each other with no "holes" in the layout.

The displacement for the branch-and-link instruction is the number of nybbles to the target address from the current one. This allows subroutines to be aligned at any nybble address.

Modifier

The branch modifier may be used to make it possible to branch to a target address contained in a register, and to store the return address in a register. Simultaneously the branch displacement is increased to 26 bits allowing a ±150MB branch range.

BAL – Branch and Link

Description:

This instruction may be used to call a subroutine using relative addressing. The address of the instruction after the BAL is stored in the specified return address register (Rt) then a jump to the address specified in the instruction is made. The address range is 26 bits or ±16MB.

The return address register is assumed to be x1 if not otherwise specified. The BAL instruction does not require space in branch predictor tables.

Formats Supported: BAL

35	10	9 8	7 0
$Constant_{26}$		Rt_2	$41h_8$

Flags Affected: none

Operation:
$Rt = IP + 9$
$IP = IP + displacement$

Execution Units: Branch

Exceptions: none

Notes:

BBS – Branch if Bit Set

Description:

This instruction branches to the target address if the bit number identified by the Rb specifier in the instruction is set in Ra. Rb may be a value in a register or a six-bit unsigned immediate value. Otherwise, program execution continues with the next instruction. With a branch modifier instruction, the target address is formed as the sum of Rc and a displacement. If Rc is x31 then the instruction pointer value is used. Otherwise, the target address is the sum of the instruction pointer value and the displacement specified in the instruction.

Formats Supported: BR

35 29	2827	26 22	2120	19 15	1413	12 8	7	6 0
$Const_7$	Tb_2	Rb_5	Ta_2	Ra_5	Ty_2	$Const_5$	0	$4Dh_8$

Operation:

If (Ra[Rb])
$\qquad$ IP = IP + Displacement12*9
With Modifier
$\quad$ Rt = IP + 9
$\quad$ If (Ra[Rb])
$\qquad$ IP = Rc + Displacement26*9

Execution Units: Branch

Exceptions: none

Notes:

BEQ – Branch if Equal

Description:

This instruction branches to the target address if the contents of Ra and Rb are equal, otherwise program execution continues with the next instruction. With a branch modifier instruction, the target address is formed as the sum of Rc and a displacement. If Rc is x31 then the instruction pointer value is used. Otherwise, the target address is the sum of the instruction pointer value and the displacement specified in the instruction.

Formats Supported: BR

35 27	26 25	24 20	19	18 14	13 8	7	6 0
$Const_9$	Tb_2	Rb_5	Ta	Ra_5	$Const_6$	0	$4Eh_8$

Operation:

If (Ra = Rb)
    IP = IP + Displacement15*9
With Modifier
    Rt = IP + 9
    If (Ra = Rb)
        IP = Rc + Displacement30*9

Execution Units: Branch

Exceptions: none

Notes:

For a floating-point comparison positive and negative zero are considered equal.

BGE – Branch if Greater Than or Equal

Description:

This instruction branches to the target address if the contents of Ra is greater than or equal to Rb, otherwise program execution continues with the next instruction. The values in Ra and Rb are treated as signed values.

Formats Supported: BR

35 29	2827	26 22	2120	19 15	1413	12 8	7	6 0
$Const_7$	Tb_2	Rb_5	Ta_2	Ra_5	Ty_2	$Const_5$	0	$49h_7$

Operation:

If (Ra >= Rb)
        IP = IP + Displacement

Execution Units: Branch

Exceptions: none

BGEU – Branch if Greater Than or Equal Unsigned

Description:

This instruction branches to the target address if the contents of Ra is greater than or equal to Rb, otherwise program execution continues with the next instruction. The values in Ra and Rb are treated as unsigned values. The target address is formed as the sum of Rc and a displacement. If Rc is x31 then the program counter value is used.

Formats Supported: BR

35 29	2827	26 22	2120	19 15	1413	12 8	7 6	0
$Const_7$	Tb_2	Rb_5	Ta_2	Ra_5	Ty_2	$Const_5$	0	$4Bh_7$

Operation:

Rt = IP + 8
If (Ra >= Rb)
    PC = Rc + Displacement

Execution Units: Branch

Exceptions: none

BGT – Branch if Greater Than

Description:

This instruction is an alternate mnemonic for the BLT instruction where the register operands have been swapped.

This instruction branches to the target address if the contents of Ra is less than Rb, otherwise program execution continues with the next instruction. The values in Ra and Rb are treated as signed values. The target address is formed as the sum of Rc and a displacement. If Rc is x31 then the program counter value is used.

Formats Supported: BR

35 29	2827	26 22	2120	19 15	1413	12 8	7	6 0
$Const_7$	Tb_2	Rb_5	Ta_2	Ra_5	Ty_2	$Const_5$	0	$48h_7$

Operation:

$Rt = IP + 8$
If $(Ra < Rb)$
$\quad\quad PC = Rc + Displacement$

Execution Units: Branch

Exceptions: none

BGTU – Branch if Greater Than Unsigned

Description:

This instruction is an alternate mnemonic for the BLTU instruction where the register operands have been swapped.

This instruction branches to the target address if the contents of Ra is less than Rb, otherwise program execution continues with the next instruction. The values in Ra and Rb are treated as unsigned values. The target address is formed as the sum of Rc and a displacement. If Rc is x31 then the program counter value is used.

Formats Supported: BR

35 29	2827	26 22	2120	19 15	1413	12 8	7	6 0
$Const_7$	Tb_2	Rb_5	Ta_2	Ra_5	Ty_2	$Const_5$	0	$4Ah_7$

Operation:

$Rt = IP + 8$
If $(Ra < Rb)$
$\quad\quad PC = Rc + Displacement$

Execution Units: Branch

Exceptions: none

BNE – Branch if Not Equal

Description:

This instruction branches to the target address if the contents of Ra and Rb are not equal, otherwise program execution continues with the next instruction.

Formats Supported: BR

35	29	2827	26	22	2120	19	15	1413	12	8	7	6	0
$Const_7$		Tb_2	Rb_5		Ta_2	Ra_5		Ty_2	$Const_5$		0	$4Fh_8$	

Operation:

If (Ra <> Rb)

IP = IP + Displacement

Execution Units: Branch

Exceptions: none

BLE – Branch if Less Than or Equal

Description:

This is an alternate mnemonic for the BGE instruction, where the register operands have been swapped.

This instruction branches to the target address if the contents of Ra is greater than or equal to Rb, otherwise program execution continues with the next instruction. The values in Ra and Rb are treated as signed values.

Formats Supported: BR

35 29	2827	26 22	2120	19 15	1413	12 8	7	6 0
$Const_7$	Ta_2	Ra_5	Tb_2	Rb_5	Ty_2	$Const_5$	0	$49h_7$

Operation:

If (Ra >= Rb)

$$PC = Rc + Displacement$$

Execution Units: Branch

Exceptions: none

BLEU – Branch if Less Than or Equal Unsigned

Description:

This is an alternate mnemonic for the BGEU instruction, where the register operands have been swapped.

This instruction branches to the target address if the contents of Ra is greater than or equal to Rb, otherwise program execution continues with the next instruction. The values in Ra and Rb are treated as unsigned values.

Formats Supported: BR

35　29	2827	26　22	2120	19　15	1413	12　8	7	6　0
$Const_7$	Ta_2	Ra_5	Tb_2	Rb_5	Ty_2	$Const_5$	0	$4Bh_7$

Operation:

If (Ra >= Rb)

　　　　IP = IP + Displacement

Execution Units: Branch

Exceptions: none

BLT – Branch if Less Than

Description:

This instruction branches to the target address if the contents of Ra is less than Rb, otherwise program execution continues with the next instruction. The values in Ra and Rb are treated as signed values.

Formats Supported: BR

35 29	2827	26 22	2120	19 15	1413	12 8	7	6 0
$Const_7$	Tb_2	Rb_5	Ta_2	Ra_5	Ty_2	$Const_5$	0	$48h_7$

Operation:

If (Ra < Rb)
$\qquad$ IP = IP + Displacement

Execution Units: Branch

Exceptions: none

BLTU – Branch if Less Than Unsigned

Description:

This instruction branches to the target address if the contents of Ra is less than Rb, otherwise program execution continues with the next instruction. The values in Ra and Rb are treated as unsigned values.

Formats Supported: BR

35 29	28 27	26 22	21 20	19 15	14 13	12 8	7	6 0
$Const_7$	Tb_2	Rb_5	Ta_2	Ra_5	Ty_2	$Const_5$	0	$4Ah_7$

Operation:

if (Ra < Rb)
    IP = IP + Displacement

Execution Units: Branch

Exceptions: none

BRA – Unconditional Branch

Description:

This instruction is an alternate mnemonic for the BAL instruction. The address range is 26 bits or ±16MB.

Formats Supported: JAL

35	10	9	8	7	0
$Constant_{26}$		0_2		$41h_8$	

Flags Affected: none

Operation:
IP = IP + Displacement

Execution Units: Branch

Exceptions: none

Notes:

BSR – Unconditional Branch to Subroutine

Description:

This instruction is an alternate mnemonic for the BAL instruction. The address range is 26 bits or ±16MB.

Formats Supported: JAL

35	10	9	8	7	0
$Constant_{26}$		1_2		$41h_8$	

Flags Affected: none

Operation:
Rt = IP + 9
IP = IP + Displacement

Execution Units: Branch

Exceptions: none

Notes:

CHK – Check Register Against Bounds

Description:

A register is compared to two values. If the register is outside of the bounds then an exception will occur.

Instruction Format: RI

31 29	28 26	25 20	19 14	1312	11 9	8	7	0
DT_3	Rm_3	Rd_6	Rc_6	A	m_3	z	$F7h_8$	

31	20	19 14	13 10	9 8	7	0
$Constant_{12}$		Ra_6	~	Cn_2	$22h_8$	

Cn_2	Interpretation
0	Ra <= Rc <= Constant
1	Ra < Rc <= Constant
2	Ra <= Rc < Constant
3	Ra < Rc < Constant

Instruction Format: R3

31 29	28 26	25 20	19 14	1312	11 9	8	7	0
DT_3	Rm_3	Rd_6	Rc_6	A	m_3	z	$F7h_8$	

31 26	25 20	19 14	13 10	9 8	7	0
$22h_6$	Rb_6	Ra_6	~	Cn_2	$03h_8$	

Cn_2	Interpretation
0	Ra <= Rb <= Rc
1	Ra < Rb <= Rc
2	Ra <= Rb < Rc
3	Ra < Rb < Rc

Supported Formats: .o

Clock Cycles: 2

Execution Units: Integer ALU, Float, Decimal Float, Posit

Exceptions: bounds check

Notes:

The system exception handler will typically transfer processing back to a local exception handler.

JAL – Jump and Link

Description:

This instruction may be used to both call a subroutine and return from it. The address of the instruction after the JAL is stored in the specified return address register (Rt) then a jump to the address specified in the instruction is made. The address range is 26 bits or 16MB.

The return address register is assumed to be x1 if not otherwise specified. The JAL instruction does not require space in branch predictor tables.

Formats Supported: JAL

35	10	9 8	7 0
$Constant_{26}$		Rt_2	$40h_8$

Flags Affected: none

Operation:
Rt = IP + 9
IP = displacement

Execution Units: Branch

Exceptions: none

Notes:

JALR – Jump and Link to Register

Description:

This instruction may be used to both call a subroutine and return from it. The sum of the current IP and a small constant is stored in the specified return address register (Rt) then a jump to the address specified in the instruction plus an index register value is made.

The return address register is assumed to be x1 if not otherwise specified. The JALR instruction does not require space in branch predictor tables.

If x31 is specified for Ra then the current instruction pointer value is used.

Formats Supported: JALR

35	22	21 20	19 15	14 10	9 8	7 0
$Constant_{14}$		Ta_2	Ra_5	$Cnst_5$	Rt_2	$42h_8$

Flags Affected: none

Operation:

$Rt = IP + Cnst_5*2$
If Ra=31
        IP = IP + displacement
Else
        IP = Ra + Displacement

Execution Units: Branch

Exceptions: none

Notes:

JMP – Jump

Description:

This instruction is an alternate mnemonic for the JAL instruction. It may be used to jump directly to a specific address. The address range is 26 bits or 16MB.

The return address register is assumed to be x0 (discarding the return address). The JMP instruction does not require space in branch predictor tables.

Formats Supported: JAL

35	10	9 8	7 0
$Constant_{26}$		0_2	$40h_8$

Flags Affected: none

Operation:
IP = displacement

Execution Units: Branch

Exceptions: none

Notes:

RET – Return from Subroutine

Description:

This instruction is an alternate mnemonic for the JALR instruction. Register Ra is assumed to be x1 and register Rt is assumed to be x0. The constant is assumed to be zero.

Formats Supported: JALR

35	22	2120	19 15	14 13	12	8	7	0
$Constant_{14}$		0_2	01_5	0_2	0_5		$42h_8$	

Flags Affected: none

Operation:

Execution Units: Branch

Exceptions: an unimplemented instruction exception may occur if a vector register is specified.

Notes:

Return address prediction hardware may make use of the RET instruction.

System Instructions

BRK – Break

Description:

This instruction initiates the processor debug routine. The processor enters debug mode. The cause code register is set to the value specified in the instruction. Interrupts are disabled. The instruction pointer is reset to the contents of tvec[4] and instructions begin executing. There should be a jump instruction placed at the break vector location. The address of the BRK instruction is stored in the EIP register.

Instruction Format: BRK

35	23	22	15	14	13	12	8	7	0
$\sim_{13}$		$Cause_8$		0_2		0_5		$00h_8$	

Operation:

$PMSTACK = (PMSTACK << 4) | 10$
$CAUSE = Const_8$
$EIP = IP$
$IP = tvec[4]$

Execution Units: Branch

Clock Cycles:

Exceptions: none

Notes:

CSRx – Control and Special / Status Access

Description:

The CSR instruction group provides access to control and special or status registers in the core. For the read operation the current value of the CSR is placed in the target register Rt.

Instruction Format: CSR

35	22	2120	19 15	1413	12 8	7	6 0
$Constant_{14}$		Ta_2	Ra_5	Op_2	Rt_5	v	$0Fh_7$

Op_2		Operation
0	CSRR	Only read the CSR, no update takes place, Ra should be R0.
1	CSRW	Write to CSR
2	CSRS	Set CSR bits
3	CSRC	Clear CSR bits

CSRS and CSRC operations are only valid on registers that support the capability.

The $Regno_{[15..12]}$ field is reserved to specify the operating mode. Note that registers cannot be accessed by a lower operating mode.

Execution Units: Integer, the instruction may be available on only a single execution unit (not supported on all available integer units).

Clock Cycles: 1

Exceptions: privilege violation attempting to access registers outside of those allowed for the operating mode.

PEEK – Peek at Queue / Stack

Description:

This instruction returns the top value into Rt from the hardware queue specified in Ra. The hardware queue position is <u>not</u> advanced. Unused value bits should read as zero. Used the STAT instruction to get the queue status.

Instruction Format: PEEKQ

31 26	25 20	19 14	13 8	7 0
$0Ah_6$	0_6	Ra_6	Rt_6	$44h_8$

Instruction Format: PEEKQI

31 26	25 20	19 14	13 8	7 0
$0Eh_6$	0_6	Qno_6	Rt_6	$44h_8$

Instruction Format: PEEKQ

Exceptions: none

PFI – Poll for Interrupt

Description:

The poll for interrupt instruction polls the interrupt status lines and performs an interrupt service if an interrupt is present. Otherwise, the PFI instruction is treated as a NOP operation. Polling for interrupts is performed by managed code. PFI provides a means to process interrupts at specific points in running software.

Instruction Format: SYS

31 26	25 20	19 14	13 8	7	6 0
$11h_6$	0_6	0_6	0_6	v	$44h_7$

Clock Cycles: 1 (if no exception present)

Execution Units: Branch

POP – Pop from Queue / Stack

Description:

This instruction pops a value into Rt from the hardware queue specified in Ra. The hardware queue position <u>is</u> advanced. Unused value bits should read as zero. To check the queue status, use the STAT instruction.

63	0
Value	

Value: the value that was pushed to the queue

Instruction Format: POP

31 26	25 20	19 14	13 8	7 0
$09h_6$	0_6	Ra_6	Rt_6	$44h_8$

Instruction Format: POPI

31 26	25 20	19 14	13 8	7 0
$0Dh_6$	0_6	Qno_6	Rt_6	$44h_8$

Exceptions: none

Notes:

Queue #15 is the instruction trace que

Page | 119

PUSH – Push on Queue / Stack

Description:

This instruction pushes an N-bit value in Ra onto the hardware queue specified in Rb. Where N is implementation defined between 1 and 64 bits. To check the queue status, use the STATQ instruction.

Instruction Format: PUSH

31 26	25 20	19 14	13 8	7 0
$08h_6$	Rb_6	Ra_6	0_6	$44h_8$

Instruction Format: PUSHI

31 26	25 20	19 14	13 8	7 0
$0Ch_6$	Qno_6	Ra_6	0_6	$44h_8$

Instruction Format: PUSHQ

Exceptions: none

REX – Redirect Exception

Description:

This instruction redirects an exception from an operating mode to a lower operating mode. This instruction if successful jumps to the target exception handler and does not return. If this instruction fails execution will continue with the next instruction.

This instruction may fail if exceptions are not enabled at the target level.

The location of the target exception handler is found in the trap vector register for that operating mode (tvec[xx]).

The cause (cause) and bad address (badaddr) registers of the originating mode are copied to the corresponding registers in the target mode.

Instruction Format: REX

59	58 56	55 48	47 44	4341	40	39 32	31 24	23 16	15 8	7 0
~	Rm_3	$7Ah_8$	Tm_3	m_3	z	Rc_8	Imm_8	Ra_8	0_8	$44h_8$

Tm_3	
0	redirect to user mode
1	redirect to supervisor mode
2	redirect to hypervisor mode
3	redirect to machine mode
4 to 7	not used

Clock Cycles: 4

Execution Units: Branch

Example:

```
REX 1           ; redirect to supervisor handler

; If the redirection failed, exceptions were likely disabled at the target level.

; Continue processing so the target level may complete its operation.

RTE             ; redirection failed (exceptions disabled ?)
```

Notes:

Since all exceptions are initially handled in debug mode the debug handler must check for disabled lower mode exceptions.

RTE – Return from Exception

Description:

Restore the previous interrupt enable setting and operating level and transfer program execution back to the address in the exception address register (EIP). One of sixty-four semaphore registers specified by the Rb field of the instruction may also be cleared. Semaphore register zero is always cleared by this instruction.

This instruction may be encoded to return a short distance past the exception address point. This may be useful to return to the next instruction or return to a point past inline parameters. The Ra field specifies a return offset in terms of instruction words.

There is really only a single instruction to return from any mode for an exception. Although there are several additional mnemonics.

Instruction Format: SYS

31 26	25 20	19 14	13 8	7 0
$13h_6$	Rb_6	Ra_6	Opt_6	$44h_8$

Opt6[0]: 0 = Ra is reg spec, 1 = Ra is six-bit unsigned immediate
Opt6[1]: 0 = Rb is reg spec, 1 = Rb is six-bit unsigned immediate

Flags Affected: none

Operation:

PMSTACK = PMSTACK >> 4
Semaphore[0] = 0
Semaphore[Rb] = 0
IP = EIP + Ra

Execution Units: Branch

Clock Cycles:

Exceptions: none

Notes:

STAT – Get Status of Queue / Stack

Description:

This instruction returns a queue status value into Rt from the hardware queue specified in Ra. The hardware queue position is not advanced. Unused value bits should read as zero.

63	62	61 54	53 48	47 0	9 0
Qe	Dv	~	~	~	Data Count

Fields

Qe: empty.If set, this bit indicates that the queue/stack is empty.

Dv: data valid. If this bit is set it indicates that valid data is present at the queue.

Dc: data count: The number of items left in the queue

Instruction Format: POP

31 26	25 20	19 14	13 8	7 0
$0Bh_6$	0_6	Ra_6	Rt_6	$44h_8$

Instruction Format: POPI

31 26	25 20	19 14	13 8	7 0
$0Fh_6$	0_6	Qno_6	Rt_6	$44h_8$

Exceptions: none

SYNC -Synchronize

Description:

All instructions for a particular unit before the SYNC are completed and committed to the architectural state before instructions of the unit type after the SYNC are issued. This instruction is used to ensure that the machine state is valid before subsequent instructions are executed.

Instruction Format:

63 61	60 58	57 50	49 48	47 44	43 41	40	39 32	31 24	23 16	15 8	7 0
$\sim_3$	Op_3	$??h_8$	U_2	Sz_4	m_3	z	Rc_8	Rb_8	Ra_8	Rt_8	$44h_8$

TLBRW – Read / Write TLB

Description:

This instruction both reads and writes the TLB. Which translation entry to update comes from the value in Ra. The update value comes from the value in Rb. Rb contains the virtual page number, ASID, and physical page number. The current value of the entry selected by Ra is copied to Rt. The TLB will be written only if bit 63 of Ra is set.

The entry number for Ra comes from virtual address bits 14 to 23.

Page numbers are in terms of a 16kB page size.

Instruction Format: SYS

31 26	25 20	19 14	13 8	7 0
$1Eh_6$	Rb_6	Ra_6	Rt_6	$44h_8$

Clock Cycles: 5

Execution Units: Memory

Ra Value Format

63	62	12	11 10	9 0
w	~		way	entry no

Rb/Rt Value Format

63 56	55	54	53	52 48	47 32	31 20	19 0
ASID	G	D	A	UCRWX	VPN	~	PPN

Bits		Meaning	
0 to 19	PPN	Physical page number	
20 to 31	~	reserved (expansion of physical page number)	
32 to 49	VPN	Virtual page number high address order bits 24 to 39	
48	X	1 = page is executable	These three combined indicate page present (P) 0 = not present
49	W	1 = page is writeable	
50	R	1 = page is readable	
51	C	1 = page is cachable	
52	U	reserved for system usage	
53	A	Accessed, set if translation was used	
54	D	Dirty, set if a write occurred to the page	
55	G	Global, global translation indicator	
56 to 63	ASID	ASID address space identifier	

Exceptions: none

WFI – Wait for Interrupt

Description:

The WFI instruction waits for an external interrupt to occur before proceeding. While waiting for the interrupt, the processor clock is stopped placing the processor in a lower power mode.

Instruction Format: SYS

31 26	25 20	19 14	13 8	7 0
$12h_6$	0_6	0_6	0_6	$44h_8$

Clock Cycles: 1 (if no exception present)

Execution Units: Branch

Vector Specific Instructions

MFILL –Mask Fill

Description

Fill vector mask register with bits.

The first Ra bits of the vector mask register (Vmt) are set to one. The remaining bits of the mask register are set to zero.

Instruction Format: R1

31 26	25 20	19 14	13 11	10 8	7 0
$0Ch_6$	$\sim_6$	Ra_6	0_3	Vmt_3	$80h_8$

Operation

Vmt = 0

for x = 0 to VLMAX

        if (x < Ra) Vmt[x] = 1

Execution Units: ALUs

MFIRST – Find First Set Bit

Description

The position of the first bit set in the mask register is copied to the target register. If no bits are set the value is 128. The search begins at the least significant bit and proceeds to the most significant bit.

Instruction Format: R1

31 26	25 20	19 17	16 14	13 8	7 0
$0Eh_6$	$\sim_6$	0_3	Vm_3	Rt_6	$80h_8$

Operation

Rt = first set bit number of (Vm)

Exceptions: none

Execution Units: ALUs

MFM – Move from Mask

Description

Move a mask register to a general-purpose register.

Instruction Format: R1

31 26	25 20	19 17	16 14	13 8	7 0
$11h_6$	$\sim_6$	0_3	Vm_3	Rt_6	$80h_8$

Operation

Vmt = Ra

Execution Units: ALUs

MFVL – Move from Vector Length

Description

Move vector length register to a general-purpose register.

Instruction Format: R1

31 26	25 20	19 17	16 14	13 8	7 0
$13h_6$	$\sim_6$	0_3	0_3	Rt_6	$80h_8$

Operation

Vmt = Ra

Execution Units: ALUs

MLAST – Find Last Set Bit

Description

The position of the last bit set in the mask register is copied to the target register. If no bits are set the value is 128. The search begins at the most significant bit of the mask register and proceeds to the least significant bit.

Instruction Format: R1

31 26	25 20	19 17	16 14	13 8	7 0
$0Fh_6$	$\sim_6$	0_3	Vm_3	Rt_6	$80h_8$

Operation

Rt = last set bit number of (Vm)

Exceptions: none

Execution Units: ALUs

MTM – Move to Mask

Description

Move a general-purpose register to a mask register.

Instruction Format: R1

31 26	25 20	19 14	13 11	10 8	7 0
$10h_6$	$\sim_6$	Ra_6	0_3	Vmt_3	$80h_8$

Operation

Vmt = Ra

Execution Units: ALUs

MTVL – Move to Vector Length

Description

Move a general-purpose register to the vector length register.

Instruction Format: R1

31 26	25 20	19 14	13 11	10 8	7 0
$12h_6$	$\sim_6$	Ra_6	0_3	0_3	$80h_8$

Operation

Vmt = Ra

Execution Units: ALUs

Arithmetic / Logical

V2BITS

Description

Convert Boolean vector to bits. The least significant bit of each vector element is copied to the corresponding bit in the target register. The target register is a scalar register.

Instruction Format: R1

39 32	31 28	27 25	24	23 22	21 16	15 14	13 8	7 0
$18h_8$	$\sim_4$	m_3	z	1_2	Va_6	0_2	Rt_6	$81h_8$

Operation

For x = 0 to VL-1

    if (Vm[x])

        Rt[x] = Va[x].LSB

    else if (z)

        Rt[x] = 0

Exceptions: none

VBITS2V

Description

Convert bits to Boolean vector. Bits from a general register are copied to the corresponding vector target register.

Instruction Format: R1

31 26	2524	23 21	20	19 14	13 8	7 0
$19h_6$	$\sim_2$	m_3	z	Ra_6	Vt_6	$81h_8$

Operation

For x = 0 to VL-1

if (Vm[x]) Vt[x] = Ra[x]

Exceptions: none

VCIDX – Compress Index

Description

A value in a register Ra is multiplied by the element number and copied to elements of vector register Vt guided by a vector mask register.

Instruction Format: R1

31 26	2524	23 21	20	19 14	13 8	7 0
$2Dh_6$	$\sim_2$	m_3	z	Ra_6	Vt_6	$81h_8$

Operation

$y = 0$

for x = 0 to VL - 1

if (Vm[x])

Vt[y] = Ra * x

y = y + 1

VCMPRSS – Compress Vector

Description

Selected elements from vector register Va are copied to elements of vector register Vt guided by a vector mask register.

Instruction Format: R1

31 26	25 24	23 21	20	19 14	13 8	7 0
$2Ch_6$	$\sim_2$	m_3	z	Va_6	Vt_6	$81h_8$

Operation

$y = 0$

for $x = 0$ to VL - 1

    if $(Vm[x])$

        $Vt[y] = Va[x]$

        $y = y + 1$

VEINS / VMOVSV – Vector Element Insert

Synopsis

Vector element insert.

Description

A general-purpose register Rb is transferred into one element of a vector register Vt. The element to insert is identified by Ra.

Operation

Vt[Ra] = Rb

Exceptions: none

VEX / VMOVS – Vector Element Extract

Synopsis

Vector element extract.

Description

A vector register element from Vb is transferred into a general-purpose register Rt. The element to extract is identified by Ra.

Operation

Rt = Vb[Ra]

Exceptions: none

VSCAN

Synopsis

.

Description

Elements of Vt are set to the cumulative sum of a value in register Ra. The summation is guided by a vector mask register.

Operation

sum = 0

for x = 0 to VL - 1

Vt[x] = sum

if (Vm[x])

sum = sum + Ra

VSLLV – Shift Vector Left Logical

Description

Elements of the vector are transferred upwards to the next element position. The first is loaded with the value zero. This is also called a slide operation.

Operation

For x = VL-1 to Amt

Vt[x] = Va[x-amt]

For x = Amt-1 to 0

Vt[x] = 0

Exceptions: none

VSRLV – Shift Vector Right Logical

Description

Elements of the vector are transferred downwards to the next element position. The last is loaded with the value zero. This is also called a slide operation.

Operation

For x = 0 to VL-Amt

Vt[x] = Va[x+amt]

For x = VL-Amt +1 to VL-1

Vt[x] = 0

Exceptions: none

Memory Operations

CVLDx – Compressed Vector Load

Description:

Formats Supported:

Stridden Form (CVLDSx)

31	21	20	19 14	1312	11 9	8	7	0
$Const_{11}$		I	Rc_6	A	m_3	z	$5Ch_8$	

31 28	27 20	19 14	13 8	7 0
$Func_{3..0}$	$Const_8$	Ra_6	Vt_6	$E6h_8$

Data is loaded from memory addresses separated by the stride amount specified by register field Rc, beginning with the sum of Ra and an immediate value. Rc may specify either a register or a six-bit unsigned constant. If the vector mask bit is clear and the 'z' bit is set in the instruction then the corresponding element of the vector register is loaded with zero. If the vector mask bit is clear and the 'z' bit is clear in the instruction then the corresponding element of the vector register is left unchanged (no value is loaded from memory).

Elements are loaded only up to the length specified in the vector length register.

Operation:

$y = 0$
for $x = 0$ to vector length
      if Rb is a constant
          stride = Rb
      else
          stride = [Rb]
      n = stride * y
      if (Vm[x])
          Vt[y] = Memory[d+Ra + n]
          y = y + 1
for $y = y$ to vector length

      Vt[y] = z ? 0 : Vt[y]

$n = 0$

Vm[x]	z	Result
0	0	Vt[x] = Vt[x] (unchanged)
0	1	Vt[x] = 0 (set to zero)
1	0	Vt[x] = memory, sign extended
1	1	Vt[x] = memory, zero extended

Indexed Form (CVLDxVX)

31	21	20	19	14	1312	11	9	8	7	0
$Const_{11}$		0	Vc_6		A	m_3		z	DCh_8	

31	28	27	20	19	14	13	8	7	0
$Func_{3..0}$		$Const_8$		Ra_6		Vt_6		$E7h_8$	

Data is loaded from memory addresses beginning with the sum of Ra and a vector element from Vc.

Operation:

$y = 0$
for x = 0 to vector length
      if (Vm[x])
            Vt[y] = Memory[d+Ra + Vc[x]]
            y = y + 1
for y = y to vector length

      Vt[y] = z ? 0 : Vt[y]

Exceptions: none

CVSTx – Compressed Vector Store

Description:

Formats Supported:

Stridden Form (CVSTSx)

31	21	20	19	14	13	12	11	9	8	7	0
$Const_{11}$		I	Rc_6		A		m_3		z	$5Ch_8$	

31	28	27	26	25	20	19	14	13	8	7	0
$Func_{3..0}$		C_2		Vb_6		Ra_6		$Cnst_6$		$F6h_8$	

Data is stored to memory at addresses beginning with the sum of Ra and a vector element from Vb. The store location is adjusted by a stride amount contained in Rc or a six-bit unsigned immediate.

Operation:

$y = 0$
for $x = 0$ to vector length
    $n = Rc * y$
    if $(Vm[x])$
        $Memory[d+Ra + n] = Vs[x]$
        if (z) $Vs[x] = 0$
        $y = y + 1$

Indexed Form (CVSTxVX)

31	21	20	19	14	13	12	11	9	8	7	0
$Const_{11}$		0	Vc_6		A		m_3		z	DCh_8	

31	28	27	26	25	20	19	14	13	8	7	0
$Func_{3..0}$		C_2		Vb_6		Ra_6		$Cnst_6$		$F7h_8$	

Data is stored to memory addresses beginning with the sum of Ra and a vector element from Vb.

Operation:

$y = 0$
for $x = 0$ to vector length
    if $(Vm[x])$
        $Memory[d+Ra + Vb[y]] = Vs[x]$
        if (z) $Vs[x] = 0$

$$y = y + 1$$

Exceptions: none

Root Opcode Map

	000	001	010	011	100	101	110	111
ALU								
00000	BRK	{R1}	{R2}	{R3/R4}	ADD	SUBF	MUL	{SYS}
00001	AND	OR	XOR			{SET}	MULU	CSR
00010	DIV	DIVU	DIVSU			MULF	MULSU	PERM
00011	REM	REMU	BYTNDX	WYDNDX	{BTFLD}			
00100	REMSU	DIVR	CHK	U21NDX	SAND	SOR	SEQ	SNE
00101	SLT	SGT	SLTU	SGTU				
00110	{DF1}	{DF2}	{DF3}	{DF4}	{F1}	{F2}	{F3}	{F4}
00111	{PST1}	{PST2}	{PST3}	{PST4}			{VM}	NOP
Branch Unit								
01000	FBLT	FBGE	DFBLT	DFBGE			FBEQ	FBNE
01001	BLT	BGE	BLTU	BGEU		BBS	BEQ	BNE
Instruction Modifiers (Prefixes)								
01010	EXI	EXI	EXI					
01011	IMOD	BTFLD	BRMOD		STRIDE			
Memory Unit								
01100	LDx	LDxX			LDxZ	LDxXZ		
01101								LSM
01110	STx	STxX						
01111	JAL	BAL	JALR					
Vector ALU								
10000		{R1}	{R2}	{R3}	ADD	SUBF	MUL	
10001	AND	OR	XOR			{SET}	MULU	
10010	DIV	DIVU	DIVSU			MULF	MULSU	PERM
10011	REM	REMU	BYTNDX	WYDNDX	{BTFLD}			
10100	REMSU	DIVR	CHK	U21NDX			SEQ	SNE
10101	SLT	SGT	SLTU	SGTU				
10110	{DF1}	{DF2}	{DF3}	{DF4}	{F1}	{F2}	{F3}	{F4}
10111	{PST1}	{PST2}	{PST3}	{PST4}				NOP
11000								
11001								
11010								
11011	IMOD	BTFLD	BRMOD		STRIDE			
11100			LDSx	LDxVX			CVLDSx	CVLDxVX
11101								
11110			STSx	STxVX			CVSTSx	CVSTxVX
11111								

{R1} Integer Monadic Register Ops – Func$_{10}$

	000	001	010	011	100	101	110	111
xxxx000	CNTLZ	CNTLO	CNTPOP	COM	NOT	NEG	ABS	NABS
xxxx001	SQRT			TST	ZXB	ZXW	ZXT	
xxxx010	PTRINC	TRANSFORM			SXB	SXW	SXT	
xxxx011	V2BITS	BITS2V			VCMPRSS	VCIDX	VSCAN	
xxxx100								
xxxx101								
xxxx110								
xxxx111								

{R2} Integer Dyadic Register Ops – Func$_7$

	000	001	010	011	100	101	110	111
x000	AND	OR	XOR		ADD	SUB	MUL	
x001	NAND	NOR	XNOR			MULF	MULU	MULH
x010	DIV	DIVU	DIVSU	REM	REMU	REMSU	MULSU	PERM
x011	DIF	SLL	SLLI	WYDNDX	MULF	MULSUH	MULUH	RGF
x100	CMP	SRL	SRLI	U21NDX			SEQ	SNE
x101	MIN	MAX			SLT	SGE	SLTU	SGEU
x110	BMM.or	BMM.xor	BMM	BMM				
x111	VSLLV	VSLRV	VEX	VEINS			RD_COEFF	WR_COEFF

{R3/R4} Triadic Register Ops

	000	001	010	011	100	101	110	111
x000					MUX			
x001								
x010	SLLP	SLLPI						
x011	PTRDIF							
x100			CHK					
x101								
x110	BLEND							FDP
x111								

{F1} Floating-Point Monadic Ops – Funct7

	000	001	010	011	100	101	110	111
x000	FMOV	FRSQRTE	FTOI	ITOF			FSIGN	FMAN
x001	FSQRT	FS2D	FS2Q	FD2Q	FSTAT		ISNAN	FINITE
x010	FTX	FCX	FEX	FDX	FRM	TRUNC	FSYNC	FRES
x011	FSIGMOID	FD2S	FQ2S	FQ2D			FCLASS	UNORD
x100	FABS	FNABS	FNEG					
x101								
x110								
x111								

{F2} Floating-Point Dyadic Ops – Funct7

	000	001	010	011	100	101	110	111
x000	SCALEB		FMIN	FMAX	FADD	FSUB		
x001	FMUL	FDIV	FREM	FNXT	FAND	FOR		
x010	FCMP	FSEQ	FSLT	FSLE	FSNE	FCMPB	FSETM	
x011	CPYSGN	SGNINV	SGNAND	SGNOR	SGNXOR	SGNXNOR	FCLASS	
x100								
x101								
x110								
x111								

{F3} Floating-Point Dyadic Ops – Funct7

	000	001	010	011	100	101	110	111
x000	FMA	FMS	FNMA	FNMS				
x001								
x010								
x011								
x100								
x101								
x110								
x111								

{VM} Vector Mask Register Ops

	000	001	010	011	100	101	110	111
x000	MAND	MOR	MXOR		MADD	SUB	MSLL	MSRL
x001	MNAND	MNOR	MXNOR		MFILL	MPOP	MFIRST	MLAST
x010	MTM	MFM	MTVL					
x011								
x100								
x101								
x110								
x111								

{OSR2} System Ops

	000	001	010	011	100	101	110	111
x000	LLAL	LLAH			LPAL	LPAH		
x001	PUSHQ	POPQ	PEEKQ	STATQ		POPQI	PEEKQI	STATQI
x010	REX	PFI	WAI	RTE	SETKEY			
x011	SETTO	GETTO	GETZL			MVSEG	TLBRW	SYNC
x100								
x101								
x110								
x111								