

CSCI 5451 Fall 2015

Week 13 Notes

Professor Ellen Gethner

November 9, 2015

NP-Completeness

- ▶ The story began in 1971 with Steve Cook's Theorem¹...

¹<http://4mhz.de/cook.html>

²Introduction to Algorithms: A Creative Approach by Udi Manber (available as a free download)

NP-Completeness

- ▶ The story began in 1971 with Steve Cook's Theorem¹...
- ▶ **Preliminaries**²

¹<http://4mhz.de/cook.html>

²Introduction to Algorithms: A Creative Approach by Udi Manber (available as a free download)

NP-Completeness

- ▶ The story began in 1971 with Steve Cook's Theorem¹...
- ▶ **Preliminaries**²
 1. Rename *algorithm* as **deterministic algorithm**.

¹<http://4mhz.de/cook.html>

²Introduction to Algorithms: A Creative Approach by Udi Manber (available as a free download)

NP-Completeness

- ▶ The story began in 1971 with Steve Cook's Theorem¹...

- ▶ **Preliminaries**²

1. Rename *algorithm* as **deterministic algorithm**.
2. In all of the algorithms we have studied so far, there was each step was clear and determined.

¹<http://4mhz.de/cook.html>

²Introduction to Algorithms: A Creative Approach by Udi Manber (available as a free download)

NP-Completeness

- ▶ The story began in 1971 with Steve Cook's Theorem¹...

- ▶ **Preliminaries**²

1. Rename *algorithm* as **deterministic algorithm**.
2. In all of the algorithms we have studied so far, there was each step was clear and determined.
3. The party is over!

¹<http://4mhz.de/cook.html>

²Introduction to Algorithms: A Creative Approach by Udi Manber (available as a free download)

NP-Completeness

- ▶ The story began in 1971 with Steve Cook's Theorem¹...

- ▶ **Preliminaries**²

1. Rename *algorithm* as **deterministic algorithm**.
2. In all of the algorithms we have studied so far, there was each step was clear and determined.
3. The party is over!
4. A **nondeterministic algorithm** has all the operations that a deterministic one has, but also has a new operation called **nd-choice**.

¹<http://4mhz.de/cook.html>

²Introduction to Algorithms: A Creative Approach by Udi Manber (available as a free download)

NP-Completeness

- ▶ The story began in 1971 with Steve Cook's Theorem¹...

- ▶ **Preliminaries**²

1. Rename *algorithm* as **deterministic algorithm**.
2. In all of the algorithms we have studied so far, there was each step was clear and determined.
3. The party is over!
4. A **nondeterministic algorithm** has all the operations that a deterministic one has, but also has a new operation called **nd-choice**.
5. Operation nd-choice is associated with a fixed number of choices such that at each choice, the algorithm follows a different computation path.

¹<http://4mhz.de/cook.html>

²Introduction to Algorithms: A Creative Approach by Udi Manber (available as a free download)

Preliminaries, continued

- Imagine that our nondeterministic algorithm has as its goal to accept or not accept a language L .

Preliminaries, continued

- ▶ Imagine that our nondeterministic algorithm has as its goal to accept or not accept a language L .
- ▶ In fact, the above point of view is simply a YES/NO question and is called a **decision problem**.

Preliminaries, continued

- ▶ Imagine that our nondeterministic algorithm has as its goal to accept or not accept a language L .
- ▶ In fact, the above point of view is simply a YES/NO question and is called a **decision problem**.
- ▶ Perhaps not surprisingly, *any* algorithm can be viewed as a decision problem (more later).

Preliminaries, continued

- ▶ Imagine that our nondeterministic algorithm has as its goal to accept or not accept a language L .
- ▶ In fact, the above point of view is simply a YES/NO question and is called a **decision problem**.
- ▶ Perhaps not surprisingly, *any* algorithm can be viewed as a decision problem (more later).
- ▶ **Visualization.** Imagine the process of running the nondeterministic algorithm as taking place on a directed graph:

Preliminaries, continued

- ▶ Imagine that our nondeterministic algorithm has as its goal to accept or not accept a language L .
- ▶ In fact, the above point of view is simply a YES/NO question and is called a **decision problem**.
- ▶ Perhaps not surprisingly, *any* algorithm can be viewed as a decision problem (more later).
- ▶ **Visualization.** Imagine the process of running the nondeterministic algorithm as taking place on a directed graph:
 - ▶ you walk from vertex to vertex along directed edges;

Preliminaries, continued

- ▶ Imagine that our nondeterministic algorithm has as its goal to accept or not accept a language L .
- ▶ In fact, the above point of view is simply a YES/NO question and is called a **decision problem**.
- ▶ Perhaps not surprisingly, *any* algorithm can be viewed as a decision problem (more later).
- ▶ **Visualization.** Imagine the process of running the nondeterministic algorithm as taking place on a directed graph:
 - ▶ you walk from vertex to vertex along directed edges;
 - ▶ at some vertices, namely the nd-choice ones, you will have to decide which way to go.

Recognizing a language

- ▶ The idea of walking around on a directed graph is this: as you travel, you are on a computation path.

Recognizing a language

- ▶ The idea of walking around on a directed graph is this: as you travel, you are on a computation path.
- ▶ **Definition.** We say that a nondeterministic algorithm recognizes language L if the following condition is satisfied.

Recognizing a language

- ▶ The idea of walking around on a directed graph is this: as you travel, you are on a computation path.
- ▶ **Definition.** We say that a nondeterministic algorithm recognizes language L if the following condition is satisfied.
 - ▶ Given an input x , it is possible to convert each nd-choice encountered during the execution of the algorithm to a real choice so that

Recognizing a language

- ▶ The idea of walking around on a directed graph is this: as you travel, you are on a computation path.
- ▶ **Definition.** We say that a nondeterministic algorithm recognizes language L if the following condition is satisfied.
 - ▶ Given an input x , it is possible to convert each nd-choice encountered during the execution of the algorithm to a real choice so that
 - ▶ the outcome of the algorithm will be to accept x if and only if $x \in L$.

About Decision Problems

- ▶ All of the problems we have worked on this semester can be converted to decision problems.

About Decision Problems

- ▶ All of the problems we have worked on this semester can be converted to decision problems.
- ▶ **Example.** Consider the division algorithm: given nonnegative integers a, b with $b \leq a$, let L be the set of all instances of pairs of non-negative integers (q, r) such that $a = bq + r$ and $0 \leq r < b$.

About Decision Problems

- ▶ All of the problems we have worked on this semester can be converted to decision problems.
- ▶ **Example.** Consider the division algorithm: given nonnegative integers a, b with $b \leq a$, let L be the set of all instances of pairs of non-negative integers (q, r) such that $a = bq + r$ and $0 \leq r < b$.
- ▶ We guess at values of q and r , and if we happen upon a correct guess, the algorithm outputs **ACCEPT**.

About Decision Problems

- ▶ All of the problems we have worked on this semester can be converted to decision problems.
- ▶ **Example.** Consider the division algorithm: given nonnegative integers a, b with $b \leq a$, let L be the set of all instances of pairs of non-negative integers (q, r) such that $a = bq + r$ and $0 \leq r < b$.
- ▶ We guess at values of q and r , and if we happen upon a correct guess, the algorithm outputs **ACCEPT**.
- ▶ Otherwise the algorithm outputs **DO NOT ACCEPT**.

Run time and new class of problems

- ▶ The run time for a given input $x \in L$ is the length of the shortest computation path that leads to **ACCEPT**.

Run time and new class of problems

- ▶ The run time for a given input $x \in L$ is the length of the shortest computation path that leads to **ACCEPT**.
- ▶ The run time for the whole nondeterministic algorithm is the worst case run time over all inputs $x \in L$ (ie, everything that leads to **ACCEPT**).

Run time and new class of problems

- ▶ The run time for a given input $x \in L$ is the length of the shortest computation path that leads to **ACCEPT**.
- ▶ The run time for the whole nondeterministic algorithm is the worst case run time over all inputs $x \in L$ (ie, everything that leads to **ACCEPT**).
- ▶ **Definition.** The class of problems for which there exists a nondeterministic algorithm whose run time is polynomial in the size of the input is called **NP**.

Intuition???

- ▶ One would think that the nondeterministic polynomial-time algorithms are more powerful than the deterministic polynomial-time algorithms.

Intuition???

- ▶ One would think that the nondeterministic polynomial-time algorithms are more powerful than the deterministic polynomial-time algorithms.
- ▶ Right?

Intuition???

- ▶ One would think that the nondeterministic polynomial-time algorithms are more powerful than the deterministic polynomial-time algorithms.
- ▶ Right?
- ▶ For example, if we let P be the set of deterministic polynomial-time algorithms, then clearly $P \subset NP$ (why?).

Intuition???


- ▶ One would think that the nondeterministic polynomial-time algorithms are more powerful than the deterministic polynomial-time algorithms.
- ▶ Right?
- ▶ For example, if we let P be the set of deterministic polynomial-time algorithms, then clearly $P \subset NP$ (why?).
- ▶ **Challenge.** Is $P = NP$?

Intuition???

- ▶ One would think that the nondeterministic polynomial-time algorithms are more powerful than the deterministic polynomial-time algorithms.
- ▶ Right?
- ▶ For example, if we let P be the set of deterministic polynomial-time algorithms, then clearly $P \subset NP$ (why?).
- ▶ **Challenge.** Is $P = NP$?
- ▶ Nobody knows!


Skip the final? Get a PhD? Get an A?

- ▶ If you show either that $P = NP$ or $P \neq NP$ then you win the following prizes: {A, PhD, skip the final, \$1,000,000 from the Clay Institute³}.

³<http://www.claymath.org/millennium-problems> 

Skip the final? Get a PhD? Get an A?

- ▶ If you show either that $P = NP$ or $P \neq NP$ then you win the following prizes: {A, PhD, skip the final, \$1,000,000 from the Clay Institute³}.
- ▶ **More Explanation.** A problem X is called **NP hard** if every problem in the set NP is polynomially reducible to x .

³<http://www.claymath.org/millennium-problems> 


Skip the final? Get a PhD? Get an A?

- ▶ If you show either that $P = NP$ or $P \neq NP$ then you win the following prizes: {A, PhD, skip the final, \$1,000,000 from the Clay Institute³}.
- ▶ **More Explanation.** A problem X is called **NP hard** if every problem in the set NP is polynomially reducible to x .
- ▶ A problem X is called **NP complete** if $X \in NP$ and X is NP hard.

³<http://www.claymath.org/millennium-problems>


Skip the final? Get a PhD? Get an A?

- ▶ If you show either that $P = NP$ or $P \neq NP$ then you win the following prizes: {A, PhD, skip the final, \$1,000,000 from the Clay Institute³}.
- ▶ **More Explanation.** A problem X is called **NP hard** if every problem in the set NP is polynomially reducible to x .
- ▶ A problem X is called **NP complete** if $X \in NP$ and X is NP hard.
- ▶ **Giant Implication:** if any single problem in P is proved to be in NP, then $P=NP$!!!

³<http://www.claymath.org/millennium-problems> 

Skip the final? Get a PhD? Get an A?

- ▶ If you show either that $P = NP$ or $P \neq NP$ then you win the following prizes: {A, PhD, skip the final, \$1,000,000 from the Clay Institute³}.
- ▶ **More Explanation.** A problem X is called **NP hard** if every problem in the set NP is polynomially reducible to x .
- ▶ A problem X is called **NP complete** if $X \in NP$ and X is NP hard.
- ▶ **Giant Implication:** if any single problem in P is proved to be in NP, then $P=NP$!!!
- ▶ **Moral of the story.** Researchers continue collecting NP complete and NP hard problems. The list continues to grow...

³<http://www.claymath.org/millennium-problems> 

Flashback to 1971 and an example

- ▶ Remember Steve Cook and that he started the show with nondeterministic algorithms?

Flashback to 1971 and an example

- ▶ Remember Steve Cook and that he started the show with nondeterministic algorithms?
- ▶ His theory would have no substance if there were no NP complete problems;

Flashback to 1971 and an example

- ▶ Remember Steve Cook and that he started the show with nondeterministic algorithms?
- ▶ His theory would have no substance if there were no NP complete problems;
- ▶ his great breakthrough came in 1971 when he proved that the **Satisfiability Problem** (or SAT for short) was NP complete and that was the first such problem so proved.

Description of SAT

- ▶ Let S be a boolean expression in **conjunctive normal form** (CNF).

Description of SAT

- ▶ Let S be a boolean expression in **conjunctive normal form** (CNF).
- ▶ That is, S is the product (AND) of several sums (OR).

Description of SAT

- ▶ Let S be a boolean expression in **conjunctive normal form** (CNF).
- ▶ That is, S is the product (AND) of several sums (OR).
- ▶ **Example.** Let $S = (x + y + \bar{z})(\bar{x} + y + z)(\bar{x} + \bar{y} + \bar{z})$,

Description of SAT

- ▶ Let S be a boolean expression in **conjunctive normal form** (CNF).
- ▶ That is, S is the product (AND) of several sums (OR).
- ▶ **Example.** Let $S = (x + y + \bar{z})(\bar{x} + y + z)(\bar{x} + \bar{y} + \bar{z})$,
- ▶ where \bar{a} means “not a ” and each expression in parentheses is called a **clause**.

Description of SAT

- ▶ Let S be a boolean expression in **conjunctive normal form** (CNF).
- ▶ That is, S is the product (AND) of several sums (OR).
- ▶ **Example.** Let $S = (x + y + \bar{z})(\bar{x} + y + z)(\bar{x} + \bar{y} + \bar{z})$,
- ▶ where \bar{a} means “not a ” and each expression in parentheses is called a **clause**.
- ▶ The values input for x , y , and z are from the alphabet $\{0, 1\}$, and we do arithmetic (mod 2).

Description of SAT

- ▶ Let S be a boolean expression in **conjunctive normal form** (CNF).
- ▶ That is, S is the product (AND) of several sums (OR).
- ▶ **Example.** Let $S = (x + y + \bar{z})(\bar{x} + y + z)(\bar{x} + \bar{y} + \bar{z})$,
- ▶ where \bar{a} means “not a ” and each expression in parentheses is called a **clause**.
- ▶ The values input for x, y , and z are from the alphabet $\{0, 1\}$, and we do arithmetic (mod 2).
- ▶ That is, we do arithmetic (mod 2) to determine the value of S , which is, a priori, 0 or 1.

Description of SAT, continued

- ▶ A boolean expression S is said to be **satisfiable** if there is some assignment of 0s and 1s to the variables such that the value of S , upon those inputs, is 1.

Description of SAT, continued

- ▶ A boolean expression S is said to be **satisfiable** if there is some assignment of 0s and 1s to the variables such that the value of S , upon those inputs, is 1.
- ▶ **The SAT Problem.** Given a CNF expression S , determine whether or not S is satisfiable (without necessarily finding the satisfying assignment).

Description of SAT, continued

- ▶ A boolean expression S is said to be **satisfiable** if there is some assignment of 0s and 1s to the variables such that the value of S , upon those inputs, is 1.
- ▶ **The SAT Problem.** Given a CNF expression S , determine whether or not S is satisfiable (without necessarily finding the satisfying assignment).
- ▶ The SAT problem is clearly a decision problem!

Description of SAT, continued

- ▶ A boolean expression S is said to be **satisfiable** if there is some assignment of 0s and 1s to the variables such that the value of S , upon those inputs, is 1.
- ▶ **The SAT Problem.** Given a CNF expression S , determine whether or not S is satisfiable (without necessarily finding the satisfying assignment).
- ▶ The SAT problem is clearly a decision problem!
- ▶ **Example, continued.** The example $S = (x + y + \bar{z})(\bar{x} + y + z)(\bar{x} + \bar{y} + \bar{z})$ is satisfied by $x = 1$, $y = 1$, and $z = 0$ because

Description of SAT, continued

- ▶ A boolean expression S is said to be **satisfiable** if there is some assignment of 0s and 1s to the variables such that the value of S , upon those inputs, is 1.
- ▶ **The SAT Problem.** Given a CNF expression S , determine whether or not S is satisfiable (without necessarily finding the satisfying assignment).
- ▶ The SAT problem is clearly a decision problem!
- ▶ **Example, continued.** The example $S = (x + y + \bar{z})(\bar{x} + y + z)(\bar{x} + \bar{y} + \bar{z})$ is satisfied by $x = 1$, $y = 1$, and $z = 0$ because
- ▶ $(1 + 1 + \bar{0})(\bar{1} + 1 + 0)(\bar{1} + \bar{1} + \bar{0}) = 1 \times 1 \times 1 = 1.$

Overview and Summary

- ▶ In 1972, Richard Karp proved that 21 important problems⁴ were NP complete and the list continues to grow.

⁴https://en.wikipedia.org/wiki/Karp's_21_NP-complete_problems#

References

⁵<https://www.wolframscience.com/prizes/tm23/turingmachine.html>

Overview and Summary

- ▶ In 1972, Richard Karp proved that 21 important problems⁴ were NP complete and the list continues to grow.
- ▶ The idea of the proof that SAT is NP complete is, briefly, that

⁴https://en.wikipedia.org/wiki/Karp's_21_NP-complete_problems#

References

⁵<https://www.wolframscience.com/prizes/tm23/turingmachine.html>

Overview and Summary

- ▶ In 1972, Richard Karp proved that 21 important problems⁴ were NP complete and the list continues to grow.
- ▶ The idea of the proof that SAT is NP complete is, briefly, that
 1. we can guess at a truth assignment and check in polynomial time to see if the outcome of S is 1; if so, then $\text{SAT} \in \text{NP}$.

⁴https://en.wikipedia.org/wiki/Karp's_21_NP-complete_problems#

References

⁵<https://www.wolframscience.com/prizes/tm23/turingmachine.html>

Overview and Summary

- ▶ In 1972, Richard Karp proved that 21 important problems⁴ were NP complete and the list continues to grow.
- ▶ The idea of the proof that SAT is NP complete is, briefly, that
 1. we can guess at a truth assignment and check in polynomial time to see if the outcome of S is 1; if so, then $\text{SAT} \in \text{NP}$.
 2. Then it remains to show that SAT is NP hard, the proof of which is nontrivial and uses the idea of a **Turing Machine**⁵.

⁴https://en.wikipedia.org/wiki/Karp's_21_NP-complete_problems#

⁵<https://www.wolframscience.com/prizes/tm23/turingmachine.html>

Another example of an NP complete problem

- **Problem:** Given an undirected simple graph G , determine whether or not G can be properly vertex colored with three colors.

Another example of an NP complete problem

- ▶ **Problem:** Given an undirected simple graph G , determine whether or not G can be properly vertex colored with three colors.
- ▶ **Tool.** 3SAT is NP complete (3SAT is a CNF expression in which all clauses have exactly three variables).

Another example of an NP complete problem

- ▶ **Problem:** Given an undirected simple graph G , determine whether or not G can be properly vertex colored with three colors.
- ▶ **Tool.** 3SAT is NP complete (3SAT is a CNF expression in which all clauses have exactly three variables).

Another example of an NP complete problem


- ▶ **Problem:** Given an undirected simple graph G , determine whether or not G can be properly vertex colored with three colors.
- ▶ **Tool.** 3SAT is NP complete (3SAT is a CNF expression in which all clauses have exactly three variables).
- ▶ **Theorem.** Graph 3-colorability is NP complete.

Another example of an NP complete problem

- ▶ **Problem:** Given an undirected simple graph G , determine whether or not G can be properly vertex colored with three colors.
- ▶ **Tool.** 3SAT is NP complete (3SAT is a CNF expression in which all clauses have exactly three variables).
- ▶ **Theorem.** Graph 3-colorability is NP complete.
- ▶ **Idea of Proof.** We will reduce the 3SAT problem to the 3-colorability problem, but first note that if we guess at a 3-coloring of a graph G we can check its validity in $O(E) = O(V^2)$ -time. Why?


Reduction to 3SAT

- From a CNF expression, we construct a graph as follows. The three colors are T , F , and A .



Reduction to 3SAT


- ▶ From a CNF expression, we construct a graph as follows. The three colors are T , F , and A .



- ▶ In general, for a CNF expression S that has k variables, there will be $k + 1$ triangles at this stage.


Attach a widget to each clause

- ▶ Next, attach the following widget to each clause $U + V + W$ in expression S .



Attach a widget to each clause


- ▶ Next, attach the following widget to each clause $U + V + W$ in expression S .



- ▶ **Facts.** The widget graph above is locally 3-colorable and forces one of u , v , or w to be assigned T .


Attach a widget to each clause

- ▶ Next, attach the following widget to each clause $U + V + W$ in expression S .




- ▶ **Facts.** The widget graph above is locally 3-colorable and forces one of u , v , or w to be assigned T .
- ▶ The above fact is important since otherwise S would never be satisfiable.

Widgets and 3-colorability, continued




Widgets and 3-colorability, continued




- ▶ Each of x , \bar{x} , y , \bar{y} , z , and \bar{z} will never be colored A because all are adjacent to a vertex colored A .

Widgets and 3-colorability, continued




Widgets and 3-colorability, continued




- ▶ Thus if x is colored T then \bar{x} must be colored F (since there is always an edge between every pair of variables u and \bar{u}).

Widgets and 3-colorability, continued




- ▶ Thus if x is colored T then \bar{x} must be colored F (since there is always an edge between every pair of variables u and \bar{u}).
- ▶ **Conclusion.** We have constructed an infinite family of 3-colorable graphs whose coloring reduces to a known NP-complete problem.

Widgets and 3-colorability, continued



- ▶ Thus if x is colored T then \bar{x} must be colored F (since there is always an edge between every pair of variables u and \bar{u}).
- ▶ **Conclusion.** We have constructed an infinite family of 3-colorable graphs whose coloring reduces to a known NP-complete problem.
- ▶ That is, vertex 3-colorability is NP-complete.

Widgets and 3-colorability, continued



- ▶ Thus if x is colored T then \bar{x} must be colored F (since there is always an edge between every pair of variables u and \bar{u}).
- ▶ **Conclusion.** We have constructed an infinite family of 3-colorable graphs whose coloring reduces to a known NP-complete problem.
- ▶ That is, vertex 3-colorability is NP-complete.
- ▶ **Exercise.** Create the entire graph associated with the example $S = (x + y + \bar{z})(\bar{x} + y + z)(\bar{x} + \bar{y} + \bar{z})$.

The Art Gallery Problem




Figure: example caption