REPORT- BEPU Building Utility Performance

WEATHER FILE- SEATTLE BOEING FI WA

	LIGHTS	TASK LIGHTS	MISC EQUIP	SPACE HEATING	SPACE COOLING	HEAT REJECT	PUMPS & AUX	VENT FANS	REFRIG DISPLAY	HT PUMP SUPPLEM	DOMEST HOT WTR	EXT USAGE	TOTAL
EM1- ELECTI KWH	RICITY 45074.	0.	631811.	117440.	47691.	0.	12185.	23421.	0.	0.	0.	0.	877617.
EM2- ELECTI KWH	RICITY 124779.	13200.	34166.	13144.	319.	0.	126934.	120308.	17441.	0.	153209.	10481.	613979.
EM3- ELECTE	9883.	0.	55183.	44433.	2817.	0.	460.	11723.	0.	0.	15291.	0.	139790.
FM1 NATURA	AL-GAS	0.	1883.	0.	0.	0.	0.	0.	0.	0.	0.	0.	1883.
	TOTAL ELECT	RICITY	1631386.	KMH	9.513	kwh /	SOFT-VR (ROSS-AREA	9.513	KWH	/SOFT-YR	NET-AREA	
			1883.		0.011		/SQFT-YR GROSS-AREA				/SQFT-YR NET-AREA		

PERCENT OF HOURS ANY SYSTEM ZONE OUTSIDE OF THROTTLING RANGE = 2.10 PERCENT OF HOURS ANY PLANT LOAD NOT SATISFIED = 0.08
HOURS ANY ZONE ABOVE COOLING THROTTLING RANGE = 161 HOURS ANY ZONE BELOW HEATING THROTTLING RANGE = 23

NOTE: ENERGY IS APPORTIONED HOURLY TO ALL END-USE CATEGORIES.