

RFP / RFI Response — Draft

Engagement: ENG-001 Generated: 2026-05-12 20:42 UTC

Summary

Band	Count
HIGH	0
MEDIUM · SME review	20
LOW · escalated	6
NO-SOURCE · escalated	1
CONFLICT · escalated	3
Total	30

ESCALATION QUEUE

10 item(s) routed to SME. See the standalone escalation_ENG-001.md document and the per-question entries below.

Per-Question Responses

Q-001

MEDIUMREVIEW

What encryption algorithm protects data at rest in Dynamix Core Platform?

Data at rest in Dynamix Core Platform is encrypted with AES-256-GCM by default, applied to primary database storage, snapshot archives, and audit logs [spec_sheet_dynamix_core_platform.md#spec-sheet-dynamix-core-platform-chunk-000][prior_rfp_response_2025_q1.md#prior-rfp-response-2025-q1-chunk-000][prior_rfp_response_2025_q3.md#prior-rfp-response-2025-q3-chunk-001]. The 2025.x release line introduced support for customer-managed keys via HSM integration (PKCS#11 and KMIP); earlier releases supported only platform-managed keys [spec_sheet_dynamix_core_platform.md#spec-sheet-dynamix-core-platform-chunk-000]. When operating in FIPS 140-2 validated mode (enabled via the `--security-profile=fips` provisioning flag), all symmetric cryptographic operations route through the FIPS-validated module bundled with the platform installer [prior_rfp_response_2025_q1.md#prior-rfp-response-2025-q1-chunk-000].

Citations: spec_sheet_dynamix_core_platform.md#spec-sheet-dynamix-core-platform-chunk-000 (0.76) · prior_rfp_response_2025_q1.md#prior-rfp-response-2025-q1-chunk-000 (0.73) · prior_rfp_response_2025_q3.md#prior-rfp-response-2025-q3-chunk-001 (0.72)

Q-002

MEDIUM

REVIEW

Which identity-federation protocols does Core Platform support?

Dynamix Core Platform supports two identity-federation protocols for enterprise integration: **SAML 2.0** and **OIDC (OpenID Connect)** [spec_sheet_dynamix_core_platform.md#spec-sheet-dynamix-core-platform-chunk-000]. SAML 2.0 is supported on all 2024.x and 2025.x releases, while OIDC is available on 2025.x and later only [spec_sheet_dynamix_core_platform.md#spec-sheet-dynamix-core-platform-chunk-000]. Both protocols use group-to-role mapping and share the same admin-console configuration [spec_sheet_dynamix_core_platform.md#spec-sheet-dynamix-core-platform-chunk-000] [prior_rfp_response_2025_q3.md#prior-rfp-response-2025-q3-chunk-000]. Note that service-account tokens are used for integration/API authentication and are distinct from these user-facing federation protocols [partner_enablement_integration_guide.md#partner-enablement-integration-guide-chunk-000].

Citations: spec_sheet_dynamix_core_platform.md#spec-sheet-dynamix-core-platform-chunk-000 (0.75) · prior_rfp_response_2025_q3.md#prior-rfp-response-2025-q3-chunk-000 (0.67) · partner_enablement_integration_guide.md#partner-enablement-integration-guide-chunk-000 (0.73)

Q-003

MEDIUM

REVIEW

What is the default audit log retention period for Core Platform?

The default audit log retention period for Dynamix Core Platform is **365 days** [spec_sheet_dynamix_core_platform.md#spec-sheet-dynamix-core-platform-chunk-000] [prior_rfp_response_2025_q1.md#prior-rfp-response-2025-q1-chunk-000]. Retention is configurable from 90 days up to 2,555 days (seven years) to accommodate long-horizon regulatory requirements [spec_sheet_dynamix_core_platform.md#spec-sheet-dynamix-core-platform-chunk-000]. Audit log entries are append-only, immutable once written, and integrity-signed using the platform key hierarchy [spec_sheet_dynamix_core_platform.md#spec-sheet-dynamix-core-platform-chunk-000] [prior_rfp_response_2025_q1.md#prior-rfp-response-2025-q1-chunk-000].

Citations: spec_sheet_dynamix_core_platform.md#spec-sheet-dynamix-core-platform-chunk-000 (0.67) · prior_rfp_response_2025_q1.md#prior-rfp-response-2025-q1-chunk-000 (0.67)

Q-004

MEDIUM

REVIEW

What is the typical power draw of the Edge Gateway 4400 appliance?

The Dynamix Edge Gateway 4400 series has a typical power draw of **280 W** in a 1U form factor [spec_sheet_dynamix_edge_gateway.md#spec-sheet-dynamix-edge-gateway-chunk-001]. For comparison, the 2200 series draws 95 W in a 1U short-depth chassis [spec_sheet_dynamix_edge_gateway.md#spec-sheet-dynamix-edge-gateway-chunk-001].

Citations: spec_sheet_dynamix_edge_gateway.md#spec-sheet-dynamix-edge-gateway-chunk-001 (0.71)

Q-005**MEDIUM****REVIEW**

How many 10 GbE uplinks does the Edge Gateway 4400 ship with?

The Edge Gateway 4400 ships with **4 × 10 GbE uplinks** [spec_sheet_dynamix_edge_gateway.md#spec-sheet-dynamix-edge-gateway-chunk-000][prior_rfp_response_2024_q4.md#prior-rfp-response-2024-q4-chunk-000]. These uplinks support 802.1Q VLAN segmentation and LACP link aggregation [spec_sheet_dynamix_edge_gateway.md#spec-sheet-dynamix-edge-gateway-chunk-000]. For comparison, the 2200 series ships with **2 × 10 GbE uplinks** [spec_sheet_dynamix_edge_gateway.md#spec-sheet-dynamix-edge-gateway-chunk-000][prior_rfp_response_2024_q4.md#prior-rfp-response-2024-q4-chunk-000].

Citations: spec_sheet_dynamix_edge_gateway.md#spec-sheet-dynamix-edge-gateway-chunk-000 (0.73) · prior_rfp_response_2024_q4.md#prior-rfp-response-2024-q4-chunk-000 (0.74)

Q-006**MEDIUM****REVIEW**

What minimum TLS version does Core Platform require on its interfaces?

Dynamix Core Platform requires a minimum of TLS 1.2 on all platform-internal and external interfaces [spec_sheet_dynamix_core_platform.md#spec-sheet-dynamix-core-platform-chunk-000]. TLS 1.3 is supported and is the negotiated default when both peers support it [spec_sheet_dynamix_core_platform.md#spec-sheet-dynamix-core-platform-chunk-000]. The REST API integration surface also enforces TLS 1.2 as a minimum [partner_enablement_integration_guide.md#partner-enablement-integration-guide-chunk-000]. When operating in FIPS 140-2 validated mode (enabled via `--security-profile=fips`), TLS 1.2 with FIPS-approved cipher suites is the default for data in transit [prior_rfp_response_2025_q1.md#prior-rfp-response-2025-q1-chunk-000].

Citations: spec_sheet_dynamix_core_platform.md#spec-sheet-dynamix-core-platform-chunk-000 (0.70) · partner_enablement_integration_guide.md#partner-enablement-integration-guide-chunk-000 (0.65) · prior_rfp_response_2025_q1.md#prior-rfp-response-2025-q1-chunk-000 (0.63)

Q-007**MEDIUM****REVIEW**

What sustained request-rate ceiling applies to Standard-tier API tokens?

Standard-tier API tokens are subject to a sustained rate ceiling of **200 requests per second per token**, with a burst allowance of 500 requests per second for periods of 10 seconds or less [partner_enablement_integration_guide.md#partner-enablement-integration-guide-chunk-001]. When the limit is exceeded, the platform returns HTTP 429 with a `Retry-After` header indicating how long to wait before retrying [partner_enablement_integration_guide.md#partner-enablement-integration-guide-chunk-001].

Citations: partner_enablement_integration_guide.md#partner-enablement-integration-guide-chunk-001 (0.68)

Q-008

MEDIUM

REVIEW

What is the standard lead time for Edge Gateway appliance shipment?

Edge Gateway appliances (both 4400 and 2200 series) ship from stock within 5 business days of purchase order acknowledgement under standard demand [spec_sheet_dynamix_edge_gateway.md#spec-sheet-dynamix-edge-gateway-chunk-001][prior_rfp_response_2024_q4.md#prior-rfp-response-2024-q4-chunk-001]. Lead times during quarterly close periods may extend to 10 business days [spec_sheet_dynamix_edge_gateway.md#spec-sheet-dynamix-edge-gateway-chunk-001]. On-site commissioning takes approximately one engineer-day per appliance, including network integration and initial telemetry validation [prior_rfp_response_2024_q4.md#prior-rfp-response-2024-q4-chunk-001].

Citations: spec_sheet_dynamix_edge_gateway.md#spec-sheet-dynamix-edge-gateway-chunk-001 (0.66) · prior_rfp_response_2024_q4.md#prior-rfp-response-2024-q4-chunk-001 (0.81)

Q-009

MEDIUM

REVIEW

What operating temperature range is the Edge Gateway 4400 certified for?

The Dynamix Edge Gateway 4400 series is certified for an operating temperature range of **0 °C to 40 °C** [spec_sheet_dynamix_edge_gateway.md#spec-sheet-dynamix-edge-gateway-chunk-001]. Note that the 2200 series carries a slightly wider range of 0 °C to 45 °C; the 4400's narrower upper limit should be confirmed against the customer's anticipated deployment environment [spec_sheet_dynamix_edge_gateway.md#spec-sheet-dynamix-edge-gateway-chunk-001].

Citations: spec_sheet_dynamix_edge_gateway.md#spec-sheet-dynamix-edge-gateway-chunk-001 (0.70)

Q-010

MEDIUM

REVIEW

What support tiers does Dynamix offer for the platform?

Dynamix publishes three support tiers for the platform [sme_faq_internal.md#sme-faq-internal-chunk-001]: - **Standard** — business-hours email support with a 1-business-day response target. - **Premium** — 24×7 email and phone support with a 4-hour response target on production-impact issues. All Enterprise-tier subscriptions include Premium support by default. - **Mission-Critical** — 24×7 support with a 30-minute response target, a named technical account manager, and quarterly health reviews.

Citations: sme_faq_internal.md#sme-faq-internal-chunk-001 (0.69)

Q-011

MEDIUM

REVIEW

What is the published pricing model for the Core Platform?

The Core Platform is priced on a per-active-user basis, with tier discounts applied at 1,000, 5,000, and 25,000 active users [sme_faq_internal.md#sme-faq-internal-chunk-000]. Edge Gateway appliances are priced per-unit and sold separately from the Core Platform subscription [sme_faq_internal.md#sme-faq-internal-chunk-000]. A 30-day evaluation tier is available with full functionality and a 500-active-user cap, provisioned by the solutions-engineering team on request [sme_faq_internal.md#sme-faq-internal-chunk-000]. Specific list prices are not published in this document and should be routed through commercial operations [sme_faq_internal.md#sme-faq-internal-chunk-000].

Citations: sme_faq_internal.md#sme-faq-internal-chunk-000 (0.67)

Q-012

MEDIUM

REVIEW

How long does a typical single-site Core Platform deployment take?

A typical single-site Dynamix Core Platform deployment takes ****5 – 10 engineer-days**** from infrastructure-ready to validated go-live [partner_enablement_deployment_playbook.md#partner-enablement-deployment-playbook-chunk-001]. This timeline covers the full provisioning sequence: infrastructure setup, Core Platform installation, identity federation configuration, optional HSM key configuration, post-install validation, and handoff to the customer's operations team [partner_enablement_deployment_playbook.md#partner-enablement-deployment-playbook-chunk-001].

Citations: partner_enablement_deployment_playbook.md#partner-enablement-deployment-playbook-chunk-001 (0.76)

Q-013

MEDIUM

REVIEW

For a tenant with approximately 4,500 active users, what HA deployment footprint should we expect?

For a tenant with approximately 4,500 active users, the standard HA footprint is a 3-node-per-AZ deployment spanning three availability zones, totalling 9 nodes [partner_enablement_deployment_playbook.md#partner-enablement-deployment-playbook-chunk-000]. This places the tenant in the 1,000–5,000 active-user bracket for the High-Availability topology, which provides synchronous replication across AZs and ensures service continuity if a single AZ is lost [partner_enablement_deployment_playbook.md#partner-enablement-deployment-playbook-chunk-000]. The sizing table also indicates 2–6 edge gateways are typical for the 500–5,000 user range [partner_enablement_deployment_playbook.md#partner-enablement-deployment-playbook-chunk-001]. A prior engagement with a ~4,500-user healthcare payer confirmed this topology as a practical reference point [prior_rfp_response_2025_q3.md#prior-rfp-response-2025-q3-chunk-000].

Citations: partner_enablement_deployment_playbook.md#partner-enablement-deployment-playbook-chunk-000 (0.66) · partner_enablement_deployment_playbook.md#partner-enablement-deployment-playbook-chunk-001 (0.70) · prior_rfp_response_2025_q3.md#prior-rfp-response-2025-q3-chunk-000 (0.66)

Q-014**MEDIUM****REVIEW**

Does the platform support hardware security modules for customer-managed key storage?

Yes, the Dynamix Core Platform supports hardware security modules (HSMs) for customer-managed key storage. As of the 2025.x release line, the platform integrates with HSMs via the PKCS#11 and KMIP protocols, enabling customers to manage their own encryption keys

[spec_sheet_dynamix_core_platform.md#spec-sheet-dynamix-core-platform-chunk-000]. This capability was introduced in the 2025.x release; earlier releases supported only platform-managed keys

[spec_sheet_dynamix_core_platform.md#spec-sheet-dynamix-core-platform-chunk-000]. Customer-managed keys via HSM integration have also been used in a prior production engagement

[prior_rfp_response_2025_q3.md#prior-rfp-response-2025-q3-chunk-001].

Citations: spec_sheet_dynamix_core_platform.md#spec-sheet-dynamix-core-platform-chunk-000 (0.67) · prior_rfp_response_2025_q3.md#prior-rfp-response-2025-q3-chunk-001 (0.62)

Q-015**MEDIUM****REVIEW**

What runtime languages are supported by the official SDKs?

The official Dynamix Core Platform SDKs are published for Python, Java, and TypeScript

[partner_enablement_integration_guide.md#partner-enablement-integration-guide-chunk-000]. These client libraries wrap the REST surface and add idempotency-key handling, paginated iterators, and retry policy

[partner_enablement_integration_guide.md#partner-enablement-integration-guide-chunk-000].

Citations:

partner_enablement_integration_guide.md#partner-enablement-integration-guide-chunk-000 (0.62)

Q-016**MEDIUM****REVIEW**

What's the upper bound on platform-supported dataset size at the Enterprise tier?

At the Enterprise tier, the platform-supported maximum dataset size is 500 TB

[spec_sheet_dynamix_core_platform.md#spec-sheet-dynamix-core-platform-chunk-001]. For reference, the

Standard tier is capped at 50 TB [spec_sheet_dynamix_core_platform.md#spec-sheet-dynamix-core-platform-chunk-001]. These limits are documented for the 2025.x release line.

Citations: spec_sheet_dynamix_core_platform.md#spec-sheet-dynamix-core-platform-chunk-001 (0.64)

Q-017**MEDIUM****REVIEW**

Can the Core Platform be deployed on Windows Server?

Windows Server is not a supported platform for the Dynamix Core Platform. Supported platforms are Linux x86_64 (RHEL 8/9, Ubuntu 22.04 LTS) and ARM64 (RHEL 9 only)

[spec_sheet_dynamix_core_platform.md#spec-sheet-dynamix-core-platform-chunk-001]. Windows-side integration is possible via the SDK, and partner-enablement guidance covers that approach

[spec_sheet_dynamix_core_platform.md#spec-sheet-dynamix-core-platform-chunk-001].

Citations: spec_sheet_dynamix_core_platform.md#spec-sheet-dynamix-core-platform-chunk-001 (0.58)

Q-018**MEDIUM****REVIEW**

What is the longest retention period available for audit log entries?

The longest available retention period for audit log entries is 2,555 days (seven years) [spec_sheet_dynamix_core_platform.md#spec-sheet-dynamix-core-platform-chunk-000] [prior_rfp_response_2025_q1.md#prior-rfp-response-2025-q1-chunk-000]. The default retention is 365 days, with the configurable range running from 90 days up to the 2,555-day maximum [spec_sheet_dynamix_core_platform.md#spec-sheet-dynamix-core-platform-chunk-000]. Audit log entries are append-only, immutable once written, and integrity-signed using the platform key hierarchy [spec_sheet_dynamix_core_platform.md#spec-sheet-dynamix-core-platform-chunk-000] [prior_rfp_response_2025_q1.md#prior-rfp-response-2025-q1-chunk-000].

Citations: spec_sheet_dynamix_core_platform.md#spec-sheet-dynamix-core-platform-chunk-000 (0.55) · prior_rfp_response_2025_q1.md#prior-rfp-response-2025-q1-chunk-000 (0.59)

Q-019**MEDIUM****REVIEW**

How long after a REST endpoint is deprecated does it remain available?

Deprecated REST endpoints remain available for two major releases after the deprecation announcement, following the platform's API deprecation policy [sme_faq_internal.md#sme-faq-internal-chunk-001].

Citations: sme_faq_internal.md#sme-faq-internal-chunk-001 (0.62)

Q-020**MEDIUM****REVIEW**

How many Core nodes are required for a 12,000-active-user Enterprise deployment?

A 12,000-active-user Enterprise deployment falls within the 5,000–25,000 active-user range, for which the recommended topology is High-Availability with 5 nodes per availability zone, giving ****15 Core nodes total**** [partner_enablement_deployment_playbook.md#partner-enablement-deployment-playbook-chunk-000] [partner_enablement_deployment_playbook.md#partner-enablement-deployment-playbook-chunk-001]. This configuration is also the certified footprint for Enterprise tier operating limits [partner_enablement_deployment_playbook.md#partner-enablement-deployment-playbook-chunk-000].

Citations: partner_enablement_deployment_playbook.md#partner-enablement-deployment-playbook-chunk-000 (0.70) · partner_enablement_deployment_playbook.md#partner-enablement-deployment-playbook-chunk-001 (0.70)

Q-021**CONFLICT**

What is the Recovery Time Objective for a regional outage event?

CONFLICTING VERSIONS — SME RESOLVES

- Under the Multi-Region Topology, the RTO for a region-out (regional outage) scenario is documented at 8 hours, with cross-region RPO and RTO described as customer-configurable and the 8-hour figure being the standard published target [partner_enablement_deployment_playbook.md#partner-enablement-deployment-playbook-chunk-000]. For single-region restore under the Standard profile, the RTO is 4 hours [partner_enablement_deployment_playbook.md#partner-enablement-deployment-playbook-chunk-000].
- The 2025.x spec sheet documents two recovery profiles, neither of which specifies an RTO for a cross-region outage event: the Standard profile carries an RTO of 4 hours for single-region restore, and the High-Availability profile carries an RTO of 90 minutes for in-region failover only [spec_sheet_dynamix_core_platform.md#spec-sheet-dynamix-core-platform-chunk-001]. No cross-region (regional outage) RTO figure is stated.
- The 2024.x prior RFP response (Q1, Standard profile) documents the RTO at 4 hours for a single-region restore using the documented runbook, with no separate cross-region RTO figure provided [prior_rfp_response_2025_q1.md#prior-rfp-response-2025-q1-chunk-000]. This figure applies only to the 2024.x standard asynchronous replication deployment and does not address a full regional outage scenario.

Citations: partner_enablement_deployment_playbook.md#partner-enablement-deployment-playbook-chunk-000 (0.60) · spec_sheet_dynamix_core_platform.md#spec-sheet-dynamix-core-platform-chunk-001 (0.68) · prior_rfp_response_2025_q1.md#prior-rfp-response-2025-q1-chunk-000 (0.59)

Q-022**LOW**

What real-time streaming ingest mechanism does Core Platform expose?

NO DRAFT — ESCALATED

The retrieved chunks describe the Core Platform's integration surfaces (REST API, Webhooks, SDKs) and Edge Gateway event throughput, but none of them mention a real-time streaming ingest mechanism (such as Kafka, WebSockets, SSE, gRPC streaming, or equivalent). Drafting an answer about streaming ingest from these chunks would require speculation beyond what is documented.

Citations: spec_sheet_dynamix_core_platform.md#spec-sheet-dynamix-core-platform-chunk-000 (0.62) · partner_enablement_integration_guide.md#partner-enablement-integration-guide-chunk-000 (0.61) · sme_faq_internal.md#sme-faq-internal-chunk-000 (0.59) · prior_rfp_response_2024_q4.md#prior-rfp-response-2024-q4-chunk-000 (0.58) · sme_faq_internal.md#sme-faq-internal-chunk-001 (0.58)

Q-023**LOW**

What is the step-by-step procedure to provision customer-managed keys in production?

NO DRAFT — ESCALATED

The retrieved chunks acknowledge that customer-managed key (CMK) support via HSM integration (PKCS#11 and KMIP) exists in the 2025.x release, and the provisioning sequence mentions "Apply customer-managed key configuration (HSM) if required" as a single high-level step, but none of the chunks provide the actual step-by-step procedure needed to carry out that configuration. Drafting a defensible procedural answer from these chunks would require speculation about the specific commands, parameters, and workflow involved.

Citations: partner_enablement_deployment_playbook.md#partner-enablement-deployment-playbook-chunk-001 (0.64) · prior_rfp_response_2025_q1.md#prior-rfp-response-2025-q1-chunk-000 (0.63) · prior_rfp_response_2025_q3.md#prior-rfp-response-2025-q3-chunk-000 (0.62) · spec_sheet_dynamix_core_platform.md#spec-sheet-dynamix-core-platform-chunk-000 (0.61) · sme_faq_internal.md#sme-faq-internal-chunk-000 (0.60)

Q-024**LOW**

What is the mean-time-to-repair for an Edge Gateway hardware failure?

NO DRAFT — ESCALATED

None of the retrieved chunks contain any MTTR metric or hardware repair/replacement SLA for the Edge Gateway. The chunks cover throughput specs, deployment timelines, shipping lead times, sizing guidance, and commercial/roadmap topics — none of which address how long it takes to repair or recover from a hardware failure. Drafting an answer would require speculation.

Citations: prior_rfp_response_2024_q4.md#prior-rfp-response-2024-q4-chunk-001 (0.70) · prior_rfp_response_2024_q4.md#prior-rfp-response-2024-q4-chunk-000 (0.65) · sme_faq_internal.md#sme-faq-internal-chunk-000 (0.65) · spec_sheet_dynamix_edge_gateway.md#spec-sheet-dynamix-edge-gateway-chunk-000 (0.65) · partner_enablement_deployment_playbook.md#partner-enablement-deployment-playbook-chunk-001 (0.63)

Q-025**LOW**

Is Dynamix Core Platform FedRAMP Moderate authorized?

NO DRAFT — ESCALATED

None of the retrieved chunks mention FedRAMP at all; they cover encryption (FIPS 140-2), identity federation, audit logging, recovery profiles, and hardware specs, but contain no facts about FedRAMP Moderate authorization. Drafting an answer would require speculation entirely unsupported by the knowledge base.

Citations: spec_sheet_dynamix_core_platform.md#spec-sheet-dynamix-core-platform-chunk-000 (0.75) · prior_rfp_response_2025_q1.md#prior-rfp-response-2025-q1-chunk-000 (0.71) · partner_enablement_integration_guide.md#partner-enablement-integration-guide-chunk-000 (0.68) · prior_rfp_response_2025_q3.md#prior-rfp-response-2025-q3-chunk-000 (0.65) · spec_sheet_dynamix_edge_gateway.md#spec-sheet-dynamix-edge-gateway-chunk-000 (0.61)

Q-026**LOW**

Does the platform comply with the HIPAA Privacy Rule for protected health information?

NO DRAFT — ESCALATED

None of the retrieved chunks address HIPAA Privacy Rule compliance, PHI handling, or any HIPAA-specific attestations. The chunks cover encryption, audit logging, identity federation, and recovery profiles — which are adjacent security controls — but do not establish whether the platform is HIPAA-compliant. The SME FAQ explicitly states it does not address regulatory authorisations or compliance attestations, directing those questions to the compliance team.

Citations: sme_faq_internal.md#sme-faq-internal-chunk-001 (0.62) · prior_rfp_response_2025_q3.md#prior-rfp-response-2025-q3-chunk-000 (0.58) · partner_enablement_integration_guide.md#partner-enablement-integration-guide-chunk-000 (0.56) · spec_sheet_dynamix_core_platform.md#spec-sheet-dynamix-core-platform-chunk-000 (0.55) · prior_rfp_response_2025_q1.md#prior-rfp-response-2025-q1-chunk-000 (0.55)

Q-027**NO_SOURCE**

What languages does the admin console UI support?

NO DRAFT — ESCALATED

No KB chunks above the retrieval relevance threshold for this question.

Q-028**LOW**

Is the platform SOC 2 Type II certified?

NO DRAFT — ESCALATED

None of the retrieved chunks mention SOC 2 Type II (or any SOC 2 variant). The chunks cover encryption, FIPS 140-2, identity federation, audit logging, and support tiers — adjacent compliance topics — but contain no facts about SOC 2 certification. Notably, the internal FAQ explicitly disclaims coverage of "compliance attestations" and directs readers to the compliance team. Drafting an answer from these chunks would require speculation.

Citations: spec_sheet_dynamix_core_platform.md#spec-sheet-dynamix-core-platform-chunk-000 (0.63) · prior_rfp_response_2025_q1.md#prior-rfp-response-2025-q1-chunk-001 (0.59) · prior_rfp_response_2025_q1.md#prior-rfp-response-2025-q1-chunk-000 (0.59) · prior_rfp_response_2025_q3.md#prior-rfp-response-2025-q3-chunk-000 (0.58) · sme_faq_internal.md#sme-faq-internal-chunk-001 (0.57)

Q-029**CONFLICT**

What is the documented Recovery Point Objective for the Core Platform?

CONFLICTING VERSIONS — SME RESOLVES

- Under the 2024.x standard deployment profile with asynchronous replication on a 15-minute snapshot cadence, the documented RPO for Dynamix Core Platform is 15 minutes [prior_rfp_response_2025_q1.md#prior-rfp-response-2025-q1-chunk-000]. The 2025.x spec sheet also lists a Standard profile (asynchronous replication) with an RPO of 15 minutes and RTO of 4 hours for single-region restore [spec_sheet_dynamix_core_platform.md#spec-sheet-dynamix-core-platform-chunk-001].
- Under the 2025.x High-Availability profile, which uses synchronous replication between availability zones [spec_sheet_dynamix_core_platform.md#spec-sheet-dynamix-core-platform-chunk-001], the documented RPO for Dynamix Core Platform is 5 minutes, with an RTO of 90 minutes for in-region failover [prior_rfp_response_2025_q3.md#prior-rfp-response-2025-q3-chunk-000]. This profile requires a multi-AZ deployment and is described as the recommended configuration for customers whose regulatory or operational continuity requirements exceed the 15-minute RPO baseline [prior_rfp_response_2025_q3.md#prior-rfp-response-2025-q3-chunk-000] [spec_sheet_dynamix_core_platform.md#spec-sheet-dynamix-core-platform-chunk-001].

Citations: prior_rfp_response_2025_q1.md#prior-rfp-response-2025-q1-chunk-000 (0.65) · prior_rfp_response_2025_q3.md#prior-rfp-response-2025-q3-chunk-000 (0.63) · spec_sheet_dynamix_core_platform.md#spec-sheet-dynamix-core-platform-chunk-001 (0.68)

Q-030

CONFLICT

What is the certified sustained ingest rate of the Edge Gateway 4400 series?

CONFLICTING VERSIONS — SME RESOLVES

- The published spec sheet certifies sustained ingest for the Edge Gateway 4400 series at 80,000 events per second, validated against a median payload size of 1.2 KB [spec_sheet_dynamix_edge_gateway.md#spec-sheet-dynamix-edge-gateway-chunk-000].
- In a 2024 Q4 prior engagement with a discrete-manufacturing customer, the sustained ingest rate for the Edge Gateway 4400 series was confirmed at 60,000 events per second, measured against that customer's mixed payload profile (median ~2.0 KB, larger than the spec-sheet median), validated over a one-week on-site trial [prior_rfp_response_2024_q4.md#prior-rfp-response-2024-q4-chunk-000].

Citations: spec_sheet_dynamix_edge_gateway.md#spec-sheet-dynamix-edge-gateway-chunk-000 (0.74) · prior_rfp_response_2024_q4.md#prior-rfp-response-2024-q4-chunk-000 (0.74)

Status: **Requires SME review before customer delivery.**