

A theory of events and situations

Robin Cooper

University of Gothenburg

Jonathan Ginzburg

Université Paris-Diderot, Sorbonne Paris-Cité

An Introduction to Semantics using Type Theory with Records

ESSLLI 2012

Lecture 1, part 2

Outline

Type theory and perception

TTR: Type theory with records

Summary and bibliography


Outline

Type theory and perception


TTR: Type theory with records

Summary and bibliography


Seeing a tree (a simulation view)




Seeing a tree (a simulation view)




Seeing a tree (a simulation view)



Seeing a tree (a simulation view)



Seeing a tree (a simulation view)



Gibson (1986); Barwise and Perry (1983)

Judgement

- ▶ (An agent judges that) object a is of type T .
- ▶ $a : T$

Outline

Type theory and perception

TTR: Type theory with records

Summary and bibliography

TTR: Type theory with records

- ▶ The most recent published reference for the details is Cooper (2012)
- ▶ Also Cooper (2005a) for an earlier detailed treatment
- ▶ Cooper (2005b) for relation to various semantic theories
- ▶ <https://sites.google.com/site/typetheorywithrecords/drafts/ch1-draft111114.pdf>
for some current work in progress we will discuss here

Rich type theory

- ▶ *traditional type theories* (e.g. Montague, 1973, 1974) provide types for basic ontological classes (e.g., for Montague, entities, truth values, time points, possible worlds and total functions between these objects)

Rich type theory

- ▶ *traditional type theories* (e.g. Montague, 1973, 1974) provide types for basic ontological classes (e.g., for Montague, entities, truth values, time points, possible worlds and total functions between these objects)
- ▶ *rich type theories* (e.g. Martin-Löf, 1984) provide a more general types, e.g. in our type theory, categories of objects such as *Tree*, types of situations such as *Hugging of a dog by a boy*

Rich type theory

- ▶ *traditional type theories* (e.g. Montague, 1973, 1974) provide types for basic ontological classes (e.g., for Montague, entities, truth values, time points, possible worlds and total functions between these objects)
- ▶ *rich type theories* (e.g. Martin-Löf, 1984) provide a more general types, e.g. in our type theory, categories of objects such as *Tree*, types of situations such as *Hugging of a dog by a boy*
- ▶ two fundamental questions when characterizing a type theory:
 - ▶ what types are there?
 - ▶ for any type, what are the objects of that type?

Basic types

- ▶ basic types (as opposed to complex ones) are types which are not constructed from smaller parts

Basic types

- ▶ basic types (as opposed to complex ones) are types which are not constructed from smaller parts
- ▶ a system of basic types contains a set of such types, **Type**

Basic types

- ▶ basic types (as opposed to complex ones) are types which are not constructed from smaller parts
- ▶ a system of basic types contains a set of such types, **Type**
- ▶ examples: *Ind* (“individual”), *Time* (“time point”)

Basic types

- ▶ basic types (as opposed to complex ones) are types which are not constructed from smaller parts
- ▶ a system of basic types contains a set of such types, **Type**
- ▶ examples: *Ind* (“individual”), *Time* (“time point”)
- ▶ a system of basic types also contains a function, *A*, which assigns a set of objects to each of the types in **Type**

Basic types

- ▶ basic types (as opposed to complex ones) are types which are not constructed from smaller parts
- ▶ a system of basic types contains a set of such types, **Type**
- ▶ examples: *Ind* (“individual”), *Time* (“time point”)
- ▶ a system of basic types also contains a function, A , which assigns a set of objects to each of the types in **Type**
- ▶ $a : T$ iff $a \in A(T)$


Intensionality

- Important: types are mathematical objects in their own right, they are not just sets of objects.

Intensionality

- ▶ Important: types are mathematical objects in their own right, they are not just sets of objects.
- ▶ Consequence: you can have two distinct types which have the same set of objects associated with them, i.e. $A(T_1) = A(T_2)$, $a : T_1$ just in case $a : T_2$. The types are *intensional*.

$a : T_1$



Types may be structured mathematical objects

- ▶ types may be constructed from other mathematical objects
- ▶ that is, they are *complex* types (*non-basic* types)

Types may be structured mathematical objects

- ▶ types may be constructed from other mathematical objects
- ▶ that is, they are *complex* types (*non-basic* types)
- ▶ one kind of complex type is *p*type, types which are constructed from predicates and objects used as arguments to the predicate

Types may be structured mathematical objects

- ▶ types may be constructed from other mathematical objects
- ▶ that is, they are *complex* types (*non-basic* types)
- ▶ one kind of complex type is *p*type, types which are constructed from predicates and objects used as arguments to the predicate
- ▶ another kind of complex type is *record type*, types which consist of a collection of types indexed by labels

Why is structure important?

Why is structure important?

- ▶ increases intensionality (e.g. same “content”, different structure)


Why is structure important?

- ▶ increases intensionality (e.g. same “content”, different structure)
- ▶ allows us to find parts within a whole (e.g. in clarification)

Why is structure important?

- ▶ increases intensionality (e.g. same “content”, different structure)
- ▶ allows us to find parts within a whole (e.g. in clarification)
- ▶ allows us to modify by adding or removing a part (e.g. in learning new meanings or coordinating meaning with your dialogue partner)

Seeing a hugging event



Predicates

- ▶ predicates such as 'run', 'hug'

Predicates

- ▶ predicates such as 'run', 'hug'
- ▶ predicates come along with an *arity* which tells you what kind of *arguments* the predicates have:
 - ▶ $\text{Arity}(\text{run}) = \langle \text{Ind} \rangle$
 - ▶ $\text{Arity}(\text{hug}) = \langle \text{Ind}, \text{Ind} \rangle$

Predicates

- ▶ predicates such as 'run', 'hug'
- ▶ predicates come along with an *arity* which tells you what kind of *arguments* the predicates have:
 - ▶ $\text{Arity}(\text{run}) = \langle \text{Ind} \rangle$
 - ▶ $\text{Arity}(\text{hug}) = \langle \text{Ind}, \text{Ind} \rangle$
- ▶ We might also want to include time intervals and locations as part of the arities of these predicates

Ptypes

- ▶ ptypes are constructed from predicates and arguments corresponding to their arities

Ptypes

- ▶ ptypes are constructed from predicates and arguments corresponding to their arities
- ▶ examples: $\text{run}(d)$, $\text{hug}(b,d)$ (where $b,d:\text{Ind}$)

Ptypes

- ▶ ptypes are constructed from predicates and arguments corresponding to their arities
- ▶ examples: $\text{run}(d)$, $\text{hug}(b,d)$ (where $b,d:\text{Ind}$)
- ▶ ptypes are types of situations (events)

Ptypes

- ▶ ptypes are constructed from predicates and arguments corresponding to their arities
- ▶ examples: $\text{run}(d)$, $\text{hug}(b,d)$ (where $b,d:\text{Ind}$)
- ▶ ptypes are types of situations (events)
- ▶ a system of complex types will contain a set of ptypes, **PType**, in addition to basic types

Ptypes

- ▶ ptypes are constructed from predicates and arguments corresponding to their arities
- ▶ examples: $\text{run}(d)$, $\text{hug}(b,d)$ (where $b,d:\text{Ind}$)
- ▶ ptypes are types of situations (events)
- ▶ a system of complex types will contain a set of ptypes, **PType**, in addition to basic types
- ▶ **PType** will be based on a set of predicates with their arities

Ptypes

- ▶ ptypes are constructed from predicates and arguments corresponding to their arities
- ▶ examples: $\text{run}(d)$, $\text{hug}(b,d)$ (where $b,d:\text{Ind}$)
- ▶ ptypes are types of situations (events)
- ▶ a system of complex types will contain a set of ptypes, **PType**, in addition to basic types
- ▶ **PType** will be based on a set of predicates with their arities
- ▶ **PType** will contain all the possible ptypes for a given predicate given what is assigned to the arity for the predicate elsewhere in the system

Ptypes

- ▶ ptypes are constructed from predicates and arguments corresponding to their arities
- ▶ examples: $\text{run}(d)$, $\text{hug}(b,d)$ (where $b,d:\text{Ind}$)
- ▶ ptypes are types of situations (events)
- ▶ a system of complex types will contain a set of ptypes, **PType**, in addition to basic types
- ▶ **PType** will be based on a set of predicates with their arities
- ▶ **PType** will contain all the possible ptypes for a given predicate given what is assigned to the arity for the predicate elsewhere in the system
- ▶ a system of complex types will also contain a function, F , which assigns a set, possibly empty, (of situations) to each ptype.

Models

- ▶ A and F together, that is, $\langle A, F \rangle$, is a *model*
- ▶ a model consists of an assignment to the basic types and an assignment to the ptypes

Models

- ▶ A and F together, that is, $\langle A, F \rangle$, is a *model*
- ▶ a model consists of an assignment to the basic types and an assignment to the ptypes
- ▶ note that a model in this sense is *part* of the type system (not an external interpretation of it)
- ▶ this is an important difference between rich type theories and traditional model theory

Are ptypes the only types of situations?

- ▶ suppose b is Bill, a boy and d is Dinah, a dog
- ▶ we have allowed ourselves the ptype $\text{hug}(b,d)$, the type of situation where Bill hugs Dinah
- ▶ but we have not allowed ourselves the type of “boy hugs dog” situations corresponding to *a boy hugs a dog*
- ▶ there are a number of ways to construct such types in rich type theories – we use *record types*

A boy hugs a dog

Record type – “a collection of labelled types”

$$\left[\begin{array}{ll} x & : \textit{Ind} \\ c_{\text{boy}} & : \text{boy}(x) \\ y & : \textit{Ind} \\ c_{\text{dog}} & : \text{dog}(y) \\ e & : \text{hug}(x,y) \end{array} \right]$$

A boy hugs a dog

Record type – “a collection of labelled types”
... not quite because of dependencies

$$\left[\begin{array}{ll} x & : \textit{Ind} \\ c_{\textit{boy}} & : \textit{boy}(x) \\ y & : \textit{Ind} \\ c_{\textit{dog}} & : \textit{dog}(y) \\ e & : \textit{hug}(x,y) \end{array} \right]$$

The official notation

$$\left[\begin{array}{ll} x & : \textit{Ind} \\ c_{\text{boy}} & : \langle \lambda v : \textit{Ind}(\text{boy}(v)), \langle x \rangle \rangle, \\ y & : \textit{Ind} \\ c_{\text{dog}} & : \langle \lambda v : \textit{Ind}(\text{dog}(v)), \langle y \rangle \rangle \\ e & : \langle \lambda v_1 : \textit{Ind}(\lambda v_2 : \textit{Ind}(\text{hug}(v_1, v_2))), \\ & \quad \langle x, y \rangle \rangle \end{array} \right]$$

A record of type *a boy hugs a dog*

$$\left[\begin{array}{lcl} x & = & a \\ c_{\text{boy}} & = & s_1 \\ y & = & b \\ c_{\text{dog}} & = & s_2 \\ e & = & s_3 \end{array} \right]$$

where: $a : \text{Ind}$
 $s_1 : \text{boy}(a)$
 $b : \text{Ind}$
 $s_2 : \text{dog}(b)$
 $s_3 : \text{hug}(a,b)$

Two important facts about records

- ▶ You can construct a record of a given type just in case there are objects of the types required by its fields – i.e. the labelling is arbitrary

Two important facts about records

- ▶ You can construct a record of a given type just in case there are objects of the types required by its fields – i.e. the labelling is arbitrary
- ▶ A record of a given type may contain more fields than required by the type – this record also belongs to a subtype of the type where the extra fields are added

Why are record types interesting for linguists?

- ▶ they allow us to model discourse representation structures

Why are record types interesting for linguists?

- ▶ they allow us to model discourse representation structures
- ▶ they allow us to model feature structures

Why are record types interesting for linguists?

- ▶ they allow us to model discourse representation structures
- ▶ they allow us to model feature structures
- ▶ they allow us to model dialogue game boards (information states)

Why are record types interesting for linguists?

- ▶ they allow us to model discourse representation structures
- ▶ they allow us to model feature structures
- ▶ they allow us to model dialogue game boards (information states)
- ▶ they allow us to model frames (as in frame semantics and FrameNet)

Outline

Type theory and perception

TTR: Type theory with records

Summary and bibliography

Summary

- ▶ Type theory as a formal theory related to perception
- ▶ A basic introduction to TTR:
 - ▶ basic types (e.g. *Ind*)
 - ▶ ptypes (e.g. `hug(Sam,Dinah)`)
 - ▶ models which supply objects of basic types and ptypes
 - ▶ record types
 - ▶ mentioned some of their linguistic applications

Bibliography I

Barwise, Jon and John Perry (1983) *Situations and Attitudes*,
Bradford Books, MIT Press, Cambridge, Mass.

Cooper, Robin (2005a) Austinian truth, attitudes and type theory,
Research on Language and Computation, Vol. 3, pp. 333–362.

Cooper, Robin (2005b) Records and Record Types in Semantic
Theory, *Journal of Logic and Computation*, Vol. 15, No. 2, pp.
99–112.

Cooper, Robin (2012) Type Theory and Semantics in Flux, in R.
Kempson, N. Asher and T. Fernando (eds.), *Handbook of the
Philosophy of Science*, Vol. 14: Philosophy of Linguistics, pp.
271–323, Elsevier BV. General editors: Dov M. Gabbay, Paul
Thagard and John Woods.

Bibliography II

- Gibson, James J. (1986) *The Ecological Approach to Visual Perception*, Lawrence Erlbaum Associates.
- Martin-Löf, Per (1984) *Intuitionistic Type Theory*, Bibliopolis, Naples.
- Montague, Richard (1973) The Proper Treatment of Quantification in Ordinary English, in J. Hintikka, J. Moravcsik and P. Suppes (eds.), *Approaches to Natural Language: Proceedings of the 1970 Stanford Workshop on Grammar and Semantics*, pp. 247–270, D. Reidel Publishing Company, Dordrecht.
- Montague, Richard (1974) *Formal Philosophy: Selected Papers of Richard Montague*, Yale University Press, New Haven, ed. and with an introduction by Richmond H. Thomason.