

Equipment Specifications, Dimensions, Weight

Maximum user weight: No Limit

Lowest Height Setting: 5'2"

Greatest Height Setting: 6'8"

Base Width: 4' Base Length: 4'

Equipment Weight: 315 lbs

Main Frame: 2.5mm and 2.0mm heavy guage oval steel tubing

Arm Size: OD is 60mm (24") with 2.5mm (1/10") wall steel tubing

Spring Box: 8.0mm (5/16") heavy commercial steel construction

Main Torsion Springs: 5mm (1/5") and 6mm (1/4") high strength springs, torque rated at 40kg-m (3450 lb-in) and 20 kg-m (1730

lb-in)

Pad Compression Springs: Arm pad springs are 2.3mm (1/10") on arms #1, 2 - Arm pad springs are 2.8mm (1/10") on arms #3, 4, 5,

6, 7 - All springs are black zinc plated

Coating and Metal Plating: Gloss charcoal powder-coating and chrome plating

Hardware Specification: High strength M10 grade 8.8 (3/8" grade 5) hardware and nylon insert nuts, black zinc or silver zinc plated

Equipment Features

Industrial grade steel welded frame

Seven Leather Pads

3-axis accelerometer in each pad to gather performance data

Wheels attached to base and handle attached to frame for easy moving

Large heavy load foot pads

Foot pads are adjustable for optimal balance



Shipping Dimensions and Weight

Frame Box Dimensions: 58" x 32" x 25"

Frame Box Weight: 183 lbs

Base Box Dimensions: 53" x 53" x 5"

Base Box Weight: 114 lbs

Monitor Box Dimensions: 25" x 6" x 17"

Monitor Box Weight: 17 lbs

Console Features

22" LCD touch screen monitor

Bluetooth capability for heart rate monitor or wireless headset

Four USB ports for saving custom profiles

Console Languages: English Units Selection: U.S. Standard

Preset Programs: Nexersys Training, Avatar Training, Multiplayer

Maximum Workout Time: 15 rounds or 60 minutes

Maximum Pause Time: 2 minutes

Levels: Beginner, Intermediate, Advanced

Number of Rounds: 1-15

Electronic Readouts: Accuracy, Strike Count, Power, Points, Heart

Rate and Caloric Burn

Warranty

Frame - 7 Years

Mechanical and Electronic Parts - 3 Years

Wear Parts - 3 Years

Power Requirements

Equipment: Powered

Input: 100-240V - 50/60 hz ZA

Corporate Offices

500 San Marcos Street Suite 201 Austin, TX 78702

www.nexersys.com sales@nexersys.com (877) 785-3818



