



Probabilistic forecasts for anomaly detection

Rob J Hyndman


3 July 2024

Australian PBS data

```
pbs
```

```
# A tibble: 17,016 x 3 [1M]
# Key:      ATC2 [84]
  ATC2      Month Scripts
  <chr>    <mth>    <dbl>
1 A01    1991 Jul     22615
2 A01    1991 Aug     20443
3 A01    1991 Sep     21389
4 A01    1991 Oct     23746
5 A01    1991 Nov     23477
6 A01    1991 Dec     26316
7 A01    1992 Jan     22041
8 A01    1992 Feb     16393
9 A01    1992 Mar     17207
10 A01    1992 Apr     18847
# i 17,006 more rows
```

Australian PBS data




Anomaly score distribution

One-step forecast distribution: $N(\mu_t, \sigma^2)$

$$f(y_t | y_1, \dots, y_{t-1}) = \phi\left(\frac{y_t - \mu_t}{\sigma}\right) = \frac{1}{\sigma\sqrt{2\pi}} \exp\left\{-\frac{(y_t - \mu_t)^2}{2\sigma^2}\right\}$$

One-step forecast density



Anomaly score distribution


One-step forecast distribution: $N(\mu_t, \sigma^2)$

$$f(y_t | y_1, \dots, y_{t-1}) = \phi\left(\frac{y_t - \mu_t}{\sigma}\right) = \frac{1}{\sigma\sqrt{2\pi}} \exp\left\{-\frac{(y_t - \mu_t)^2}{2\sigma^2}\right\}$$


Anomaly score distribution: $S \sim \frac{1}{2}\chi_1^2 + c$

$$s_t = -\log f(y_t | y_1, \dots, y_{t-1}) = \frac{1}{2}\left(\frac{y_t - \mu_t}{\sigma}\right)^2 + \frac{1}{2}\log(2\pi\sigma^2)$$

One-step forecast density



Anomaly score density



Anomaly score distribution

One-step forecast distribution: $N(\mu_t, \sigma^2)$

$$f(y_t | y_1, \dots, y_{t-1}) = \phi\left(\frac{y_t - \mu_t}{\sigma}\right) = \frac{1}{\sigma\sqrt{2\pi}} \exp\left\{-\frac{(y_t - \mu_t)^2}{2\sigma^2}\right\}$$

Anomaly score distribution: $S \sim \frac{1}{2}\chi_1^2 + c$


$$s_t = -\log f(y_t | y_1, \dots, y_{t-1}) = \frac{1}{2}\left(\frac{y_t - \mu_t}{\sigma}\right)^2 + \frac{1}{2}\log(2\pi\sigma^2)$$

Extreme anomaly score distribution


$$H(x) = P(S \leq u + x \mid S > u)$$

→ Generalized Pareto Distribution for almost all forecast distributions f .


One-step forecast density



Anomaly score density



Anomaly score exceedance density




Anomaly detection algorithm

- Estimate one-step forecast densities: $f(y_t|y_1, \dots, y_{t-1})$.
- Anomaly score: $s_t = -\log \hat{f}(y_t|y_1, \dots, y_{t-1})$.
- High anomaly scores indicate potential anomalies.
- Fit a Generalized Pareto Distribution to the top 5% of anomaly scores.
- Use the GPD to estimate the probability of each observation being an anomaly.


Example

```
n07 <- pbs > filter(ATC2 == "N07", Month <= yearmonth("2001 Jan"))
n07plus <- pbs > filter(ATC2 == "N07", Month <= yearmonth("2001 Feb"))
fc <- n07 > model(ets = ETS(Scripts)) > forecast(h = 1)
fc > autoplot(n07)
```




Example

```
n07 <- pbs > filter(ATC2 == "N07", Month <= yearmonth("2001 Jan"))  
n07plus <- pbs > filter(ATC2 == "N07", Month <= yearmonth("2001 Feb"))  
fc <- n07 > model(ets = ETS(Scripts)) > forecast(h = 1)  
fc > autoplot(n07plus)
```




Example

```
n07 <- pbs > filter(ATC2 == "N07", Month <= yearmonth("2001 Jan"))  
n07plus <- pbs > filter(ATC2 == "N07", Month <= yearmonth("2001 Feb"))  
fc <- n07 > model(ets = ETS(Scripts)) > forecast(h = 1)  
fc > autoplot(n07plus)
```



Rolling origin forecasts



Rolling origin forecasts

```
pbs_stretch ← stretch_tsibble(pbs, .step = 1, .init = 36)
```

```
# A tsibble: 1,684,884 x 4 [1M]
```

```
# Key:           .id, ATC2 [14,076]
```

	ATC2	Month	Scripts	.id
	<chr>	<mth>	<dbl>	<int>
1	A01	1991 Jul	22615	1
2	A01	1991 Aug	20443	1
3	A01	1991 Sep	21389	1
4	A01	1991 Oct	23746	1
5	A01	1991 Nov	23477	1
6	A01	1991 Dec	26316	1
7	A01	1992 Jan	22041	1
8	A01	1992 Feb	16393	1
9	A01	1992 Mar	17207	1
10	A01	1992 Apr	18847	1

```
# i 1,684,874 more rows
```

Rolling origin forecasts

```
pbs_fit ← pbs_stretch ▷ model(ets = ETS(Scripts))
```

```
# A mable: 14,076 x 3  
# Key:      .id, ATC2 [14,076]
```

	.id	ATC2	ets
	<int>	<chr>	<model>
1	1	A01	<ETS(M,N,A)>
2	1	A02	<ETS(M,A,M)>
3	1	A03	<ETS(M,A,M)>
4	1	A04	<ETS(M,N,M)>
5	1	A05	<ETS(A,Ad,N)>
6	1	A06	<ETS(M,N,M)>
7	1	A07	<ETS(M,A,M)>
8	1	A09	<ETS(M,A,M)>
9	1	A10	<ETS(M,A,M)>
10	1	A11	<ETS(M,A,M)>

```
# i 14,066 more rows
```

Rolling origin forecasts

```
pbs_fc ← forecast(pbs_fit, h = 1)
```

```
# A fable: 14,076 x 4 [1M]
```

```
# Key:      .id, ATC2 [14,076]
```

	.id	ATC2	Month	Scripts
	<int>	<chr>	<mth>	<dist>
1	1	A01	1994 Jul	N(22722, 2441206)
2	1	A02	1994 Jul	N(588422, 1.1e+09)
3	1	A03	1994 Jul	N(84529, 1.9e+07)
4	1	A04	1994 Jul	N(70220, 1.5e+07)
5	1	A05	2003 Jul	N(1372, 13768)
6	1	A06	1994 Jul	N(30624, 5537439)
7	1	A07	1994 Jul	N(78305, 1.5e+07)
8	1	A09	1994 Jul	N(3658, 28241)
9	1	A10	1994 Jul	N(166969, 5.4e+07)
10	1	A11	1994 Jul	N(30575, 2947627)

```
# i 14,066 more rows
```

Finding anomalies

```
pbs_scores <- pbs_fc >
  left_join(pbs > rename(actual = Scripts), by = c("ATC2", "Month")) >
  mutate(
    s = -log_likelihood(Scripts, actual), # Density scores
    prob = lookout(density_scores = s)    # Probability not an anomaly
  )
```

A fable: 14,076 x 7 [1M]

Key: .id, ATC2 [14,076]

	.id	ATC2	Month	Scripts	actual	s	prob
	<int>	<chr>	<mth>	<dist>	<dbl>	<dbl>	<dbl>
1	1	A01	1994 Jul	N(22722, 2441206)	20854	8.99	1
2	1	A02	1994 Jul	N(588422, 1.1e+09)	516122	13.8	0.583
3	1	A03	1994 Jul	N(84529, 1.9e+07)	80471	9.73	1
4	1	A04	1994 Jul	N(70220, 1.5e+07)	66125	9.74	1
5	1	A05	2003 Jul	N(1372, 13768)	1468	6.02	1
6	1	A06	1994 Jul	N(30624, 5537439)	29194	8.87	1
7	1	A07	1994 Jul	N(78305, 1.5e+07)	68542	12.4	1
8	1	A09	1994 Jul	N(3658, 28241)	3320	8.07	1

Finding anomalies

```
pbs_scores ► arrange(prob)
```

```
# A tsibble: 14,076 x 7 [1M]
```


```
# Key:           .id, ATC2 [14,076]
```

	.id	ATC2	Month	Scripts	actual	s	prob
	<int>	<chr>	<mth>	<dist>	<dbl>	<dbl>	<dbl>
1	80	N07	2001 Feb	N(4261, 136066)	24616	1529.	0.000925
2	44	R06	1998 Feb	N(-1222, 17510)	4986	1106.	0.00128
3	146	P01	2006 Aug	N(26, 5.6)	129	951.	0.00148
4	81	N07	2001 Mar	N(8484, 4549377)	98942	908.	0.00156
5	18	L03	1996 Dec	N(329, 536)	1231	763.	0.00185
6	131	D11	2005 May	N(136, 178)	596	598.	0.00236
7	24	C05	1996 Jun	N(5, 1.8)	50	567.	0.00249
8	141	P01	2006 Mar	N(506, 1617)	1505	313.	0.00455
9	55	R06	1999 Jan	N(-835, 12055)	1452	223.	0.00648
10	57	D05	1999 Mar	N(783, 11837)	2789	176.	0.00832

```
# i 14,066 more rows
```



Finding anomalies

```
pbs > filter(ATC2 == "N07") > autoplot() +  
  scale_x_yearmonth(date_breaks = "2 years", date_labels = "%Y") +  
  geom_vline(xintercept = as.Date("2001-02-01"), color = "red")
```



Finding anomalies

```
pbs > filter(ATC2 == "R06") > autoplot() +  
  scale_x_yearmonth(date_breaks = "2 years", date_labels = "%Y") +  
  geom_vline(xintercept = as.Date(c("1998-02-01", "1999-01-01")), color = "red")
```



Online anomaly detection

- Demonstrate using weird package with (a) univariate models for tourism data; and (b) univariate models for age-specific time series from French mortality.