




Outline

Notation reminder

- Data: $\mathbf{y}_t = \mathbf{S}\mathbf{b}_t$ where \mathbf{S} is a summing matrix and \mathbf{b}_t is a vector of disaggregated time series
- Base forecasts: $\hat{\mathbf{y}}_{T+h|T}$
- Reconciled forecasts: $\tilde{\mathbf{y}}_{T+h|T} = \mathbf{SG}\hat{\mathbf{y}}_{T+h|T}$
- MinT: $G = (S'W_h^{-1}S)^{-1}S'W_h^{-1}$ where W_h is covariance matrix of base forecast errors.







- Forecast series at each available frequency.
- Optimally combine forecasts within the same

For a time series y_1, \ldots, y_T , observed at frequency m, we generate aggregate series

$$y_j^{[k]} = \sum_{t=1+(j-1)k}^{jk} y_t,$$
 for $j = 1, \ldots, \lfloor T/k \rfloor$

- $k \in F(m) = \{\text{factors of } m\}.$
- A single unique hierarchy is only possible when there are no coprime pairs in F(m).
- \blacksquare M_k = m/k is seasonal period of aggregated series.
- Proposed by Athanasopoulos, Hyndman, Kourentzes, Petropoulos (EJOR, 2017)

Cross-temporal reconciliation

- Kourentzes, Athanasopoulos (ATR, 2019)
- Punia, Singh, Madaan (C&IE, 2020)
- Di Fonzo, Girolimetto (2020)

Cross-temporal reconciliation

- Kourentzes, Athanasopoulos (ATR, 2019)
- Punia, Singh, Madaan (C&IE, 2020)
- Di Fonzo, Girolimetto (2020)

ISF talks coming up!

- Mitch O'Hara-Wild: Probabilistic cross-temporal hierarchies in fable (in about 3 hours)
- Tommi Di Fonzo: Non-negative cross-temporal forecast reconciliation. An application to the Australian domestic tourism flows (in about 11 hours).

Thief

thief paper

Daniele and Tommy's papers

References

- Athanasopoulos, G, RJ Hyndman, N Kourentzes, and F Petropoulos (2017). Forecasting with temporal hierarchies. *European J Operational Research* **262**(1), 60–74.
- Di Fonzo, T and D Girolimetto (2023). Cross-temporal forecast reconciliation: Optimal combination method and heuristic alternatives. *International Journal of Forecasting* **39**(1), 39–57.