

High-dimensional time series analysis


Rob J Hyndman
1 November 2017




Outline

- 1 Sub-daily time series analysis
- 2 Time series feature analysis
- 3 Time series anomaly detection
- 4 Probabilistic electricity demand analysis
- 5 Forecast reconciliation
- 6 Temporal hierarchies
- 7 R packages

Pedestrian counts




Pedestrian counts



Sub-daily time series analysis

- How to visualize many series of sub-daily data over several years?
- How to identify unusual patterns/incidents?
- How to forecast sub-daily data taking account of public holidays and special events?

Sub-daily time series analysis



Sub-daily time series analysis

- How to visualize many series of sub-daily data over several years?
- How to identify unusual patterns/incidents?
- How to forecast sub-daily data taking account of public holidays and special events?



Di Cook



Earo Wang



Mitchell O'Hara-Wild

Outline

- 1 Sub-daily time series analysis
- 2 Time series feature analysis
- 3 Time series anomaly detection
- 4 Probabilistic electricity demand analysis
- 5 Forecast reconciliation
- 6 Temporal hierarchies
- 7 R packages

Walmart weekly sales data



Time series feature analysis

- Can we use time series features for fast identification of forecasting models?
- How to generate new time series with specified feature vectors?
- What can we say about the feature space of time series?

Time series feature analysis

- Can we use time series features for fast identification of forecasting models?
- How to generate new time series with specified feature vectors?
- What can we say about the feature space of time series?



Kate Smith-Miles



George
Athanasopoulos



Thiyanga Talagala

Outline

- 1 Sub-daily time series analysis
- 2 Time series feature analysis
- 3 Time series anomaly detection
- 4 Probabilistic electricity demand analysis
- 5 Forecast reconciliation
- 6 Temporal hierarchies
- 7 R packages

Security monitoring



Security monitoring



Time series anomaly detection

- How to identify anomalous behaviour within streaming data?
- How to define an anomaly in a large multivariate data set?

Time series anomaly detection

- How to identify anomalous behaviour within streaming data?
- How to define an anomaly in a large multivariate data set?



Kate
Smith-Miles



Mario Andrés
Muñoz Acosta



Sevvandi
Kandanaarachchi



Dilini Talagala


Outline

- 1 Sub-daily time series analysis
- 2 Time series feature analysis
- 3 Time series anomaly detection
- 4 Probabilistic electricity demand analysis
- 5 Forecast reconciliation
- 6 Temporal hierarchies
- 7 R packages

Electricity demand



Electricity demand



Electricity demand

- How to forecast future demand by household?
- How to reconcile household demand forecasts with state and national demand forecasts?
- How to identify unusual demand patterns?
- How to measure forecast accuracy when forecasts are probability distributions within a hierarchy?

Electricity demand

- How to forecast future demand by household?
- How to reconcile household demand forecasts with state and national demand forecasts?
- How to identify unusual demand patterns?
- How to measure forecast accuracy when forecasts are probability distributions within a hierarchy?



Souhaib
Ben Taieb




Cameron
Roach

Outline

- 1 Sub-daily time series analysis
- 2 Time series feature analysis
- 3 Time series anomaly detection
- 4 Probabilistic electricity demand analysis
- 5 Forecast reconciliation
- 6 Temporal hierarchies
- 7 R packages

Forecast reconciliation



- Huawei sales by division, group, sub-group, etc.
- Australian tourism demand by state, region, zone.

Forecast reconciliation

- Forecasts at all nodes must be coherent
- Bottom level typically has thousands or millions of time series
- How to define coherence probabilistically?
- How to visualize so many time series?



George
Athanasopoulos



Anastasios
Panagiotelis



Shanika
Wickramasuriya




Puwasala
Gamakumara




Earo Wang

Australian tourism demand




Australian tourism demand


- Quarterly data on visitor night from 1998:Q1 – 2013:Q4
 - From *National Visitor Survey*, based on annual interviews of 120,000 Australians aged 15+, collected by Tourism Research Australia.
 - Split by 7 states, 27 zones and 76 regions (a geographical hierarchy)
 - Also split by purpose of travel
 - Holiday
 - Visiting friends and relatives (VFR)
 - Business
 - Other
 - 304 bottom-level series



Hierarchical time series



Hierarchical time series




y_t : observed aggregate of all series at time t .

$y_{X,t}$: observation on series X at time t .

b_t : vector of all series at bottom level in time t .

Hierarchical time series




y_t : observed aggregate of all series at time t .

$y_{X,t}$: observation on series X at time t .

b_t : vector of all series at bottom level in time t .

$$\mathbf{y}_t = [y_t, y_{A,t}, y_{B,t}, y_{C,t}]' = \begin{pmatrix} 1 & 1 & 1 \\ 1 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 1 \end{pmatrix} \begin{pmatrix} y_{A,t} \\ y_{B,t} \\ y_{C,t} \end{pmatrix}$$

Hierarchical time series




y_t : observed aggregate of all series at time t .

$y_{X,t}$: observation on series X at time t .

b_t : vector of all series at bottom level in time t .

$$\mathbf{y}_t = [y_t, y_{A,t}, y_{B,t}, y_{C,t}]' = \underbrace{\begin{pmatrix} 1 & 1 & 1 \\ 1 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 1 \end{pmatrix}}_s \begin{pmatrix} y_{A,t} \\ y_{B,t} \\ y_{C,t} \end{pmatrix}$$

Hierarchical time series




y_t : observed aggregate of all series at time t .

$y_{X,t}$: observation on series X at time t .

b_t : vector of all series at bottom level in time t .

$$\mathbf{y}_t = [y_t, y_{A,t}, y_{B,t}, y_{C,t}]' = \underbrace{\begin{pmatrix} 1 & 1 & 1 \\ 1 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 1 \end{pmatrix}}_s \underbrace{\begin{pmatrix} y_{A,t} \\ y_{B,t} \\ y_{C,t} \end{pmatrix}}_{b_t}$$

Hierarchical time series



y_t : observed aggregate of all series at time t .

$y_{X,t}$: observation on series X at time t .

b_t : vector of all series at bottom level in time t .

$$\mathbf{y}_t = [y_t, y_{A,t}, y_{B,t}, y_{C,t}]' = \underbrace{\begin{pmatrix} 1 & 1 & 1 \\ 1 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 1 \end{pmatrix}}_S \underbrace{\begin{pmatrix} y_{A,t} \\ y_{B,t} \\ y_{C,t} \end{pmatrix}}_{b_t}$$

$\mathbf{y}_t = S b_t$

Disaggregated time series

Every collection of time series with aggregation constraints can be written as

$$\mathbf{y}_t = \mathbf{S}\mathbf{b}_t$$

where

- \mathbf{y}_t is a vector of all series at time t
- \mathbf{b}_t is a vector of the most disaggregated series at time t
- \mathbf{S} is a “summing matrix” containing the aggregation constraints.

Forecasting notation

Let $\hat{\mathbf{y}}_n(h)$ be vector of initial h -step forecasts, made at time n , stacked in same order as \mathbf{y}_t .

Forecasting notation

Let $\hat{\mathbf{y}}_n(h)$ be vector of initial h -step forecasts,
made at time n , stacked in same order as \mathbf{y}_t .
(In general, they will not “add up”.)

Forecasting notation

Let $\hat{\mathbf{y}}_n(h)$ be vector of initial h -step forecasts, made at time n , stacked in same order as \mathbf{y}_t .
(In general, they will not “add up”.)

Reconciled forecasts must be of the form:

$$\tilde{\mathbf{y}}_n(h) = \mathbf{S}\mathbf{P}\hat{\mathbf{y}}_n(h)$$

for some matrix \mathbf{P} .

Forecasting notation

Let $\hat{\mathbf{y}}_n(h)$ be vector of initial h -step forecasts, made at time n , stacked in same order as \mathbf{y}_t .
(In general, they will not “add up”.)

Reconciled forecasts must be of the form:

$$\tilde{\mathbf{y}}_n(h) = \mathbf{S}\mathbf{P}\hat{\mathbf{y}}_n(h)$$

for some matrix \mathbf{P} .

- \mathbf{P} projects base forecasts $\hat{\mathbf{y}}_n(h)$ to bottom level.

Forecasting notation

Let $\hat{\mathbf{y}}_n(h)$ be vector of initial h -step forecasts, made at time n , stacked in same order as \mathbf{y}_t .
(In general, they will not “add up”.)

Reconciled forecasts must be of the form:

$$\tilde{\mathbf{y}}_n(h) = \mathbf{S}\mathbf{P}\hat{\mathbf{y}}_n(h)$$

for some matrix \mathbf{P} .

- \mathbf{P} projects base forecasts $\hat{\mathbf{y}}_n(h)$ to bottom level.
- \mathbf{S} adds them up

General properties: bias and variance

$$\tilde{\mathbf{y}}_n(h) = S P \hat{\mathbf{y}}_n(h)$$

General properties: bias and variance

$$\tilde{\mathbf{y}}_n(h) = \mathbf{S}P\hat{\mathbf{y}}_n(h)$$

Bias

Reconciled forecasts are unbiased iff $\mathbf{SPS} = \mathbf{S}$.

General properties: bias and variance

$$\tilde{\mathbf{y}}_n(h) = \mathbf{S}P\hat{\mathbf{y}}_n(h)$$

Bias

Reconciled forecasts are unbiased iff $\mathbf{SPS} = \mathbf{S}$.

Variance

Let error variance of h -step base forecasts $\hat{\mathbf{y}}_n(h)$ be

$$\mathbf{W}_h = \text{Var}[\mathbf{y}_{n+h} - \hat{\mathbf{y}}_n(h) \mid \mathbf{y}_1, \dots, \mathbf{y}_n]$$

Then error variance of the reconciled forecasts is

$$\text{Var}[\mathbf{y}_{n+h} - \tilde{\mathbf{y}}_n(h) \mid \mathbf{y}_1, \dots, \mathbf{y}_n] = \mathbf{SPW}_h P' S'$$

Optimal forecast reconciliation

$$\tilde{\mathbf{y}}_n(h) = \mathcal{S}\mathcal{P}\hat{\mathbf{y}}_n(h)$$

Optimal forecast reconciliation

$$\tilde{\mathbf{y}}_n(h) = \mathbf{S}\mathbf{P}\hat{\mathbf{y}}_n(h)$$

Theorem: MinT Reconciliation

If \mathbf{P} satisfies $\mathbf{SPS} = \mathbf{S}$, then

$$\min_{\mathbf{P}} = \text{trace}[\mathbf{SPW}_h \mathbf{P}' \mathbf{S}']$$

has solution $\mathbf{P} = (\mathbf{S}' \mathbf{W}_h^{-1} \mathbf{S})^{-1} \mathbf{S}' \mathbf{W}_h^{-1}$.

Optimal forecast reconciliation

$$\tilde{\mathbf{y}}_n(h) = \mathbf{S}P\hat{\mathbf{y}}_n(h)$$

Theorem: MinT Reconciliation

If P satisfies $\mathbf{SPS}' = \mathbf{S}$, then

$$\min_P = \text{trace}[\mathbf{SPW}_h P' \mathbf{S}']$$

has solution $P = (\mathbf{S}' \mathbf{W}_h^{-1} \mathbf{S})^{-1} \mathbf{S}' \mathbf{W}_h^{-1}$.

$$\tilde{\mathbf{y}}_n(h) = \mathbf{S}(\mathbf{S}' \mathbf{W}_h^{-1} \mathbf{S})^{-1} \mathbf{S}' \mathbf{W}_h^{-1} \hat{\mathbf{y}}_n(h)$$

Reconciled forecasts

Base forecasts

Optimal forecast reconciliation

$$\tilde{\mathbf{y}}_n(h) = \mathbf{S}(\mathbf{S}'\mathbf{W}_h^{-1}\mathbf{S})^{-1}\mathbf{S}'\mathbf{W}_h^{-1}\hat{\mathbf{y}}_n(h)$$

Reconciled forecasts

Base forecasts

Optimal forecast reconciliation

$$\tilde{\mathbf{y}}_n(h) = \mathbf{S}(\mathbf{S}'\mathbf{W}_h^{-1}\mathbf{S})^{-1}\mathbf{S}'\mathbf{W}_h^{-1}\hat{\mathbf{y}}_n(h)$$

Reconciled forecasts

Base forecasts

Assume that $\mathbf{W}_h = k_h \mathbf{W}_1$ to simplify computations.

Optimal forecast reconciliation

$$\tilde{\mathbf{y}}_n(h) = \mathbf{S}(\mathbf{S}'\mathbf{W}_h^{-1}\mathbf{S})^{-1}\mathbf{S}'\mathbf{W}_h^{-1}\hat{\mathbf{y}}_n(h)$$

Reconciled forecasts

Base forecasts

Assume that $\mathbf{W}_h = k_h \mathbf{W}_1$ to simplify computations.

WLS solution

- Approximate \mathbf{W}_1 by its diagonal.

Optimal forecast reconciliation

$$\tilde{\mathbf{y}}_n(h) = \mathbf{S}(\mathbf{S}'\mathbf{W}_h^{-1}\mathbf{S})^{-1}\mathbf{S}'\mathbf{W}_h^{-1}\hat{\mathbf{y}}_n(h)$$

Reconciled forecasts

Base forecasts

Assume that $\mathbf{W}_h = k_h \mathbf{W}_1$ to simplify computations.


WLS solution

- Approximate \mathbf{W}_1 by its diagonal.

GLS solution

- Estimate \mathbf{W}_1 using shrinkage to the diagonal.


Australian tourism



Australian tourism

Hierarchy:

- States (7)
 - Zones (27)
 - Regions (82)



Australian tourism

Hierarchy:


- States (7)
- Zones (27)
- Regions (82)



Base forecasts


ETS (exponential smoothing)
models

- -3% to 0
- 0 to 3%
- > 3%




Base forecasts

Domestic tourism forecasts: Total




Base forecasts

Domestic tourism forecasts: NSW




Base forecasts

Domestic tourism forecasts: VIC




Base forecasts

Domestic tourism forecasts: Nth.Coast.NSW




Base forecasts

Domestic tourism forecasts: Metro.QLD




Base forecasts

Domestic tourism forecasts: Sth.WA




Base forecasts

Domestic tourism forecasts: X201.Melbourne




Base forecasts

Domestic tourism forecasts: X402.Murraylands



Base forecasts

Domestic tourism forecasts: X809.Daly



Forecast evaluation

Training sets

Test sets $h = 1$



Forecast evaluation

Training sets


Test sets $h = 1$



Forecast evaluation

Training sets


Test sets $h = 1$



Forecast evaluation

Training sets


Test sets $h = 1$



Forecast evaluation

Training sets


Test sets $h = 1$



Forecast evaluation

Training sets


Test sets $h = 1$



Forecast evaluation

Training sets


Test sets $h = 1$



Forecast evaluation

Training sets


Test sets $h = 1$



Forecast evaluation

Training sets


Test sets $h = 1$



Forecast evaluation

Training sets


Test sets $h = 1$



Forecast evaluation

Training sets


Test sets $h = 1$



Forecast evaluation

Training sets


Test sets $h = 1$



Forecast evaluation

Training sets


Test sets $h = 1$



Forecast evaluation

Training sets


Test sets $h = 1$



Forecast evaluation

Training sets


Test sets $h = 1$



Forecast evaluation

Training sets


Test sets $h = 1$



Forecast evaluation

Training sets


Test sets $h = 1$



Forecast evaluation

Training sets


Test sets $h = 1$



Forecast evaluation

Training sets


Test sets $h = 1$



Forecast evaluation

Training sets


Test sets $h = 1$



Forecast evaluation

Training sets


Test sets $h = 2$



Forecast evaluation

Training sets


Test sets $h = 3$



Forecast evaluation

Training sets


Test sets $h = 4$



Forecast evaluation

Training sets


Test sets $h = 5$



Forecast evaluation

Training sets

Test sets $h = 6$




Hierarchy: states, zones, regions

RMSE	Forecast horizon							Ave
	$h = 1$	$h = 2$	$h = 3$	$h = 4$	$h = 5$	$h = 6$		
Australia								
Base	1762.04	1770.29	1766.02	1818.82	1705.35	1721.17	1757.28	
Bottom	1736.92	1742.69	1722.79	1752.74	1666.73	1687.43	1718.22	
WLS	1705.21	1715.87	1703.75	1729.56	1627.79	1661.24	1690.57	
GLS	1704.64	1715.60	1705.31	1729.04	1626.36	1661.64	1690.43	
States								
Base	399.77	404.16	401.92	407.26	395.38	401.17	401.61	
Bottom	404.29	406.95	404.96	409.02	399.80	401.55	404.43	
WLS	398.84	402.12	400.71	405.03	394.76	398.23	399.95	
GLS	398.84	402.16	400.86	405.03	394.59	398.22	399.95	
Regions								
Base	93.15	93.38	93.45	93.79	93.50	93.56	93.47	
Bottom	93.15	93.38	93.45	93.79	93.50	93.56	93.47	
WLS	93.02	93.32	93.38	93.72	93.39	93.53	93.39	
GLS	92.98	93.27	93.34	93.66	93.34	93.46	93.34	


Outline

- 1 Sub-daily time series analysis
- 2 Time series feature analysis
- 3 Time series anomaly detection
- 4 Probabilistic electricity demand analysis
- 5 Forecast reconciliation
- 6 Temporal hierarchies
- 7 R packages

Temporal hierarchies




Temporal hierarchies



Basic idea:


- Forecast series at each available frequency.
- Optimally reconcile forecasts within the same year.

Monthly series



■ $k = 2, 4, 12$ nodes


Monthly series



■ $k = 2, 4, 12$ nodes

■ $k = 3, 6, 12$ nodes

Monthly series



- $k = 2, 4, 12$ nodes
- $k = 3, 6, 12$ nodes
- Why not $k = 2, 3, 4, 6, 12$ nodes?

Monthly data

$$\left(\begin{array}{c}
 A \\
 SemiA_1 \\
 SemiA_2 \\
 FourM_1 \\
 FourM_2 \\
 FourM_3 \\
 Q_1 \\
 \vdots \\
 Q_4 \\
 BiM_1 \\
 \vdots \\
 BiM_6 \\
 M_1 \\
 \vdots \\
 M_{12}
 \end{array} \right) = \left(\begin{array}{ccccccccc}
 1 & 1 & 1 & 1 & 1 & 1 & 1 & 1 & 1 \\
 1 & 1 & 1 & 1 & 1 & 1 & 0 & 0 & 0 \\
 0 & 0 & 0 & 0 & 0 & 0 & 1 & 1 & 1 \\
 1 & 1 & 1 & 1 & 0 & 0 & 0 & 0 & 0 \\
 0 & 0 & 0 & 0 & 1 & 1 & 1 & 0 & 0 \\
 0 & 0 & 0 & 0 & 0 & 0 & 0 & 1 & 1 \\
 1 & 1 & 1 & 0 & 0 & 0 & 0 & 0 & 0 \\
 \vdots & & & & & \vdots & & & \\
 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 1 \\
 1 & 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
 \vdots & & & & & \vdots & & & \\
 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
 \end{array} \right) \underbrace{\left(\begin{array}{c}
 M_1 \\
 M_2 \\
 M_3 \\
 M_4 \\
 M_5 \\
 M_6 \\
 M_7 \\
 M_8 \\
 M_9 \\
 M_{10} \\
 M_{11} \\
 M_{12}
 \end{array} \right)}_{b_t} \quad I_{12}$$

(28×1) s

In general

For a time series y_1, \dots, y_T , observed at frequency m , we generate aggregate series

$$y_j^{[k]} = \sum_{t=1+(j-1)k}^{jk} y_t, \quad \text{for } j = 1, \dots, \lfloor T/k \rfloor$$

- $k \in F(m) = \{\text{factors of } m\}$.

In general

For a time series y_1, \dots, y_T , observed at frequency m , we generate aggregate series

$$y_j^{[k]} = \sum_{t=1+(j-1)k}^{jk} y_t, \quad \text{for } j = 1, \dots, \lfloor T/k \rfloor$$

- $k \in F(m) = \{\text{factors of } m\}$.
- A single unique hierarchy is only possible when there are no coprime pairs in $F(m)$.


In general

For a time series y_1, \dots, y_T , observed at frequency m , we generate aggregate series

$$y_j^{[k]} = \sum_{t=1+(j-1)k}^{jk} y_t, \quad \text{for } j = 1, \dots, \lfloor T/k \rfloor$$

- $k \in F(m) = \{\text{factors of } m\}$.
- A single unique hierarchy is only possible when there are no coprime pairs in $F(m)$.
- $M_k = m/k$ is seasonal period of aggregated series.


UK Accidents and Emergency Demand



Outline

- 1 Sub-daily time series analysis
- 2 Time series feature analysis
- 3 Time series anomaly detection
- 4 Probabilistic electricity demand analysis
- 5 Forecast reconciliation
- 6 Temporal hierarchies
- 7 R packages

R packages



Papers, packages and
slides available at
robjhyndman.com