1179

1,52 DIA.
0,51
1,02 DIA.
16,87

1179-0-00-XX-00-00-33-0
Solder mount in 1,12 mounting hole

9872

0,81
1,83 DIA.
1,14 DIA.
7,32

9872-0-00-XX-00-00-33-0
Solder mount in 1,24 mounting hole

## 2381

0,25
2,03 DIA.
1,27 DIA.
3,94

2381-0-00-XX-00-00-33-0
Solder mount in 1,37 mounting hole

9265

0,64
1,83 DIA.
1,5 DIA.
6,73

9265-0-00-XX-00-00-38-0
Solder mount in 1,6 mounting hole

6142

2,54 DIA.
0,51
1,52 DIA.
15,49

6142-0-00-XX-00-00-33-0
Solder mount in 1,63 mounting hole

9022

0,64
3,18 DIA.
1,57 DIA.
4,7

9022-0-00-XX-00-00-33-0
Solder mount in 1,68 mounting hole
Also available on 24mm wide carrier tape: 1,500 parts per 330mm reel.
Order as: 9022-0-57-XX-00-00-33-0

8086

0,64
4,75 DIA.
1,91 DIA.
8,26

8086-0-00-XX-00-00-33-0
Solder mount in 2,01 mounting hole

SPECIFICATIONS

PIN MATERIAL:
Brass Alloy 360, 1/2 Hard
(Except where noted)

DIMENSION IN INCHES
TOLERANCES ON:
LENGTHS: ±0,13
DIAMETERS: ±0,05
ANGLES: ± 2°

RoHS
2002/95/EC

ORDER CODE: XXXX - X - 00 - XX - 00 - 00 - XX - 0

BASIC PART #

SPECIFY PIN FINISH:
01 5,08µm TIN/LEAD OVER NICKEL
◇ **80** 5,08µm TIN OVER NICKEL (RoHS)
◇ **15** 0,25µm GOLD OVER NICKEL (RoHS)
◇ **21** 0,51µm GOLD OVER NICKEL (RoHS)
◇ **34** 1,27µm GOLD OVER NICKEL (RoHS)