Probably Approximately Correct String Theory: A Verification Discipline for the Landscape

Rob Mitchell

PACLAND · github.com/robmitchellengineering-hub/pacland

Abstract

The string landscape contains on the order of 10^{500} vacua, and no experiment distinguishes most of them, so "unified string theory" is two conflated problems — *verification* (does some vacuum match our universe?) and *selection* (why that one?). We separate them, and build a verification discipline for the first: a probably-approximately-correct certificate that bounds a candidate's error even when the verifier is itself approximate (Theorem 2), a proof that search over the flux superpotential is not evolvable (Denef–Douglas uniformity + Valiant's contrapositive, measured on 380 real SUSY vacua), a measured log-uniform prior for $|W_0|$ (CDF linearity $R^2 = 0.92$), a certified Mitchell Verification Deficit that is total today ($m = 0$ validated oracle outputs), and a boundary map — a taxonomy of the four senses in which the problem is "uncomputable," each with its certified positive remainder. We do not claim to select the vacuum. We claim something narrower and we believe more useful: *the field currently has no verification layer for its unverifiable theory, and this is one.*

1. Introduction

String theory is not a single theory but a family of ~10^{500} metastable vacua — the *landscape* [1,2,3]. "Unified string theory" decomposes into two claims the literature habitually fuses: verification (there exists a vacuum matching our universe) and selection (a measure singles it out). The first is checkable in principle; the second is the open measure problem. This paper concerns the first, and does so rigorously.

Two facts make verification hard. First, the search space is astronomically large. Second, and more fundamentally, the *verifier is not ground truth*: the map from a compactification to its low-energy observables is computed by an approximate solver, with systematic error from α' corrections, non-perturbative truncations, and the Kaluza–Klein tower. Any rigorous statement about verification must contend with an *imperfect labeler*.

We import the framework built for exactly this regime — Valiant's probably-approximately-correct (PAC) learning [4] — and apply it to verification itself. The result is a certificate whose two error terms are separately estimable, three consequences (a verify/search separation, a necessary-condition conjecture, and a measurable-physics bound), and, on running the machinery against real data, a set of empirical findings summarized in the abstract.

Field context. Independently of us, the field is converging on verification from three directions: Michael Douglas is formalizing QFT in Lean 4 [13]; PhysProver is the first LLM theorem-prover for physics [14]; and a 2025 line formalizes *falsification* targets at a collider [15]. Our contribution is the complementary angle: guards, certificates, and measured limits — verification for the regime where ground truth is absent.

2. The two-level certificate

Let X be the observable space, D a measure over X, c* : X → Y the target (our universe's true physics), and h : X → Y a candidate's prediction. We observe c* only through an approximate oracle Ô. Define

$$g(x) = |h(x) - \hat{O}(x)|, \quad e(x) = |\hat{O}(x) - c^*(x)|,$$

and the true error

$$\mathrm{err}_D(h) = \Pr_{x \sim D}[\, |h(x) - c^*(x)| > \varepsilon \,].$$

The triangle inequality splits the unobservable error into two estimable pieces, and a union bound gives, for any $\beta \in (0, \varepsilon)$,

$$\mathrm{err}_D(h) \;\le\; p_g(\varepsilon - \beta) + p_e(\beta), \qquad (\star)$$

where $p_g(\tau) = \Pr[g > \tau]$ and $p_e(\beta) = \Pr[e > \beta]$. The two terms are *separately estimable*: p_g compares two things we can both compute (h and Ô), while p_e is the oracle's own failure rate, estimated by validating Ô on points where c* is known.

Theorem 1 (candidate bound). *For fixed h, with n samples $x_1 \ldots x_n \sim D$ and empirical disagreement rate $\hat{p}_g$, with probability $\ge 1 - \delta_s$:*

$$p_g(\varepsilon - \beta) \;\le\; \hat{p}_g + \sqrt{\ln(1/\delta_s) / (2n)}.$$

Theorem 1′ (oracle bound). *On m points where c* is known, with empirical exceedance $\hat{p}_e$, with probability $\ge 1 - \delta_e$:*

$$p_e(\beta) \;\le\; \hat{p}_e + \sqrt{\ln(1/\delta_e) / (2m)}.$$

Theorem 2 (two-level Valiant certificate). *With probability $\ge 1 - \delta_s - \delta_e$:*

$$\mathrm{err}_D(h) \;\le\; \hat{p}_g + \hat{p}_e + \sqrt{\ln(1/\delta_s)/(2n)} + \sqrt{\ln(1/\delta_e)/(2m)}.$$

The certificate is the tuple $(\varepsilon, \beta, n, m, \hat{p}_g, \hat{p}_e, \delta_s, \delta_e)$. This is verification in the presence of an imperfect labeler — the generalization of PAC's clean oracle that string theory actually requires.

3. Verification without learnability; search with it

Theorem 2 never invokes the complexity of the hypothesis class: **verifying what you are handed is cheap**, a Bernoulli-rate estimate. *Search* is different — it selects the empirically best of many hypotheses, which is biased, and bounding the bias needs uniform convergence (VC dimension, or the statistical-query dimension SQdim). The consequence is a graceful-degradation statement: if search is infeasible, the verifier survives and can still certify any externally proposed candidate.

4. The measurable-physics bound, and the total deficit

Make D finite: X is a finite list of N log-space observables. Then the candidate term is *exact* — no sampling:

$$p_g(\varepsilon - \beta) = \Sigma_i\, w_i \cdot 1[\, |\ln(h(x_i)/\hat{O}(x_i))| > \varepsilon - \beta \,],$$

and the certificate collapses to the oracle term alone, bounded by **m, the number of validated oracle outputs** — observables that are simultaneously *measured* (c* known), *computable* (Ô evaluates them), and *validated* (Ô calibrated against c*).

The honest finding. For our universe, c* is known but Ô is not (the compactification is unknown); for exact/tractable backgrounds, Ô is computable but they are not our universe. The intersection — the true m — is zero today. With m = 0 the radius sqrt(ln(1/δ_e)/(2m)) is infinite: the certificate is vacuous, and the verification deficit is *total*, not "~31%" as an earlier conflation of "measured" with "validated" suggested. The binding constraint is validated oracle outputs, not compute; each observable that gains a calibrated error model moves m from 0 toward the ~10–19 targets and shrinks the radius from ∞.

5. The negative result: W_0 is log-uniform, hence not evolvable

Denef–Douglas [6] shows the flux superpotential W_0 is statistically uniform in the complex plane across the flux ensemble, so the map flux → W_0 carries ~zero mutual information. We measured the distribution directly.

Measurement. 380 SUSY flux vacua, sampled by JAXVacua's natural (ISD) measure [11]. The empirical CDF of $\log|W_0|$ is linear to $R^2 = 0.92$ (the $|W_0|^2$ CDF is not, $R^2 = 0.45$):

variable		CDF linearity R^2	
log\	W_0\	(log-uniform)	0.923
\	W_0\	² (area-uniform)	0.450

So $|W_0|$ is log-uniform — the standard KKLT prior, now measured rather than assumed. (Uniform-in-a-box sampling does *not* reproduce this: $R^2 \approx 0.2$–0.3 regardless of box width; the natural measure is required.)

Valiant's evolvability theorem [5]: evolvable ⇒ learnable. A log-uniform (hence zero-information) map is not learnable, hence — by the contrapositive — **not evolvable**: no certificate-only evolutionary search over W_0 can converge. The graceful-degradation statement of §3 applies: the *search dies, the verifier survives.*

A direct consequence, measured: $P(|W_0| < 1) = 42.6\%$ (so "small W_0" eliminates ~57%, not the ~95% that biased sampling suggested), while the KKLT target $|W_0| \sim 10^{-4}$ lies 7.6 nats below the observed range — its tuning probability is an extrapolation the data cannot confirm.

6. Empirical characterization: structure, constraints, uniformity

Structure mining. A non-linear miner (mutual information with permutation test, plus a ridge-on-quadratic-features learnability test, self-validated on the deterministic

tadpole control at r = 0.99) finds no strong geometric fingerprint in the flux-sector observables: W_0 random (ridge r = 0.10), g_s weakly structured (r = 0.21), the gauge couplings at noise ($r \leq 0.17$). The geometry-pinning structure, if it exists, lives in the observables we have not yet computed (the full spectrum with instanton corrections).

Constraint verification. Treating constraints as certifiable statements — "this constraint eliminates fraction p of the sampled vacua, with confidence $1 - \delta$" — we measure, on the natural-measure sample:

constraint	eliminates	95% CI
weak coupling ($g_s < 1$)	68.7%	[59%, 78%]
small W_0 ($\|W_0\| < 1$)	57.4%	(measured)

A single constraint eliminates a large, certified fraction; a chain of them narrows by elimination, which is the search-free route the framework is designed for.

7. The boundary of the computable

The object we actually want — pin down the compactification — is uncomputable in several distinct senses. The contribution of this paper is to *name* them and certify each as data, so that "uncomputable" is a map, not a wall:

sense	meaning	the move
intractable	answer exists, no feasible algorithm	prove intractability
unmeasurable	answer exists, data/ground-truth absent	compute the deficit
underdetermined	no unique answer exists	compute the set's invariants
undecidable	provably no algorithm	prove undecidability

Seven questions are certified to date (search over W_0 = intractable; verify-today and KKLT-tail and full-EFT and small-Λ = unmeasurable; the measure and the inverse problem = underdetermined). None is undecidable — the landscape problem is an *epistemic* and *underdetermination* limit, not a Turing limit. That is itself a finding: the path forward is not "invent a faster computer" but "build the missing oracles" and "compute the invariants of the underdetermined set."

8. Discussion and limits

The framework does not unify. It does not select a vacuum; the measure problem remains open physics. It does not eliminate oracle error; it bounds it. Every certificate is conditional on the stipulated observable measure D.

What we do not claim. No new prediction, no measure, no unique compactification. The negative result is scoped to the IIB flux corner and to W_0 (g_s is weakly structured; the full-spectrum observables are unmeasured). The log-uniform prior is measured over 3.7 nats; its extension to the KKLT tail is explicitly an extrapolation.

What we do claim. A verification discipline for a theory that currently has none: a certified deficit, a mutation-tested computation vault, a measured prior, a negative result, and a boundary map — built in the exact gap the field's leaders (Douglas [13], PhysProver [14]) are independently formalizing. The two approaches — our

guard/certificate discipline and their Lean formalization — are complementary, not competing.

9. Conclusion

The obstacle to unified string theory is a shortage of *checkable claims*, and the deepest checkable claim in reach is not "is this vacuum ours?" but "is the compactification→observables map learnable?" — answered negatively for W_o, and mapped for the rest. Verification, done with Valiant's guarantees, is the honest first move; the boundary map makes the *second* move (where does computation end?) equally honest. We have not solved the theory. We have built, tested, and measured the missing verification layer — and the field's convergence on the same gap suggests that is the right thing to have built.

References

[1] Bousso & Polchinski, *Quantization of four-form fluxes…*, JHEP 2000.
[2] Douglas, *The statistics of string/M theory vacua*, JHEP 2003.
[3] Susskind, *The anthropic landscape of string theory*, 2003.
[4] Valiant, *A theory of the learnable*, CACM 27(11), 1984.
[5] Valiant, *Evolvability*, J. ACM 56(1), 2009.
[6] Denef & Douglas, *Distributions of flux vacua*, hep-th/0404116.
[7] Kearns, *Efficient noise-tolerant learning from statistical queries*, J. ACM 45(6), 1998.
[8] Feldman, *A complete characterization of statistical query learning…*, FOCS 2009.
[9] Valiant, *Probably Approximately Correct*, Basic Books, 2013.
[10] Demirtas et al., *CYTools*, arXiv:2211.03823.
[11] Dubey, Krippendorf, Schachner, *JAXVacua*, arXiv:2306.06160.
[12] Kachru, Kallosh, Linde, Trivedi, *de Sitter vacua in string theory*, hep-th/0301240.
[13] Douglas et al., *Formalizing QFT in Lean 4*, arXiv:2603.15770.
[14] *PhysProver*, arXiv:2601.15737.
[15] *How to falsify string theory at a collider*, arXiv:2412.13192, PRR 2025.