Story space: salient concepts as volumes in a story-conditioned latent space

1 Problem

Definition 1 (Story, paragraphs)**.** *A story $s \in \mathcal{T}$ is a string of text from the space of texts $\mathcal{T}$. It is split into paragraphs $p_1, \ldots, p_N \in \mathcal{T}$.*

s	the story, a string of text
$\mathcal{T}$	the space of all strings of text
p_i	the story's i-th paragraph
N	the number of paragraphs in the story

Definition 2 (Salient concept)**.** *A salient concept $c \in \mathcal{T}$ is a string of text naming an idea the story contains. It need not be copied out of the story: the idea may never be mentioned directly. A story comes with a set of salient concepts $C_s = \{c_1, \ldots, c_K\}$.*

c	a salient concept, a string of text naming an idea
C_s	the set of the story's salient concepts
K	the number of salient concepts

Definition 3 (Story state)**.** *A story state σ is a structured description of a moment of the story (characters, location, event, action). A fixed template τ renders it as text, $\tau(\sigma) \in \mathcal{T}$.*

σ	a story state: characters, location, event, action
τ	the fixed template that writes a state out as text
$\tau(\sigma)$	the text of state σ

Definition 4 (Story space)**.** *The story space $\mathcal{Z}_s \subseteq \mathbb{R}^d$ is the latent space of story s. Every salient concept c is a volume $B_c \subset \mathcal{Z}_s$ and every story state σ is a point $z(\sigma) \in \mathcal{Z}_s$. A state is related to a concept when its point lies inside the concept's volume. Two concepts are related when their volumes overlap.*

$\mathcal{Z}_s$	the story space of story s
d	the number of dimensions of the story space
$\mathbb{R}^d$	the space of vectors of d real numbers
B_c	the volume of concept c in the story space
$z(\sigma)$	the point of state σ in the story space

Figure 1 shows two overlapping concept volumes and a story moving through them.

The story space is a conditioning of the general latent space of all texts: of all the places a text can occupy in the general space, the story picks out the region that it, its concepts and its states occupy.




Figure 1: Illustration, not computed from data. Two concept volumes in a story space and the trajectory of SCENE_1's states in story order. z_1 and z_2 are two of the story space's d dimensions; σ_k marks the point of the story's k-th state. σ_1, a warm sunny day, lies in neither volume. σ_2, Michael and Sarah setting out for a walk, lies only in B_{Michael}. σ_3, an unexpected knock at their door, and σ_4, Michael going down to check, lie in the overlap. σ_5, Sarah calling "Who is it?", and σ_6, no answer coming, lie only in $B_{\text{surprise visitor}}$.

Tasks.

(T1) Define the story space for s, given s and C_s: the operation `encode_basis`.

(T2) Map a story state into the story space: the operation `encode_from_state`. States are described with arbitrary text, yet two states described with the same words must land on the same point.

(T3) Find the boundaries of the volumes of the salient concepts.

Requirements.

Requirement 1 (Non-degenerate volume)**.** *The volume of a concept has non-zero width along every dimension of $\mathcal{Z}_s$.*

Requirement 2 (Containment)**.** *A state related to concept c maps to a point inside B_c. A state unrelated to c maps outside it.*

Requirement 3 (Multiple membership)**.** *A state may be related to several concepts at once, so volumes may overlap and a point may lie in several of them.*

Requirement 4 (Identity)**.** *Equal states map to the same point: $\sigma = \sigma' \Rightarrow z(\sigma) = z(\sigma')$.*

Requirement 5 (Separation)**.** *Different states map to different points: $\sigma \neq \sigma' \Rightarrow z(\sigma) \neq z(\sigma')$.*

σ' a second story state, compared with σ

2 How Qwen encodes a text

Qwen is used as it is: frozen, nothing in it trained. The figures were measured with Qwen3-8B, which has $L = 36$ layers and a latent space of $D = 4096$ dimensions.

A point in latent space. Qwen splits a text t into tokens $k = 0, \ldots, n-1$. After each layer ℓ it holds, for every token, a point $h_{\ell,k}(t)$ in its latent space $\mathbb{R}^D$; $\ell = 0$ is the token's lookup before any layer.

The latent space. $\mathbb{R}^D$ is a real vector space with the dot product $u \cdot v = \sum_{i=1}^{D} u_i v_i$, which gives lengths, angles and distances. All layers share it. The points are not normalised, and their lengths are bounded: the longest here is about 12,000. The points crowd into a narrow cone whose apex is the space's zero, because training gives every point one large common component.

One point per token. Qwen gives one point per token, not one per text. Each point summarises the text up to and including its token. The text "Bob" gives one point after each layer; a passage of n tokens gives n.

A token's path through the layers. Following one token from layer 0 to layer L gives a trajectory of $L + 1$ points. Each step is one layer: the layer analyses the point, attending to the points of the tokens before it and passing the result through a feed-forward network, and adds what it finds to the point:

$$h_{\ell,k}(t) = h_{\ell-1,k}(t) + \Delta_{\ell,k}(t). \tag{1}$$

Where the information is. In each point itself: in where it lies along the space's feature directions, not in how the points relate to each other.

Token 0**.** From layer 7 on, the first token's point becomes an attention sink: about 185 times longer than the others and the same for every text, whatever its first word. It is left out of everything below.

t	any text given to Qwen
k	a token's position in the text, starting at 0
n	the number of tokens in the text
ℓ	a layer of Qwen; 0 means the lookup before the first layer
L	the number of Qwen's layers
D	the number of dimensions of Qwen's latent space
$\mathbb{R}^D$	Qwen's latent space
$h_{\ell,k}(t)$	the point in $\mathbb{R}^D$ that Qwen holds for token k of text t after layer ℓ
u, v	any two points of $\mathbb{R}^D$
u_i	the i-th of the D coordinates of u
$u \cdot v$	the dot product of u and v
$\Delta_{\ell,k}(t)$	what layer ℓ adds to token k's point

2.1 Extending a text

Three texts share a beginning:

A	"Bob buys Alice coffee"
A + B	"Bob buys Alice coffee, because he loves her"
A + C	"Bob buys Alice coffee and bagels with salmon"

B adds Bob's motivation; C adds a detail that changes nothing important. Figure 2 shows their points after layer 16.




Figure 2: The points of A, A + B and A + C after layer 16, token 0 ("Bob") left out. Black: A's points, shared by all three texts. Orange: the points B adds after A. Blue: the points C adds after A. Lines join the points in reading order. The 13 points live in $\mathbb{R}^{4096}$; they are drawn along the two directions in which they differ most, which hold 34% of their spread.

Salient information. Write $I(t)$ for the salient information a text t carries, and $V(t)$ for the volume that surrounds text t. We take as given:

$$\begin{aligned} |V(A)| &\approx |V(B)|, \qquad |V(A)| > |V(C)|, \\ |V(A+B)| &\gg |V(A+C)|, \qquad |V(A)| \approx |V(A+C)|. \end{aligned} \tag{2}$$

What remains to be found is how Qwen encodes and represents this information.

$I(t)$	the salient information text t carries
$V(t)$	the volume that surrounds text t
$\lvert V(t)\rvert$	the size of that volume

Shannon information. The Shannon information of a text under Qwen is the number of bits Qwen needs to predict it, token by token:

$$H(t) = -\sum_k \log_2 p\big(\text{token}_k \mid \text{tokens before it}\big), \qquad H(B \mid A) = H(A+B) - H(A). \tag{3}$$

$H(t)$	the Shannon information of text t under Qwen, in bits
$p(\text{token}_k \mid \cdot)$	the probability Qwen gives token k after reading the tokens before it
$H(B \mid A)$	the bits B costs once A has been read

Every token is scored, the first one included, by starting each text with Qwen's document separator.

text	H (bits)
A	63.4
B	50.8
C	72.6
A + B	92.1
A + C	111.9
B, after A: $H(B \mid A)$	28.7
C, after A: $H(C \mid A)$	48.6

Table 1: The Shannon information of every text under Qwen3-8B.

salient information	Shannon information	holds
$\lvert V(A)\rvert \approx \lvert V(B)\rvert$	$H(A) = 63.4$, $H(B) = 50.8$	no: A costs a quarter more
$\lvert V(A)\rvert > \lvert V(C)\rvert$	$H(A) = 63.4$, $H(C) = 72.6$	no: C costs more
$\lvert V(A+B)\rvert \gg \lvert V(A+C)\rvert$	$H(A+B) = 92.1$, $H(A+C) = 111.9$	no: the reverse
$\lvert V(A)\rvert \approx \lvert V(A+C)\rvert$	$H(A) = 63.4$, $H(A+C) = 111.9$	no: A + C costs 76% more

Table 2: The relations of salient information, tested with Shannon information.

None of the four relations holds for Shannon information (Tables 1 to 2). Every added token costs bits, so a longer text always carries more, and what costs most is what surprises Qwen: "salmon" costs 16.4 bits, "her" in "because he loves her" 0.4. Salient information is therefore not what Qwen's surprise measures.

2.2 Properties of the function that measures salient information

The data give the function I three properties:

1. **It is not surprise.** Shannon information breaks all four relations (Table 2), so the function cannot be built from Qwen's token probabilities.

2. **It is not additive over tokens.** $\lvert V(A)\rvert \approx \lvert V(A+C)\rvert$ although A + C has five more tokens than A, so the function must give C's points almost nothing while giving B's a lot.

3. **It is not distance.** B and C move the points by about the same amount: after layer 16, the last points of A + B and A + C lie equally far from A's last point (cosine 0.34 and 0.37, distance 96 and 95). They move them in different directions (Figure 2), so the function must tell directions apart.

Together: the function is a projection onto a subspace of Qwen's latent space that keeps the directions B's points move in and discards the directions C's points move in.

2.3 Movement

Figure 3 shows the points of A, B and C as areas with their centroids after layers 1, 10, 20 and 36.

Figure 4 runs A, B, C, A + B and A + C through Qwen separately and draws the area of each.

Adding B or C never moves A's points: inside A + B and A + C they stay within 2.4% of their length of where A alone puts them, which is rounding. Qwen reads left to right, so A's tokens

cannot see what follows them. B's and C's tokens do see A, and A moves their points away from where they sit alone, by a share of their length that grows with depth and then falls:

after layer	1	10	16	20	36
distance from where they sit alone	16–29%	51–86%	64–84%	59–81%	24–59%

Everything A + B means beyond A is therefore written into B's points. The areas in Figures 3 and 4 do not represent the meaning of a sentence: an area only shows how spread out one text's token points are. What reading A does to B is the drift: the gap between where B's points sit alone and where they sit inside A + B.

The areas do not measure salient information either:

1. **Their size does not grow with salient information.** From layer 10 on, A + C's points are more spread out than A + B's, although $|V(A+B)| \gg |V(A+C)|$.

2. **Their centroids do not tell B from C by distance.** A + B's and A + C's centroids lie equally far from A's centroid. They lie in different directions from it, as the last points do in the properties above, so the two centroids are as far from each other as from A's.

after layer	1	10	16	20	36
spread of A + B	10.2	43.4	54.5	71.0	59.6
spread of A + C	10.2	47.6	58.8	75.1	67.7
distance of A + B's centroid from A's	6.3	25.1	31.9	42.0	32.5
distance of A + C's centroid from A's	6.1	25.8	31.6	40.2	30.0
distance between A + B's and A + C's centroids	3.7	23.5	30.3	39.6	30.7

The spread of a text is the root mean square distance of its points from their centroid, measured in $\mathbb{R}^{4096}$, token 0 left out.

Conclusion. Nothing in Figures 3 and 4 or in these tables indicates that Qwen understands which information is salient.




Figure 3: The points of A, A + B and A + C after layers 1, 10, 20 and 36, token 0 ("Bob") left out. Black: A's points. Orange: the points B adds after A. Blue: the points C adds after A. Each shaded area is the smallest polygon around one colour's points; the cross is their centroid. Each panel draws its layer's 13 points along the two directions in which they differ most, with the share of their spread those directions hold in the title.




Figure 4: A, B, C, A + B and A + C, each run through Qwen on its own, after layers 1, 10, 20 and 36, every text's token 0 left out. Filled areas: A, B and C alone. Dashed outlines and hollow circles: A + B (left) and A + C (right). Crosses: centroids. Both panels of a row are drawn along the same two directions, those in which that layer's points differ most.

3 Transforming Qwen's output

3.1 Volumes that represent salient information

Figures 3 and 4 show the transformations Qwen applies to tokens: they project them into a generic latent space, shaped by the loss Qwen was trained with, next-token prediction. We want to fine-tune or adapt Qwen's output so that volumes begin to represent salient information. In the adapted space, $V(t)$ is the volume that surrounds text t.

$V(t) \cap V(t')$ the overlap of the volumes of texts t and t'

Requirement 6 (Size is salience)**.** *The larger the salient information, the larger the volume:* $I(t) > I(t') \implies |V(t)| > |V(t')|$.

Requirement 7 (Overlap is shared salience)**.** *Volumes that overlap share salient information:* $V(t) \cap V(t')$ *is the salient information* t *and* t' *share.*

For example, with four texts

A "Bob buys Alice coffee"
B "because he loves her"
D "Charlie takes Jean to the movies"
E "where they share an intimate kiss"

the volumes must satisfy

$$\begin{aligned} V(A) \cap V(D) &= \emptyset, \\ V(A+B) \cap V(D+B) &= V(B), \\ V(A+B) \cap V(D+E) &= V(B) \cap V(E) \neq \emptyset, \\ V(A+E) \cap V(D+B) &= V(B) \cap V(E) \neq \emptyset. \end{aligned}$$

Figures 5 and 6 illustrate how these relations would look on transformed points.




Figure 5: Illustration, not computed from data: the first two relations on transformed points. Each dot is the point of one token in the adapted space; z_1 and z_2 are two of its dimensions. A text's volume is the smallest polygon around its tokens' points. Filled areas: texts alone. Dashed outlines and hollow circles: joined texts, whose points are the points of their parts. Hatched: the overlap of the two dashed volumes, the left side of the relation. Left: $V(A) \cap V(D) = \emptyset$; A's and D's volumes do not meet. Right: $V(A + B) \cap V(D + B) = V(B)$; A + B and D + B overlap exactly in B's volume.




Figure 6: Illustration, not computed from data: the last two relations on transformed points, drawn as in Figure 5. B and E overlap. Left: $V(A+B) \cap V(D+E) = V(B) \cap V(E)$; A + B and D + E overlap exactly where B and E do. Right: $V(A+E) \cap V(D+B) = V(B) \cap V(E)$; so do A + E and D + B.

3.2 Alternatives we considered

3.2.1 A deterministic transformation

Could the transformation be computed without learning anything? No. The only deterministic, untrained signal we know of is how much a span moves Qwen's points for the text that follows it. To test it, we put a span after A and a follow-up sentence after the span, and measured how far the follow-up's points move compared with A followed directly by the same follow-up: 1 minus the mean cosine between the two sets of points, averaged over five follow-ups ("Alice smiled.", "She thanked him.", "Then they sat down.", "Alice looked at him.", "She took a sip.").

	span after A	$1 - \cos$ after layer 16
motives	", because he loves her"	0.14
	", since he misses her"	0.14
	", hoping to win her"	0.21
details	"and bagels with salmon"	0.09
	"with oat milk and sugar"	0.07
	"and two glasses of water"	0.07
	", and he pays cash"	0.12
	", with his left hand"	0.14

The signal falls short in two ways:

1. **It does not separate cleanly.** The motives move the follow-ups more than the food details do, but "and he pays cash" and "with his left hand" move them almost as much as the motives.

2. **It gives only a size.** It does not say which directions two texts share, and Requirement 7 needs exactly that.

Choosing the subspace that keeps B's directions and discards C's (Section 2.2) needs examples of what is salient. That is learning, even when it is done in closed form rather than by gradient descent.

3.2.2 How to train

Qwen does not understand which information is salient (Section 2.3), so every approach learns it from our labelled texts and maps it into a new space. They differ only in where the learned part sits. Qwen provides the text understanding; the learned part learns which information is salient. An approach can be used if its learned part is trained by minimising our loss, leaves Qwen's text understanding intact, and has few enough parameters for our few labelled examples. Among those that can, what the learned part sees decides how much it can learn:

approach	trained by our loss	Qwen kept intact	trained parameters	learned part sees	usable
LoRA adapter	yes	yes	44 million	every layer of Qwen	yes
soft prompt	yes	yes	82 thousand	every layer, through its vectors	yes
fully connected head	yes	yes	262 thousand	Qwen's finished points	yes
closed-form head	no	yes	none	Qwen's finished points	no
retraining all of Qwen	yes	no	8.2 billion	every layer of Qwen	no

The soft prompt is counted as 20 vectors of 4096 numbers. The closed-form head fails the first test; retraining all of Qwen fails the second and the third. The head sees only Qwen's finished points, so it can learn salience only if salience is a simple function of them, and nothing indicates that it is (the conclusion of Section 2.3). LoRA works inside every layer of Qwen and has no such condition, so it comes first. The soft prompt also changes what every layer computes, through its vectors, so it comes before the head too.

Sorted from the best option to start with:

approach	mechanism	applicable	because
LoRA adapter	learned changes inside Qwen's layers, then a map into the new space	yes	it changes what Qwen's layers compute, so it does not depend on Qwen already computing what salience is judged from.
soft prompt	learned vectors before the text steer Qwen's layers	yes	like LoRA, it changes what every layer of Qwen computes, so it does not depend on Qwen already computing what salience is judged from; but it is weaker, because it changes only what the layers read, not their weights.
fully connected head	a learned map from Qwen's frozen points into the new space	yes	cheaper than LoRA and leaves Qwen untouched, but works only if salience is a simple function of Qwen's finished points, which nothing indicates (the conclusion of Section 2.3).
closed-form head	a map computed by a formula from labelled texts	no	a formula, such as a difference of means, cannot be fitted to the overlap relations; only minimising a loss can
retraining all of Qwen	all of Qwen's weights learned anew	no	our few labelled examples cannot constrain 8.2 billion parameters: it would overfit them and erase Qwen's knowledge of language, and costs about 130 GB to train and a second copy of Qwen to serve

3.2.3 To do

approach	to do
LoRA adapter	1. Train the adapter and a head on the labelled texts with the volume loss. 2. Serve with the adapter switched on per request.
soft prompt	1. Train the vectors and a head on the labelled texts with the volume loss. 2. Add an endpoint that accepts vectors in place of tokens.
fully connected head	1. Run every labelled text through Qwen once and store its points. 2. Train the head on them with the volume loss. 3. Test the relations on texts it was not trained on.

3.3 Training data

Schema.

```
{"data": [
  {
    "file": "my_file.author",
    "concepts": {
      "love": 1,
      "hate": 2,
      "Michael": 3,
      ...
```

```
    },
    "annotations": [
      {"start_word": 13, "end_word": 25, "concept": 1},
      {"start_word": 18, "end_word": 22, "concept": 2},
      ...
    ]
  },
  ...
]}
```

`start_word` and `end_word` index the author document's words: its prose numbered from 0, in reading order across all its cells, a word being a run of characters between whitespace that contains a letter or a digit.

3.4 LoRA parameters and justification

setting	value	justification
rank r	1	data needed $D \propto N^{-\alpha/\beta}$ with $\lvert\alpha/\beta\rvert \leq 0.18$ [3]: it does not depend on the adapter's size, so the smallest rank
layers	all 7 linear maps of all 36 layers	attention-only LoRA underperforms [2]
trained parameters N	2,727,936	$36 \cdot \sum_{m=1}^{7}(d_m^{\text{in}} + d_m^{\text{out}}) \cdot r = 36 \cdot 75{,}776 \cdot 1$
α	32	[2]
learning rate	10× full fine-tuning	fitted multiplier 9.8 [2]
batch size	small	LoRA tolerates large batches worse [2]

3.5 Dataset size

Dataset. 10 stories, 10,000 words each; about 1,780 annotated spans per story.

Metric: pair accuracy. Take two annotated spans from a story the adapter was not trained on. The adapter is right when their volumes overlap exactly when the two spans share a salient concept. Pair accuracy is the share of such pairs it gets right, over equal numbers of pairs that share a concept and pairs that do not, so guessing scores 0.5.

Predicted value. It cannot be predicted from published results: the smallest dataset they report, 1,000 clinical conversations of about 3,700 words each [1], holds 37 times more text than these 10 stories. It has to be measured: train on 9 stories, measure pair accuracy on the 10th, and repeat for each of the 10.

References

[1] Baseten. Practical LoRA research. October 2025. `labs.baseten.co/articles/practical-lora-research`.

[2] J. Schulman and Thinking Machines Lab. LoRA Without Regret. 2025. `thinkingmachines.ai/blog/lora`.

[3] B. Zhang, Z. Liu, C. Cherry and O. Firat. When Scaling Meets LLM Finetuning: The Effect of Data, Model and Finetuning Method. ICLR 2024. arXiv:2402.17193.