

ARES Protocol — Quick Start

How a robot connects to ARES: register, heartbeat, claim, release

[REST/JSON](#)
[REST/XML](#)
[ROS2DDS](#)

A robot does exactly four things: **register** once, **heartbeat** while it runs, **claim** the space it needs, and **release** when done. Each call carries a **key** and gets back a tiny **decision + reason**. That is the whole protocol — this page is all most integrations need.

REST/JSON, REST/XML and ROS2DDS are shown here — the same four calls in three encodings. Native Zenoh, route planning, scheduling, snapshots and the fine-level “tier-2” calls live in **PROTOCOL-advanced.typ**.

1 Connect

Transport	Address
REST / JSON	<code>http://<host>:8080/ares/v1/...</code> — the default; send <code>application/json</code> (or nothing at all).
REST / XML	<code>http://<host>:8080/ares/v1/...</code> — send/accept <code>application/xml</code> .
ROS2DDS	ROS2 service <code>/ares/v1/...</code> , type <code>ares_interfaces/srv/Json</code> (a JSON string in, a JSON string out), via <code>zenoh-bridge-ros2dds</code> .

Check the server is up (no key needed):

```
curl http://<host>:8080/ares/v1/health
# {"status":"ok","version":"0.1.0"}
```

That is already JSON — the read endpoints answer JSON unless you ask for XML with `Accept: application/xml`.

2 ROS2: build the service type once

REST users — JSON or XML — can skip this section. The ROS2 side reaches every call through one generic service type, `ares_interfaces/srv/Json` (a JSON string in, a JSON string out), relayed by `zenoh-bridge-ros2dds`. Build that interface package once so `ros2 service call` knows the type. Lay out three files:

```
ares_interfaces/
package.xml
CMakeLists.txt
srv/Json.srv
```

`srv/Json.srv` — the service (request above the `---`, response below):

```
string request
---
bool success
string response
```

`package.xml`:

```
<?xml version="1.0"?>
<package format="3">
  <name>ares_interfaces</name>
  <version>0.1.0</version>
  <description>ARES generic JSON service.</description>
  <maintainer email="dev@example.com">dev</maintainer>
  <license>MIT</license>
  <buildtool_depend>ament_cmake</buildtool_depend>
```

```
<buildtool_depend>roslaunch_default_generators</buildtool_depend>
<depend>roslaunch_default_runtime</depend>
<member_of_group>roslaunch_interface_packages</member_of_group>
<export><build_type>ament_cmake</build_type></export>
</package>
```

CMakeLists.txt:

```
cmake_minimum_required(VERSION 3.8)
project(ares_interfaces)
find_package(ament_cmake REQUIRED)
find_package(roslaunch_default_generators REQUIRED)
roslaunch_generate_interfaces(${PROJECT_NAME} "srv/Json.srv")
ament_package()
```

Build it, source it, and point the bridge at the ARES host (note `tcp/`, **not** `tcp://`):

```
colcon build --packages-select ares_interfaces
source install/setup.bash
zenoh-bridge-ros2dds -e tcp/<host>:7447
```

Use CycloneDDS. Run the ROS2 side with `export RMW_IMPLEMENTATION=rmw_cyclonedds_cpp` — the bridge speaks CycloneDDS, and a mismatched middleware lets the request through but drops the reply.

3 The key

Each call may carry a `key`. Two forms:

Key	Meaning
an integer, e.g. <code>1234</code>	a simple numeric password
<code>did:pass=<secret></code>	a password in DID form

The key is set at **register** and bound to the robot. Every later call resends it; a wrong key is rejected with reason `1` (**mismatched key**).

The key is optional. If you omit it the server uses a shared default password — convenient but insecure (anyone can act as a robot that skipped the key). If a robot registers **with** a key, it must keep sending that same key.

4 The reply

Every call answers with the same two fields:

- `decision` — `1` = ok / granted, `0` = denied.
- `reason` — `0` = ok and `1` = mismatched key on **every** call; other values are listed per call below.

In JSON the reply is a flat object: `{"decision":1,"reason":0}`, plus `"blocked"` on a denied claim. In XML the reply root is always `<reply>`. (On XML input the request's outer tag name is ignored — only the inner fields matter.)

5 The four calls

Each call shows the JSON body, the XML body, and the equivalent ROS2 service call — all three are the same request in different clothes. The robot id may be an **integer or a UUID string**; in JSON it is written **quoted** either way (see the note at the end).

5.1 Register

Bind a robot id to a key. Do this once. Optional `<alive>` is the heartbeat interval in seconds (default 2); if no heartbeat arrives for `2×` that, the server marks the robot inactive **and auto-releases all its claims** (so a crashed robot never leaves a zone stuck).

```
POST /ares/v1/robots
{"robot":"7","key":"1234","alive":2}
{"decision":1,"reason":0}
```

```
POST /ares/v1/robots
<reg><robot>7</robot><key>1234</key><alive>2</alive></reg>
<reply><decision>1</decision><reason>0</reason></reply>
```

```
ros2 service call /ares/v1/robots/register ares_interfaces/srv/Json \
  "{request: '{\"robot\":\"7\", \"key\":\"1234\", \"alive\":2}'}"
# response.success=true response.response="{\"decision\":1, \"reason\":0}"
```

reason	meaning
0	registered
1	mismatched key
2	already registered
3	bad id (not an integer or UUID)
4	unsupported key scheme

5.2 Heartbeat

Liveness + where the robot is. The reply is just an ack; the server timestamps it. Send one of `zone` / `node` / `edge`. Use `zone = -1` when the robot holds no zone and its location is unknown.

```
POST /ares/v1/robots/7/heartbeat
{"key":"1234","zone":42} // or "zone":-1 if unknown
{"decision":1,"reason":0}
```

```
POST /ares/v1/robots/7/heartbeat
<hb><key>1234</key><zone>42</zone></hb> <!-- or <zone>-1</zone> if unknown -->
<reply><decision>1</decision><reason>0</reason></reply>
```

```
ros2 service call /ares/v1/robots/heartbeat ares_interfaces/srv/Json \
  "{request: '{\"robot\":\"7\", \"key\":\"1234\", \"zone\":42}'}" # or "zone":-1 if unknown
# response.success=true response.response="{\"decision\":1, \"reason\":0}"
```

reason	meaning
0	ok
1	mismatched key
2	not registered

5.3 Claim

Reserve a zone (or node/edge — the type is in the path). To reserve several at once, repeat `<id>`; it is **all-or-nothing**. On denial, `<blocked>` names the id that stopped it. Two optional fields:

Field	Meaning
<code>access_mode</code>	<code>0</code> = unspecified (→ exclusive), <code>1</code> = exclusive (default), <code>2</code> = shared; <code>3</code> + reserved and rejected.
<code>lease_time</code>	seconds the claim should hold: <code>0</code> (default) = unlimited, <code>X</code> = X seconds.

How several ids are sent. JSON uses an array — `"id": [42]` for one, `"id": [42, 43]` for several. XML repeats the element — `<id>42</id><id>43</id>`. Release takes a **single** id in both, never an array.

Shared zones. On a zone whose capacity is greater than 1, several robots may hold it at once with `access_mode=2` (shared), up to that capacity; once full, a further shared claim is denied with reason `3` (**capacity exceeded**). An **exclusive** claim (`access_mode=1`) on a shared zone still **conflicts** with the current holders (reason `2`).

Lease time, today. `<lease_time>` is accepted but timed wall-clock expiry is not enforced yet: only `0` (unlimited) is currently effective, and a non-zero value is accepted but the claim is **not** auto-expired on a timer today. The expiry that does work is auto-release when a robot stops heartbeating (after `2×` its `alive` interval).

```
POST /ares/v1/claims/zone
{"key":"1234","robot":"7","id":[42]}
{"decision":1,"reason":0}
```

```
// several zones, atomic, exclusive, 30-second lease — id is an ARRAY even for one
{"key":"1234","robot":"7","id":[42,43],"access_mode":1,"lease_time":30}
{"decision":0,"reason":2,"blocked":43}
```

```
POST /ares/v1/claims/zone
<claim><key>1234</key><robot>7</robot><id>42</id></claim>
<reply><decision>1</decision><reason>0</reason></reply>

<!-- several zones, atomic, exclusive, 30-second lease -->
<claim><key>1234</key><robot>7</robot><id>42</id><id>43</id>
  <access_mode>1</access_mode><lease_time>30</lease_time></claim>
<reply><decision>0</decision><reason>2</reason><blocked>43</blocked></reply>
```

```
ros2 service call /ares/v1/claims/zone ares_interfaces/srv/Json \
  "{request: '{\"key\":\"1234\",\"robot\":\"7\",\"id\":[42]}'}"
# response.success=true response.response='{"decision":1,"reason":0}'

# several zones, atomic, exclusive, 30-second lease — id is an ARRAY even for one
ros2 service call /ares/v1/claims/zone ares_interfaces/srv/Json \
  "{request: '{\"key\":\"1234\",\"robot\":\"7\",\"id\":[42,43],\"access_mode\":1,\"lease_time\":30}'}"
# response.success=true response.response='{"decision":0,"reason":2,"blocked":43}'
```

reason	meaning
0	granted
1	mismatched key
2	conflict — someone holds it
3	capacity exceeded (shared zone full)
4	unknown id
5	bad request (no id, or unsupported <code>access_mode</code>)

Claiming a zone reserves everything inside it — so a zone claim and a claim on a node/edge within that zone conflict with each other.

5.4 Release

Give back what this robot holds on a resource.

```
POST /ares/v1/leases/release/zone
{"key":"1234","robot":"7","id":42}
{"decision":1,"reason":0}
```

```
POST /ares/v1/leases/release/zone
<rel><key>1234</key><robot>7</robot><id>42</id></rel>
<reply><decision>1</decision><reason>0</reason></reply>
```

```
ros2 service call /ares/v1/leases/release/zone ares_interfaces/srv/Json \
  "{request: '{\"key\":\"1234\",\"robot\":\"7\",\"id\":42}'}"
# response.success=true response.response='{"decision":1,"reason":0}'
```

reason	meaning
0	released
1	mismatched key
2	no such lease (robot holds nothing there)
3	unknown id

6 A full run

```
B=http://<host>:8080/ares/v1
json() { curl -s -X POST "$B$1" -H 'content-type: application/json' -d "$2"; echo; }
```

```

json /robots          '{"robot":"7","key":"1234"}'
json /claims/zone     '{"key":"1234","robot":"7","id":[42]}'
json /robots/7/heartbeat '{"key":"1234","zone":42}'
json /leases/release/zone '{"key":"1234","robot":"7","id":42}'

```

The same run over XML — register, claim, heartbeat, release:

```

xml() { curl -s -X POST "$B$1" -H 'content-type: application/xml' -d "$2"; echo; }

xml /robots          '<reg><robot>7</robot><key>1234</key></reg>'
xml /claims/zone     '<claim><key>1234</key><robot>7</robot><id>42</id></claim>'
xml /robots/7/heartbeat '<hb><key>1234</key><zone>42</zone></hb>'
xml /leases/release/zone '<rel><key>1234</key><robot>7</robot><id>42</id></rel>'

```

And over ROS2:

```

J=ares_interfaces/srv/Json

ros2 service call /ares/v1/robots/register $J "{request: '{\"robot\": \"7\", \"key\": \"1234\"}'}"
ros2 service call /ares/v1/claims/zone $J "{request: '{\"key\": \"1234\", \"robot\": \"7\", \"id\": [42]}'}"
ros2 service call /ares/v1/robots/heartbeat $J "{request: '{\"robot\": \"7\", \"key\": \"1234\", \"zone\": 42}'}"
ros2 service call /ares/v1/leases/release/zone $J "{request: '{\"key\": \"1234\", \"robot\": \"7\", \"id\": 42}'}"

```

Pick one and stay with it — or don't. The three encodings are the same protocol: the same ids, the same keys, the same `decision` / `reason`. A fleet can mix them freely, one format per client, and a zone claimed over JSON blocks a robot asking over XML or ROS2 exactly as if they shared a transport.

Two shape differences to remember. First, the claim `id` is an **array** in JSON (`{"id": [42]}` even for one) and a **repeated element** in XML (`<id>42</id>`), while release takes a single id in both.

Second, **quote robot and key in JSON** — `{"robot": "7", "key": "1234"}`, not `{"robot": 7, "key": 1234}`. Those two fields accept an integer **or** a UUID, so they are read as text on every transport, and a bare number is rejected with `invalid type: integer ... expected a string or integer scalar`. Every other numeric field — `id`, `zone`, `node`, `edge`, `alive`, `access_mode`, `lease_time` — is a plain JSON number.