smacc2::ISmaccClientBehavior

- stateMachine_
- currentState
- currentOrthogonal

+ ISmaccClientBehavior()
+ ~ISmaccClientBehavior()
+ getStateMachine()
+ getName()
+ requiresClient()
+ requiresComponent()
# runtimeConfigure()
# onEntry()
# onExit()
# postEvent()
# postEvent()
# getCurrentState()
# dispose()
# getNode()
# getLogger()
- executeOnEntry()
- executeOnExit()
- onOrthogonalAllocation()

△

smacc2::SmaccAsyncClient Behavior

- onEntryThread_
- onExitThread_
- postFinishEventFn_
- postSuccessEventFn_
- postFailureEventFn_
- onFinished_
- onSuccess_
- onFailure_
- isShutdownRequested_

+ onOrthogonalAllocation()
+ ~SmaccAsyncClientBehavior()
+ onSuccess()
+ onFinished()
+ onFailure()
+ requestForceFinish()
# postSuccessEvent()
# postFailureEvent()
# dispose()
# isShutdownRequested()
- waitFutureIfNotFinished()
- executeOnEntry()
- executeOnExit()

△

cl_move_group_interface ::CbMoveCartesianRelative

+ offset_
+ scalingFactor_
+ group_
+ moveGroupSmaccClient_

+ CbMoveCartesianRelative()
+ CbMoveCartesianRelative()
+ onEntry()
+ onExit()
+ moveRelativeCartesian()