```
smacc2::ISmaccClientBehavior
  -stateMachine
  currentState
 - currentOrthogonal
 + ISmaccClientBehavior()
 + ~ISmaccClientBehavior()
 + getStateMachine()
 + getName()
 + requiresClient()
 + requiresComponent()
 # runtimeConfigure()
 # onEntry()
 # onExit()
 # postEvent()
# postEvent()
 # getCurrentState()
 # dispose()
 #getNode()
 # getLogger()
- executeOnEntry()
 - executeOnExit()
 - onOrthogonalAllocation()
                 À
smacc2::SmaccAsyncClient
             Behavior
 onEntryThread
 - onExitThread
 - postFinishEventFn
 - postSuccessEventFn
 -postFailureEventFn_
 onFinished_
 - onSuccess
 - onFailure

    isShutdownRequested

 + onOrthogonalAllocation()
 + ~SmaccAsyncClientBehavior()
 + onSuccess()
 + onFinished()
 + onFailure()
 + requestForceFinish()
 # postSuccessEvent()
 # postFailureEvent()
 #dispose()
 # isShutdownRequested()
- waitFutureIfNotFinished()
 - executeOnEntry()
 -executeOnExit()
          ove_group_inte
::CbMoveJoints
                      interface
     cl move
     + scalingFactor
     + jointValueTarget
     + group
     # movegroupClient
     + CbMoveJoints()
     + CbMoveJoints()
     + onEntry()
     + onExit()
     # moveJoints()
                 Δ
   move
          _group
                 _interface
::CbMoveLastTrajectoryInitialState

    backIndex

 CbMoveLastTrajectoryInitial
State()
 CbMoveLastTrajectoryInitial
State()
 ~CbMoveLastTrajectoryInitial
State()
+ onEntry()
```