```
smacc2::ISmaccClientBehavior

    stateMachine

 currentState

    currentOrthogonal

+ ISmaccClientBehavior()
+ ~ISmaccClientBehavior()
+ getStateMachine()
+ getName()
+ requiresClient()
+ requiresComponent()
# runtimeConfigure()
# onEntry()
# onExit()
# postEvent()
# postEvent()
# getCurrentState()
# dispose()
# getNode()
# getLogger()
- executeOnEntry()
executeOnExit()
- onOrthogonalAllocation()
               Λ
smacc2::SmaccAsyncClient
           Behavior

    onEntryThread

    onExitThread

postFinishEventFn
- postSuccessEventFn

    postFailureEventFn

    onFinished

- onSuccess
- onFailure
+ onOrthogonalAllocation()
+ ~SmaccAsyncClientBehavior()
+ onSuccess()
+ onFinished()
+ onFailure()
# postSuccessEvent()
# postFailureEvent()
# dispose()
- waitFutureIfNotFinished()
executeOnEntry()
executeOnExit()
cl_move_base_z::CbWaitNav2
             Nodes
- topicname
 -sub

    receivedAliveMsg

 + CbWaitNav2Nodes()
 + CbWaitNav2Nodes()
 + onEntry()
 - onMessageReceived()
```