```
smacc2::ISmaccClientBehavior

    stateMachine

 currentState

    currentOrthogonal

+ ISmaccClientBehavior()
+ ~ISmaccClientBehavior()
+ getStateMachine()
+ getName()
+ requiresClient()
+ requiresComponent()
# runtimeConfigure()
# onEntry()
# onExit()
# postEvent()
# postEvent()
# getCurrentState()
# dispose()
# getNode()
# getLogger()
- executeOnEntry()
executeOnExit()
- onOrthogonalAllocation()
smacc2::SmaccAsyncClient
            Behavior

    onEntryThread

    onExitThread

postFinishEventFn
- postSuccessEventFn

    postFailureEventFn

    onFinished

- onSuccess

    onFailure

    isShutdownRequested_

+ onOrthogonalAllocation()
+ ~SmaccAsyncClientBehavior()
+ onSuccess()
+ onFinished()
+ onFailure()
+ requestForceFinish()
# postSuccessEvent()
# postFailureEvent()
# dispose()
#isShutdownRequested()
- waitFutureIfNotFinished()
executeOnEntry()
executeOnExit()
   smacc2::client behaviors
      ::CbSequenceNode

    sequenceNodes

   + CbSequenceNode()
   + onEntry()
   + then()
```