```
smacc2::ISmaccClient
# components
stateMachine_

    orthogonal

+ ISmaccClient()
+ ~ISmaccClient()
+ onInitialize()
+ getName()
+ getComponent()
+ getComponent()
+ getComponent()
+ getType()
+ getStateMachine()
+ connectSignal()
+ requiresClient()
+ getComponents()
+ postEvent()
+ postEvent()
# onOrthogonalAllocation()
# createComponent()
# createNamedComponent()
# getNode()
# getLogger()
initialize()
setStateMachine()
setOrthogonal()
                   smacc2::client_bases
                   ::SmaccSubscriberClient
                        < MessageType >
                   + topicName
                   + queueSize
                   + onFirstMessageReceived_
                   + onMessageReceived_
                   + postMessageEvent
                   + postInitialMessageEvent
                   - sub
                   - firstMessage_
                   - initialized_
                   + SmaccSubscriberClient()
                   + SmaccSubscriberClient()
                   + ~SmaccSubscriberClient()
                   + onMessageReceived()
                   + onFirstMessageReceived()
                   + onOrthogonalAllocation()
                   # onInitialize()
                    messageCallback()
                        < std_msgs::msg::UInt16 >
smacc2::client_bases
::SmaccSubscriberClient
 < std_msgs::msg::UInt16 >
+ topicName
+ queueSize
+ onFirstMessageReceived
+ onMessageReceived_
+ postMessageEvent
+ postInitialMessageEvent
- sub
- firstMessage_

    initialized_

+ SmaccSubscriberClient()
+ SmaccSubscriberClient()
+ ~SmaccSubscriberClient()
+ onMessageReceived()
+ onFirstMessageReceived()
+ onOrthogonalAllocation()
# onInitialize()
```

cl\_keyboard::ClKeyboard

messageCallback()

- + OnKeyPress\_ + postEventKeyPress - initialized
- + CIKeyboard() + ~CIKeyboard()

+ onInitialize()

- + OnKeyPress()
- + onOrthogonalAllocation()
- + onKeyboardMessage()
- + postKeyEvent()