```
{smacc2::ISmaccClientBehavior
|- stateMachine_
- currentState
- currentOrthogonal
|+ ISmaccClientBehavior()
+ ~ISmaccClientBehavior()
+ getStateMachine()
+ getName()
+ requiresClient()
+ requiresComponent()
+ onEntry()
+ onExit()
+ executeOnEntry()
+ executeOnExit()
# runtimeConfigure()
# postEvent()
# postEvent()
# getCurrentState()
# dispose()
# getNode()
# getLogger()
- onOrthogonalAllocation()
                    }
```

```
{smacc2::SmaccAsyncClient
              Behavior
|- onEntryThread_
- onExitThread_
- postFinishEventFn_
- postSuccessEventFn_
- postFailureEventFn_
- onFinished_
- onSuccess_
- onFailure_
- isShutdownRequested_
|+ onOrthogonalAllocation()
+ ~SmaccAsyncClientBehavior()
+ onSuccess()
+ onFinished()
+ onFailure()
+ requestForceFinish()
+ executeOnEntry()
+ executeOnExit()
+ waitOnEntryThread()
+ onSuccess()
+ onFinished()
+ onFailure()
# postSuccessEvent()
# postFailureEvent()
# dispose()
# isShutdownRequested()
- waitFutureIfNotFinished()
                    }
```

```
{cl_moveit2z::CbMoveCartesian
              Relative
|+ offset_
+ scalingFactor_
+ group_
+ moveGroupSmaccClient_
|+ CbMoveCartesianRelative()
+ CbMoveCartesianRelative()
+ onEntry()
+ onExit()
+ moveRelativeCartesian()
                    }
```